



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 5 Issue: V Month of publication: May 2017 DOI:

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)

Detection of Diabetic Retinopathy using Wavelet Transform and SVM Classifier

Roopashree. C. S.¹, Saritha Chakrasali²

^{1,2}Department of Information Science, Vishveshwaraiah University, BNM Institute of Technology,

Abstract: The process and knowledge of image processing is applied to diagnose diabetic retinopathy from images of retina. The proposed work uses wavelet transform to decompose the given image. Colour and texture features are been extracted from the frequency domain co-efficients. Classification of the image is performed using Euclidean distance and support vector machine (SVM).

Keywords: Diabetic Retinopathy, Euclidean distance, Feature extraction, Support vector machine (SVM), Wavelet Transform

I. INTRODUCTION

Diabetic retinopathy is the most common diabetic eye disease and a leading cause of blindness in adults. It is caused by changes in the blood vessels of the retina. In some people with diabetic retinopathy, blood vessels may swell and leak fluid. In other people, abnormal new blood vessels grow on the surface of the retina. The retina is the light-sensitive tissue at the back of the eye. A healthy retina is necessary for good vision. If you have diabetic retinopathy, at first you may not notice changes to your vision. But over time, diabetic retinopathy can get worse and cause vision loss. Diabetic retinopathy usually affects both eyes. In the proposed system an attempt is made to classify the given image based on their severity into mild, moderate and severe diabetic retinopathy. In the process of classification wavelet transform is been used to decompose the image for extracting colour and texture features. Applying Euclidean distance & SVM classifier on these features, the proposed system classifies the image to mild, moderate and severe diabetic retinopathy images. The proposed system can be used in telemedicine [5] [6] where it helps to eliminate distance barriers and can improve access to medical services that would often not be consistently available in distant rural communities.

II. LITERATURE SURVEY

ManjushaS et, al [1] proposed that the visual features are extracted using wavelet transform, colour, texture and edge descriptors and the user feedback is done by Interactive Genetic algorithm. The visual contents of the images in the database are extracted and described by multidimensional feature vectors. Wavelet based features provide valid information required for classification of the retinal images [2]. Jisha. K. P, A. Vasuki et, al [3] discussed gray level co-occurrence matrix for texture feature extraction. Wavelet transform can be implemented by using wavelet sub-bands of R, G and B components of images [4]. Chakrasali.S et, al has proposed the use of wavelet transform on medical images in telemedicine to eliminate the distance barriers and provide medical support to rural areas [5] [6]. The literature survey shows limited work in the detection of diabetic retinopathy using wavelet transform. It has highlighted the need of the proposed system in the field of Telemedicine.

III. WAVELET TRANSFORM

Transforms are basically used to know the information present in the image which is usually hidden in time domain. Since transforms refer to frequency domain where all the hidden informations can be retrieved. Wavelet transform consists series of highpass and lowpass filters which removes all the high and low frequencies separately. The image should be pre-processed before it is been transformed to remove all the noise present in the image and also in some circumstances the contrast of an image can also be increased [1]. Fig 1 & Fig 2 shows the wavelet decomposition where x[n] represents the input image, g[n] is a high pass filter, h[n] is a low pass filter resulting in level 1 co-efficient which will then be down sampled by 2 and once again led to high and low pass filter banks. In decomposition, at level one the image is decomposed into four sub bands i.e. LL (Approximation details of the original image), HL (Horizontal details of the original image), LH (Vertical details of the original image) and HH(Diagonal details of the original image) called One Level Decomposition. The LL- sub band will be further decomposed into four more sub bands which is called Two Level Decomposition. The required features will be extracted from the LL sub band of second level decomposed image [3].

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



Fig.1 Wavelet Decomposition

HL	HL (H)	
HH		
H (7)	HH (D)	
	HIL HIH H	

Fig.2 Two level decomposition

IV.IMPLEMENTATION

Fundus image is an RGB color image, and this feature will be investigated in the study for localization of the blood vessels. The blue channel is characterized by low contrast and does not contain much information, the red channel usually contains too much noise or it is simply saturated, since most of the features emit a signal in the red channel, while the green component of the color retina image gives the best result in the contrast of blood vessels (darker blood vessels on a bright background). Hence, the green channel of the image is used in the proposed system. The Fig 3 clearly shows that green channel is best for analysis when compared to other two channels.



Fig 3: Colour Channels of Retinal Image :(a)Green (b)Blue (c)Red

Once the green channel is extracted, it will be processed for image enhancement where adaptive histogram equalization, denoising and morphological open operations are performed in order to increase the contrast of an image, remove noise, remove optic disk and finally extracting the blood vessels. Further, this will be transformed into a binary image and level two wavelet decomposition is applied on it since it gives the valid information required ,whereas in level one decomposition the blood vessels are still narrowed and in case of level three decomposition valid information is been lost. The features will be extracted from LL band of the decomposed image. Using Euclidean distance method, classification between a normal and affected image is performed. In order to classify within the affected images SVM classifier is been used.

Volume 5 Issue V, May 2017 ISSN: 2321-9653

International Journal for Research in Applied Science & Engineering Technology (IJRASET)

A. Database

The data set used for the work was provided by Dr.Hemanth Murthy from Retina Institute of Karnataka. He has also provided the information vital for classifying the images to normal, mild, moderate and severe. The data set contains more than 200 images in jpeg format, of these 150 images were used for training and the rest were used for testing purpose. The table 1 shows the statistics of the images. The example images of each are shown in Fig 4.

TABLE 1

STATISTICS of IMAGES				
Image Type	No. of Images	Size in Pixel per	Size in Mega Byte per	
		Image	Image	
Normal	50	500 X 700	160	
MILD	50	500 X 700	160	
MODERATE	50	500 X 700	160	
SEVERE	50	500 X 700	160	



Fig 4: Example of Retinal Image :(a)Normal (b)Mild (c)Moderate (d)Severe

B. Experimental Results

The Fig 5 shows the input fundus image and the blood vessels after image enhancemet, which is then fed to wavelet transform for decomposition.



Fig 5 Wavelet Decomposition LL band

The Fig 6 & Fig 7 shows the wavelet decomposition of normal and affected eye fundus image respectively. The decomposition is performed till second level and its respective LL band is also shown.



Fig 6 Wavelet Decomposition of Normal Eye

Volume 5 Issue V, May 2017 ISSN: 2321-9653

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



Fig 7 Wavelet Decomposition for Affected eye fundus and its LL band

The Fig 8 & Fig 9 shows the result of Euclidean distance for both normal and affected eye respectively. Given an image using Euclidean distance method it's easier to identify whether a given image is normal or affected. Fig 10 Shows that to further classify the affected images SVM classifier has been used.



Fig 8 Euclidean Distance result of Normal Eye



Fig 9 Euclidean Distance result of Affected Eye



www.ijraset.com IC Value: 45.98 *Volume 5 Issue V, May 2017 ISSN: 2321-9653*

International Journal for Research in Applied Science & Engineering Technology (IJRASET)

The Fig 11 shows the efficiency of the proposed system. The system shows 100% accuracy in classifying a normal image, 80% accuracy in classifying the image to mild, 90%-93% accuracy in classifying the image to moderate and severe respectively.



Fig 11 Evaluation Metric of Wavelet Transform

V. CONCLUSIONS

The proposed system is used for an early detection of Diabetic Retinopathy which will aid the physicians for easy detection of retinopathy. The system helps in classifying whether a given image is normal or affected, if it is affected the system also specifies at which stage (mild, moderate, severe) it is currently. The proposed system has shown that the green channel is the best for blood vessels extraction and also found that wavelet decomposition of level two gives the valid information required. It can be concluded that Euclidean distance method gives the better result for the classification between normal and affected image. Whereas, for further classification of affected images SVM shows the better results. This work can be extended to other frequency domain transform to compare the performances.

VI.ACKNOWLEDGMENT

I would like to thank my college BNMIT for providing me with the facilities for aiding me in completing my project. I am thankful to Dr. Saritha Chakrasali, my guide for her constant support, advice and motivation. I owe my sincere gratitude to Dr.Hemanth Murthy from Retina Institute of Karnataka who provided me with the data set and information required for my work.

REFERENCES

- ManjushaS, Nelwin Raj ,Content Based Image Retrieval Using Wavelet Transform and Feedback Algorithm, International Journal of Innovative Research in Science, Engineering and Technology, July 2014
- [2] Yusra .T. Mshari, Hameed A. Younis ,Content Based Image Retrieval using Haar Wavelet to Extracted Colour Histogram and Texture Features ,International Journal of Computer Science and Mobile Computing August 2015.
- [3] isha. K. P, Thusnavis Bella Mary. I, Dr. A. Vasuki, An Image Retrieve Al Technique Based On Texture Features Using Semantic Properties, International Conference on Signal Processing, Image Processing and Pattern Recognition [ICSIPR], 2013.
- [4] Sheetal Jagannath Dalavi, Mahadev S. Patil, Sanjay R. Patil, Content Based Image Retrieval by Using Daubechies Wavelet Transform, International Journal of Innovative Research in Science, Engineering and Technology, March 2014
- [5] Ramachandran Murugesan ,Saritha Chakrasali, Mahadevan Sumathi, Raman Bhaskaran, Secure Dual Watermarking in the Wavelet Domain for Teleradiology, International Conference on Advances in Information and Communication Technologies (ICICOT07), ISBN 0230634370 Macmillan Publisher, 2007.
- [6] Ramachandran Murugesan, Saritha Chakrasali, Raman Bhaskaran, Wavelet Based Image Adaptive Dual watermarking for Teleradiology, 52nd Congress of The Indian Society of Theoretical and Applied Mechanics,2007.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)