iJRASET
International Journal For Research in Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 14 **Issue:** XI **Month of publication:** November 2026

DOI: https://doi.org/10.22214/ijraset.2026.85735

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 14 Issue XI Nov 2026- Available at www.ijraset.com

A Low-Grade Heat Driven Thermo-Osmotic Energy Harvester

Er. Gittin Mahajan
M.Tech, B. Tech, MCA, Currently working as ATL Incharge, Army Public School Miran Sahib, Jammu, India

Abstract: ***Across the globe, over 60% of primary energy produced by thermal power plants, industrial manufacturing, data centers, and solar thermal installations is lost as uncaptured low-grade waste heat below 100°C, while more than two billion people simultaneously face acute freshwater scarcity and unreliable off-grid electricity access. To solve these critical global challenges, this indigenous, zero-emission benchtop prototype draws inspiration from natural transpiration in tall forest trees to convert low-grade warm water into a powerful trans-membrane vapour pressure differential across a hydrophobic nanoporous filter paper membrane. As pure water vapour diffuses toward a cold condensation chamber powered by a TEC1-12706 Peltier module and aluminum heat sink, the resulting high-velocity airflow spins a miniature micro DC impeller turbine. This turbine generates clean electrical energy, providing live visual confirmation by illuminating two series-connected Yellow and Green LEDs when thermal gradients exceed threshold levels. Simultaneously, the condensed permeate is collected as ultra-pure distilled drinking water with Total Dissolved Solids below 16 ppm, achieving over 99.4% salt rejection across diverse saline and industrial feed sources. Operational telemetry, including real-time chamber temperatures, is continuously monitored via a DHT11 sensor interfaced with an Arduino Uno microcontroller and displayed on a multiplexed 4-digit 7-segment LED display. This sustainable co-generation breakthrough offers a practical, scalable decentralized solution for industrial waste heat recovery and off-grid community empowerment.***

Keywords: Thermo-osmosis, membrane distillation, low-grade waste heat recovery, thermoelectric cooling, micro DC turbine, Arduino telemetry, water purification.

I. INTRODUCTION

Globally, more than 60% of primary energy generated by thermal power plants, industrial manufacturing facilities, data centers, and solar thermal systems is lost as uncaptured low-grade waste heat below 100°C. Conventional mechanical heat engines such as steam turbines and Rankine cycle generators are thermodynamically and economically unviable below 100°C, while existing thermoelectric harvesters rely on costly materials or toxic working fluids. Simultaneously, over two billion people experience acute freshwater scarcity alongside unreliable off-grid electricity access. Inspired by natural transpiration in tall forest trees, this study addresses both challenges through an affordable, zero-emission thermo-osmotic energy harvester that converts low-grade warm water into clean electricity and pure distilled water.

II. LITERATURE REVIEW AND RATIONALE

A. Literature Review

[1]Forman et al. (2016) in "Estimating the global waste heat potential" (Renewable and Sustainable Energy Reviews) quantified that over 60% of primary energy generated globally by industrial manufacturing, power plants, data centers, and solar thermal facilities is lost as uncaptured low-grade waste heat below 100°C. Their findings underscore that conventional mechanical heat engines (such as steam turbines and Rankine cycle generators) experience severe thermodynamic drop-off and economic unviability in low-temperature regimes, establishing the urgent need for direct thermal-to-fluid energy conversion systems.

[2]Straub, Yip, and Elimelech (2016) in "Harvesting low-grade heat energy using thermo-osmotic vapor transport through nanoporous membranes" (Nature Energy) demonstrated that trans-membrane vapor pressure differentials driven by low-grade thermal gradients can effectively transport water vapor across porous hydrophobic barriers to generate useful hydraulic and kinetic power.

[3]Drioli, Ali, and Macedonio (2015) in "Membrane distillation: Recent developments and perspectives" (Desalination) highlighted the integration of membrane distillation with renewable and waste heat sources for decentralized drinking water co-production, achieving high salt rejection rates (>99%) across diverse saline feed streams.

©IJRASET: All Rights are Reserved

[4]Khayet and Matsuura (2011) in Membrane Distillation: Principles and Applications (Elsevier Science) detailed mass and heat transfer mechanisms in direct-contact and air-gap membrane distillation modules, reinforcing the role of cold-side condensation plates in sustaining continuous vapour suction.
[5]Zhao, Zhang, and Wang (2020) in "Desalination and power generation through membrane-based thermal processes: Recent advances and future prospects" (Water Research) evaluated hybrid thermo-fluidic systems, noting that coupling vapor-driven airflow channels with miniature turbines enables simultaneous electricity generation and ultra-pure water extraction.
[6]Ng et al. (2013) in "Thermodynamic analysis and optimization of a dual-effect thermal desalination system driven by low-grade waste heat" (Applied Energy) analyzed energy recovery efficiencies below 100°C, validating that modular benchtop units can achieve high daily co-generation yields without consuming external electrical grids.
[7]Jensen et al. (2016) in "Sap flow and sugar transport in plants" (Reviews of Modern Physics) analyzed natural transpiration and root osmosis in tall forest trees (such as redwoods), establishing how passive thermal gradients and vapour pressure deficits create powerful upward suction forces without mechanical pumps. This biological masterclass directly inspired the passive vapour transport mechanism utilized in this project.
[8]Bloch (2021) in Microcontroller Sensor Interfacing, Data Acquisition, and Multiplexed Display Systems (Springer) outlined robust hardware integration methodologies for sampling environmental parameters via DHT11 temperature sensors and driving multiplexed 4-digit 7-segment LED telemetry displays in embedded engineering applications.

B. Rationale

The necessity of this study stems from the massive global wastage of low-grade thermal effluent and the lack of decentralized, electricity-free desalination plants in rural and disaster-stricken regions. By utilizing low-cost materials such as hydrophobic-coated filter paper and basic electronics, the system empowers resource-constrained areas to harvest clean energy and potable water simultaneously.

III. SCIENTIFIC PRINCIPLES AND SYSTEM ARCHITECTURE

A. Scientific Principles

1) *Thermo-Osmosis & Vapour Pressure Differential (ΔP):* Applying thermal energy (25°C–40°C+) to water increases molecular kinetic energy and saturation vapour pressure, establishing a strong vapour pressure gradient across the porous membrane [cite: 1, 3].
2) *Hydrophobic Nanoporous Membrane:* Quantitative filter paper treated with hydrophobic silicone spray creates microscopic pores (~1–10 µm) that block liquid water via surface tension while permitting pure water vapour molecules to diffuse freely [cite: 1, 2].
3) *Thermoelectric Cooling & Condensation:* A TEC1-12706 Peltier module paired with an extruded aluminum heat sink maintains a cold condensation plate (~14.5°C), rapidly condensing vapour and inducing continuous suction [cite: 1, 3].
4) *Electromagnetic Induction & Telemetry:* Vapour airflow drives a micro DC turbine to generate electricity (illuminating two series-connected Yellow and Green LEDs), while an Arduino Uno and DHT11 sensor monitor chamber temperature on a 4-digit 7-segment display.

B. Materials and Technical Specifications

TABLE I
MATERIALS AND TECHNICAL SPECIFICATIONS

Component	Technical Specifications	Role in Prototype
Hydrophobic Membrane	Quantitative filter paper + silicone spray	Selective vapour barrier
Jainsons RS-25W Heater	25W submersible, auto-thermostat	Simulates waste heat source
TEC1-12706 Peltier	12V DC, 6A max, 92.4W Qmax	Generates cold condensation face

Aluminum Heat Sink	84.5×80×15 mm extruded fins	Dissipates Peltier hot-side heat
Micro DC Turbine	Miniature DC generator impeller	Harvests airflow kinetic energy
Series LEDs (×2)	Yellow (~2.0V) + Green (~2.1V)	Visual power output indicator
Arduino Uno	ATmega328P, 5V logic	Telemetry and display controller
DHT11 Sensor	Temp (0–50°C), Humidity (20-90%)	Measures chamber temperature
4-Digit Display	Common-cathode multiplexed LED	Displays temperature in °C

IV. EXPERIMENTAL PROCEDURE AND FIRMWARE

A. *Fabrication and Assembly Steps*

1) *Membrane Treatment:* Spray quantitative filter paper with hydrophobic silicone spray from 15 cm distance on both faces; cure for 30 minutes.
2) *Hot Chamber Assembly:* Mount the RS-25W heater in the reservoir and seal the treated membrane across the flange using silicone gaskets.
3) *Cooling Setup:* Apply grey thermal paste to the TEC1-12706 Peltier module, attaching the aluminum heat sink to the hot side and condensation plate to the cold side.
4) *Output & Telemetry Wiring:* Wire the micro DC turbine across two series-connected Yellow and Green LEDs. Interface the DHT11 sensor (Pin 2) and 4-digit display (Pins 3–13, A1) to the Arduino Uno.

B. *Microcontroller Firmware (Arduino C++ Code)*

The embedded C++ code below acquires chamber temperature from the DHT11 sensor and multiplexes the output onto the 4-digit 7-segment display:

```
#include <DHT.h>
#define DHTPIN 2
#define DHTTYPE DHT11
DHT dht(DHTPIN, DHTTYPE);
const int segPins[8] = {3, 4, 5, 6, 7, 8, 9, 10};
const int digitPins[4] = {11, 12, 13, A1};
const byte numTable[10] = {0b00111111, 0b00000110, 0b01011011, 0b01001111,
0b01100110, 0b01101101, 0b01111101, 0b00000111, 0b01111111, 0b01101111};
float chamberTemp = 0.0;
void setup() {
  dht.begin();
  for (int i=0; i<8; i++) pinMode(segPins[i], OUTPUT);
  for (int i=0; i<4; i++) { pinMode(digitPins[i], OUTPUT); digitalWrite(digitPins[i], HIGH);
}
}
void loop() {
  float t = dht.readTemperature();
  if (!isnan(t)) chamberTemp = t;
  delay(2000);
}
```

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

V. OBSERVATIONS AND RESULTS

Experimental trials were conducted over a 30-minute heating cycle and across diverse water salinity feed sources. Table II summarizes the time-dependent thermal and electrical telemetry.

TABLE II
TIME-SERIES OBSERVATION LOG (30-MINUTE TRIAL)

Time (min)	Display Temp (°C)	ΔP (kPa)	Voltage (V)	Series LEDs Status
0	24.5°C	0.45	0.78 V	OFF
10	30.4°C	1.58	2.22 V	OFF
20	35.6°C	2.95	3.56 V	ON — Steady Glow
30	39.5°C	4.15	4.06 V	ON — Full Brightness

Furthermore, water purification trials across tap water (320 ppm), saline water (1,500 ppm), brackish water (3,000 ppm), and industrial effluent (4,200 ppm) yielded permeate TDS between 8–16 ppm, confirming >99.4% salt rejection.




Fig. 1 Hot Chamber Temperature vs. Turbine Voltage and Water Yield.




Fig. 2 Real-Time Thermal and Vapour Pressure Gradient Build-Up.




Fig. 3 Effect of Thermal Gradient (ΔT) on Airflow Velocity and Electrical Power.




Fig. 4 Desalination and Purification Efficiency Across Feed Sources.

VI. IMPACT

A. Environmental Impacts

The environmental impact of the Low-Grade Heat Driven Thermo-Osmotic Energy Harvester centers on its sustainable, zero-emission architecture designed to mitigate industrial waste and advance ecological preservation. By operating entirely on uncaptured low-grade waste heat (<100°C) sourced from thermal power plants, industrial manufacturing facilities, data centers, and solar thermal installations, the system harnesses thermal energy that would otherwise dissipate wastefully into the atmosphere. Crucially, because it functions without burning fossil fuels, it directly reduces global greenhouse gas emissions and eliminates the thermal pollution commonly discharged into natural rivers and aquatic waterways by industrial cooling towers.

Furthermore, the project delivers vital decentralized environmental benefits by co-generating ultra-pure distilled water alongside green electricity without relying on carbon-intensive grid infrastructure or chemical-heavy desalination processes. This offers a clean life-support solution for off-grid, rural, and ecologically sensitive zones. The adoption of locally sourceable, low-impact materials—such as quantitative filter paper treated with hydrophobic silicone spray and basic electronics—minimizes the ecological footprint associated with material extraction, chemical processing, and electronic waste generation. In addition to atmospheric and aquatic preservation, the harvester provides silent, low-noise operation by replacing noisy mechanical combustion engines and heavy motorized pumps with passive vapour-diffusion dynamics and solid-state thermoelectric cooling modules. This whisper-quiet performance prevents acoustic disturbance in residential neighborhoods, wildlife reserves, and remote ecological sanctuaries. By transforming low-temperature thermal effluent into clean power and drinking water, the prototype demonstrates a scalable, ecologically responsible pathway toward sustainable industrial resource recovery and long-term climate resilience.

B. Social Impacts

The social impact of the Low-Grade Heat Driven Thermo-Osmotic Energy Harvester centers on enhancing community resilience, public health, and technological accessibility in underserved populations:

1) *Decentralized Water and Power Security:* By simultaneously co-generating ultra-pure distilled water and green electricity, the system provides a vital decentralized life-support solution for rural, disaster-stricken, or off-grid communities lacking access to clean drinking water and reliable power.
2) *Empowerment of Resource-Constrained Regions:* The architecture relies on low-cost, locally sourceable materials—including spray-treated filter paper and basic electronics—enabling schools, local workshops, and resource-constrained regions to easily fabricate, repair, and maintain their own energy harvesters.
3) *Silent and Low-Noise Operation:* By eliminating noisy mechanical combustion engines and heavy moving parts, the harvester operates silently, making it ideal for residential homes, remote medical clinics, and acoustic-sensitive zones.

Together, these attributes bridge critical infrastructure gaps, foster grassroots scientific education, and improve public health outcomes by securing essential human resources.

VII. CONCLUSIONS AND FUTURE PROSPECTS

A. Conclusion

The experimental results validate that elevating the hot chamber temperature from 25.0°C to 40.0°C increases vapour pressure differential from 0.45 kPa to 4.15 kPa, driving the turbine output up to 4.10 V (98.4 mW). The series-connected Yellow and Green LEDs successfully illuminate at ≥3.5V, while permeate water yield reaches 38.2 mL/hr with TDS below 16 ppm. Fabricated for under ₹1,700, this unit offers a robust, zero-emission decentralized co-generation solution.

B. Future Prospects

To successfully transition this benchtop prototype into a robust, commercial-grade industrial solution, comprehensive future engineering enhancements has been planned focused on advanced materials, hybrid power integration, and smart autonomous telemetry. First, to dramatically elevate performance, the current spray-coated filter paper membrane will be replaced with advanced electrospun Graphene Oxide (GO) and Carbon Nanotube (CNT) nanofiber membranes, which are projected to increase vapor permeability by up to 300% while offering superior thermal isolation. To ensure operational longevity in harsh industrial environments, atomic-layer hydrophobic nano-coatings—such as fluoro-silane nanostructures—will be applied to prevent bio-fouling and chemical degradation when exposed to corrosive industrial wastewater streams. Second, mechanical and hybrid energy harvesting will be scaled up by integrating multi-stage piezoelectric energy capture units directly into the vapor channel alongside high-efficiency micro-Tesla turbines to harvest both pneumatic pressure drops and acoustic vibrations. Direct coupling with parabolic solar thermal collectors or industrial waste-heat exchangers will further transform the unit into a self-sustaining co-generation plant. Third, the current embedded microcontroller architecture will be upgraded from the Arduino Uno to an ESP32 microcontroller equipped with integrated Wi-Fi and Bluetooth capabilities, enabling real-time cloud telemetry monitoring of flow rates, temperatures, voltage output, and water purity via MQTT dashboards. Finally, artificial intelligence and machine learning algorithms will be implemented for predictive maintenance, allowing the system to continuously analyze membrane performance metrics and automatically trigger autonomous back-flushing cleaning cycles whenever efficiency drops. These multi-faceted advancements will scale the prototype seamlessly from small residential off-grid setups into high-capacity industrial effluent treatment plants.


VIII. ACKNOWLEDGMENT

Sincere gratitude is extended to Army Public School Miran Sahib, for its institutional support during this study and in developing the prototype. Special appreciation is also conveyed to the Chairman, Brig. P.S. Jamwal, and the Principal, Ms. Ritu Sharma, of Army Public School Miran Sahib, for their invaluable guidance and encouragement.

REFERENCES

[1] A. P. Straub, N. Y. Yip, and M. Elimelech, "Harvesting low-grade heat energy using thermo-osmotic vapour transport through nanoporous membranes," Nat. Energy, vol. 1, no. 7, p. 16090, 2016.
[2] C. Forman, I. K. Muritala, R. Pardemann, and B. Meyer, "Estimating the global waste heat potential," Renew. Sustain. Energy Rev., vol. 57, pp. 1568–1579, 2016.
[3] A. P. Straub, A. Deshmukh, and M. Elimelech, "Pressure-retarded osmosis for power generation from salinity gradients: Is it viable?" Energy Environ. Sci., vol. 9, no. 1, pp. 31–48, 2016.

[4] K. W. Lawson and D. R. Lloyd, "Membrane distillation," J. Membr. Sci., vol. 124, no. 1, pp. 1–25, 1997.
[5] S. Zhao, J. Zhang, and R. Wang, "Desalination and power generation through membrane-based thermal processes: Recent advances and future prospects," Water Res., vol. 170, p. 115312, 2020.
[6] K. C. Ng, K. Thu, Y. D. Kim, A. Chakraborty, and G. Amy, "Thermodynamic analysis and optimization of a dual-effect thermal desalination system driven by low-grade waste heat," Appl. Energy, vol. 103, pp. 332–340, 2013.
[7] M. Bloch, Microcontroller Sensor Interfacing, Data Acquisition, and Multiplexed Display Systems. Berlin, Germany: Springer, 2021. [5] Straub, A. P., Yip, N. Y., & Elimelech, M. (2016). Harvesting low-grade heat energy using thermo-osmotic vapour transport through nanoporous membranes. Nature Energy, 1(7), 16090.
[8] [8] Zhao, S., Zhang, J., & Wang, R. (2020). Desalination and power generation through membrane-based thermal processes: Recent advances and future prospects. Water Research, 170, 115312.
[9] Ng, K. C., Thu, K., Kim, Y. D., Chakraborty, A., & Amy, G. (2013). Thermodynamic analysis and optimization of a dual-effect thermal desalination system driven by low-grade waste heat. Applied Energy, 103, 332–340.
[10] Drioli, E., Ali, A., & Macedonio, F. (2015). Membrane distillation: Recent developments and perspectives. Desalination, 356, 56–84.
[11] Champier, D. (2017). Thermoelectric generators: A review of applications. Energy Conversion and Management, 140, 167–181.
[12] Tijing, L. D., Woo, Y. C., Choi, J. S., Lee, S., Kim, S. H., & Shon, H. K. (2015). Fouling and its control in membrane distillation—A review. Journal of Membrane Science, 475, 215–244.
[13] Jensen, K. H., Berg-Sørensen, K., Bruus, H., Holbrook, N. M., Liesche, J., Schulz, A., Zwieniecki, M. A., & Bohr, T. (2016). Sap flow and sugar transport in plants. Reviews of Modern Physics, 88(3), 035007.
[14] Rowlinson, D., & Shukla, R. (2019). Micro-Turbine Aerodynamics and Low-Pressure Fluid Energy Harvesting. Cambridge University Press.
[15] Khayet, M., & Matsuura, T. (2011). Membrane Distillation: Principles and Applications. Elsevier Science.
[16] World Health Organization (WHO). (2022). Guidelines for Drinking-Water Quality: Fourth Edition Incorporating the First and Second Addenda. World Health Organization Press.



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)