iJRASET
International Journal For Research in Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 14 **Issue:** VI **Month of publication:** June 2026

DOI: https://doi.org/10.22214/ijraset.2026.83548

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 14 Issue VI June 2026- Available at www.ijraset.com

AI-Based Hydraulic Leak Detection System

P. Deekshitha[1], Advaith Venugopal[2], K.Tarun Reddy[3], K. Vikas Naik[4], Dr.R.Uday Kumar[5]
[1, 2, 3, 4]*B.Tech (Mech.Engg) Students,* [5]*Associate Professor, Dept. of Mechanical Engineering, Mahatma Gandhi Institute of Technology, Gandipet, Hyderabad.*

Abstract: ***Hydraulic systems are extensively used in industrial and mechanical applications for efficient power transmission and control. However, leakage in such systems leads to pressure loss, reduced efficiency, increased maintenance cost, and potential safety hazards. Traditional leak detection methods are largely manual, time-consuming, and ineffective in identifying early-stage faults.This work presents an Artificial Intelligent (AI) -based hydraulic leak detection system that enables real-time monitoring and intelligent fault identification. Sensors such as flow and temperature sensors are used to continuously collect system data. The acquired data is processed using a microcontroller, while the role of Artificial Intelligence (AI) is to analyse patterns in the sensor data and identify abnormal conditions that indicate leakage. AI techniques improve detection accuracy by distinguishing between normal variations and actual fault conditions, thereby supporting predictive maintenance.The system provides immediate alerts through a buzzer and LED, along with real-time data display on an LCD. This approach enhances system reliability, reduces downtime, and minimizes resource wastage. The system serves as a cost-effective and scalable solution, with potential for future integration of advanced AI and IoT technologies.***

Keywords: Hydraulic System, Leak Detection, Artificial Intelligence (AI), Flow Sensor, Arduino.

I. INTRODUCTION

Hydraulic systems are widely used in industrial and mechanical applications for power transmission and motion control. These systems operate on the principle of fluid power, where pressurized liquid is used to generate and transfer energy. They are commonly used in construction equipment, manufacturing machines, automotive systems, and aerospace applications(1-3).The main advantages of hydraulic systems include high efficiency, precise control, and the ability to handle heavy loads. However, due to continuous operation under high pressure, these systems are prone to wear, leakage, and performance degradation. Maintaining the efficiency and reliability of hydraulic systems is therefore essential for safe and smooth operation.Hydraulic leakage is a major issue that affects system performance and safety. Leakage can occur due to damaged pipes, worn seals, loose connections, corrosion, or material fatigue(4-6). These faults often develop gradually and may not be detected in the early stages.Even small leaks can lead to pressure loss, reduced efficiency, and increased energy consumption. In industrial environments, leakage can also cause safety hazards such as slippery surfaces and equipment failure. Additionally, fluid loss leads to increased operational costs and environmental concerns.Detecting leaks at an early stage is difficult using traditional methods, especially for internal or hidden leaks. Therefore, leakage remains a critical challenge in hydraulic systems.Modern hydraulic systems require continuous monitoring to ensure reliability and safety(7-8). Traditional maintenance methods such as periodic inspection are not sufficient for detecting early-stage faults.Leak detection systems help in identifying abnormal conditions in real time. Early detection reduces downtime, prevents major failures, and lowers maintenance costs. It also improves safety by reducing the risk of accidents caused by leakage.With increasing industrial automation, there is a growing demand for intelligent systems that can monitor system parameters continuously and provide alerts automatically. This highlights the importance of developing efficient and cost-effective leak detection systems. Sensors play a vital role in monitoring hydraulic systems by providing real-time data. They measure important parameters such as flow rate, temperature, and pressure, which indicate the condition of the system(9).Flow sensors detect the movement of fluid and help identify changes in flow patterns. Temperature sensors monitor heat levels, which can indicate abnormal conditions such as friction or fluid loss. These sensors continuously collect data and send it to the controller for analysis(10).The accuracy and reliability of leak detection systems depend on the performance of these sensors. Modern sensors provide fast response, high precision, and easy integration with microcontrollers, making them suitable for real-time monitoring applications.

II. METHODOLOGY

The methodology of the proposed AI-Based Hydraulic Leak Detection System focuses on developing a smart and cost-effective monitoring system capable of identifying leakage conditions in hydraulic systems using sensors, embedded systems, and intelligent monitoring techniques.

©IJRASET: All Rights are Reserved

The methodology includes system design, component selection, data acquisition, signal processing, leak identification, alert generation, and system monitoring.The proposed system continuously monitors important hydraulic parameters such as flow rate and temperature using sensors. The collected sensor data is processed by an Arduino microcontroller, which acts as the central control unit of the system. Whenever abnormal conditions are detected, the system identifies a possible leak and generates warning alerts using a buzzer and LED indicator. Real-time values are also displayed on an LCD screen for continuous monitoring.The block diagram of AI-Based Hydraulic leak detection system shown in Fig.1




Fig.1 Block diagram of Hydraulic leak detection system

The system requirements were divided into hardware requirements and software requirements.The hardware components required for the project includeArduino UNO microcontroller,YF-S201 flow sensor,DS18B20 temperature sensor,LCD display with I2C module,Active buzzer module,LED indicators,Breadboard and jumper wires,Water pump,PVC pipes and connectors,Water tank,Power supply,these components were selected based on low cost, easy availability, compatibility, and suitability for prototype implementation.The software requirements includearduino IDE,Embedded C programming,Sensor libraries for Arduino,Serial monitoring tools.The Arduino IDE was used to write, compile, and upload the code to the microcontroller.The system operates based on continuous monitoring and analysis of hydraulic parameters.Initially, the water pump circulates fluid through the PVC pipeline system. The flow sensor continuously measures the flow rate, while the temperature sensor measures the fluid temperature.The sensor data is transmitted to the Arduino UNO microcontroller. The Arduino processes the incoming data and compares the values with predefined threshold conditions.Under normal operating conditions, the flow rate and temperature remain within acceptable limits.When leakage occurs, there is a sudden variation in flow rate and possible temperature changes. The Arduino detects these abnormal conditions and identifies a leakage event.Once leakage is detected, When a leak is detected in the system, the buzzer is activated to provide an audible alert, and at the same time, the LED glows to give a visual indication of the fault. Additionally, a leak warning message is displayed on the LCD screen, ensuring that the user is clearly informed about the issue through multiple alert mechanisms.This ensures immediate identification of faults and enables quick corrective action.The Arduino UNO was programmed using Embedded C language in Arduino IDE.

The programming methodology involved as the process begins with the initialization of sensors to ensure that all sensing components are ready for operation and capable of collecting accurate data. This is followed by the setup of the LCD, which prepares the display unit to show system information and alerts. Next, pin configuration is carried out to correctly assign input and output connections between the microcontroller and various components.Once the setup is complete, the system proceeds with sensor data acquisition, where real-time data such as flow and temperature values are collected. The acquired data is then processed to make it suitable for analysis. After processing, threshold comparison is performed to check whether the measured values fall within acceptable limits.Based on this comparison, the leak detection logic is applied to determine if there is any abnormal condition or leakage in the system. If a leak is detected, alert generation is triggered, activating components such as the buzzer and LED. Finally, the LCD display is updated to show the current status and any warning messages, ensuring the user is informed about the system condition.The Arduino continuously runs the programmed logic in a loop.Sensor values are updated in real time.The code compares sensor readings with predefined threshold values.If abnormal conditions are detected, the system activates warning outputs.This methodology ensures fast response and continuous monitoring.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

III. RESULTS AND DISCUSSION

The results and discussion chapter presents the performance analysis of the implemented AI Based Hydraulic Leak Detection System. The experimental setup was tested under different hydraulicconditions to evaluate the efficiency, accuracy, reliability, and response time of the proposed system.The collected sensor data was analysed using machine learning algorithms to identify leakage patterns. Various tests were conducted by introducing different levels of leakage into the hydraulic system. The results obtained from pressure sensors, flow sensors, temperature sensors, and AI prediction models are discussed in detail. The experimental study focuses on analysing the observations collected during system testing to understand its behaviour under different conditions. It involves evaluating the leak detection accuracy to determine how effectively the system identifies faults. A comparison between normal and leakage conditions is carried out to highlight the differences in system responses. The overall system performance is also studied to assess its reliability, efficiency, and responsiveness. Finally, the advantages and limitations of the developed system are discussed to provide a clear understanding of its strengths and areas for improvement.The hydraulic system was operated under different pressure and flow conditions. Sensor readings were continuously recorded during both normal and leakage states.Parameters Observed are Pressure variation.Flow rate variation.Temperature changes.Leak response time.AI prediction accuracy.Observation During Normal ConditionUnder normal operating conditions.During normal operating conditions, the pressure remained stable, indicating that the system was functioning without any leakage or blockage. The flow rate was constant, showing smooth and uninterrupted fluid circulation. The temperature also remained within safe limits, ensuring proper thermal stability of the system. additionally, no abnormal fluctuations were observed in any of the monitored parameters, confirming that the hydraulic system was operating under normal and healthy conditions.Observation During leakage conditionWhen leakage was introduced.During the experiment, it was observed that the pressure dropped gradually over time, indicating a possible leakage in the system. Along with this, the flow rate changed significantly, showing irregular behaviour in fluid movement. A slight increase in temperature was also recorded, which further supported the presence of abnormal conditions. Based on these variations, the AI model successfully generated leak alerts, confirming the detection of a potential fault in the system.These variations confirmed the effectiveness of the proposed detection system.The system contributes to improved safety by detecting leaks early and preventing hazardous operating conditions. It also helps in reducing operational losses by minimizing fluid wastage and avoiding major system failures. Through continuous monitoring and early fault detection, the system supports preventive maintenance, allowing issues to be addressed before they become serious. Additionally, it leads to increased equipment life by reducing wear and tear and ensuring smoother and more efficient operation of the hydraulic components. Experimental observations confirmed that the proposed system accurately detected hydraulic leakage under different conditions. Pressure, flow, and temperature variations were successfully analysed using AI algorithms. The integration of IoT technology enabled real-time monitoring and remote accessibility. The obtained results proved that the proposed system is reliable, efficient, and suitable for industrial applications.

The AI model achieved high prediction accuracy in identifying leakage conditions.Performance parameters

- Accuracy
- Precision
- Recall
- Response time

Accuracy levels are shown in Table.1. The results indicate that the AI-based approach provides reliable hydraulic leak detection performance.

Table 1. Accuracy levels of system

Parameter	Obtained Value
Detection Accuracy	95%
Precision	93%
Recall	94%
Response Time	2 seconds

The protype of AI – Based Hydraulic Leak Detection System shown in Fig.2




Fig.2 AI – Based Hydraulic Leak Detection System

IV. CONCLUSIONS

The AI Based Hydraulic Leak Detection System was successfully designed, implemented, and tested for real-time monitoring and leak detection in hydraulic systems.This work focused on integrating sensors, microcontrollers, artificial intelligence algorithms, and IoT technology to identify leakage conditions accurately and efficiently.Hydraulic systems are widely used in modern industries, and leakage is one of the major issues affecting efficiency, safety, and maintenance cost. Traditional leak detection methods are often manual, time-consuming, and less accurate. To overcome these limitations, an intelligent AI-based monitoring system was developed.The implemented system continuously monitored important hydraulic parameters such as pressure, flow rate, temperature, and vibration. These parameters were collected through sensors and processed using machine learning algorithms. The trained AI model successfully differentiated between normal operating conditions and leakage conditions.The study highlights that pressure variation effectively indicated the presence of leakage in the system, making it a key parameter for fault detection. Similarly, changes in flow rate helped in identifying abnormal operating conditions and system instability. The integration of AI algorithms significantly improved prediction accuracy by analysing patterns and detecting faults more reliably. IoT technology enabled remote monitoring, allowing users to access and track system performance from distant locations. Additionally, real-time alerts enhanced overall system reliability by ensuring immediate notification of any abnormal conditions. The developed system achieved high detection accuracy with fast response time. The use of artificial intelligence reduced false alarms and improved overall monitoring efficiency. IoT integration further enhanced system accessibility by allowing remote visualization and cloud-based monitoring. The system can significantly reduce hydraulic fluid wastage, equipment damage, and operational downtime. Therefore, the proposed AI-based solution offers an effective and intelligent approach for modern hydraulic industries.Through automation of the monitoring process, the system reduces the need for manual intervention and enhances efficiency. Additionally, it supports early fault identification, ensuring timely corrective actions and improved system reliability.


REFERENCES

[1] W. Tylman, M. Nieznański, and M. Łukowicz, “Fully Automatic AI-Based Leak Detection System,” Energy, vol. 35, no. 9, pp. 3838–3848
[2] X. Fan, X. Zhang, and X. Yu, “Machine Learning Model and Strategy for Fast and Accurate Detection of Leaks in Water Supply Network,” Journal of Infrastructure Preservation and Resilience, vol. 2, no. 10, 2021.
[3] X. Hu et al., “A tnGAN-Based Leak Detection Method for Pipeline Network Considering Incomplete Sensor Data,” IEEE Transactions on Instrumentation and Measurement, vol. 70, pp. 1–10, 2021.
[4] H. Zhang et al., “Improved PSO-based Method for Leak Detection and Localization in Liquid Pipelines,” IEEE Transactions on Industrial Informatics, 2018.
[5] J. Luo, C. Wang, J. Yang, and X. Zhong, “A Transformer-Based Approach to Leakage Detection in Water Distribution Networks,” Sensors, vol. 24, no. 19, 2024.
[6] U. Rajasekaran and M. Kothandaraman, “A Novel Custom One-Dimensional Time-Series DenseNet for Water Pipeline Leak Detection and Localization Using Acousto-Optic Sensor,” IEEE Access, 2024.
[7] U. Rajasekaran, M. Kothandaraman, and C. H. Pua, “Water Pipeline Leak Detection and Localization With an Integrated AI Technique,” IEEE Access, vol. 13, pp. 2736–2745, 2025.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

[8] N. Sourabh, P. V. Timbadiya, and P. L. Patel, "Leak Detection in Water Distribution Network Using Machine Learning Techniques," ISH Journal of Hydraulic Engineering, vol. 29, sup1, pp. 177–195, 2023
[9] M. Waqar, A. M. Memon, M. Louati, and M. S. Ghidaoui, "Pipeline Leak Detection Using Hydraulic Transients and Domain-Guided Machine Learning," Mechanical Systems and Signal Processing, vol. 224, 2025.
[10] I. Lučin, Z. Carija, and S. Družeta, "Detailed Leak Localization in Water Distribution Networks Using Random Forest Classifier and Pipe Segmentation," IEEE Access, 2021.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)