



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 14 **Issue:** IX **Month of publication:** September 2026

DOI: <https://doi.org/10.22214/ijraset.2026.84727>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

AIOT in Predictive Agriculture - IoT and AI Integration for Real-Time Soil Monitoring and Smart Irrigation in Predictive Agriculture

Gowri M.¹, Boomika M.², Rakshana S.³, Rubali R.⁴

^{1,2,3}U.G. Student, Department of Bachelor of Information Technology, Annai Womens College, Karur, TamilNadu, India

⁴Assistant Professor, Department of BCA IT, Annai Womens College, Karur, India

Abstract: Modern agriculture faces severe challenges due to climate volatility, accelerating groundwater depletion, and the global imperative to maximize crop production on diminishing arable land. Traditional irrigation frameworks rely predominantly on static schedules or reactive threshold switching, leading to substantial water waste, energy inefficiencies, and suboptimal crop yields. To overcome these limitations, this paper proposes an end-to-end Artificial Intelligence of Things (AIoT) framework designed for real-time multi-parameter soil tracking and predictive smart irrigation. The system architecture deploys low-power IoT field nodes driven by ESP32 microcontrollers, integrated with capacitive soil moisture sensors, environmental sensors, and soil pH probes that stream telemetry data over lightweight MQTT protocols. To transition from reactive monitoring to proactive resource allocation, a cloud-based predictive engine utilizes Long Short-Term Memory (LSTM) neural networks to forecast 24-to-48-hour soil moisture depletion dynamics based on historical moisture profiles and localized meteorological factors. Experimental validation across a 90-day testbed demonstrates that the proposed predictive framework achieves a reduction in total water consumption while maintaining optimal volumetric soil water content. Furthermore, deep-sleep dynamic power profiling confirms node energy autonomy of up to 219 days on a single battery charge, presenting a scalable, sustainable, and economically viable solution for precision agriculture.

Keywords: Artificial Intelligence of Things (AIoT), Precision Agriculture, Smart Irrigation, Predictive Modeling, LSTM Neural Networks, MQTT, Energy Efficiency.

I. INTRODUCTION

Agriculture remains a fundamental pillar of global socio-economic stability. However, contemporary farming systems operate under compounding environmental and economic pressures. Erratic precipitation patterns, acute groundwater depletion, soil degradation, and rising labor expenses necessitate a paradigm shift from traditional intuition-guided farming to data-driven precision agriculture.

A. Problem Statement

Conventional irrigation techniques—ranging from manual flood irrigation to rigid, timer-automated systems—fail to adapt to real-time environmental dynamics and crop evapotranspiration variations. These conventional practices yield two critical failure modes:

- 1) Over-Irrigation: Induces root asphyxiation, promotes nutrient leaching into local watersheds, accelerates topsoil erosion, and unnecessarily consumes electrical energy via prolonged water pump cycles.
- 2) Under-Irrigation: Triggers severe drought stress, causes irreversible physiological damage, stunts crop growth, and drastically reduces harvest yields.

B. The Technological Solution: AIoT

The convergence of the Internet of Things (IoT) and Artificial Intelligence (AI)—collectively termed the Artificial Intelligence of Things (AIoT)—presents a transformative solution. While IoT provides the continuous physical sensing pipeline across farmlands, AI supplies the cognitive analytics needed to interpret temporal environmental dynamics, forecast future soil moisture states, and orchestrate autonomous, closed-loop irrigation actuation.

C. Research Contributions

This paper introduces an autonomous, closed-loop AIoT architecture for predictive soil moisture management. The key contributions of this work include:

- 1) **Hardware Architecture Design:** The engineering and deployment of a low-power, multi-sensor IoT node optimized for outdoor field conditions with dynamic power management.
- 2) **Mathematical & AI Modeling:** The implementation and formulation of an LSTM time-series predictive engine capable of anticipating soil moisture dry-downs 24 to 48 hours in advance.
- 3) **Energy Autonomy & Resource Efficiency:** Empirical validation demonstrating a reduction in water usage alongside a rigorous mathematical power analysis confirming long-term field node sustainability.

II. RELATED WORK

Existing literature in agricultural automation generally falls into three key architectural evolutionary phases:

- 1) **Threshold-Based Systems:** Early automation relied on basic relay drivers triggered when soil moisture dropped below a static threshold value. While reducing manual intervention, these systems lack adaptability to changing ambient microclimates, humidity fluctuations, or specific crop phenological stages.
- 2) **IoT Data Loggers:** Recent developments integrated cloud-connected microcontrollers (e.g., ESP8266, Arduino) to log sensor telemetry to remote dashboards using HTTP/REST or MQTT protocols. However, these implementations remain largely reactive, providing visual monitoring without automated predictive action.
- 3) **Predictive AI Frameworks:** Recent academic literature has explored standalone machine learning for crop yield or weather prediction. However, a gap remains in fully coupling real-time telemetry streaming with predictive neural networks in a low-latency, autonomous closed-loop actuator ecosystem.


The comparison in Table 1 summarizes the technological evolution and highlights the novelty of the proposed framework.

Table 1: Comparative Analysis of Agricultural Irrigation Frameworks

Feature / Metric	Traditional Threshold Systems	Reactive IoT Dashboards	Advanced ML (Standalone)	Proposed AIoT System
Control Logic	Static Hardcoded Rules	Manual / Static Web	Off-line Analytics	Autonomous Closed-Loop
Forecasting Horizon	None (0 Hours)	None (0 Hours)	24 Hours	24–48 Hours Predictive
Communication Protocol	Local Relay Wire	HTTP / REST	Batch Transfer	Lightweight MQTT
Water Reduction Efficiency	5% – 10%	15% – 20%	~22%	28% – 35%
Field Energy Autonomy	Poor	Average	Not Addressed	High (Deep Sleep + Solar)

III. SYSTEM ARCHITECTURE AND METHODOLOGY

The system operates as a three-tier closed-loop framework consisting of the Perception Tier, Network Tier, and Application/Intelligence Tier.



A. Hardware Layer (Perception Tier)

- 1) Microcontroller Unit: ESP32 chosen for its dual-core 240 MHz processing capability, integrated Wi-Fi/Bluetooth, dynamic clock scaling, and ultra-low-power (ULP) sleep functionality.
- 2) Soil Moisture Sensing: Capacitive soil moisture sensors measure volumetric water content (θ_v) via dielectric permittivity, avoiding the rapid electrolytic corrosion seen in resistive sensors.
- 3) Environmental Probes: A DHT22 sensor captures ambient air temperature and relative humidity, while a waterproof DS18B20 probe measures deep soil thermal dynamics.
- 4) Soil pH Sensor: Monitors localized soil acidity/alkalinity to track nutrient availability parameters.

B. Network Layer

Sensor measurements are serialized into compact JSON structures and transmitted over the Message Queuing Telemetry Transport (MQTT) protocol to an EMQX cloud broker. MQTT's minimal packet headers ensure low network bandwidth overhead and reliable delivery in rural cellular/Wi-Fi environments.

C. Intelligence Layer & Mathematical Framework

1) LSTM Network Formulation

The predictive backend utilizes a Long Short-Term Memory (LSTM) network to model non-linear temporal dependencies in soil water depletion. For a time step t , given input vector $\mathbf{x}_t$ (containing moisture, temperature, humidity, and rainfall forecasts) and previous hidden state $\mathbf{h}_{t-1}$, the gate mechanics operate as follows:

Where σ denotes the logistic sigmoid activation function, $\odot$ represents the Hadamard element-wise product, $\mathbf{W}$ represents the network weight matrices, and $\mathbf{b}$ represents the bias vectors.

2) Optimization & Evaluation Metrics

The predictive model accuracy is quantified using Root Mean Square Error (RMSE) and Mean Absolute Error (MAE):

IV. IMPLEMENTATION AND POWER ANALYSIS

A. Deployment Setup

The prototype was deployed over a 90-day seasonal crop cycle across a multi-zone agricultural testbed. Microcontroller firmware was developed in C++ within the Arduino framework, while the machine learning pipeline was built using Python (TensorFlow/Keras, Pandas, Scikit-Learn).

B. Power Consumption Analysis

To ensure reliable off-grid deployment, the node uses a cyclic duty-cycle operational strategy:

- 1) Active Phase (T_{active}): The ESP32 wakes up, powers sensor rails via MOSFET switches, collects samples, establishes an MQTT connection, publishes telemetry, and enters sleep.
- 2) Deep-Sleep Phase (T_{sleep}): All primary CPU cores, Wi-Fi radios, and external sensor power rails are powered down. Only the Real-Time Clock (RTC) timer remains active.
- 3) Mathematical Battery Longevity Calculation:

For a 30-minute sampling interval (Δt):

Given a standard Li-ion battery, the estimated operational lifespan without solar recharging is calculated as:

V. RESULTS AND DISCUSSION

A. Real-Time Telemetry Performance

Throughout the 90-day trial, the IoT nodes maintained stable continuous streaming without severe packet loss. Data visualization logged daily temperature peaks and localized irrigation infiltration spikes accurately.

B. Predictive Accuracy Evaluation

The LSTM predictive engine demonstrated strong performance on temporal soil moisture trends, outperforming basic linear regression and decision tree models:

- 1) LSTM Model RMSE: volumetric water content (θ_v)
- 2) LSTM Model MAE: By identifying moisture depletion trends up to 48 hours in advance, the framework initiated micro-irrigation events before crops reached their permanent wilting point (θ_{wp}).

C. Resource Conservation Impact

Comparing the proposed AIoT framework against traditional timer-based irrigation showed clear performance improvements:

- 1) Water Savings: A to reduction in total water volume applied.
- 2) Energy Minimization: Reduced pump run times lowered electrical utility costs proportionally.
- 3) Crop Stress Avoidance: Volumetric water content remained stable within optimal agronomic bounds (), preventing both drought stress and root rot from over-saturation.

VI. CONCLUSION AND FUTURE SCOPE

A. Conclusion

This paper presented an integrated end-to-end AIoT framework combining low-power hardware sensor nodes, lightweight MQTT communications, and cloud-based LSTM predictive neural networks for precision agriculture. By transitioning from reactive irrigation to data-driven proactive forecasting, the system addresses key agricultural water and energy management challenges. Experimental results confirm a reduction in water usage, high soil moisture prediction accuracy, and autonomous hardware battery performance of up to 219 days.


B. Future Scope

Future enhancements include:

- 1) Expanding field communication using LoRaWAN mesh topologies to cover large-scale commercial farms.
- 2) Incorporating multispectral aerial imaging (NDVI) from agricultural drones to validate canopy health metrics.
- 3) Implementing edge computing architectures to run lightened TensorFlow Lite models directly on local field microcontrollers.

REFERENCES

- [1] S. P. Sudha and J. B. Shajilin Loreto, "A review on machine learning-based precision agriculture techniques for crop farming monitoring with IOT," *Discover Environment*, vol. 4, article 10, 2026.
- [2] A. Goap, D. Sharma, A. K. Shukla, and C. Rama Krishna, "An IoT based smart irrigation management system using Machine learning and open source technologies," *Computers and Electronics in Agriculture*, vol. 155, pp. 41–49, 2018. DOI: 10.1016/j.compag.2018.09.040.
- [3] A. E. G. Anoop and G. Josemin Bala, "IoT and ML-based automatic irrigation system for smart agriculture system," *Agronomy Journal*, 2023. DOI: 10.1002/agj2.21344.
- [4] "Artificial intelligence of things (AIoT) for precision agriculture: applications in smart irrigation, nutrient and disease management," *Smart Agricultural Technology*, vol. 12, article 101629, 2025. DOI: 10.1016/j.atech.2025.101629.
- [5] "Advances in soil moisture measurement techniques and prediction using artificial intelligence: An extensive and systematic review," *Smart Agricultural Technology*, vol. 12, article 101613, 2025. DOI: 10.1016/j.atech.2025.101613.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)