



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 11 Issue: IV Month of publication: April 2023

DOI: https://doi.org/10.22214/ijraset.2023.50478

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



D-Drive: Decentralized Storage Space using Blockchain and IPFS Protocol

Smita Shinde¹, Anuj Srivastava², Dr. Piyush Samant³, Ananya Singh⁴, Siddharth Singh⁵, Ronak Chaudhary⁶ Apex Institute of Technology (CSE))Chandigarh University, Mohali, India

Abstract: Centralized cloud-based storage has received great attention and has been extensively used by many companies in recent years. However, these cloud based storage are not secure because of the involvement of a centralized entity or a third party. On the other hand, there is a need for blockchain based decentralized storage to maximize data privacy and security. This paper proposed D-Drive, an IPFS-based decentralized storage space to solve the problem. D-Drive is a software solution trying to prove that centralized cloud-based storage applications can be decentralized, more secure, and efficient. This paper proposed developing a web-based application that provides a user interface, from which the user can directly share their data or files. Then, the user file is encrypted and stored across a peer-to-peer network using IPFS protocol instead of HTTP protocol and a cryptocurrency will be used as a payment mechanism. D-Drive's primary objective is to provide secure decentralized storage space.

Keywords: Blockchain, Data Security, IPFS, Encryption, CloudStorage, Decentralized storage

I. INTRODUCTION

Nowadays, huge amounts of data are produced every day. To meet the increasing demand for data storage space, cloud-based centralized storage systems have been widely used in terms of data storage and sharing. Cloud drive lets anyone upload and transfer data or files to the cloud and share them with anyone. However, centralized cloud storage has a lot of disadvantages including data leaking or breaching by malware during the process and a proprietorship of data by a single entity that increases the chances of personal data being used by third parties for their analysis or personal use. We are all aware of information leakage cases of Facebook-Cambridge Analytica [15], [16] which motivates us to shift from centralized storage to a decentralized storage system.

Decentralization distributes data, applications, power, people, or things into a peer-to-peer rather than on a central authority. If a System is decentralized, it means that it is not controlled, or managedby a single entity or authority [5]. In addition, decentralization facilitates more benefits such as privacy, security, low price, and completely removing trust in a third party. Nowadays, the concept of Inter-Planetary File system (IPFS) [10], has been introduced. The Inter-Planetary File System (IPFS) is a version controlled decentralized file system that uses Distributed Hash Table (DHT) technology for storing data in a peer-to-peer network [7]. It enables us to store and share any type and size of data over a decentralized network without any limitations. Still IFPS needs lot of research to meet specific demands of real world problem, suchas how to allow users to share data for multiple users in different organizations without any trust issues [4]. To sort out above problem cryptographic techniques [3], have been widely used in traditional storage system. This paper proposed a data storage system named D- Drive that provides decentralized, secure, and transparent means of storing and sharing data. For that, we make the use of decentralized technologies to build this system. First, we rely on advantages of IPFS network to store data of users in a decentralized manner.





International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue IV Apr 2023- Available at www.ijraset.com



Fig. 2. Schema of decentralized storage system

II. PROBLEM IDENTIFICATION

Cloud-based storage pointed out the problem of data privacy and security, as there is an involvement of a centralized entity or a third party. The proposed system introduced the need for blockchain based decentralized storage to maximize the data privacy and security.

III. BACKGROUND

A. Blockchain Technology

There are three types of blockchain named as public, private, and consortium blockchain in decentralized systems [2]. The concept of cryptocurrency is more related to solving issues of a public blockchain. Blockchain [1], [4] is a collection of blocks, in which each block is composed by transactions and includes a hash of the previous block. Distributed technology provides immutability of the data because changing data in one block will affect all next blocks [8], and is beneficial for record-keeping, digital notary, and smart contracts [9]. This technology has been initially used for digital currency [6], and secure distributed transaction storage systems. Bitcoin is a great example of cryptocurrency. Ethereum[11], is another decentralized, open source, public platform based on blockchain technology. The structure of the Ethereum is almost similar to the other blockchain networks. It has a feature called a smart contract, which facilitates online contract agreements.

B. Smart Contract

A smart contract is a small piece of code that executes on the blockchain platform without the involvement of any third party. The platform includes a virtual machine - Ethereum Virtual Machine(EVM) [14], which can execute scripts using an Ethereum computer network.



Fig. 3. Schema of blockchain transaction

Ethereum has a cryptocurrency named "Ether" which can be transferred between accounts and used to pay miners as a gas feeto help with the calculations.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue IV Apr 2023- Available at www.ijraset.com

C. Distributed Systems and Hash Tables

Hash is the output of a hashing algorithm such as MD5 (Message Digest 5) or SHA (secure hash algorithm) [13]. It is used for several different areas such as cryptography and data indexing. A hash function generates a hash value that can only be decoded by looking up the value from a hash table. The table may be any data structure. Hash function is one-way and noninvertible.

A DHT is a distributed form of hash table. The main advantages of the DHT is that it makes blockchain faster as all nodes can be added or removed at a minimum time just by redistributing the keys [13].

D. IPFS

The IPFS (InterPlanetary File System) is a protocol for sharing and storing data on a peer-to-peer distributed network that uses DHT to track the information about data. Hash tables is used tostore a data package. Kademlia [12], is used to learn about data in nodes. Kademlia is a hash table for decentralized computer networks designed by Petar Maymounkov and David Mazi'eres in 2002. When we upload the data, a hash has been generated. IPFS stores the hash and then user can use the hash to get their data back. When datais uploaded on the IPFS network, the data will split into multiple pieces. These pieces of data are identified with its own hash.

IV. METHODOLOGY AND ARCHITECTURE

The proposed prototype enables user to upload the data or file to the peer-to-peer network. For that, the user need to configure blockchain network(Ganache is used for local blockchain network) and integrating it into the web browser using the Metamask extension.



Fig. 4. Architecture of D-Drive

From the fig 4. the user needs a blockchain network, which is provided by Ganache. The accounts provided by Ganache are added to Metamask for transaction purpose. A Specific amount of Gas is needed in the form of Ether. Ether is a type of crypto token that fuels the blockchain network. Then, the user need to create an account on metamask and connect it with their wallet. Now, as our Web browser supports blockchain network, we can now upload the files through our own designed user interface. When the user select the file to upload that file goes to the IPFS and IPFS returns a hash value that will mapped with smart contract. After that the user need to pay the gas amount from their metamask account. After the successful payment, the smart contract allows the file to get uploaded on a peer-to-peer network.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue IV Apr 2023- Available at www.ijraset.com

The process of retrieving the file from IPFS requires the previously obtained IPFS hash value, which is generated after uploading the file. We have to put the IPFS hash in the web browser, IPFS will search for the file, and preview is shown. Thus, the file is retrieved back from the IPFS System.

V. RESULTS AND ANALYSIS

This paper proposed developing a web-based application that provides a user interface, from which the user can directly upload or share their data and files over a decentralized network. The proposed solution works in multiple segments. *1*) Firstly, the user needs to create an account on metamask and login with their credentials.





Forgot password? Fig. 5. Metamask login interface

2) Then, the user needs to connect their metamask account with their wallet. The user's account address and wallet balance are fetched in the metamask account through web3.js



Fig. 6. Account balance fetched



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 11 Issue IV Apr 2023- Available at www.ijraset.com

3) After that, the user needs to open Dapp(D-Drive) and select the files to upload.



Fig. 7. User Interface

4) Further, the AES algorithm link the user wallet address as a key and encrypt the uploaded file. Payment dialogue box pop-ups for the payment confirmation.

We've updated customization v Turn on Enhance	how gas fee estimation and vorks. ed Gas Fee UI in Settings
ETAILS DATA	HEX
Total	0.00908504
Amount + gas fee	0.00908504 ETH Max amount: 0.00908504 ETH
Reject	Confirm

Fig. 8. Payment confirmation dialogue box

5) After the successful payment, the user's file stored on the peer- to-peer network using IPFS protocol. IPFS returns a hash value of the uploaded file, that will mapped with address using a smartcontract and get stored over a blockchain network.

##752	ty - Derly	e -					
		_					
			SUALS FILS				
		dess	riacies				
			Overse falle for falle character			1	
			and the second se				
				_	_		
		_					
	-	Brace Spillan	7,94	****	***	ng Tanadar Tutan	heat/steelige
	A NUMBER A NUMBER NUMBER AND	description to te	Ryse age a surface with operate formers of Type bound and the operation of the former		1000 1000 1000 1000 1000	ap lansa rutar	had relaying
	Lanta A rijetna Hijstikar Johis Kasti Maati Magi Kasti Magi Kasti	denari (pt sati Sa Sar Nasi perpari pal	For and states for any second formers offy stream and processing of course and assess you questificmers. Second second		600 0 0.00 00 0 0.00 0 0 0 0 0 0 0 0 0 0	19 basisteres	faatinine ge
	Name A rightne Trighter shore Name Name Name Name Name Name Name Name	drar (stat) Ta ter Tati (stat)	Egen Maria chartera fund general Antonia 1975 substances autoritarias de la decada María calacitado se van apacad noras a utorita calacitado se de paracetarias apartecidados que		6474 5.5.50 70 5.5.50 70 5.5.50 70 5.5.50 70 70 70 70 70 70 70 70 70 70 70 70 70		Badhraine gen Bernara - Bannara -

Fig. 9. File Uploaded with hash value

6) Further, if the user want to share their uploaded file, they just need to share the hash view with the other user, so that they can view or download by clicking it.

16	namo	description	type	91.04	ente	uploader/view	hash/wiew/get
4	4. Pythen thanter.aucx	fos bar	<pre>spplication/ved.epexem/formats- officedocument.wardprocessings1.document</pre>	41. NB	5:31:25 P8 b/16/2622	0x0xE25172	QuantineErj
2	Block Chain PisserPoint Templales.ppla	MLADY PROJECT DOT	application/ved.openexiformats. officedocument.presentational.presentation	2.18	5:35:43 98 6/18/2822	0+00035172	Qualificing for

Fig. 10. Hash value of a uploaded file



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue IV Apr 2023- Available at www.ijraset.com

type	size	date	uploader/view	hash/view/get
application/vnd.openvmlformats- officedocument.wordprocessingml.document	41 KB	5:31:25 PM 5/19/2022	6xCdE25172	QaNt7deEzj
application/vnd.opencelformatx- officedocument.presentationnl.presentation	3 MB	5:30:43 PM 5/19/2022	0xCdE25172	QaaLReigdv
application/pdf	410 KB	5:26:55 PM 5/19/2822	0xCdE25172	QwQ9CwC88T
image/jpeg	122 KB	5:25:43 PM 5/19/2022	6xCdt25172	QaQcSddUi4

Fig. 11. Hash value of a uploaded file

VI. CONCLUSION AND FUTURE SCOPE

This paper proposed an innovative IPFS based decentralized stor- age system named as D-Drive. The proposed system maximize the data security by distributing our data across peer-to-peer network in a decentralized manner. This system uses the IPFS protocol for ensuring the confidentiality of the user's data. Apart from these advantages, it needs certain level of improvement for accuracy and speed. In the proposed system, IPFS protocol is used, but if there is a better system in future, that can also be implemented.

REFERENCES

- [1] S. Nakamoto, "Bitcoin: A peer-to-peer electronic cash system," [Online; accessed 01 Nov. 2019]. Available: https://bitcoin.org/bitcoin.pdf.
- [2] Z. Zheng, S. Xie, H. Dai, X. Chen, and H. Wang, "An overview of blockchain technology: Architecture, consensus, and future trends," in IEEE International Congress on Big Data, 2017, pp. 557–564.
- [3] Y. Peng, W. Zhao, F. Xie, Z.-h. Dai, Y. Gao, and D.-q. Chen, "Secure cloud storage based on cryptographic techniques," Journal of ChinaUniversities of Posts and Telecommunications, vol. 19, pp. 182–189, 2012.
- [4] I.-C. Lin and T.-C. Liao, "A survey of blockchain security issues and challenges.," International Journal of Network Security, vol. 19, no. 5, pp. 653–659, 2017.
- [5] S. Wang, Y. Zhang, and Y. Zhang, "A blockchain-based framework for data sharing with fine-grained access control in decentralized storage systems," IEEE Access, vol. 6, pp. 38 437–38 450, 2018.
- [6] M. Conti, E. S. Kumar, C. Lal, and S. Ruj, "A survey on security and pri-vacy issues of bitcoin," IEEE Communications Surveys & Tutorials, vol. 20, no. 4, pp. 3416–3452, 2018.
- [7] E. Politou, E. Alepis, C. Patsakis, F. Casino, and M. Alazab, "Delegated content erasure in IPFS," Future Generation Computer Systems, vol. 112, pp. 956–964, 2020.
- [8] M. H. ur Rehman, K. Salah, E. Damiani, and D. Svetinovic, "Trust in blockchain cryptocurrency ecosystem," IEEE Transactions on Engineer-ing Management, 2019.
- [9] V. L. Lemieux, "Blockchain and distributed ledgers as trusted record- keeping systems: An archival theoretic evaluation framework," in Future Technologies Conference (FTC), vol. 2017, pp. 1–11, 2017.
- [10] J. Benet, "IPFS Content Addressed, Versioned, P2p File System," [Online; accessed 01 Nov. 2019]. Available: https://www.hirego.io/.
- [11] X. Xu, I. Weber, M. Staples, L. Zhu, J. Bosch, L. Bass, C. Pautasso, and P. Rimba, "A taxonomy of blockchain-based systems for architecture design," in International Conference on Software Architecture (ICSA), 2017, pp. 243–252.
- [12] P. Maymounkov and D. Mazieres, "Kademlia: A peer-to-peer informa- tion system based on the XOR metric," in International Workshop on Peer-to-Peer Systems, pp. 53–65, Springer, 2002.
- [13] I. I. Yiakoumis, M. E. Papadonikolakis, H. E. Michail, A. P. Kakaroun- tas, and C. E. Goutis, "Maximizing the hash function of authentication codes," IEEE Potentials, vol. 25, no. 2, pp. 9–12, 2006.
- [14] Y. Hirai, "Defining the ethereum virtual machine for interactive theorem provers," in International Conference on Financial Cryptography and Data Security, 2017, pp. 520–535.
- [15] J. Isaak and M. J. Hanna, "User data privacy: Facebook, cambridge analytica, and privacy protection," Computer, vol. 51, no. 8, pp. 56–59, 2018.
- [16] C. Cadwalladr and E. Graham-Harrison, "Revealed: 50 million facebookprofiles harvested for cambridge analytica in major data breach," The Guardian, vol. 17, p. 22, 2018.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)