iJRASET
International Journal For Research in Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 13 **Issue:** V **Month of publication:** May 2025

DOI: https://doi.org/10.22214/ijraset.2025.70231

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 13 Issue V May 2025- Available at www.ijraset.com

Deep-Learning Based Fundus Analysis for Early Detection and Management of Diabetic Retinopathy

Dr. D. Srujan Chandra Reddy[1], G. Suman[2]
[1]*Professor, Dept of CSE, PBR VITS, Kavali, AP-524201*
[1]*Assistant Professor, Dept of EEE, PBR VITS, Kavali, AP-524201*

Abstract: ***Diabetic retinopathy (DR) is a progressive condition that can cause vision loss. It starts out subtly and gets worse with time. It affects approximately 35% of people with diabetes worldwide. According to research, a new case of diabetic retinopathy is diagnosed every few minutes. In its early stages, retinal images are frequently difficult to recognize due to their complexity. In the area of medical imaging, Deep Learning is growing. Convolutional Neural Networks (CNN) and other architectures are used in this study to see how they can be used to accurately detect and classify the stages of diabetic retinopathy. Our approach utilizes publicly available datasets and several deep learning techniques are used to identify and categories the Fundus images into four stages of DR will be compared in this work. Model robustness is enhanced using data preprocessing methods like normalization, augmentation, and segmentation. The models are evaluated using performance metrics like accuracy, precision, recall, F1-score, and Area Under Curve (AUC). The results demonstrate that deep learning models can achieve high classification accuracy, outperforming traditional machine learning methods. Ophthalmologists may find it easier to comprehend model predictions if they are able to gain insight into the regions of interest that are essential for decision-making through visual interpretation of the models. This study underscores the potential of deep learning to revolutionize diabetic retinopathy diagnosis, offering a foundation for future research in integrating multi-modal data and real-world applications.***

I. INTRODUCTION

Diabetic Retinopathy (DR) is a progressive eye disease caused by long-term diabetes that damages the blood vessels in the retina, potentially leading to vision impairment or blindness.Itisoneoftheleadingcausesofvisionlossworldwide,affectingmillionsofpeople. Earlyand accuratediagnosis is crucial foreffectivemanagement and treatment, yet traditional diagnostic methods—such as manual examination of retinal images by ophthalmologists— often require expert interpretation and may not detect the disease in its early stages.

Recent advancements in deep learning, a subset of artificial intelligence (AI), have shown promising results in automating and improving the accuracy of diabetic retinopathy detection. Deep learning models, particularly Convolutional Neural Networks (CNNs) and Transformer-basedarchitectures, cananalyzecomplexretinalimages(fundusphotography)to identifyearlysignsofDR, suchasmicroaneurysms,hemorrhages,andexudates.Thesemodels extract patterns and features that might be imperceptible to human experts, allowing for faster and more reliable diagnosis.

Despite significant progress, challenges remain, including data scarcity, class imbalance,modelinterpretability ,andgeneralizabilityacrossdiversepopulationsandimaging conditions. Addressing these challenges requires interdisciplinary collaboration among ophthalmologists, data scientists, and AI researchers to develop more reliable and ethical AI- driven diagnostic tools.

This study explores the role of deep learning in diabetic retinopathy detection, highlightingdifferentmodelarchitectures ,datasets,preprocessingtechniques,andperformance evaluation metrics. The integration of AI in retinal imaging has the potential to revolutionize eye disease detection, improving early intervention strategies and patient outcomes.

Diabetic Retinopathy (DR) is a progressive eye disease caused by diabetes that affects theretinaandcanleadtosevere visionlossifnotdetectedearly.EarlydetectionofDRiscrucial for timely intervention and treatment, which can help prevent or delay vision impairment. Traditionaldiagnosticmethods,suchasmanualscreeningofretinalimages,canbeexpensive, time-consuming, and subject to variability in interpretation.

©IJRASET: All Rights are Reserved

Thechallengeistodevelopanaccurateandefficientmethodfordetectingdiabeticretinopathyatanearlystageusingretinalimages(fundusphotography).Machinelearninganddeeplearning models have shown promise in automating this detection by analyzing patterns in retinal images.

Thisprojectaims to:

1) Developamodelthatcanclassifyindividualsintothefivestagesofdiabeticretinopathy (no DR, mild, moderate, severe non-proliferative DR, and proliferative DR) using retinal imaging data.
2) Note: The original text mentions "four stages in Diabetic Retinopathy's disease," but this appears to be an error, as DR is typically classified into five stages.
3) Improvetheaccuracy andreliabilityofexistingdiagnosticmethods.
4) Provideanon-invasiveand cost-effectivesolutionforearly diagnosis.

II. OBJECTIVE

1) Thegoalofthisstudyistodevelopanefficientdeeplearning-basedmodelfortheearly detection of diabetic retinopathy using Xception Net. Diabetic retinopathy is a progressive eye disease that affects people with diabetes and can lead to vision loss. Early detection is crucial for timely treatment and preventing vision loss.
2) Building a deep learning model for the precise and early identification of diabetic retinopathy is the main objective of this work. The dataset, neural network (Xception Net),andweightparametersthatarelearnedduringtrainingmakeuptheessentialparts ofanydeeplearningmodel.Themodelisconstructedwiththemetricstoprovidegood accuracy.
3) The model will be tested on the test data after it has been created to determine its accuracy. Aftercomparing accuracy, the diseased imageis extracted from the data set. Thus, it is classified into four classes.
4) Early detection of diabetic retinopathy involves a multifaceted approach, incorporating regular eye exams, blood sugar control, and emerging AI technologies likeXceptionNet.Continuedresearchandadvancementsindiagnostictoolscontribute to improved accuracy, allowing for timely intervention and better patient outcomes.

III. EXISTING SYSTEM

Diabetic Retinopathy (DR) is a progressive eye disease caused by long-term diabetes that damages the blood vessels in the retina, potentially leading to vision impairment or blindness.Itisoneoftheleadingcausesofvisionlossworldwide,affectingmillionsofpeople. Earlyand accuratediagnosis is crucial foreffectivemanagement and treatment, yet traditional diagnostic methods—such as manual examination of retinal images by ophthalmologists— often require expert interpretation and may not detect the disease in its early stages.

DisadvantagesofExisting system:

1) Lower accuracy
2) DataQuality
3) Data integration
4) Data interpretability

IV. PROPOSED SYSTEM

This system will provide early detection, continuous monitoring, and personalized healthcarerecommendationsto patientswithafocusonimprovingthediagnosisandtreatmentjourney.Byleveragingcuttingedge AImodelsandhealthcareintegration,theproposedsystem intendstosupportbothcliniciansandpatientsinmakinginformeddecisionsregardingDiabetic retinopathy management.

AdvantagesofProposed system:

1) Multimodalintegration
2) AdvancedDeeplearningmodels
3) Higheraccuracy
4) Notification system

©IJRASET: All Rights are Reserved

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 13 Issue V May 2025- Available at www.ijraset.com

V. SYSTEM ARCHITECTURE




Fig.1: Architecture

1) User Input

- Usersuploadanretinaimagealongwiththeirnameand email.

2) Preprocessing& Prediction

- Theimageis resized to224x224 pixels and convertedto a normalized NumPy array.
- Thepre-traineddeeplearningmodel(model.h5)processestheimageandpredictsthe Diabetic Retinopathy's stage.

3) Prediction&Labelling

- Themodelreturnsprobabilitiesfordifferentstages-MildDR,ModerateDR,Proliferative-DR&SevereDR.

4) EmailNotification

- Thesystem generates adiagnosticreport.
- Aconfirmationemail withthe predictedstageissent tothe user.

5) APICommunication& Response

- Theresultis returnedasaJSONresponse.

VI. RESULTS AND DISCUSSIONS

- Home Page: Whenthecommandisexecutedinvscodeterminal,thehomepagewillbeopened. The home page has description about Diabetic retinopathy.
- AboutPage:TheAboutPageprovidesanoverviewofthewebsite,itspurpose,andkey features, offering users insight into its functionality and objectives.
- Predict:
- BeforePrediction:Beforeprediction,thesystemprocessestheuploadedretinaimageto prepare it for deep learning analysis.

SAMPLEFUNDUS IMAGES:




Fig 2:a.mild.png b. moderate.png

©IJRASET: All Rights are Reserved





Fig 3: a.Severe.png b.proliferative.png

- AfterPrediction:Afterprediction,thesystemgeneratesanddisplaystheDiabetic retinopathy's classification result based on the analyzed Fundus image.



- E-mailNotification:ThesystemsendsanemailnotificationcontainingtheDiabetic Retinopathy's prediction result to the user or healthcare provider.



VII. CONCLUSION

The development of a Diabetic Retinopathy Prediction System leveraging Deep Learning represents a major advancement in early detection and diagnosis. By employing the architecture and transfer learning, the system effectively analyzes retina images, accurately classifying diabetic retinopathy into distinct stages. It is essential to have this improved diagnostic precision in order to intervene promptly and prevent vision loss. Patients and medical professionals alike will have easy access thanks to the cloud-based deployment and user-friendly Streamlit integration. By optimizing the model's performance through precise hyperparameter tuning and rigorous data preprocessing, healthcare professionals are able to make more confident, well-informed decisions. Additionally, the system will provide email delivery via SMTP and automated report generation to facilitate prompt communication. Upon analysis, a detailed report summarizing the findings will be sent directly to the patient's and/or clinician's email inbox, ensuring timely access to critical diagnostic information. Future enhancements should focus on incorporating multimodal data, such as blood sugar levels, optical coherence tomography (OCT) scans, and comprehensive patient medical histories, to further enhance the system's efficacy.

©IJRASET: All Rights are Reserved

Integrating explainable AI (XAI) is also vital, providing transparent insights into the model's decision-making process, thereby fostering trust in automated diagnostics. In real-world clinical applications, scalability and sustained reliability are ensured by the system's ability to adapt to changing data through regular retraining and continuous monitoring.


VIII. FUTURE SCOPE

The Diabetic Retinopathy Prediction System holds a lot of potential for future developments. A key area for development is the integration of multimodal data, including patient medical history, blood glucose levels, and other clinical test results, to enhance diagnostic accuracy. By combining retina images with additional medical data, the system can deliver more precise and comprehensive predictions. In addition, incorporating real-time monitoring via wearable devices and IoT-based sensors may facilitate early intervention and individualized treatment plans by tracking disease progression. A significant enhancement involves refining the deep learning models, specifically leveraging the Xception Net architecture. Boosting prediction accuracy and reducing misclassification errors, this model excels at feature extraction from retina images. In addition, techniques known as explainable artificial intelligence, or XAI, can be incorporated to provide transparent reasoning for predictions, fostering trust and encouraging adoption among healthcare professionals. Remote diagnostics can also be made easier with cloud-based deployment, making the system accessible to rural and underserved areas. Moreover, the system can be expanded beyond Diabetic Retinopathy detection to identify other ocular diseases, such as glaucoma, macular degeneration, and cataracts. By retraining models on diverse datasets of retinal images and relevant medical records, the platform can evolve into a generalized ocular diagnostic tool. To ensure timely communication with patients, the system will incorporate SMTP functionality for automated email notifications, delivering diagnostic results and follow-up instructions directly to their inboxes. In order to guarantee the system's future scalability, dependability, and clinical relevance, collaborations with ophthalmology clinics and research institutions will further improve the quality of the dataset and make it possible to validate it in the real world.

REFERENCES

[1] Gulshan, V., et al., “A deep learning system for detecting diabetic retinopathy across the disease spectrum,” Nature Communications, 2021. https://www.nature.com/articles/s41467-021-23458-5
[2] Gargeya,R.,andLeng,T.,“AutomatedIdentificationofDiabeticRetinopathyUsing Deep Learning,” Ophthalmology, 2017. https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5961805/
[3] Abramoff, M. D., et al., “Improved Automated Detection of Diabetic Retinopathy on a Publicly Available Dataset Through Integration of Deep Learning,” JAMA, 2016. https://jamanetwork.com/journals/jama/fullarticle/2588763
[4] Reddy, G. T., and Khanna, P., “A Survey on Deep-Learning-Based Diabetic Retinopathy Classification,” Diagnostics, 2022. https://pmc.ncbi.nlm.nih.gov/articles/PMC9914068/
[5] Fong,D.S.,Aiello,L.,Gardner,T.W.,King,G.L.,Blankenship,G.,Cavallerano,J.D.,... AmericanDiabetesAssociation.(2003).Diabeticretinopathy.Diabetescare,26(suppl_1),s99- s102.
[6] Qiao, L., Zhu, Y., & Zhou, H. (2020). Diabetic retinopathy detection using prognosis of microaneurysm and early diagnosis systemfornon-proliferativediabeticretinopathy based on deep learning algorithms. IEEE Access, 8, 104292-104302.
[7] Sisodia, D. S., Nair, S., & Khobragade, P. (2017). Diabetic retinal fundus images: Preprocessingandfeatureextractionforearly detectionofdiabeticretinopathy. Biomedicaland Pharmacology Journal, 10(2), 615-626.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)