



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: VIII Month of publication: August 2022

DOI: https://doi.org/10.22214/ijraset.2022.46244

www.ijraset.com

Call: © 08813907089 E-mail ID: ijraset@gmail.com

Volume 10 Issue VIII August 2022- Available at www.ijraset.com

### Design and Analysis of Composite Structure for Industrial Platforms

Ratnadeep Rajendra Mane<sup>1</sup>, Dr. Digambar D. Date<sup>2</sup>

<sup>1</sup>Student, Mtech Mechanical Design, <sup>2</sup>Head, Department of Mechanical Engineering, TPCT College of Engineering Osmanabad

#### I. INTRODUCTION

This construction has often used in lightweight applications such as Lift, EOT crane beam, vehicle body, aircrafts, marine applications, wind turbine blades. In principle two approaches exist to develop efficient structures either application of new structural design. A proven and well-established solution is the use of sandwich structures. In this way high strength to weight ratio and minimum weight can be obtained. The sandwich structures have potential to offer a wide range of attractive design solutions. Sandwich panels in general can be classified as composite sandwich and metallic sandwich panels. Composite sandwich panels consist of non-metallic components such as FRP, PU foam etc. and are typically applied as load carrying structures in naval vessels and leisure yachts, and mainly as non-load carrying elements on merchant and large cruise ships. For metallic sandwich panels there are basically two types of panels: panels with metallic face plates and bonded core such as SPS panels and panels with both metallic face plates and core welded together. The metal material can be either regular, high tensile or stainless steel, or aluminum alloys. The choice of the core depends on the application under consideration. The standard cores such as Z-, tube- and hat profiles are easier to get and they are typically accurate enough for the demanding laser welding process. The special cores, such as corrugated core (V-type panel) and I-core, need specific equipment for production, but they usually result with the lightest panels




Figure. Different sandwich structure with various cores.

#### II. PROBLEM STATEMENT

The demand for bigger, faster and lighter moving vehicles, such as ships, trains, trucks and buses has increased the importance of efficient structural arrangements. In principle two approaches exist to develop efficient structures either application of new materials or the use of new structural design. A proven and well-established solution is the use of composite materials and sandwich structures. In this way minimum weight can be obtained. The sandwich structures have potential to offer a wide range of attractive design solutions. In addition to the obtained weight reduction, these solutions can often bring space savings, noise control. Steel sandwich panels can offer 10-25 % weight savings compared to the conventional steel structures.

#### III. EXPERIMENTATION

For the Experimentation the 3 types of geometry with particular specification are selected, by testing on UTM machine and software analysis the results are carried out. Following case study for experiment, for testing Triangular, Square and Circular geometry get Selected.



#### International Journal for Research in Applied Science & Engineering Technology (IJRASET)


ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue VIII August 2022- Available at www.ijraset.com

#### ANSYS Result Of All Structure Compare Between The Total Weight, Total Deformation And Equivalent Stress.

•	The Total Weight, Total Deformation	
Circular steel structure Case 1:	Triangular steel structure Case 2:	Rectangular steel structure Case 3:
Top Plate width (W): 103mm	Top Plate width (W): 103mm	Top Plate width (W): 103mm
Top Plate length (L): 103mm	Top Plate length (L): 103mm	Top Plate length (L): 103mm
Top Plate thickness (t): 3 mm	Top Plate thickness (t): 3 mm	Top Plate thickness (t): 3 mm
Bottom Plate width (W): 103mm	Bottom Plate width (W): 103mm	Bottom Plate width (W): 103mm
Bottom Plate length (L): 103mm	Bottom Plate length (L): 106mm	Bottom Plate length (L): 103mm
Bottom Plate thickness (t): 3 mm	Bottom Plate thickness (t): 3 mm	Bottom Plate thickness (t): 3 mm
Inner diameter of pipe (core) (di): 13 mm	Core material size: 25x25x3mm	Core Plate width (W): 19mm
Outer diameter of pipe (core) (do): 19	Top and Bottom plate, core material:	Core length (L): 103mm
mm	Steel Material	Core Plate thickness (t): 3mm
Length of pipe (core) (L): 103mm		Top and Bottom plate, core material:
Top and Bottom plate, Core material:		Steel Material
Steel Material		
Case Study:	Modulus of Elasticity (E): 2.1 * 10 <sup>3</sup>	
Rectangular steel structure:	kg/mm^2 (For steel)	structure by using following formula
Top Plate width (w): 103mm	Force $(F) = 10000N$	Stress = force/ Area
Top Plate length (L): 103mm	Top and Bottom plate material: Steel	6 = F/A
Top Plate thickness (t): 3 mm	Material:	=10000/1246
Bottom Plate width (w): 103mm	Fe 410 having UTS = 410 Mpa	= 8.02 N/mm^2
Bottom Plate length (L): 103mm	&	
Bottom Plate thickness (t): 3 mm	Syt = 235 Mpa	Einding Total deformation Destauration
Core Plate width (w): 19 mm		Finding Total deformation Rectangular
Core length (L): 103mm		Steel structure by using following
Core Plate thickness (t): 3 mm		formula.
		Total Deformation ( $\delta l$ ) = FL/AE
		=10000x100/1245x210x10^3
		=0.04mm

#### Applied force and obtained value of design characteristics using FEA for Triangular Steel Structure

Triangular Steel Structure				
Sr. No.	Force (N)	Equivalent Stress (Mpa)	Deformation (mm)	Weight (Kg)
1	500	4.3838	0.002225	
2	1000	8.7676	0.0044499	
3	1500	13.151	0.0066749	
4	2000	17.535	0.0088999	0.04672
5	2500	21.919	0.011125	0.94672
6	3000	25.828	0.01288	
7	3500	30.132	0.015027	
8	4000	34.437	0.017174	





Volume 10 Issue VIII August 2022- Available at www.ijraset.com

Applied force and obtained value of design characteristics using FEA for Circular Steel Structure

	Circular Steel Structure				
Sr. No.	Force (N)	Equivalent Stress (Mpa)	Deformation (mm)	Weight (Kg)	
1	500	0.59117	0.0056488		
2	1000	39.029	0.011301	-	
3	1500	58.544	0.016952	-	
4	2000	78.058	0.022603	0.06060	
5	2500	97.573	0.028254	0.86869	
6	3000	117.09	0.033904	1	
7	3500	136.6	0.039555		
8	4000	156.12	0.045206		

#### Applied force and obtained value of design characteristics using FEA for Rectangular Steel Structure

Rectangular Steel Structure					
Sr. No.	Force (N)	Equivalent (Mpa)	Stress	Deformation (mm)	Weight (Kg)
1	500	7.8382		0.0059418	
2	1000	15.676		0.011884	
3	1500	23.515		0.017826	
4	2000	31.353		0.023767	0.63795
5	2500	39.191		0.029701	0.03793
6	3000	47.029		0.035651	
7	3500	54.565		0.041593	
8	4000	62.706		0.047535	

#### IV. WEIGHT COMPARISONS OF ALL STRUCTURE

Weight comparisons of all structure

Sr. No.	Name of Structure	Weight (Kg)
1	Circular Steel Structure	0.86869
2	Triangular Steel Structure	0.94672
3	Rectangular Steel Structure	0.63795




Volume 10 Issue VIII August 2022- Available at www.ijraset.com

#### V. DEFORMATION COMPARISON OF ALL STEEL STRUCTURE

Deformation comparison of all steel structure in ANSYS

Sr. No.	Force (N)	Circular steel Structure (Deformation)	Triangular steel Structure (Deformation)	Rectangular steel Structure (Deformation)
1	500	0.0056488	0.002225	0.0059418
2	1000	0.011301	0.0044499	0.011884
3	1500	0.016952	0.0066749	0.017826
4	2000	0.022603	0.0088999	0.023767
5	2500	0.028254	0.011125	0.029701
6	3000	0.033904	0.01288	0.035651
7	3500	0.039555	0.015027	0.041593
8	4000	0.045206	0.017174	0.047535



Load vs. Deformation of steel structure by ANSYS

Series 1- Circular Structure

Series 2- Triangular Structure


Series 3- Rectangular Structure

#### VI. EQUIVALENT STRESS COMPARISON OF ALL STEEL STRUCTURE

Equivalent Stress comparison of all steel structure in ANSYS

Sr. No.	Force (N)	Circular steel Structure Equivalent Stress (Mpa)	Triangular steel Structure Equivalent Stress (Mpa)	Rectangular steel Structure Equivalent Stress (Mpa)
1	500	0.59117	4.3838	7.8382
2	1000	39.029	8.7676	15.676
3	1500	58.544	13.151	23.515
4	2000	78.058	17.535	31.353
5	2500	97.573	21.919	39.191
6	3000	117.09	25.828	47.029
7	3500	136.6	30.132	54.565
8	4000	156.12	34.437	62.706

Volume 10 Issue VIII August 2022- Available at www.ijraset.com




Force vs. Equivalent Stress of steel structure by ANSYS

Series 1- Circular Structure

Series 2- Triangular Structure

Series 3- Rectangular Structure

In above table shows the deflection, equivalent stress and self-weight of investigated Triangular, Rectangular and Circular composite structure and Triangular, Rectangular and Circular steel structure. The weight of composite structure is 0.785 kg is small as compare to the steel structure (weight of Mild steel plate of same thickness is 2.08 kg.) The Equivalent Stresses, Total deformation of Rectangular steel structure is also small as compare to Triangular, circular steel structure. From above table it is observed that the minimum stress and minimum deformation is observed in rectangular composite structure when it is compare with Triangular, Circular composite structure.



VII. UTM TESTING FOR EVERY GEOMETRY


For Circular Shape

Foe Square Shape

#### International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 10 Issue VIII August 2022- Available at www.ijraset.com



For Triangular Shape

#### VIII. CONCLUSION

The composite structure models in CATIA are efficiently imported into ANSYS workbench structural analysis is done and max stress and total deflection is observed.

For given span of the structure, decreasing the weight of composite structure also the strength increases and weight is reduced. The weight of composite structure is decrease of 19-40% as compares to steel structure. And also increases the strength of composite structure as compare to steel structure.

By comparing Triangular composite structure with Rectangular and circular composite structure it is observed that Triangular composite structure have minimum stresses and also have minimum deflection. As per maximum principal stress theory we get that all structure we select having within the limit of allow able stress so we take a structure with minimum weight is rectangular. So, rectangular structure is the perfect replacement for the traditional industrial crane base platform.

#### REFERENCES

- [1] A.Gopichand, Dr.G.Krishnaiah, B.Mahesh Krishna, Dr.Diwakar Reddy. V.N.L.Sharma, "Design And Analysis Of Corrugated Steel Sandwich Structures Using Ansys Workbench." International Journal of Engineering Research & Technology (IJERT) Vol. 1 Issue 8, October 2012.
- [2] Kamlesh G. Ambule, Dr. Kishor P. Kolhe, "FEM and Experimental Analysis of Stainless Steel Sandwich Panels for Weight Reduction", "IJIRST –International Journal for Innovative Research in Science & Technology Volume 3 | Issue 02 | July 2016 ISSN (online): 2349-6010.
- [3] Francois Cote, Russell Biagi b, Hilary Bart-Smith b, Vikram S. Deshpande, "Structural response of pyramidal core sandwich columns," International Journal of Solids and Structures 44 (2007) 3533–3556.
- [4] A.Gopichand, Dr.G.Krishnaiah, D.Krishnaveni, Dr.Diwakar Reddy.V, "Numerical simulation of steel sandwich plate system (sps) floor," International Journal of Innovative Research in Science, Engineering and Technology (An ISO 3297: 2007 Certified Organization) Vol. 2, Issue11, November 2013.









45.98



IMPACT FACTOR: 7.129



IMPACT FACTOR: 7.429



## INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call: 08813907089 🕓 (24\*7 Support on Whatsapp)