



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 11 Issue: V Month of publication: May 2023

DOI: https://doi.org/10.22214/ijraset.2023.51497

www.ijraset.com

Call: © 08813907089 E-mail ID: ijraset@gmail.com



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 11 Issue V May 2023- Available at www.ijraset.com

Design and Development of Deep Learning Based Model for Video Analysis

Safa Umatia¹, Tanisha Varshney², Neelam Yadav³, Ms. Veena Kulkarni⁴ Department of Computer Engineering, Thakur College of Engineering and Technology, Mumbai

Abstract: In order to analyze video streams and extract particular features or patterns, such as object recognition, motion detection, facial recognition, or behavior analysis, video analysis employs computer vision and machine learning techniques. Analyzing video footage to spot suspicious activity or items and locate people or vehicles is part of the process. This approach comprises keeping an eye on and controlling traffic at crossings, on roads, and in highways. It entails reviewing video footage to find traffic jams and overcrowding and to offer prompt alerts or suggestions for crowd management.

Keywords: Open CV, Real time, Video analysis, facial recognition, object recognition, feature Extraction

I. INTRODUCTION

In order to conduct their investigations, law enforcement officials frequently need to spend a significant amount of time manually reviewing CCTV material. In order to make their job easier, a video analysis system is required that can automatically scan through CCTV footage for known facilitators like criminals and potential suspects. This system aims to improve object tracking and detection accuracy both in real-time and using historical data. We are counting and locating recognized facilitators in addition to conducting real-time human detection. Real-time human detection uses either a live capture, static video, or snapshot for identification. We produce a report and analysis for it after detection.

II. LITERATURE SURVEY

Paper	Author & Year	Gap	Accuracy
Edge AI Face Recognition for	Rusoke, Blaise	Our system's pipeline makes use of a pre-trained anti spoof	94%
Public Transport Fare Payment	Marvin; Musinguzi,	model based off research by Costa et al. [7]. During our	
	Denis; Miyingo,	deployment tests, this model efficiency deteriorated with vari-	
	Simon Peter;	ations in lighting, and with low image quality	
	Katumba, Andrew	Our system's pipeline makes use of a pre-trained anti spoofmodel	
	(2022)	based off research by Costa et al. [7]. During ourdeployment tests,	
		this model efficiency deteriorated with vari-ations in lighting, and	
		with low image quality	
Face Recognition Method for	Sukmandhani, Arief &	further application development is expected by using	96.3%
Online Exams	Sutedja, Indrajani.	updated algorithms for face recognition with a higher degree of	
	(2019).	accuracy. Trials for this method are only carried out with the	
		same level of lighting, not yet done at different lighting levels	
		and distances	
		further application development is expected by using updated	
		algorithms for face recognition with a higher degree of accuracy.	
		Trials for this method are only carried out with the same level of	
		lighting, not yet done at different lighting levels and distances	
Our system's pipeline makes	HarikaPalivela,	If multiple cameras are used, additionally, the area or location	Our system's pipeline makes use of a
use of a pre-trained anti spoof	Lakshmi & P M,	at which the	pre-trained anti spoof
model based off research by	Ashok Kumar &	suspected individual was identified can also be included so as to	model based off research by Costa et
Costa et al. [7]. During our	Krishna, V.V (2022).	better facilitate the	al. [7]. During our
deployment tests, this model		authorities to apprehend that particular suspect. If a suspect is	deployment tests, this model efficiency
efficiency deteriorated with		identified for a	deteriorated with vari-
vari-		continuous protracted period of time, back-to-back emails will be	ations in lighting, and with low image
ations in lighting, and with low		sent to the authorities,	quality
image quality		which will lead to a spamming problem	98%
Smart Surveillance System		If multiple cameras are used, additionally, the area or location at	
Using Face and Optical		which the suspected individual was identified can also be	
Character Recognition for		included so as to better facilitate the authorities to apprehend	
Secure Environment		that particular suspect. If a suspect is identified for a continuous	
		protracted period of time, back-to-back emails will be sent to the	
		authorities, which will lead to a spamming problem	

Table 1: Literature Survey

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538


Volume 11 Issue V May 2023- Available at www.ijraset.com

III. METHODOLOGY

A. Proposed Work

This is a rudimentary flowchart for a computer vision-based people detection system:

- 1) Image or video Feed Capture: The system begins by taking a picture or video from a camera or sensor.
- 2) *Preprocessing:* To improve the quality of the collected image or video and get rid of noise or artefacts, the data is first processed.
- 3) Object Detection: In order to identify faces or human bodies in the image or video, the system uses an object detection technique like Haar cascades and Histogram Oriented Gradients.
- 4) Feature Extraction: The algorithm collects information including shape, size, color, and location after identifying human bodies or faces.



- 5) Classification: The system classifies the collected features as human or non-human using a machine learning method, such as support vector machines (SVM) or neural networks.
- 6) Alerting: If a human is found, the system notifies a monitoring station, security staff, or other pertinent parties by sending an alarm or notification.
- 7) *Tracking:* Using methods like optical flow or Kalman filters, the system may also follow the motion of any persons it has identified in an image or video over time.
- 8) *Post processing:* The system then applies postprocessing to the result, such as removing false positives or enhancing the precision of the categorization, and creates a final report.

When utilizing computer vision to recognize humans, preprocessing is crucial. These are a few typical preprocessing methods for human detection: Image normalization: is the process of enhancing an image's quality and making it better suited for human detecting algorithms by altering its brightness and contrast. Picture resizing: is the process of adjusting an image's dimensions while keeping its aspect ratio. When the image resolution needs to be changed to meet the specifications of the human detection algorithm because it is either too high or too low, this technique can be helpful. Noise reduction is essential for human detection systems because it gets rid of noise or other artefacts from an image or video input. The quality of the input data is increased by using methods like smoothing, median filtering, and Gaussian filtering to minimize noise.

Image enhancement By enhancing the contrast and edges in an image, one can make it simpler for human recognition algorithms to recognize the aspects of interest. Such approaches include contrast stretching, histogram equalization, and sharpness.

IV. RESULT

We have developed a system that can help identify known facilitators, and can identify human as well as keep a count of it. We have developed a interface where user can input image, video or he/she can make use of camera. After taking the input it's processes it, and extract features from it after which it detects the human.



Fig.2. Frontend of application



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue V May 2023- Available at www.ijraset.com




Fig.3. Frontend of human detection

Other then detecting humans, we have also developed a interface in which user can input image, and any video, after which our model will process through the video input and find that particular person in the video and will show the output in the form of image, with bounding boxes created on the person face.



Fig.4. Frontend interface of known facilitators

We have used haar cascade and histogram orientated gradient for human detection purpose, where as for face identification we have used OpenCV etc.




Fig.5. Frontend interface of detection page



Fig.6. Bounding Box



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue V May 2023- Available at www.ijraset.com



Fig.7.Human detection output

We are also generating crowd report which shows, maximum human count, average accuracy as well as maximum average accuracy in the end it's show's if the area is crowded or not as output.

This crowd report can be helpful for detecting crowded areas, and places.




Fig.8.Crowd Report Output




Fig.9. Accuracy Plot

V. CONCLUSION

The proposed system is vital in today's world. This system can be used for various purposes such as at public areas like streets, parks, transportation hub to get rid of crime as well as to assist in emergency response. People can use for their personal use to monitor any activity, prevent theft and vandalism, and ensure safety. Also this proposed system can help identify known facilitators in case of criminal identification, where police professional can input image and check in the surveillance video and identify the criminal.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue V May 2023- Available at www.ijraset.com

VI. FUTURE SCOPE

For future work, we can work more in image preprocessing as well improving our accuracy further. As well as we can work on to make a background running application could be made which keeps working without interfering and notifies when detects something abnormal. Accidents happening in public places could be detected. The model can further be trained in such a way that unusual events such as eve-teasing or involving any kind of violence could be detected. Can be used in the defense sector for security purposes.

VII. ACKNOWLEDGEMENT

We gratefully acknowledge our mentor Ms. Veena Kulkarni ma'am, for guiding and supporting us throughout this project work, as well as our Principal Sir, for providing us a platform to showcase our work.

REFERENCES

- [1] K. Jin, X. Xie, F. Wang, X. Han and G. Shi, "Human Identification Recognition in Surveillance Videos," 2019 IEEE International Conference on Multimedia & Expo Workshops (ICMEW), 2019, pp. 162-167.
- [2] L. Fu and X. Shao, "Reseach and Implementation of Face Detection, Tracking and Recognition Based on Video," 2020 International Conference on Intelligent Transportation, Big Data & Smart City (ICITBS), 2020, pp. 914-917.
- [3] Zafar, U., Ghafoor, M., Zia, T. et al. Face recognition with Bayesian convolutional networks for robust surveillance systems. J Image Video Proc. 2019, 10
- [4] Sathiyavathi, V., M. Jessey, K. Selvakumar, and L. SaiRamesh. "Smart Surveillance System for Abnormal Activity Detection Using CNN."Advances in Parallel Computing Technologies and Applications 40 (2021): 341...
- [5] S. Manna, S. Ghildiyal and K. Bhimani, "Face Recognition from Video using Deep Learning," 2020 5th International Conference on Communication and Electronics Systems (ICCES), 2020, pp. 1101-1106.
- [6] M. Khan, S. Chakraborty, R. Astya and S. Khepra, "Face Detection and Recognition Using OpenCV," 2019 International Conference on Computing, Communication, and Intelligent Systems (ICCCIS), 2019, pp. 116-119.
- [7] A. Bharadwaj K H, Deepak, V. Ghanavanth, H. Bharadwaj R, R. Uma and G. Krishnamurthy, "Smart CCTV Surveillance System for Intrusion Detection With Live Streaming," 2018 3rd IEEE International Conference on Recent Trends in Electronics, Information & Communication Technology (RTEICT), 2018, pp. 1030-1035.
- [8] A. Hampapur, L. Brown, J. Connell, S. Pankanti, A. Senior and Y. Tian, "Smart surveillance: applications, technologies and implications," Fourth International Conference on Information, Communications and Signal Processing, 2003 and the Fourth Pacific Rim Conference on Multimedia. Proceedings of the 2003 Joint, 2003, pp. 1133-1138 vol.2.
- [9] Sukmandhani, Arief & Sutedja, Indrajani. (2019). Face Recognition Method for Online Exams. 175-179. 10.1109/ICIMTech.2019.8843831.
- [10] Rusoke, Blaise & Musinguzi, Denis & Miyingo, Simon & Katumba, Andrew. (2022). Edge AI Face Recognition for Public Transport Fare Payment. 10.36227/techrxiv.21432000.
- [11] HarikaPalivela, Lakshmi & P M, Ashok Kumar & Krishna, V.V.. (2022). Smart Surveillance System Using Face and Optical Character Recognition for Secure Environment. 10.3233/APC220054.
- [12] Sathiyavathi, V. & M, Jessey & Kamalanathan, Selvakumar & Lakshmanan, Sairamesh. (2021). Smart Surveillance System for Abnormal Activity Detection Using CNN. 10.3233/APC210157.
- [13] Dragos D. Margineantu, Weng-Keen Wong, and Denver Dash "Machine learning algorithms for event detection", 2010.
- [14] Lin Wang, Fuqiang Zhou, Zuoxin Li, Wangxia Zuo, and Haishu Tan "Abnormal Event Detection in Videos Using Hybrid Spatio-Temporal Autoencoder", 25th IEEE International Conference on Image Processing, 2018.
- [15] Roberto Levya, Victor Sanchez, and Chang-Tsun Li "The LV dataset: A realistic surveillance video dataset for abnormal event detection", 5th International Workshop on Biometrics and Forensics (IWBF), 2017.
- [16] Waqas Sultani, Mubarak Shah, and Chen Chen "Real-world Anamoly Detection in Surveillance Videos", CVPR, 2018.
- [17] Dinesh, S. & Kavitha, A.. (2023). Development of Algorithm for Person Re-Identification Using Extended Openface Method. Computer Systems Science and Engineering. 44. 545-561. 10.32604/csse.2023.024450.
- [18] T. Baltrušaitis, P. Robinson and L. P. Morency, "3D constrained local model for rigid and non-rigid facial tracking," in IEEE Conf. on Computer Vision and Pattern Recognition, USA, pp. 2610–2617, 2012.
- [19] M. R. Golla and P. Sharma, "Performance evaluation of facenet on low-resolution face images," in Int. Conf. onCommunication, Networks and Computing, Gwalior, India, pp. 317–325, 2018.
- [20] T. Baltrušaitis, P. Robinson and L. P. Morency, "Openface: An open source facial behavior analysis toolkit," in IEEE Winter Conf. on Applications of Computer Vision (WACV), NY, USA, pp. 1–10, 2016.
- [21] A. Fydanaki and Z. Geradts, "Evaluating OpenFace: An open-source automatic facial comparison algorithm forforensics," Forensic Sciences Research, vol. 3, no. 3, pp. 202–209, 2018.
- [22] K. Santoso and G. P. Kusuma, "Face recognition using modified open face," Procedia Computer Science, vol.135, pp. 510-517, 2018
- [23] K. Zhang, Z. Zhang, Z. Li and Y. Qiao, "Joint face detection and alignment using multitask cascadedconvolutional networks," IEEE Signal Processing Letters, vol. 23, no. 10, pp. 1499–1503, 2016.
- [24] M. Zeng, C. Tian and Z. Wu, "Person re-identification with hierarchical deep learning feature and efficient xqdametric," in Proc. of the 26th ACM Int. Conf. on Multimedia, Seoul Republic of Korea, pp. 1838–1846, 2018.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 11 Issue V May 2023- Available at www.ijraset.com

- [25] W. Li, X. Zhu and S. Gong, "Person re-identification by deep joint learning of multi-loss classification," in Proc.IJCAI-26, Melbourne, Australia, pp. 2194–2200, 2017.
- [26] S. Li, S. Bak, P. Carr and X. Wang, "Diversity regularized spatiotemporal attention for video-based person re-identification," in Proc. of the IEEE Conf. on Computer Vision and Pattern Recognition, San Juan, PR, USA,pp. 369–378, 2018.
- [27] W. Zhang, S. Hu, K. Liu and Z. Zha, "Learning compact appearance representation for video-based person re-identification," IEEE Transactions on Circuits and Systems for Video Technology, vol. 29, no. 8, pp. 2442–2452, 2018.
- [28] N. McLaughlin, J. M. Del Rincon and P. Miller, "Recurrent convolutional network for video-based person re-identification," in Proc. of the IEEE Conf. on Computer Vision and Pattern Recognition, Las Vegas, NV, USA,pp. 1325–1334, 2016.
- [29] Z. Zhou, Y. Huang, W. Wang, L. Wang and T. Tan, "See the forest for the trees: Joint spatial and temporal recurrentneural networks for video-based person reidentification," in Proc. of the IEEE Conf. on Computer Vision and Pattern Recognition, Honolulu, HI, USA, pp. 4747–4756, 2017.
- [30] D. Ouyang, J. Shao, Y. Zhang, Y. Yang and H. T. Shen, "Video-based person re-identification via self-pacedlearning and deep reinforcement learning framework," in Proc. of the 26th ACM Int. Conf. on Multimedia, Seoul Republic of Korea, pp. 1562–1570, 2018.









45.98



IMPACT FACTOR: 7.129



IMPACT FACTOR: 7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call: 08813907089 🕓 (24*7 Support on Whatsapp)