



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 12 **Issue:** IV **Month of publication:** April 2024

DOI: <https://doi.org/10.22214/ijraset.2024.59913>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

Design and Fabrication of Shrink Wrapping Machine

Dr. P. G. Mehar¹, Suraj Dhande², Bhavesh Hatzade³, Rohan Mankar⁴, Atharv Meshram⁵, Vivek Binzade⁶

¹Asst. Professor, ^{2, 3, 4, 5, 6} Students, Dept. Of Mechanical Engineering K.D.K. College Of Engineering, Nagpur, Maharashtra, India

Abstract: In order to handle most of the products like cloth peg, container, hanger, tooth brush, shaving blades, heavy duty cell etc. shrink wrapping machine is universally used. By shrink wrapping of the products, it is possible to handle the products conveniently, it makes the packing attractive, it is very convenient during transport also. An attempt is made here to discuss the development and design of shrink wrapping machine for cloth peg. The various components of machine are geared d.c. motor, sprocket, chain, rollers, heater, structure etc.

Keywords: Shrink Wrapping Machine, Shrinkage Film, Polymer, Polythene

I. INTRODUCTION

Shrink wrapping machine is a device that wraps a product with heat shrinkable film, then heats and shrinks the film to wrap around the product. Automatic shrink packaging machine is mainly composed of wrapping machine, heat shrinkage channel conveying device, etc. The conveying device conveys the packaged goods to be wrapped and sealed in shrinkable material packing film according to package specifications, before they pass through the heat shrinkable channel. Such films revolve tightly around the products and pack it properly. It is also expected that quality of shrink wrapping will be excellent as there will be uniform heating of the packet. In shrink wrapping, a shrink film i.e. polyvinylchloride (PVC) is used as basic material and heat forms an important part of the operation. Shrink wrapping is done in 4 stages namely wrapping, sealing, shrinking and cooling. When the film is stretch axially oriented in one direction while it is heated then it is randomly twisted and inter twined molecules lineup.

II. LITERATURE REVIEW

- 1) *Design and Development of Shrink Wrapping Machine for Wrapping of Cloth Peg:* In order to handle most of the products like cloth peg, container, hanger, tooth brush, shaving blades, heavy duty cell etc.^[1] shrink wrapping machine is universally used. By shrink wrapping of the products, it is possible to handle the products conveniently, it makes the packing attractive, it is very convenient during transport also. An attempt is made here to discuss the development and design of shrink wrapping machine for cloth peg. The various components of machine are geared d.c. motor, sprocket, chain, rollers, heater, structure etc.
- 2) *Design And Analysis Of Multipurpose Conveyor For Shrink Wrapping Machine:* Conveyor units play an important role in packaging industries for material handling purpose.^[2] Different type of conveyors are using for industrial application now-a-days like belt conveyors, screw conveyors, bucket conveyors etc. This paper mainly focus on the design & analysis of a multipurpose conveyor system for shrink wrapping machine which can adjust its length, height used as powered & gravity type.
- 3) *A Categorical Review of Shrink Wrap Packaging:* In this paper, in order to carry out in-depth study regarding shrink wrap packaging, generalized design of shrink wrap packaging machine.^[3] properties of shrinkable film and research methodology and exhaustive literature review is carried out and is presented in this paper.

III. SPECIFICATION OF SHRINK WRAPPING MACHINE

- 1) *Gear D.C motor :*
 - Torque - 10 Nm
 - Power - 100 Watt
 - Speed - 60 Rpm
 - 24 V Dc
- 2) *A.c to D.c convertor :*
 - It convert A.c current to D.c current.

- Provide D.c to motor.

3) Heater:

- Motor Speed 3000 Rpm
- Capacity – 100 Watt coil
- 90-350 kw Heat Is Produce
- Blower fan motor speed 3000rpm

4) Adjustable Settings:

- Temperature control for sealing.
- Conveyor speed adjustment.
- Shrink time and temperature settings.

5) Control System:

- Manual & semi-automatic

6) Optional Features:

- Print registration for printed films.
- Automatic film feed.
- Film perforation devices

7) Conveyor System:

- Conveyor chain speed and type.

Typical Shrink Film Properties

Film type	Tensile Strength psi (mpa)	Elongation (%)	Tear Strength gf / mil (m N / M)	Maximum Shrink %	Shrink Tension psi (MPa)	Film Shrink Temperature Range °F(°C)
Polyethylene (low density)	9000(62)	120	8(3.1)	80	250 – 400 (1.7-2.8)	150 – 250 (65 – 120)
Polyethylene (low density irradiated)	8000-13000	115	5-10 (1.9 – 3.9)	80	400 (2.8)	170 – 250 (75 – 120)
Polyethylene (copolymer)	19000(131)	130	7 (2.7)	50	450 (3.1)	180 – 260 (85 – 125)

IV. DESIGN OF VARIOUS COMPONENTS

After carrying out type synthesis, design of various components of shrink wrapping machine for cloth peg is carried out. Various components are geared D.C motor. motor, sprocket, chain, roller, heater. Initially process force is estimated and based on the process force remaining components are designed. Various stresses coming are shear stress, tensile stress, bending stress etc. The design procedure is mentioned as below:

- 1) Process force is estimated and considered by taking into account friction, maximum expected load as 1200N. How ever weight of one packet is 1.5N and such 10 packets are placed at a time. Thus total weight of 15 N is placed on rollers. The system process force is1200N, hence it is safe

2) Torque required(T)= F*r

Where F = force on roller = 1200 N ,r = outer radius of roller = 13 mm,

Speed of motor (N)= 300rpm

$T=1200*13=15600 \text{ N-mm} =15.6 \text{ N-m}$

Thus, power = $2*\pi*N*T/60 = 471 \text{ W}$

Assuming standard power (pR)as350W

3) Design of chain drive

Design power (PD) = PR *K1 = 350 * 1.0 = 350 W

Where K1 = Load factor (1.0 for uniform and for 10hrs of service)

Pitch line velocity (V) = R * ω

Where R = pitch radius of Sprocket = 20 mm

ω = angular velocity of sprocket = $2*\pi*N/60 = 5.235 \text{ V}$ =

$0.02 * 5.235 = 0.1047 \text{ m/s}$




Fig-1: Roller chain

4) Tooth load (FT) = PD / V = 35 / 0.1047 = 3342.2 N = 3.35 KN

5) Power capacity of roller chain $P = p_2 * \{V/104 - V^{1.41}/526*(26-25\cos(180/t)) * KC$

Where KC =1 (Capacity factor for number of strands)

$P = 12.5 * \{0.1047/104 - 0.1047^{1.41}/526*(26-25\cos(180/10))\}$ =

0.129 W

6) Length of chain in pitches (L) = $(T_1+T_2) / 2 + 2*C/P + P*(T_1 - T_2) / 40*C$

Where $T_1 \& T_2 = t = 10$ $L = 20/2 + (2*700) / 12.5 = 122 \text{ mm}$

Therefore, total chain length = 122*pitch 1525 mm

7) Pitch Diameter of sprocket = $P / \sin(180 / t) = 12.5 / \sin(180 / 10) = 40.45 \text{ mm}$ Sprocket teeth design

- Width of sprocket (T0) = $0.58*P - 0.15 = 0.58*12.5 - 0.15 = 7.1 \text{ mm}$
- Outside Diameter (D0) = $P*[0.6 + \cot(180 / 10)] = 46 \text{ mm}$
- Root Diameter = DP = $0.0625P = 32 \text{ mm}$
- Pitch circle diameter of sprocket = 40 mm
- Pitch of sprocket (P) = 12.5,
- No of teeth (t) = 10




Fig -2 : Sprocket wheel

- 817

VI. FOLLOWING PLASTICS FILMS ARE COMMONLY USED FOR SHRINK AND STRETCH WRAPPING

- 1) Polyethylene • Used almost exclusively or as a combination of LDPE + co-polymers EVA (ethylene vinyl acetate) or EEA (ethylene ethyl acrylate).
- 2) Copolymer Modification: LDPE is sometimes modified by addition of EVA and EEA (up to 8%). EVA is approved by US-FDA for direct contact with food. EEA is approved up to 7% for direct contact with food. However, Vinyl Acetate (VA) or Ethyl Acrylate (EA) content is normally restricted to 3-4%.
- 3) Irradiated polyethylene film containing EVA, shrinks strongly in boiling water and is generally used for wrapping chickens.
- 4) Used for foodstuffs (e.g. meat and vegetables). Both are also used for non-food applications, where increased transparency and gloss justify the increased price in comparison with LDPE.

VII. CONCLUSION

After determining dimension by carrying out design of various components, the shrink wrapping machine is fabricated. Trials and testing is carried out in order to make the machine refined.

- 1) The System Process Force Is 1200N.
- 2) Tooth Load (Ft) N = 3.35 Kn.
- 3) Total Chain Length = 122*Pitch 1525 Mm.
- 4) Total Electrical Power Consumption Is 3 Unit Per Hour By Heater.

REFERENCES

- [1] K.A.Vanalkar, R.H.Parikh. Design and Development of Shrink Wrapping Machine for Wrapping of Cloth Peg
- [2] Cherian Johny, Rajesh R. Design and Analysis of Multipurpose Conveyor for Shrink Wrapping Machine
- [3] K.A.Vanalkar, R.H.Parikh .A Categorical Review of Shrink Wrap Packaging
- [4] Zehra S.Kalkan-Sevinc, Caitlin T. Strobel, (2015). Material Characterization of Heat Shrinkable Film. Journal of Testing and Evaluation. Volume 43, Issue 6.
- [5] Pejman Hadi, A.A. babuluo, (2017). Additives effects on the shrinkage behavior of PVC sheets. Journal of Applied Polymer Science. Volume 106, Issue 6, pages 3967-3974.
- [6] Bhagwat Kumar and S.Patel, (2018). Application of Different Flexible Films in Shrink Wrap Packaging Machine for Packing of Tamarind (Tamarindus indica L.) Pulp Briquettes. Advances in Life Sciences 7(1) Print: ISSN 2278-3849, 5759.
- [7] Thakur, A. K., Kumar, R., Bhushan Shambhu, V., & Shekhar Singh, I. (2017). Effectiveness of Shrink-wrap Packaging on Extending the Shelf-life of Apple. International Journal of Current Microbiology and Applied Sciences, 6(12), pages 3365–3374.
- [8] Rajinder Kumar Dhall, Sanjeev R.Sharma, B. V. C. Mahajan, (2012). Effect of shrink wrap packaging for maintaining quality of cucumber during storage. Journal of Food Science and Technology. Volume 49, Issue 4, pages 495- 499.
- [9] Dr. Han Chi-Yeh (2003). A general method for the optimum design of mechanisms. Journal of Mechanisms Volume 1, Issues 3–4, Pages 301-313.
- [10] Sivam Krish, (2011). A practical generative design method. Journal Computer-Aided Design. Volume 43, issue 1, pages 88-100.
- [11] P.G.Maher formulation of mathematical model, design of experimentation, optimization and investigation of parameters for integrated bamboo processing machine” IJETT, vol.3, issue 2, July 2016.
- [12] P.G.Maher “ formulation of mathematical model and investigation of parameters for integrated bamboo processing machine” IJNTSE, vol.2, issue 4, oct 2015
- [13] P.G. Maher “ design of experimentation, Artificial neural network simulation and optimization for integrated bamboo processing machine” IJERA, vol.5, issue 11, January 2015, pp 23-29



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)