



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: V Month of publication: May 2022

DOI: https://doi.org/10.22214/ijraset.2022.42429

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



Design and Implementation of Juicer Using BLDC Motor

Tushar Mahakalkar¹, Tilak Uikey², Priya Hatwar³

^{1, 2, 3, 4, 5, 6}Student, Department of Electrical Engineering, KDK College of Engineering, Maharashtra, India ⁷Prof. Dr. G. H. Agrawal, KDK College of Engineering, Maharashtra, India

Abstract: In a present scenario, the usage of energy efficient appliances is occupying the market to deal with the problem of increasing energy demand. The mixture with universal motor having commutator brush assembly cause sparking and increase the chances of maintenances results in reduction of lifespan all the above problem can eliminated by use of BLDC motor for Juicer. So the BLDC motor is suitable for mixture grinder because it is capable to give easy speed torque control and it is compact in size. Application of a mixture grinder to the performance and losses analysis of a conventional universal motor and proposed BLDC motor, it has lower power consumption compared to the existing universal motor available. Keywords: BLDC-Brushless DC Motor, Universal Motor, Conventional Mixer, Energy Savings, Fossils Fuels

I. INTRODUCTION

Now a days, the usage of energy efficient appliance is occupying the market to deal with the problem of increasing energy demand, thus fossil fuel scarcity. In home appliances induction motor and universal motor because it takes very high current at start can cause of voltage sag. It will cause malfunctioning of other appliances in home. Universal motor having commutator assembly, cause sparking and increase chances of maintenance results in reduction of life span. Fine speed control is difficult as the tapped windings are provided at stator. The mixers with universal motor are difficult to use with UPS system because of high starting current. All the above problems can be eliminated by using BLDC motor for juicer.

BLDC motors are very small in size. BLDC is capable of give the easy speed-torque control required for mixer. Electronic commutation increases the efficiency and reliability of operation. Some of the applications required the lower speed for mixing it can be achieved by this motor. Efficiency verses torque characteristics is nearly flat. Energy saving can be achieved at any torque and speed. These advantages makes possible to use the BLDC Motor for juicer.

II. NEED OF SYSTEM

A study by Berkeley National Laboratories calculates that 33% of energy savings could be achieved when AC appliances are replaced with high-efficiency DC appliance. In a system with DC sources, and DC appliances, energy saving of 47% could be achieved. Universal motor employed in mixers can work on DC supply, but it is very inefficient because of mechanical commutator and brushes. In addition, it draws high starting current. So in place of universal motor, BLDC (Brushless Direct Current Motor) is used in mixer grinder, it saves abundant energy.

III. WHY BLDC?

The brushes in universal motors wear out over the time and may cause sparking. This is illustrated . As a result the universal motors require occasional maintenance. Controlling the brushes spark is also a difficult affair. Thus the brushed motor should never be used for operations that demand long life and reliability. For this issue and the other issues listed in the introduction, BLDC motors are used in most of the modern equipment. Efficiency of BLDC motor is typically around 85-90%, whereas the brushed motors are only 75-80% efficient. BLDC motors are also suitable for highspeed appliances (10000 rpm or above). The BLDC motors are also well known for their better speed control and efficiency.

A. Brushless DC Motor is More Efficient

While converting electricity into mechanical power, brushless motors are more efficient than brushed motors primarily in that there is brushes which reduces mechanical energy loss due to friction. BLDC motors are also suitable for high speed appliances. Motor has the 3000 rpm speed at full load. According to the requirement of load it can vary by using speed regulator provided with controller of motor. On load the slightly change in speed with respect to the standard speed. BLDC has good speed regulation. Motor has 300Watt maximum power .The BLDC motors are also well known for their better speed control.



IV. COMPONENTS



A. SMPS

SMPS stands for switching mode power supply. SMPS is an electronic power supply system that makes use of a switching regulator to transfer electrical power effectively.



B. Regulator IC

The 7805 voltage regulator is a three-terminal voltage regulator IC. In various applications, A voltage regulator maintains the output voltage at a constant value.



C. Controller

A device that controls the flow of electrical power to a motor and used to control speed .





International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue V May 2022- Available at www.ijraset.com

D. Arduino UNO

It is main controller belongs to Arduino family. which is used to control the signal received from any input voltage source like sensor and transmitter/receiver module. It is attached LCD display to show the command.









Front View

HD44780 Controller Auxiliary Controller



Back View



F. BLDC Motor



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue V May 2022- Available at www.ijraset.com

V. SPECIFICATIONS OF MOTOR

Motor has the 3000 rpm speed at full load. According to the requirement of load it can vary by using speed regulator provided with controller of motor. On load the slightly change in speed with respect to the standard speed. BLDC has good speed regulation. Motor has 1200 Watt power and operated at 12V dc supply.

Sr. No	Parameter	Value
1	Operating Power	120 W
2	Operating Voltage	12 V
3	Current	10A
4	No Load Speed	3000 RPM
5	Rated Speed	2750 RPM
6	Rated Current	6A
7	Maximum power	300W
8	Weight	2.56 Kg
9	Efficiency	>= 78%
10	Length(mm)	108

Table -1: Motor Details

VI. BLOCK DIAGRAM AND SPEED CONTROL



Fig.1 Block Diagram

For household purpose single phase 230V AC supply is available, but the motor needs 12V DC supply for operation. First need to step down the voltage to 12V AC, for this operation 230/12V, 10A SMPC is connected to supply mains. For this operation we need DC then AC to DC conversion is done by bridge rectifier unit. The rectifier gives the 12V DC at output. Then this 12V DC is given to the input to the controller which drives the motor.



The speed of the BLDC motor can be controlled by different methods like input voltage control, PWM control.

Sr.	Feature	BLDC	Universal				
No		Motor	Motor				
1.	Commutation	Electronic	Mechanical				
		commutation	brushes and				
		based on	commutator				
		rotor					
		position					
		information					
2.	Efficiency	High	Moderate				
3.	Thermal	Better	Good				
	performance						
4.	Maintenance	Little/None	Periodic				
5.	Speed/Torque	Flat	Moderately				
	Characteristics		flat				
6.	Speed Range	High	High				
7.	Lifetime	Long	Short				

Table -3.	Comparison	with	Existing	System
rable 5.	Comparison	withi	LAISting	by stem

VII. FUTURE SCOPE

In the future all AC equipment replaced by the DC equipment because in the DC equipment the power loss is low as compare to the AC equipment so BLDC motor can be used in juicer. Also the use of Photovoltaic cells goes on increasing, so the juicer+ with BLDC motor can directly operate on DC supply without any converting devices and also the energy saving is achieved by use of energy efficient BLDC motor. This is a main reason of representing this paper.

VIII. CONCLUSION

In the project, in order to provide an efficient alternative to universal motor in a juicer, design of a low cost ferrite magnet based BLDC motor is carried out. It is found that, iron and copper losses are just 5.1%. BLDC motor can operate at DC supply and because of efficient design, it consumes very less power than universal motor. Thus, it is suitable for operation with the DC distribution system. In addition, its size is smaller than universal motor.

REFERENCES

- [1] V. Gholase, B. G. Fernandes, "Design of efficent BLDC motor for DC operated mixer rinder", IEEE ICIT. Conf, 17-19 Mar 2015.
- [2] D Kamalakannan, N Jeyapaul Singh, M Karthi, V Narayanan and N S Ramanathan "Design and development of DC powered BLDC motor for Mixer-Grinder application," IEEE Energy 2030, Atlanda USA, 978-1-5090-34987/16/\$31.00 ©2016 IEEE, Nov, 2006.
- [3] Mohammed Fazil and K R Rajagopal, Senior Member, IEEE, "Development of External Rotor Single-Phase PM BLDC Motor Based Drive for Ceiling Fan", IEEE ICIT Indian Institute of Technology Delhi, New Delhi 110016, India
- [4] M A Rodriguez Otero, E O Neill- Carrillo, "Efficient home appliences for a future DC residence," IEEE Energy 2030, Atlanda USA, 17-18, Nov, 2008.
- [5] Y.B. Adyapaka Apatya, Aries Subiantoro and Feri Yusivar "Design and Prototyping of 3-Phase BLDC Motor" Electrical Engineering Department, Universitas Indonesia, Depok 16424, Indonesia 2017 15th Intl. Conf. QiR: Intl. Symp. Elec. and Com. Eng
- [6] S Ekram, N Ravi, K R Rajagopal, D Mahajan, "Design and development of a high efficiency switched relutance motor for a mixer grinder application", IEEE Industrial Electronic society IECON, Taiwan, Nov 5 -8, 2007, pp 193-197.
- [7] G.Santhosh Kumar, S.Arockia Edwin Xavier "BRUSHLESS DC MOTOR SPEED CONTROLUSING MICROCONTROLLER" ISSN (PRINT): 2393-8374, (ONLINE): 2394-0697, VOLUME-2, ISSUE-2,2015











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)