



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: III Month of publication: March 2022 DOI: https://doi.org/10.22214/ijraset.2022.40636

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Design of Manual Operated Oil Extraction Machine

Vivek Vaidya¹, Ashwin Girhe², Chetan Lanjewar³, Sarang Thakre⁴, Shailendra Chavhan⁵, Pushpak Vaidya⁶, Snehal Humane⁷

¹Assistant Professor, Department of Mechanical Engineering, Kdk College of Engineering, Nagpur, Maharashtra India ^{2, 3, 4, 5, 7}Ug students, Mechanical Engineering, Kdk College of Engineering, Nagpur

Abstract: This paper aim on design and Development of pedal operated Seed oil extraction machine. The machine is portable which makes it light in weight and can be used for small scale industries and for Household and Pure oil extraction. Since this machine requires less space to move, it can be used in a more versatile manner as compared to heavy powered machines that are mounted on heavy and large industries. This machine can be efficient and easy to operate and maintain. The oil extracted has various applications in food, medicine, and industry (1). This paper is also aim on Literature Survey on various mechanism used by top Universities professors According to the Need. Keywords: Expeller, Design, Chain, Speed, Seeds, Oil.

I. INTRODUCTION

Expeller presses (also called oil extractors) are a mechanical method for extracting oil from raw ma-terials. The raw materials are squeezed under high during a single step. When used for the extraction of food oils, typical seeds such as flex, mustard, and peanut which are supplied to the press in a continuous feed. As the seeds is pressed, friction causes it to heat up; in the case of harder nuts (which require higher pressures) the material can exceed temperatures of 140 °F (60 °C). Oil expeller may be a device which may produce pressure by rotating feed to expeller screw manually or automatically. Screw press method for oil extraction may be a mechanical method for extracting oil from raw materials. Oil extracted by screw pressing is employed either as a foodstuff or as an indus-trial product. Food products include raw oil in dressings and made up to vegetable oil, groundnut oil, rice bran oil etc. For this heat generation it faces some common problem including overheating, excessive thermal stress, dimensional stability and other thermal related factors. By analysing through simulating software design verification of parts used in screw presser can be modified and increase performance efficiency (2). Locally available material low-carbon steel was utilized in construction of the oil expeller. In the construction of oil expeller firstly it had been designed and validity of stress checked in Ansys. After constructing the oil extraction barrel rectangular bars were placed surrounding it as it permits the passage of oil only and helps to create pressure inside the barrel. The choke mechanism was set in the screw at the outlet of extraction barrel. It was adjusted accordingly to regulate the output of wastage and to extend and reduce pressure accordingly. A reducing gear was used to reduce the rpm of the motor and to increase the energy in the screw shaft (3). Power is transmitted by using pedal which is maintained at gear ratio 18:44 which is for smaller and larger sprocket respectively. The gearbox is connected at output of smaller sprocket shaft. The gearbox used is worm and pinion gearbox which rotates the lead screw at 140 rpm.

II. DESIGN CALCULATION

A. Chain Drive

The speed of the larger sprocket is equal to speed of the rotation of the pedal.

No.of teeth on larger sprocket = 44

No.of teeth on smaller sprocket= 18

Let,

The speed of rotation of Larger sprocket = N_1

The speed of rotation of smaller sprocket = N_2

Therefore,

The relation between the rotations of the two sprocket is

 $\frac{N2}{N1} = \frac{44}{18}$

Therefore,

The gear ratio of power transmission of chain drive is 2.4



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

B. Velocity Ratio of Chain Drive

Velocity ratio (VR) = $\frac{N_1}{N_2} = \frac{T_2}{T_1}$

Where,

N1 = Speed of rotation of smaller sprocket in rpm				
N2 = Speed of rotation of Larger	sprocket in rpm			
T1 = No.of teeth on the smaller	sprocket.			
No of tooth on the lower owned but				

T2 = No.of teeth on the larger sprocket.

N1 =?

N2 = 100 rpm (approximately)

- T1 = 18
- T2 = 44

$$VR = \frac{T2}{T1}$$
$$= \frac{44}{18}$$

$$VR = 2.44$$

Now,

$$VR = \frac{N1}{N2}$$

N1 = 2.44 × 100
N1 = 244
N1 = 244 **rpm.**

The revolution of smaller sprocket will be 244 rpm.

Take N_3 = Speed of revolution of bicycle rim.

As the bicycle rim and sprocket is mounted on the same shaft

$$\therefore$$
 N₂ = N₃

The average velocity of chain is given by,

$$V = \frac{\pi DN}{60} m/s$$

Considering the diameter and revolution of larger sprocket D = 177.8 cmN1 = 100

$$V = \frac{\pi \times 177.8 \times 10^{-3} \times 100}{60}$$

V = 0.9309 m/s.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

C. Length of Chain and its Centre Distance The open chain containing the two sprockets as on T1 = No. of teeth on smaller sprocket T2 = No. of teeth on larger sprocket P = pitch of chain X = Centre distanceThe length of chain is given by L = K.P

Where,

K = no of chain drive links and P = pitch of chain.

The no of chain links (K) is given by

 $K = \frac{T_1 + T_2}{2} + \frac{2X}{P} + \frac{[T_2 - T_1]^2}{2\pi} + \frac{P}{X}$

We have, Centre distance = X = 34''

X = 863.6 mm

= 0.8636 m

$$K = \frac{T_1 + T_2}{2} + \frac{2X}{P} + \frac{[T_2 - T_1]^2}{2\pi} + \frac{P}{X}$$

$$=\frac{18+44}{2}+\frac{2(863.6)}{12}+\frac{[44-18]^2}{2\pi}+\frac{12}{863.6}$$

= 175.17

K = 175 Nos

: The length of chain is given by L = K.P

= 2100 mm

= 2.1 m

 \therefore The total length of chain is 2.1 m

D. Gearbox Selection

The speed of rotation of smaller sprocket N1 = 244 rpm. The gear ratio of the gearbox = 1: 15 = 0.6 \therefore The output of the gearbox in rpm will be

 $= 244 \times 0.6$ = 146.4 rpm

Therefore, we use worm and pinion gearbox.

III. APPROXIMATE EFFICIENCY

Efficiency, percentage of the oil obtained from the extraction machine Extraction efficiency E,

E = Y/Co x 100%

Where

Y = oil yield in percentage. Co = oil content of Seeds/Nuts/Copra



The oil yield Y is calculated from $Y = (W1 - W2)/W1 \times 100\%$

Where

W1 = Initial weight of seeds (Before extracting)

W2 = weight of cake (after extracting)

1) Considering Value of peanut Table 1

 $W1 = (150 - 86)/150 \ge 100 = 42\%$

Efficiency of the machine is

 $E = Y/Co \times 100 = (0.42/0.49) \times 100 = 85\%$ ['Co' for peanut is 45 - 50%]

2) Considering value of flex seeds from Table 1, $W1 = (150 - 95.5)/150 \times 100 = 36\%$

Efficiency of the machine is $E = Y/Co \ge 0.36/0.47 \ge 100 = 76\%$ ['Co' for flaxseeds is 45 - 55%]

3) Considering value of mustard from Table1, $W1 = (120 - 51)/120 \times 100 = 57.5\%$

Туре	Feed rate	Pressing	Initial	Final	Yield
	(gm/min)	Time	weight of	weight	of oil
			seed	of seed	(gm)
			(gm)	(gm)	
Peanut	6	25	150	95.5	56.30
Flex seeds	5	30	120	51	68.5
Mustard	6	25	150	86	80

IV. CONCLUSION

The gear ratio of the chain drive will be 2.44, the velocity of chain drive will be 0.9309 as we taken the speed of the revolution of larger sprocket N1 = 100 rpm. It can be increased by increasing the power output of the chain drive. Therefore we use worm and pinion gearbox which is connected directly to the main shaft of the lead screw, the gear ratio of the gearbox will be 0.6 which gives the output of 146.4 rpm. The length of the chain will be 2.1 m which will be open and connected to the input shaft of the gearbox in the end.

REFERENCES

- International Journal of Research Available at <u>https://edupediapublications.org/journals</u>, Volume 04 Issue 01 January 2017, Alva's Institute of Engineering & Technology (Affiliated to VTU Belgavi, Karnataka) Mijar, Moodbidri Karnataka, India.
- [2] International Journal of Engineering Research & Technology (IJERT) Published by: www.ijert.org Vol. 8 Issue 06, June-2019 BITM Ballari Assistant t Professor, Department of Mechanical Engineering, BITM Ballari
- [3] Md. Habib Ullah Khan, Dipayan Mondal, Shahidul Hoque Department of Mechanical Engineering, Khulna University of Engineering & Technology, Khulna-9203, Bangladesh, International Conference on Mechanical, Industrial and Energy Engineering 2016.
- [4] S.A. Kalogirou; 10 Feb 2004; "Solar Thermal Collectors and Applications". Progression Energy and Combustion Science 231-295.
- [5] S. Dubowsky; "A New Design Approach For Solar Concentrating Parabolic Dish Based On Optimized Flexible Petals", Publication in the Journal Mechanism and Machine Theory.
- [6] Akerele O. V. and *Ejiko, S.O. Department of Mechanical Engineering, the Federal Polytechnic Ado-Ekiti, Ekiti State.
- [7] D.D. Bawalan, K.R. Chapman; Feb. 2006; "Virgin Coconut Oil Manual for Micro and Village Scale processing", National Library, Bangkok cataloguing in publication data; ISBN 974-7946-81-5.
- [8] C.Y. Zhao, April 2013, "Review of solar collector and thermal energy storage in solar thermal application"; volume 104, ISSN 0306-2619; pages 538-553.
- Y.R. Suple; Dr. S.B. Thombre; Jan-Feb 2013, "Performance Evaluation of Parabolic Solar Disc for Indoor Cooking"; ISSN: 2278-1684 Volume 4, Issue 6; Pages 42-47.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)