



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 12 Issue: II Month of publication: February 2024

DOI: <https://doi.org/10.22214/ijraset.2024.58367>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Detection of Illegal Goods using X-ray Image Enhancement Algorithm

S.Bhargavi¹, B.Sadvik Reddy², T.Sumanth Reddy³, T.Sushma⁴, S.Narendra Reddy⁵, P.Sai Kusuma⁶

^{1, 2, 3, 4, 5, 6}Department of ECE, Sri Venkateswara College of Engineering, Tirupati, Andhra Pradesh, India

Abstract: In order to facilitate the security personnel to identify the items in the X-ray image, it is necessary to enhance the security X-ray image to highlight the color, edge, shape and other details of the different items in the image, so that the security personnel can identify the inspected items more accurately and quickly, to ensure the safe operation of the airport. Aiming at the problem of color distortion in CLAHE enhanced airport security X-ray images, an X-ray image enhancement algorithm combining USM+CLAHE is proposed. In this work, First, we calculate the grayscale images on the R, G, and B channels of the X-ray image and perform Contrast Limited Adaptive Histogram Equalization (CLAHE) enhancement respectively, and then merge the enhanced R, G, and B grayscale images. Next, we perform the Unsharp Mask (USM) sharpening operation on the X-ray image enhanced by CLAHE, and finally merge the original image and the USM sharpened image according to the weight. The experimental results show that the USM+CLAHE algorithm can effectively enhance the security X-ray image, and at the same time can suppress the color distortion of the enhanced image.

I. INTRODUCTION

Security inspection of illegal goods is a challenging task. There are a large number of dangerous goods passing through airports and many other places daily, and it is very hard to inspect each item manually. The security of airports is very important because there are many people who travel in them every day. The main purpose of airport security is to prevent any dangerous item that could harm passengers or staff. The purpose of this project is to develop a novel algorithm for detecting dangerous goods from an X-ray image. The algorithm will aid airport security officers in their inspection of luggage and other packages for threats such as explosives or weapons. This research is motivated by the need for improved security at airports due to the increase in terrorist attacks over the past decade. Airport security is a vital component of the aviation industry, as it is responsible for protecting passengers and their luggage from potentially dangerous goods. One of the most critical aspects of airport security is the use of X-ray machines to scan luggage, which allows security personnel to view the contents of luggage and detect any hazardous items. However, the quality of X-ray images can be poor, making it challenging for security personnel to identify dangerous goods. This is particularly true for items that are dense, such as metals or electronic devices, which can obscure other items in the luggage. To address this issue, researchers have developed an X-ray image enhancement algorithm that can improve the quality of X-ray images and make it easier for security personnel to identify dangerous goods. The algorithm uses a combination of image processing techniques, such as contrast enhancement, noise reduction, and edge detection, to improve the clarity and visibility of the images.

There are currently few publications on X-ray image enhancement in security, and most domestic and international research on X-ray image enhancement is focused on the medical area and industrial inspection field [1]-[5].and there are few literatures on X-ray image enhancement in security inspection [6]-[8].The most popular picture enhancement technique is histogram equalisation (HE), which has the advantages of a straightforward theory, straightforward application, and high real-time performance.

The Contrast Limited Adaptive Histogram Equalization (CLAHE) algorithm, which is based on the local adaptive histogram enhancement algorithm (Adaptive Histogram Equalization, AHE), effectively suppresses the excessive enhancement of local contrast and the amplification of noise, making it particularly suitable for low-contrast images. Researchers have given the CLAHE algorithm a lot of thought since it combines the benefits of two technologies— adaptive histogram equalisation and restricted contrast. To improve picture details, Sun Dongmei et al. [9] devised an adaptive parameter T that automatically modifies the pixel redistribution range of each image sub-block.

Wang Hong et al. [10] proposed the brightness component of the foggy image using the constrained local histogram algorithm, which improved the brightness and contrast of the foggy image. They used the fuzzy enhancement algorithm to achieve the adaptive contrast enhancement of the global foggy image. In order to enhance the underwater sea cucumber image, Yang Weizhong [11] employed the CLAHE method, which successfully preserved the image's fine features while enhancing the image quality.

In order to successfully improve the contrast and edge detail information of the original infrared picture, Liu Yuting et al. [12] coupled the CLAHE method with bilateral filtering algorithm

II. EXISTING SYSTEM

In the digital image application field, images with high contrast and bright colors are the crucial prerequisite for good understanding of the real scenes, such as detection and classification for underwater dam cracks, and multitarget detection under complex environment. The images having a higher contrast level usually display a larger degree of color scale difference as compared to the lower contrast level ones. Light plays a crucial role in generating images of satisfactory quality in photography. Strong light causes an image to have a washed-out appearance; on the contrary, weak light leads to an image that is too dark to be visible.

In these two cases, the contrasts of the images are low and their detailed textures are difficult to discern. The underwater images may lose contrast suffering from degradation due to poor visibility conditions and effects such as light absorption, light reflection, bending of light and scattering of light, which result in dimness and distortion. Furthermore, the poor sensitivity of charge-coupled device /complementary-metal- oxide-semiconductor (CCD/CMOS) sensors leads to images with excessive narrow dynamic ranges and renders their details unclear.

The purpose of image enhancement is a process that allows image features to show up more visibly details and highlight the useful information by making best use of the color presented on the display devices. Image enhancement is used to improve the quality of an image for visual perception of human being. Therefore, it is particularly important to design effective enhancement algorithms to improve contrast and restore color for the degenerated underwater image.

A. Retinex Theory

Recently, Retinex, Homomorphic and Wavelet Multi-Scale techniques have been popular for enhancing images. These methods perform much better than those traditional ones. The Retinex theory is firstly introduced to image enhancement by Edwin et al.

There are some different algorithms based on Retinex theory such as single-scale Retinex (SSR), multi-scale Retinex (MSR), multi-scale Retinex with color restoration (MSRCR), and fast multi-scale Retinex (FMSR) etc. Among them, the MSRCR method proposes to estimate the illumination of the input image using gaussian surround filtering of different scales and conducts enhancement by applying color restoration followed by linear stretching to the logarithm of reflectance.

Though the MSRCR method has demonstrated a strong ability in providing dynamic range compression, color restoration and preserving most of details, a large number of parameters are involved and set empirically, which limit the generalization ability and often result in pseudo halos and unnatural color.

The classical contrast enhancement is Histogram Equalization (HE) which has good performance in ordinary images, such as human portraits or natural images. This method increases the contrast of an image globally by spreading out the most frequent intensity values. However, it suffers from noise amplification in relatively homogeneous regions. HE has been generalized to a local histogram equalization which is known as adaptive histogram equalization (AHE). AHE is based on HE that the adaptive method formulates each histogram of sub-image to redistribute the brightness values of the images. AHE is therefore suitable for improving the local contrast of an image and bringing out more details. Some AHE algorithms have got important progress in suppressing noise and enhancing contrast.

The hybrid cumulative histogram equalization (HCHE) can improve the enhancement effect on hot objects rather than background. The gap adjustment histogram equalization can solve the over-enhancement problem and alleviate the feature loss problem in the dark regions of the image. However, the problem remains the same with the global histogram equalization because of amplifying noise in relatively homogeneous regions.

In order to overcome this problem, contrast limited adaptive histogram equalization (CLAHE) was proposed. CLAHE is a well-known block-based processing, and it can overcome the over amplification of noise problem in the homogeneous region of image with standard histogram equalization. CLAHE algorithm differs from standard HE in the respect that CLAHE operates on small regions in the image, called tiles, and computes several histograms, each corresponding to a distinct section of the image and use them to redistribute the lightness values of the image.

In order to improve contrast and restore color for underwater image captured by camera sensors without suffering from insufficient details and color cast, a fusion algorithm for image enhancement in different color spaces based on contrast limited adaptive histogram equalization (CLAHE) is proposed in this article.

The original color image is first converted from RGB colorspace to two different special color spaces: YIQ and HSI. The color space conversion from RGB to YIQ is a linear transformation, while the RGB to HSI conversion is nonlinear.

Then, the algorithm separately operates CLAHE in YIQ and HSI color spaces to obtain two different enhancement images. The luminance component (Y) in the YIQ color space and the intensity component (I) in the HSI color space are enhanced with CLAHE algorithm. The CLAHE has two key parameters: Block Size and Clip Limit, which mainly control the quality of CLAHE enhancement image. After that, the YIQ and HSI enhancement images are respectively converted backward to RGB color. When the three components of red, green, and blue are not coherent in the YIQ-RGB or HSI-RGB images, the three components will have to be harmonized with the CLAHE algorithm in RGB space. Finally, with 4 direction Sobel edge detector in the bounded general logarithm ratio operation, a self-adaptive weight selection nonlinear image enhancement is carried out to fuse YIQ-RGB and HSI-RGB images together to achieve the final fused image. The enhancement fusion algorithm has two key factors: average of Sobel edge detector and fusion coefficient, and these two factors determine the effect of enhancement fusion algorithm.




Fig.1 : CLAHE OUTPUT

B. Drawbacks

- 1) It may increase the contrast of background noise, while decreasing the usable signal/image data
- 2) Suffer from color distortion
- 3) This method is the tendency to over-amplify noise in relatively homogeneous regions of an image.

III. PROPOSED SYSTEM

This section will elaborate on the security inspection Xray image enhancement algorithm process:

- 1) CLAHE enhancement. First, calculate the grayscale images on the R, enhancement respectively, and then merge the enhanced R, G, and B grayscale images.
- 2) USM sharpening. This algorithm uses an improved USM (Unsharp Mask) algorithm to sharpen the CLAHE-enhanced image to highlight details such as image edges and shapes. The USM algorithm combines the sharpened image with the original image according to the superposition coefficient for the second level image fusion.
- 3) Image fusion. The original image and the USM sharpened image are weighted and summed to reduce image color distortion.




Fig.2: Block Diagram of Proposed Method

CLAHE Enhancement

a) Introduction to CLAHE

The statistical link between each grey level in the image and its frequency is represented by the image histogram, sometimes referred to as the grey level histogram. The histogram's definition is displayed in "(1)".

$$P(r_k) = \frac{n_k}{N} \quad (k=0,1,2,\dots,L-1) \quad (1)$$

Using grayscale transformation, histogram equalisation (HE) is a technique for automatically altering picture contrast quality. The main concept is to expand the original image's grayscale histogram from a relatively narrow grayscale interval to encompass the complete grayscale spectrum uniformly of distribution. The conventional HE approach is distinct from adaptive histogram equalisation (AHE). By first computing the local histogram of the picture and then redistributing the brightness, the AHE method modifies the image's local contrast, thus enhancing it and revealing more image details. However, AHE has the issue of overly magnifying the visual noise.

Contrast-limited The approach of adaptive histogram equalisation is improved by the CLAHE algorithm. Noise amplification in AHE may be controlled by restricting the height of the histogram in each section. The following are the main steps of the CLAHE algorithm:

- Step1: Division of image subregions: Each subregion of the original image is the same size, has a constant amount of pixels (C), does not overlap any other subregions, and is divided into many equal-sized subregions. The enhancing impact, which can often be modified in accordance with real demands, is better the greater the sub-area.
- Step 2: Calculate the histogram. The histogram of a particular subregion is represented by using, where denotes the grey level, its value is, and is the total number of grey levels.
- Step 3: Determine the limit value Determine the cutoff limit indicated by "(2)"

$$\beta = \frac{c}{L} \left(1 + \frac{\alpha}{100} (Smax - 1) \right) \quad (2)$$

The determined limit value, the cutoff coefficient, whose range of values is [0,100], and the maximum slope, which is used to calculate the contrast enhancement amplitude, are among them. The maximum slope's value is an integer between 1 and 4.

- Step 4: Redistribute pixels. Use the matching value for each sub-region to crop, then redistribute the cropped pixels to the histogram's grey levels. The aforementioned allocation procedure is carried out repeatedly until all of the cropped pixels have been assigned.
- Step 5: Histogram equalisation: Following cropping, equalise the grey histogram for each sub-region.
- Step 6: Reconstructed pixel grey value: To compute the grey value of each pixel in the output picture, use bilinear interpolation to conduct grey linear interpolation on each pixel in the input image. This is done by using the centre point of each sub-region as a reference point.




Fig 3. CLAHE

b) Image Merge

The enhanced R, G, and B grayscale images are combined and converted into RGB and HSV images, and then CLAHE enhancement of the RGB image and the HSV image, respectively, is performed to further improve the colour fidelity of the processed image. The enhanced image is then marked with the appropriate CLAHE enhancement of RGB image and HSV image designations marked as Ir,Ig,Ib adopts the Euclidean norm at last, as shown in "(3)" Ir,Ig,Ib the combined picture will go through USM sharpening processing after merging to produce the first degree of image fusion.

$$I_{\text{merge}(i,j)} = \sqrt{I_r^2(i,j) + I_g^2(i,j) + I_b^2(i,j)}$$

(i=0,1,2,.....,M-1; j= 0,1,2,.....N-1) (3)

The merged picture is one of them, and the number of rows and columns is the same below.

➤ USM sharpening

It is vital to employ image sharpening technology to emphasise the fine areas of the picture, notably the edge information of the image, in order to make it easier for the security people to view and recognise the shape of the item in the X-ray image. Image sharpening is a technique used in image processing to make the edges of the image more distinct.

The basic idea is to first extract the original picture's high frequency components, then superimpose those components with the original image in accordance with predetermined criteria to obtain the sharpened image. Although the sharpened picture produced by the conventional unsharp mask (USM) procedure is less prone to noise and false edges, it may still be used to eliminate some minor interference elements from images. As a result, the USM method and threshold are used in this paper.

The following are the key actions.

- Step 1: First, the original image is filtered using a Gaussian process.
- Step 2: Calculating the mask as indicated in "(4)." The threshold and a two-dimensional matrix are two of them.

$$\text{Mask}(i,j) = \begin{cases} 1 & \text{if } |I(i,j) - i_{\text{blur}}(i,j)| \leq \text{Threshold} \\ 0 & \text{if } |I(i,j) - i_{\text{blur}}(i,j)| > \text{Threshold} \end{cases}$$

(I = 0,1,2,.....,M-1; j=0,1,2,.....,N-1) (4)

- Step 3: Calculating the High Frequency Component Image(Ihf) as indicated in "(5)."

$$I_{\text{hf}}(i,j) = I(i,j) - I_{\text{blur}}(i,j)$$

(I = 0,1,2,.....,M-1;j=0,1,2,.....,N-1) (5)

- Step 4: Calculating the sharpened picture (I sharp) as seen in "(6)".

$$I_{\text{sharp}}(i,j) = I(i,j) + k \times I_{\text{hf}}(i,j)$$

(i = 0,1,2,.....,M-1; j=0,1,2,.....,N-1) (6)

The superposition coefficient's location is k.

- Step 5: The original picture is combined with the sharpened image (I sharp), as shown in "(7)"

$$I_{\text{sharp}}(i,j) = \begin{cases} I(i,j) & \text{if } \text{Mask}(i,j) = 1 \\ I_{\text{sharp}}(i,j) & \text{if } \text{Mask}(i,j) = 0 \end{cases}$$

(i 0,1,2,....., M - 1 ; j = 0,1,2,....., N - 1)(7)

➤ Image fusion

The edge, form, and other aspects of the security X-ray picture have been improved after CLAHE enhancement and USM sharpening, but the processed image has a significant colour difference from the original image, making it difficult for the security staff to identify the items in the image. In order to decrease colour distortion in the picture produced by the algorithm in this article compared to the original image, as shown in "(8),"

This work fuses the sharpened image with the original image according to the coefficient.

$$I_{\text{final}}(i,j) = C_{\text{sharp}} \times I_{\text{sharp}}(i,j) + C_{\text{origin}} \times I(i,j)$$

(i= 0,1,2,....., M - 1 ; j = 0,1,2,....., N - 1)(8)

The fusion coefficients of the original picture and the USM sharpened image, respectively, are among them.



Fig.4. Unsharp/Final Output

➤ *Threshold Value*

In MATLAB, the threshold value represents a crucial parameter used in various image processing and analysis tasks, particularly in segmentation. Essentially, it defines a dividing line or limit between two regions or classes within an image. When applied to image processing, this value serves as a criterion to differentiate between foreground and background elements or to isolate specific features within an image. For instance, in grayscale images, a threshold value can be set to classify pixels as either black or white, creating a binary image. Choosing an appropriate threshold is vital; it impacts the accuracy of segmentation and subsequent analysis.

IV. SIMULATION RESULTS

MATLAB provides numerous methods to determine an optimal threshold, such as Otsu's method or adaptive thresholding techniques, allowing users to automate this process based on statistical properties of the image. Adjusting the threshold value can significantly influence the outcome of image processing operations, making it a fundamental aspect of MATLAB-based image analysis workflows.

PSNR:

In MATLAB, Peak Signal-to-Noise Ratio (PSNR) is a metric used to evaluate the quality of an image by comparing the original image to a compressed or distorted version. It measures the ratio between the maximum possible power of a signal and the power of corrupting noise that affects the fidelity of its representation.

To calculate PSNR in MATLAB, you can use the formula $PSNR = 20 * \log_{10}(MAX_I) - 10 * \log_{10}(MSE)$, where MAX_I is the maximum pixel value of the image (typically 255 for an 8-bit grayscale image), and MSE is the Mean Squared Error between the original and distorted images. MATLAB provides functions like ``imread`` to read images, ``imresize`` to change image dimensions, and ``psnr`` to directly calculate PSNR between two images. For instance, to compute PSNR for two images ``original`` and ``distorted``, you'd use ``psnr_val = psnr (distorted, original) ``. This value helps quantify how much the distortion affects the image fidelity, with higher PSNR values indicating better similarity between the images.




Fig. 5. PSNR

V. CONCLUSION

This work investigates the subject of “ security X-Ray image enhancement” using Matlab as an analytical framework and offers a USM+CLAHE image enhancement technique. This approach may greatly improve the X-ray image of popular goods in airport security checks while also successfully suppressing image colour distortion. This method provides more adequate results when compared to existing works.

REFERENCES

- [1] Saenpaen J, Arwatchananukul S, Aunsri N. A Comparison of Image Enhancement Methods for Lumbar Spine X-ray Image[C]// 2018 15th International Conference on Electrical Engineering/Electronics, Computer, Telecommunications and Information Technology (ECTICON). 2018:798-801.
- [2] Khan S, See C, Khan A. X-ray image enhancement using boundary division wiener filter and wavelet-based image fusion approach[J]. Journal of Information Processing System, 2016, 12(01): 35–45..
- [3] Zhou Chong, Liu Huan, Zhao Ailing, et al. Industrial X-ray image enhancement algorithm based on gradient field [J]. Journal of Computer Application, 2019, 39(10): 35-45.
- [4] Xiang Jiankai, Wu Meng, Wang Zhan, et al.. Application of Image Enhancement in X-Ray Photography of Cultural Relics[J]. Laser & Optoelectronics Progress, 2019, 56(06): 257–262.
- [5] Koonsanit K, Thongvigitmanee S, Pongnapang N, et al. Image enhancement on digital x-ray images using NCLAHE[C]// Biomedical Engineering International Conference. 2017:1-4.
- [6] Zheng Lintao, Dong Yongsheng, Shi Hengliang. A New Enhancement Algorithm of X-ray Security Inspection Images [J]. Science Technology and Engineering. 2014, 14(23): 252–256.
- [7] Han Ping, Liu Zexu, He Weikun, Girshick R, et al. An Efficient Twostage Enhancement Algorithm of X-ray Carry-on Luggage Images[J]. Opto-Electronic Engineering, 2011, 38(7): 99–105.
- [8] Wang Jian, Pang Yanwei. X-Ray Luggage Image Enhancement Based on CLAHE [J] Journal of Tianjin University (Science and Technology), 2010(03): 10–14.
- [9] Sun Dongmei, Lu Jianfeng, Zhang Shanqing. The Application of an Improved CLAHE Algorithm in Image Enhancement of Medical Test Strip[J]. Chinese Journal of Biomedical Engineering, 2016, 35(04): 502-506.
- [10] Wang Hong, He Xiaohai, Yang Xiaomin. An Adaptive Foggy Image Enhancement Algorithm Based on Fuzzy Theory and CLAHE [J]. Microelectronics & Compute, 2012, 29(01): 32-34.
- [11] Yang Weizhong, Xu Yinli, Qiao Xi, et al. Metho for image intensification of underwater sea cucumber based on contrast-limited adaptive histogram equalization[J]. Transactions of the Chinese Society of Agricultural Engineering, 2016, 32(06): 197-203.
- [12] Liu Yuting, Chen Zheng, Fu Zhanfang, et al. Infrared image enhancement algorithm based on CLAHE[J]. Laser & Infrared, 2016, 46(10): 1290-1294.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)