



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: VI Month of publication: June 2022

DOI: https://doi.org/10.22214/ijraset.2022.44281

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Detectsy: A System for Detecting Language from the Text, Images, and Audio Files

Riya Menon

Department of Computer Engineering, VESIT, University of Mumbai

Abstract— Language detection is a natural language processing task where we need to identify the language of a text or document. As a human, we can easily detect the languages we know. However, it is not possible for an individual to identify many languages. This is where the language identification task can be used. The proposed solution is a complete system that detects language from the text, images, and audio files. Language identification task from text is carried out by training a Multinomial Naive Bayes classifier model. In the case of image and audio inputs, Python libraries are used to achieve the goal of language detection.

Keywords— Language identification, Natural Language Processing, Multinomial Naive Bayes classifier, Optical Character Recognition, Speech Recognition

I. INTRODUCTION

The task of identifying the language of text or utterances has a number of applications in natural language processing. It is a key step in the automatic processing of real-world data, where a multitude of languages may be present. Language detection is the first step towards achieving a variety of tasks like detecting the source language for machine translation, improving the search relevancy by personalizing the search results according to the query language [1], providing a uniform search box for a multilingual dictionary [2], etc. It is also a key component of many web services. For example, the language that a web page is written in is an important consideration in determining whether it is likely to be of interest to a particular user of a search engine, and automatic identification is an essential step in building language corpora from the web. It has practical implications for social networking and social media, where it may be desirable to organize comments and other user-generated content by language.

In this paper, a complete system for language identification is proposed. It has three distinct modules to detect language from text input, images, and audio files. The language identification is carried out by using a Multinomial Naive Bayes classifier in the case of text input. It is trained on a dataset containing 17 languages and has an accuracy of 97.87%. For images and audio files, a combination of Python libraries is used to achieve the goal of language identification.

The rest of the paper is organized as follows: Section II gives an overview of the related work on language detection. Section III explains the methodology adopted by the proposed system. Section IV explains the algorithms employed by the proposed approach. Section V discusses the results of the Detectsy along with the outputs obtained. Section VI describes the evaluation results obtained. Finally, the conclusion and future works are described in section VII.

II. LITERATURE SURVEY

Various papers were reviewed pertaining to different modules of the system. Each paper delved deeper into different methods of implementing functionality with each having its own shortcomings.

An off-the-shelf language identification tool, langid.py [3], is trained over a naive Bayes classifier with a multinomial event model over a mixture of byte n-grams. It is fast, unaffected by domain-specific features, is a single file with minimal dependencies, and has a flexible interface. However, it has an accuracy of 94%.

Support vector machines (SVMs) with n-gram counts as features are proposed for the language identification of very short texts such as proper nouns [4]. But language identification accuracy attained is 84% which is too low to be useful.

A graph-based N-gram approach for language identification (LI) called LIGA is proposed in [5] that allows learning elements of grammar besides using N-gram frequencies. To capture the ordering of words, a graph model is created on labelled data. Once the graph is created, it is used to classify unlabelled texts. It finds its application in language identification on relatively short texts typical for social media like Twitter.

Tesseract [6] is an open-source OCR engine that was developed at HP between 1984 and 1994. It assumes that its input is a binary image and makes use of an adaptive classifier for word recognition. Its key weakness is probably its use of a polygonal approximation as input to the classifier instead of the raw outlines.

A novel language identification (LID) method is proposed in [7] that accepts the architecture of time delay neural network (TDNN) followed by long short term memory (LSTM) recurrent neural network (RNN) to learn long-term phonetic patterns and



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue VI June 2022- Available at www.ijraset.com

model the phonetic dynamics for different languages. It achieves better identification performance in both cases of long utterance and short utterance but is computationally expensive and resource intensive.

Mel Frequency Cepstral Coefficients (MFCC) have been used [8] to derive features of speech signals that can be used for identifying languages. For classification purposes, Support Vector Machines and Decision Tree classifiers were used with accuracies of 76% and 73% respectively.

Another approach is based on Linear Discriminant Analysis (LDA) [9] which is developed using the database of seven different Indian languages giving a maximum classification accuracy of 93.88%.

An approach based on Convolution Neural Networks (CNN) based on AlexNet for the automatic language identification of four Indian languages, Bengali, Gujarati, Tamil, and Telugu has been proposed in [10]. However, being a heavy model, its training time is more. Another weakness of this system is that most of the Tamil audio files are predicted as Telugu because Telugu and Tamil languages sound very similar to each other.



III.PROPOSED SYSTEM

Fig. 1 Block diagram for Detectsy

Fig [1] represents the block diagram of the proposed system. The three major components of the proposed solution are as follows:

A. Language Identification from the Text

For identifying language from text input, the user can either type the text or paste it into the provided textbox. A Multinomial Naive Bayes classifier model is trained to detect the language. The algorithm is explained in detail in the next section. The dataset [11] is first pre-processed wherein many unwanted symbols, numbers are removed. Then, the text is converted into numerical form by creating a Bag of Words model. The next step is to create the training set, for training the model and the test set, for evaluation. The user input is passed to this trained classifier model to predict the language of the text.

B. Language Identification from Images

Language is detected from images containing printed text. The task is performed using Python-tesseract, a wrapper for Google's Tesseract-OCR (Optical Character Recognition) engine. It is available under the Apache 2.0 license. It can be used directly using an API to extract printed text from images. Further, Python's *langdetect* library [12] is used to identify the possible languages of the extracted text. The language with the highest probability is selected and provided as the output to the user.

C. Language Identification from Audio Files

In the case of audio files, the file taken as input from the user is first converted into WAV file format because *SpeechRecognition* [13] supports WAV (must be in PCM/LPCM format), AIFF, AIFF-C, FLAC (must be native FLAC format;



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue VI June 2022- Available at www.ijraset.com

OGG-FLAC is not supported) file formats. Python's SpeechRecognition library acts as a wrapper for several popular speech APIs and is thus extremely flexible. One of the included APIs—the Google Web Speech API—supports a default API key that is hard-coded into the SpeechRecognition library. It is used to recognize speech from an audio source with the help of recognize_google(). Finally, the extracted content is passed through langdetect's detect_lang() to determine the language of the input audio file.

IV. ALGORITHMS

A. Multinomial Naive Bayes

The Multinomial Naive Bayes algorithm [14] is a Bayesian learning approach popular in Natural Language Processing (NLP). It is suitable for classification with discrete features. The classifier guesses the tag of a text using the Bayes theorem. It calculates each tag's likelihood for a given sample and outputs the tag with the greatest probability. The Multinomial Naive Bayes is widely used for assigning documents to classes based on the statistical analysis of their contents. In this case, the Multinomial Naive Bayes classifier model is trained on a dataset containing 17 languages including English, French, Spanish, Portuguese, Italian, Russian, Swedish, Malayalam, Dutch, Arabic, Turkish, German, Tamil, Danish, Kannada, Greek, and Hindi.

B. LangDetect

LangDetect [15] implements a Naive Bayes classifier, using a character n-gram-based representation without feature selection, with a set of normalization heuristics to improve accuracy. It is trained on data from Wikipedia and can be trained with usersupplied data. The language detection algorithm is non-deterministic, which means that if we try to run it on a text which is either too short or too ambiguous, we might get different results every time we run it. To enforce consistent results, it is recommended to set the DetectorFactory seed to some number.

V. RESULTS

The proposed system is developed in the form of a web application. Fig. [2] represents the home page screenshots through which users can navigate to text, image, or audio language detection pages.



Fig. 2 Homepage screenshots

For detecting language from text input, the user either types in or pastes the text into the textbox provided and the system would detect the language. Some of the results for text language identification (LID) are shown in Figs.[3-6].

Please type or paste the text to detect the language...

Please type or paste the text to detect the language...

Detect Language Language detected: <u>Malayalam</u>	Detect Language Language detected: <u>Spanish</u>
ടാണം എന്നാൽ മലയാളിക്ക് ആഘോഷത്തിന്റെ നാളുകളാണ്. ചിങ്ങ മാസത്തിലെ അത്തം മുതൽ പത്ത് ദിവസം നീണ്ടുന്നൽക്കുന്ന ആഘോഷം കേരളത്തിലെ ഒരു പധാന ഉസേവമാണ് ഒന്നെം. സാധാരണയായി ആഗന്റ് സെപ്പംബർ മാസങ്ങളിൽ ഇത് വരുന്നു. കേരളത്തിലെ പുരുഷയാരും സിതികളും കുട്ടികളും ഈ ഉസേവത്തിനിനെ ആപിലാദത്തോടെ കാത്തിരിക്കുകയാണ്. മ	El verano es tiempo de calabacines, una de las hortalizas más versátiles de nuestras despensas. Cientos de recetas pueden prepararse con este producto de la huerta y muchas de ellas requieren que esté rallado. El problema es que el calabacin está compuesto por un 95% de agua y en algunas recetas ese extra de líquido es innecesario e incluso contraproducente. La solución es drenarlo, pero no es una tarea tan fácil. O no lo era hasta ahora.

Fig. 3 Malayalam language identification

Fig. 4 Spanish language identification



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 10 Issue VI June 2022- Available at www.ijraset.com

Please type or paste the text to detect the language...



Language detected: Dutch

Fig. 5 Dutch language identification

Please type or paste the text to detect the language...

சமீபத்திய அறிக்கை ஒன்றில் சுமாடிட்டி நிபுணர் ஒருவர் தங்கம் விலையானது மீடியம் டெர்மில் அவ்வப்போது சரியலாம். ஆனால் பணவீக்கத்திற்கு எதிரான சிறந்த ஹெட்ஜிங் ஆக இருப்பதால் நீண்டகால நோக்கில் அதிகரிக்கவே வாய்ப்புகள் அதிகம்.

Detect Language

Language detected: <u>Tamil</u>

Fig. 6 Tamil language identification

For images, the user has to provide the image with printed text as input. After extraction of text, the language is identified and provided to the user as output as shown in Figs. [7-10].

Please upload the image to detect the language...

Choose File	No file chosen
	Detect Language
Normal te	ext and bold text
Italic text	and bold italic text
Normal te	ext and artificially bold text
Artificially	y outlined text
Artificially	v italic text and bold italic text

Language detected: English

Fig. 7 English language identification

Please upload the image to detect the language...

Choose File	No file chosen
	Detect Language
ة ودقيقة ومتكاملة ومتنوحة و. طي الإنترنت, بدأت النسخة تزال في طور التشكل، بينما ا	و ويكيينيا مشروع تعاوني متحد اللغان يسم ويكيت بأكثر من 300 فنه العمل في مشاريع موسو حات هر ا في تحرير ها، شنات ويكيينيا في عام 2001، حيث نست وتعاون ت بسر ماء العصبح والحاة من أكبر العو الع الدي ويكسنها بعض السياسات (الار تحالك الذي ساحة عطام حيا اطر العل فيها، محر هذا السياسات لا ز
ن له آن يغطي كل تتويعة ط ماركة في مشروع موسو هي ،	ومع أن سياسك ويكيينيا مستمرة في النموء إلا أن بعض الإيكيينيين يشعرون أن كتابة القواهد أمر. لا يمك مؤلاه الذين يحررون بنية هسته ويظهرون سلومًا منتيًا ويسعون وراه التوالق ويعطون للعظي هنفهم بالسَّد
	مر جية
	Choose File و ریفیهٔ و سکامله و متو مه و خر الاتر نب بنان تسمه زن له م خور تشکل بینما س له ان وعطی کل توریعه ط

Language detected: Arabic

Fig. 9 Arabic language identification

Please upload the image to detect the language...

Choose File	No file chosen
सफलता के लिए पैर्थ रखना प को सुखमय और बेहतर बन असफलताओं को डेलना पड़ क्षमताओं पर मिर्भर करता है इसोर अस-पास बहुन से लेगा ही अपनी सफलता को बरका अपनी महत्वकोक्षाओं तक पूर्व करना पडता हैं। राजमार्यांबी पर निर्भर करता है कि इस इस	Detect Language रम आवश्यक हैं। लगातार अभ्यास और धीरव रखना ही अपने जीवन ने के लिए सर्ववेष्ठ विकस्य है। कामगाव होने के लिए कितनी बार गा यह नियमित प्रवासों और मुक्तिलेती का सामना करने की हमारी खुद को अपने स्वयों की बार बार दाद दिलते रहना सीखना होगा। देश भी है विज्ञीने कम समय में अपने आप को बेहतर बनाय है बाथ र भी रेखा है। नियमित रूप से दोलत प्रयास और निर्रत्तर विन्न ही हमें वाने में प्रयाद करता है। जीवन में हर व्यक्ति को असफसता का सामना में रेपा का बाना स्वी है और पीछे प्रकेशने का कार्य भी थे। हम से क्या सीखते है?

Language detected: Hindi

Fig. 8 Hindi language identification

Please upload the image to detect the language...

Choose File	No file chosen
	Detect Language
Adem yilgale sayari yilgan kon in	Corvic on Ris superkologen. The authorit 7 bits systemm, Kathvallater me or calcula globers files ga antra-streament having beit Klob of konnoge m. Klog is hite writek kathegem san: Kathegen rig yapanda wa rentar git sener. Statis fine gib's klob gong met wa gakis klob. Kathegen is an ularana garrangi senera il Sazari met didas yemenkite i Sib havafaria a
Annua milato pratik kučian milato sovetli	here badaran her halta ärge göttalses. Annoren, för mislak gestansstar gran mer haltada är gran konson varkt, för dör är grän var here grän gran grän badaran, för ennskarda grän för an därgara synnan känstarla, ning är senna gränna synna synna som misla an attagala gräne. Antalar ann angen senna filtanstar annanskolskettig grangen assens. Tikatarin attaga söra "töranstar vär och anna tättatta värkä gögermegt elle grän anstänna där til taltettar.
Bitten oynan yet ve	bir veçil hayavarıma çıkır) kü yaşında bir köşeni. Gün boyu aktarı hoştanır. Güneşi ve bahçayı çak seren i her geot yamak yanığında disterini. Her gün ümurla yürüküz, Bazen birlakte in cenarım.

Language detected: Turkish

Fig. 10 Turkish language identification

In the case of audio files, the user uploads the audio file. The system processes it to detect the language of the speech. The results are shown in Figs.[11-14]. The audio files uploaded in the given examples have the following text:

French: Je m'appelle Hugo et j'ai seize ans. Aujourd'hui, avec mes parents et ma sœur nous partons en voyage. Ma sœur s'appelle Laura, elle a treize ans. Nous sommes à l'aéroport : direction Barcelone en Espagne !



- Portuguese: Rubens sempre quis ser jornalista. Desde quando era criança ele já escrevia para o jornal que havia na escola onde estudava. Quando entrou para a faculdade, ele achou que era o momento de organizar uma espécie de noticiário sobre os acontecimentos da própria universidade.
- Italian: I genitori di mio marito vivono lontano da qui, in città. I miei genitori invece abitano vicino a noi, nello stesso paese. Vogliono molto bene ai nostri tre figli e spesso si occupano di loro.
- German: Hansi Flick war nicht zufrieden, das konnte man seinem Gesichtsausdruck während des Spiels in Budapest deutlich ablesen. Der Bundestrainer hatte zwar vor dem Spiel in Ungarn gewarnt, es sei 'nach England das schwerste Spiel' und es warte eine 'ganz große Aufgabe', aber dass seine Elf mit so wenig Durchschlagskraft nach vorne agieren würde wie beim 1:1 (1:1) in Budapest, hätte er wohl nicht gedacht.

Please upload the audio file to detect the language...

Please upload the audio file to detect the language...

Choose File	No file chosen
	Detect Language
•	0:00 / 0:14 🛛 🕘 🗄



Fig. 11 French language identification

Please upload the audio file to detect the language...

Choose File	No file chosen		
	Detect Language		

Language detected: Italian

Fig. 13 Italian language identification

Choose File	No file chosen		
	Detect Language		
•	0:00 / 0:23	•)	:

Language detected: Portuguese

Fig. 12 Portuguese language identification

Please upload the audio file to detect the language...

Choose File	No file chosen		
	Detect Language		

Language detected: German

Fig. 14 German language identification

English

French

Spanish

Portugee

Italian

Russian Sweedish

Malayalam Dutch

Arabic Turkish

German

Tamil Danish

Kannada

Greek Hindi 1385

1014

819

739

698

692 676

594 546

536 474

470 469

428

369 365

Name: Language, dtype: int64

VI.EVALUATION

A dataset containing 17 languages is used for training the classifier model to detect languages from text input. Fig. [15] shows a snapshot of the dataset used and fig. [16] displays the value count of text for each language in the dataset. The trained Multinomial Naive Bayes classifier model is evaluated and the accuracy is computed to be 97.87%. Fig. [17] represents the confusion matrix for the same.

	Text	Language
0	Nature, in the broadest sense, is the natural	English
1	"Nature" can refer to the phenomena of the phy	English
2	The study of nature is a large, if not the onl	English
3	Although humans are part of nature, human acti	English
4	[1] The word nature is borrowed from the Old F	English
5	[2] In ancient philosophy, natura is mostly us	English
6	[3][4] \nThe concept of nature as a whole, the	English

Fig. 25 Dataset

Fig.36Value count for each language



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue VI June 2022- Available at www.ijraset.com



Fig. 47 Confusion matrix

VII. CONCLUSION AND FUTURE WORKS

In this paper, a complete language detection system is proposed having different modules for text input, image, and audio files. The trained Multinomial Naive Bayes classifier model has achieved an accuracy of 97.87% for 17 languages. The current work can be extended to include more languages. Currently, language can be detected from printed text. It can be extended to include handwritten text documents. Also, models can be trained for speech-language detection in order to achieve better performance.

REFERENCES

- [1] Juliane Stiller, Maria Gade, and Vivien Petras. Ambiguity of queries " and the challenges for query language detection. CLEF 2010 Labs and Workshops Notebook Papers, 2010.
- [2] Dong Nguyen and a Seza Do. Word level language identification in online multilingual communication. 23(October):857–862, 2013.
- [3] Marco Lui and Timothy Baldwin. 2012. langid.py: An Off-the-shelf Language Identification Tool. In Proceedings of the ACL 2012 System Demonstrations, pages 25–30, Jeju Island, Korea. Association for Computational Linguistics.
- [4] Aditya Bhargava and Grzegorz Kondrak. 2010. Language identification of names with SVMs. In Human Language Technologies: The 2010 Annual Conference of the North American Chapter of the Association for Computational Linguistics, pages 693–696, Los Angeles, California. Association for Computational Linguistics.
- [5] Erik Tromp and Mykola Pechenizkiy. Graph-based n-gram language identification on short texts. "Proceedings of the 20th annual BelgianDutch Conference on Machine Learning", pages 27–34, 2011.
- [6] R. Smith, "An Overview of the Tesseract OCR Engine," Ninth International Conference on Document Analysis and Recognition (ICDAR 2007), 2007, pp. 629-633, doi: 10.1109/ICDAR.2007.4376991.
- [7] L. Sun, "Language Identification with Unsupervised Phoneme-like Sequence and TDNN-LSTM-RNN," 2020 15th IEEE International Conference on Signal Processing (ICSP), 2020, pp. 341-345, doi: 10.1109/ICSP48669.2020.9320919.
- [8] H. Venkatesan, T. V. Venkatasubramanian and J. Sangeetha, "Automatic Language Identification using Machine learning Techniques," 2018 3rd International Conference on Communication and Electronics Systems (ICCES), 2018, pp. 583-588, doi: 10.1109/CESYS.2018.8724070.
- [9] J. S. Anjana and S. S. Poorna, "Language Identification From Speech Features Using SVM and LDA," 2018 International Conference on Wireless Communications, Signal Processing and Networking (WiSPNET), 2018, pp. 1-4, doi: 10.1109/WiSPNET.2018.8538638.
- [10] L. R. Arla, S. Bonthu and A. Dayal, "Multiclass Spoken Language Identification for Indian Languages using Deep Learning," 2020 IEEE Bombay Section Signature Conference (IBSSC), 2020, pp. 42-45, doi: 10.1109/IBSSC51096.2020.9332161.
- [11] https://www.kaggle.com/datasets/basilb2s/language-detection
- [12] https://pypi.org/project/langdetect/
- [13] https://pypi.org/project/SpeechRecognition/
- [14] https://www.upgrad.com/blog/multinomial-naive-bayes-explained/
- [15] https://towardsdatascience.com/benchmarking-language-detection-for-nlp-8250ea8b67c











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)