



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 12 Issue: II Month of publication: February 2024 DOI: https://doi.org/10.22214/ijraset.2024.58577

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Enhancing Seismic Performance of Semi-Commercial Apartment having Telecommunication Tower at Roof

Shantilal Katare¹, Prof. Prachi Chincholikar²

¹M. Tech. Scholar, ²Assistant Professor, Department of Civil Engineering, Vikrant Institute of Technology and Management, Indore (M. P.), India

Abstract: When studying the impact of seismic activities on a structure, we focused on the efficient case and didn't consider the worst-case scenario. If a telecommunication tower is planned on a multistoried building in the future, and the tower is in the worst possible location, certain measures need to be taken to stabilize it and adjust the parametric values.

In this research, we analyzed a total of 5 semi-commercial apartment building cases with G+19 floors, each having different telecommunication tower locations.

After the analysis, we identified the worst case and implemented an outrigger system, as discussed in the graphical representations in the discussion section. In conclusion, we compared parametric results and observed that Case TTD is very efficient, while Case TTA is the worst among all the cases.

We also improved the stability of the worst-case TTA and transformed it into Case TTO through the implementation of the outrigger system, as indicated by our results and discussions.

Keywords: Seismic activities, Multistoried Building, Response spectrum method, telecommunication tower

I. INTRODUCTION

When considering the safety of human civilization, earthquakes emerge as a major threat, causing harm to lives, structures, and property. Worldwide, ongoing experimental efforts aim to address this issue and create environments that can withstand earthquakes, ensuring a secure and hassle-free life. Modern structures are designed with special techniques to withstand earthquake forces, often at a higher manufacturing cost.

In India, the common practice for constructing tall buildings is using a reinforced concrete frame. The country is divided into earthquake zones (Zone II, III, IV, and V), and structures in these zones need to be analyzed and designed with extra stiffness and ductility to minimize damage. Steel bracing arrangements within the frame structure are used to reduce lateral effects, providing strength, stiffness, and architectural appeal. Bracings are crucial for resisting movement in structures.

Another element to enhance stiffness in construction is the shear wall, typically located around the lift area in what is known as the core-type shear wall system. Shear walls not only increase stiffness but also enhance stability against overturning and reduce lateral effects. Following Taranath's approach, shear walls can serve as an outrigger system to minimize deflection and mitigate the worst effects of lateral forces.

This system can be implemented at 0.466 of the structural height, combining shear wall outriggers with shear core to form a comprehensive outrigger system.

II. PROCEDURE AND 3D MODELLING OF THE STRUCTURE

An earthquake analysis was conducted on a G+19 storey semi commercial apartment using a software-based approach. Five different models were created in the software, initially placing the tower in various positions atop the apartment. Subsequently, the most efficient and worst-case scenarios were identified, and optimization measures were applied to the parameters of the worst-case using an Outrigger system.

The analysis involved assessing the impact on the building under different loads, including dead load, live load, and lateral loads such as those from earthquakes and wind, using the software's mechanisms. Seismic data conforming to IS 1893(PART1):2016 standards was utilized, and the analysis employed the response spectrum analysis method to evaluate the building's behavior.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 12 Issue II Feb 2024- Available at www.ijraset.com

Table 1: Descriptions of different models

S. No.	Buildings framed for analysis	Abbreviation
1	Semi commercial apartment with telecommunication tower at A	Case TTA
2	Semi commercial apartment with telecommunication tower at B	Case TTB
3	Semi commercial apartment with telecommunication tower at C	Case TTC
4	Semi commercial apartment with telecommunication tower at D	Case TTD
5	Semi commercial apartment with telecommunication tower at E	Case TTE
6	Semi commercial apartment with telecommunication tower at worst location with outrigger support system	Case TTO

Table 2: Data taken for analysis of structure

Constraint	Assumed data for all buildings	
Soil used Medium Soil		
Zone factor Z	0.16	
Importance factor I	1.2	
(For all semi commercial building)		
Build up area of building	625 sq. m	
Floors configuration	G + 19 (Semi-commercial Apartment)	
Depth of foundation	4 m	
Floor to floor height	GF-4 m, All floors-3.5 m each	
Fundamental natural period of vibration (T _a)	$0.09*h/(d)^{0.5}$	
Earthquake parameters	Zone III with RF 4 & 5% damping ratio	
Period in X & Z direction	1.341sec. for both direction	
Slab thickness	128 mm	
Shear wall and Outrigger thickness	138 mm	
Tower horizontal and Vertical elements	ISA 130x130x16	
Tower bracing elements	ISA 100x100x15	
Tower steel standing plate	25mm thick steel plate	
	0 to 25.50m - 0.55m x0.40m	
Beam sizes	25.50 to 50m – 0.50m x0.35m	
	50 to 75.50m – 0.45m x0.30m	
	0 to 25.50m – 0.65m x0.60m	
Column sizes	25.50 to 50m - 0.55m x0.50m	
	50 to 75.50m – 0.45m x0.40m	
Material properties	M 30 Concrete	
Material properties	Fe 415 grade steel	

III. RESEARCH OBJECTIVES

To find the most efficient and worst location of telecommunication tower placements, following objectives have been decided for Semi commercial apartment building:-

- 1) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- 2) To determine Time period and Mass participation factor in both X and Z direction.
- 3) To find Maximum Axial Forces, Shear Force and Bending Moment in Column.
- 4) To compare Maximum Shear Forces, Bending Moments and Torsional Moments in beams parallel to X and Z direction.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 12 Issue II Feb 2024- Available at www.ijraset.com

To obtain the most efficient parametric case and worst case by comparing all and then to erect the worst one, following objectives have been decided for both Semi commercial apartment buildings:-

- a) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- b) To determine Time period and Mass participation factor in both X and Z direction.
- c) To find Maximum Axial Forces, Shear Force and Bending Moment in Column.
- d) To compare Maximum Shear Forces, Bending Moments and Torsional Moments in beams parallel to X and Z direction
- e) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- *f)* To determine Time period and Mass participation factor in both X and Z direction.
- g) To find Maximum Axial Forces, Shear Force and Bending Moment in Column.



Fig. 1: Plan of different building telecommunication tower locations



Fig. 3: Top view of Case TTA: Semi commercial apartment with telecommunication tower at A `



Fig. 4: Top view of Case TTB: Semi commercial apartment with telecommunication tower at B



Fig. 2: 3D model of Telecommunication Tower



Fig. 5: Top view of Case TTC: Semi commercial apartment with telecommunication tower at C





Fig. 6: 3D view of Case TTA: Semi commercial apartment with telecommunication tower at A



Fig. 9: Top view of Case TTD: Semi commercial apartment with telecommunication tower at D



Fig. 7: 3D view of Case TTB: Semi commercial apartment with telecommunication tower at B



Fig. 10: Top view of Case TTE: Semi commercial apartment with telecommunication tower at E



Fig. 8: 3D view of Case TTC: Semi commercial apartment with telecommunication tower at C



Fig. 11: Top view of Case TTO: Semi commercial apartment with telecommunication tower at worst location with outrigger support system



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 12 Issue II Feb 2024- Available at www.ijraset.com







Fig. 12: 3D view of Case TTD: Semi commercial apartment with telecommunication tower at D

Fig. 13: 3D view of Case TTE: Semi commercial apartment with telecommunication tower at E

Fig. 14: 3D view of Case TTO: Semi commercial apartment with telecommunication tower at worst location with outrigger support system

IV. RESULTS ANALYSIS

The result parameters obtained by the application of loads and their combinations on various cases as per Indian Standard 1893: 2016 code of practice. Result of each parameter has discussed with its representation in graphical form below:-



Fig. 15: Comparative representation of Maximum Displacement and Base Shear in X and Z direction obtained for all Cases





Fig. 16: Comparative representation of Time Period and Mass Participation Factor in X and Z direction obtained for all Cases



Fig. 17: Comparative representation of Maximum Axial Forces in Column obtained for all Cases



Fig. 18: Comparative representation of Maximum Shear Forces and Bending Moments in Columns obtained for all Cases



Fig. 19: Comparative representation of Maximum Shear Forces and Bending Moments in Beams obtained for all Cases



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 12 Issue II Feb 2024- Available at www.ijraset.com



Fig. 20: Comparative representation of Maximum Torsional Moment in beams obtained for all Cases

S. no.	Parameter	Optimum case observed	Worst case observed
1	Maximum Displacement in X direction	Case TTB	Case TTE
2	Maximum Displacement in Z direction	Case TTB	Case TTE
3	Base Shear in X direction	Case TTC	Case TTD
4	Base Shear in Z direction	Case TTD	Case TTC
5	Mass Participation Factor in X direction	Case TTB	Case TTA
6	Mass Participation Factor in Z direction	Case TTD	Case TTA
7	Axial Forces in Column	Case TTB	Case TTD
8	Shear Forces in Columns	Case TTD	Case TTA
9	Bending Moment in Columns	Case TTD	Case TTA
10	Shear Forces in Beams	Case TTA	Case TTC
11	Bending Moment in Beams	Case TTD	Case TTB
12	Torsional Moment in Beams	Case TTD	Case TTA

Table 3: Comparative result of optimum and worst results observations

After looking at many cases and comparing them based on different factors, it was found that the best scenario is Case TTD out of a total of 6 cases, while the worst scenario is Case TTA out of a total of 5 cases. The same has mentioned in table 4.46 above. If it's not possible to place the tower in the best scenario, the plan is to put it in the worst scenario, as suggested by this research. In this case, an outrigger system will be added to make the tower more stable than before. The comparison between the worst-case and the case with the added outrigger system is shown below:



Fig. 21: Maximum Displacement and Base Shear in X and Z direction obtained in Worst Case and Erected Case









Fig. 23: Maximum Axial Forces in Column obtained in Worst Case and Erected Case







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 12 Issue II Feb 2024- Available at www.ijraset.com



Fig. 25: Maximum Shear Forces and Bending Moment in Beams obtained in Worst Case and Erected Case



Fig. 26: Maximum Torsional Moment in beams obtained in Worst Case and Erected Case

As per comparison between the worst case and the erected case, it has been proved that if such kind of provision situation arises, provision of erection in the analysis phase should be performed before the construction to lessen the higher parametric values as discussed in this research.

V. CONCLUSIONS

The conclusion can be pointed out are as follows:-

- 1) The least nodal displacement for X and Z directions for the semi commercial apartment is observed in Model Case TTB.
- 2) When determining the Base Shear for both X and Z directions, the Base Shear values observed least in Case TTC for X and TTD for Z directions respectively.
- *3)* When comparing the mass participation factor in both X and Z directions, the maximum mass over time is taken into account. The optimal case is Case TTB and Case TTD, while the worst case is Case TTA for both X and Z direction.
- 4) In Column Axial Forces, Case TTB performs the best, and Case TTD is the least favorable when compared among all cases.
- 5) In Column Shear Forces, Case TTD performs the best, and Case TTA is the least favorable when compared among all cases.
- 6) In Column Bending Moment, Case TTD performs the best, and Case TTA is the least favorable when compared among all cases.
- 7) In Beam Shear Forces, Case TTA performs the best, and Case TTC is the least favorable when compared among all cases.
- 8) In Beam Bending Moment, Case TTD performs the best, and Case TTB is the least favorable when compared among all cases.
- 9) In Beam Torsional Moment, Case TTD performs the best, and Case TTA is the least favorable when compared among all cases.

In general, it is noticed that Case TTD is the most efficient among all the cases. Additionally, we improved the stability of the worst-case scenario, Case TTA, based on our findings and discussions by adding an outrigger system.

Therefore, the most appropriate location for the tower had always been taken but the worst case if taken should be re-structured first, taking into account various result parameters, we attempted to reduce the adverse effects in certain parameters by incorporating outrigger walls and erected the worst case to TTO with better outcomes.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 12 Issue II Feb 2024- Available at www.ijraset.com

VI. ACKNOWLEDGEMENT

I, *Shantilal Katare*, M. Tech. Scholar, would like to thank *Prof. Prachi Chincholikar*, Assistant Professor, Department of Civil Engineering, Vikrant Institute of Technology and Management, Indore (M.P.), India, for her valuable guidance from the commencement of the work up to the completion of the work along with her encouraging thoughts.

REFERENCES

- Nitin Bhosale, Prabhat Kumar, Pandey A. D, (2012), "Influence of host structure characteristics on response of rooftop telecommunication towers", International Journal Of Civil And Structural Engineering, ISSN: 0976-4399, Volume 2, Issue 3, pp. 737-748.
- [2] G. Ghodrati Amiri, M, A. Barkhordari, S.R. Massah and M.R. Vafaei, (2007), "Earthquake Amplification Factors for Self-supporting 4-legged Telecommunication Towers", World Applied Sciences Journal, ISSN: 1818-4952, Volume 2, Issue 6, pp. 635-643.
- [3] Ghyslaine McCLURE, Laura GEORGI and Rola ASSI, (2004), "SEISMIC CONSIDERATIONS FOR TELECOMMUNICATION TOWERS MOUNTED ON BUILDING ROOFTOPS", 13th World Conference on Earthquake Engineering, Paper No. 1988.
- [4] C. Preeti and K. Jagan Mohan, (2013), "Analysis of Transmission Towers with Different Configurations", Jordan Journal of Civil Engineering, Volume 7, Issue 4, pp. 450-460.
- [5] G. Ghodrati Amiri, M. A. Barkhordari, S. R. Massah, (2004), "Seismic Behavior Of 4-Legged Self-Supporting Telecommunication Towers", 13th World Conference on Earthquake Engineering, Vancouver, B.C., Canada, Paper No. 215.
- [6] Gholamreza Soltanzadeh, Hossein Shad, Mohammadreza Vafai, Azlan Adnan, (2014), "Seismic performance of 4-legged Self-supporting Telecommunication towers", International Journal of Applied Sciences and Engineering Research, ISSN: 2277-9442, Volume 3, Issue 2, pp. 319-332.
- [7] Shailesh S. Goral, Prof. S. M. Barelikar, (2017), "Review on Wind and Non-Linear Dynamic Analysis of Self-Supporting Telecommunication Tower", IJSTE -International Journal of Science Technology & Engineering, ISSN: 2349-784X, Volume 3, Issue 10, pp. 183-185.
- [8] Arpit Chawda, Vijay Baradiya, (2015), "Influence Of Structure Characteristics On Earthquake Response Under Different Position Of Rooftop Telecommunication Towers", International Journal Of Engineering Sciences & Research Technology, ISSN: 2277-9655, Volume 4, Issue 10, pp. 73-78.
- [9] Sourabh Rajoriya, K.K. Pathak, Vivekanand Vyas, (2016), "Analysis of Transmission Tower for Seismic Loading Considering Different Height and Bracing System", International Journal for Research in Applied Science & Engineering Technology (IJRASET), ISSN: 2321-9653, Volume 4, Issue 9, pp. 108-118.
- [10] Patil Vidya M., Lande Abhijeet C., (2016), "Structural Response of Lattice Steel Masts for Seismic Loading", IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE), ISSN: 2278-1684, pp. 36-42.
- [11] Suyash Malviya, Sagar Jamle, (2019), "Response of Multistorey Building with Rooftop Telecommunication Tower in Different Positions: An Approach to Efficient Case", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 4, pp. 3783-3790.
- [12] Siddesha H., (2010), "Wind Analysis of Microwave Antenna Towers", International Journal Of Applied Engineering Research, Dindigul, ISSN: 0976-4259, Volume 1, Issue 3, pp. 574-584.
- [13] Jithesh Rajasekharan, S Vijaya, (2014), "Analysis Of Telecommunication Tower Subjected To Seismic & Wind Loading", International Journal of Advancement in Engineering Technology, Management and Applied Science, ISSN: 2349-3224, Volume 1, Issue 2, pp. 68-79.
- [14] Richa Bhatt, A.D.Pandey, Vipul Prakash, (2013), "Influence of modeling in the response of steel lattice mobile tower under wind loading", International Journal of Scientific Engineering and Technology, ISSN: 2277-1581, Volume 2, Issue 3, pp. 137-144.
- [15] Hemal J shah, Dr. Atul K Desai, (2014), "Seismic Analysis Of Tall Tv Tower Cosidering Different Bracing Systems", International Journal of Engineering, Business and Enterprise Applications (IJEBEA), ISSN: 2279-0020, Volume 7, Issue 1, pp. 113-120.
- [16] [15] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building under Seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE) ISSN: 2347-4890 Vol.-05, Issue-3, pp. 14-31.
- [17] [16] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building Analysis When Structure Length is greater than width under seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE) ISSN: 2347-4890 Vol.-05, Issue-3, pp. 32-53.
- [18] [17] Prakash Mandiwal, Sagar Jamle, (2018), "Use of Polyethylene Glycol as Self Curing Agent in Self Curing Concrete An Experimental Approach", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 5, no. 11, pp. 916-918.
- [19] [18] Surendra Chaurasiya, Sagar Jamle, (2018), "Determination of Efficient Twin Tower High Rise Building Subjected to Seismic Loading", International Journal of Current Engineering and Technology, INPRESSCO, E-ISSN 2277 – 4106, P-ISSN 2347 – 5161, Vol. 8, No. 5, pp. 1200 – 1203, DOI: https://doi.org/10.14741/ijcet/v.8.5.1.
- [20] [19] Archit Dangi, Sagar Jamle, (2018), "Determination of Seismic parameters of R.C.C. Building Using Shear Core Outrigger, Wall Belt and Truss Belt Systems". International Journal of Advanced Engineering Research and Science(ISSN : 2349-6495(P) | 2456-1908(O)),vol. 5, no. 9, pp.305-309 AI Publications, doi:10.22161/ijaers.5.9.36
- [21] Mohd. Arif Lahori, Sagar Jamle, (2018), "Investigation of Seismic Parameters of R.C. Building on Sloping Ground", International Journal of Advanced Engineering Research and Science, (ISSN: 2349-6495(P), 2456-1908(O)), vol. 5, no. 8, pp.285-290 AI Publications, doi: 10.22161/ijaers 5.8.35.
- [22] Suyash Malviya, Sagar Jamle, (2019), "Determination of Optimum Location of Rooftop Telecommunication Tower over Multistory Building under Seismic Loading", International Journal of Advanced Engineering Research and Science(ISSN: 2349-6495(P) | 2456-1908(O)), vol. 6, no. 2, 2019, pp. 65-73, AI Publications, doi:10.22161/ijaers.6.2.9.
- [23] Suyash Malviya, Sagar Jamle, (2019), "Response of Multistorey Building with Rooftop Telecommunication Tower in Different Positions: An Approach to Efficient Case", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 4, pp. 3783-3790.
- [24] Yash Joshi, Sagar Jamle, (2019), "Effect of Curtailed Shear Wall on Dynamic Analysis of RC Building", International Journal of Management, Technology And Engineering, (ISSN: 2249-7455(O)), vol. 9, no. 7, pp. 223-230.
- [25] Yash Joshi, Sagar Jamle, Kundan Meshram, (2019), "Dynamic Analysis of Dual Structural System", International Journal of Research and Analytical Reviews, (ISSN: 2348-1269 (O), 2349-5138 (P)), vol. 6, no. 2, pp. 518-523.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 12 Issue II Feb 2024- Available at www.ijraset.com

- [26] [25] Rajesh Chouhan, Sagar Jamle, Kundan Meshram, (2019), "Dynamic Analysis of Tuned Mass Damper Steel Structure: A Review", International Journal of Management, Technology And Engineering, (ISSN: 2249-7455(O)), vol. 9, no. 7, pp. 212-216.
- [27] Rajesh Chouhan, Sagar Jamle, Kundan Meshram, (2019), "Dynamic Analysis of Tuned Mass Damper on Steel Structure: A Technical Approach", International Journal of Research and Analytical Reviews, (ISSN: 2348-1269 (O), 2349-5138 (P)), vol. 6, no. 2, pp. 956-960.
- [28] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building", International Journal for Research in Engineering Application & Management (ISSN : 2454-9150), vol. 4, no. 10, pp. 596-603, doi: 10.18231/2454-9150.2018.1372.
- [29] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building: A Review", International Journal of Advanced Engineering Research and Science(ISSN: 2349-6495(P) | 2456-1908(O)),vol. 6, no. 4, pp. 310-314, AI Publications, doi:10.22161/ijaers.6.4.36
- [30] Taha A. Ansari, Sagar Jamle, (2019), "Performance Based Analysis of RC Buildings with Underground Storey Considering Soil Structure Interaction", International Journal of Advanced Engineering Research and Science (ISSN: 2349-6495(P) | 2456-1908(O)),vol. 6, no. 6, pp. 767-771, AI Publications, doi:10.22161/ijaers.6.6.89.
- [31] Taha A. Ansari, Sagar Jamle, (2019), "Performance Based Seismic Analysis of Regular R.C. Building", International Journal of Management, Technology And Engineering, ISSN: 2249-7455, Vol. 09, no. 07, pp. 342-351, DOI:16.10089.IJMTE.2019.V9I7.19.28639.
- [32] Markanday Giri, Sagar Jamle, (2019), "A Review on Response Spectrum Analysis over Flat Slab-Shear Wall Interface", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 5, pp. 5173-5177.
- [33] Mariyam, Sagar Jamle, (2019), "A Technical Approach to Flat Slab Multistorey Building under Wind Speed of 39 m/s", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 5, pp. 7629-7636.
- [34] Mariyam, Sagar Jamle, (2019), "Wind Analysis over Multistorey Building Having Flat Slab-Shear Wall Interaction: A Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2349-6495(P), 2456-1908(O)), vol. 6, no. 5, pp. 340-344, AI Publications, https://dx.doi.org/10.22161/ijaers.6.5.45.
- [35] Prakash Mandiwal, Sagar Jamle, (2019), "Tensile Strength & Durability Study on Self-Curing Concrete as a Partial Replacement of Cement by PEG-400", International Journal for Research in Engineering Application & Management(ISSN : 2454-9150), vol. 4, no. 10, pp. 244-248, doi: 10.18231/2454-9150.2018.1314
- [36] Surendra Chaurasiya, Sagar Jamle, (2019), "Twin Tower High Rise Building Subjected To Seismic Loading: A Review". International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 4, pp. 324-328, AI Publications, doi:10.22161/ijaers.64.38.
- [37] Archit Dangi, Sagar Jamle, (2019), Stability Enhancement of Optimum Outriggers and Belt Truss Structural System", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 2, pp. 772-780.
- [38] Mohd. Arif Lahori, Sagar Jamle, (2019), "Response of Multistory Building Located on 200 and 300 Sloping Ground under Seismic Loading", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 1, pp. 1063-1069.
- [39] Markanday Giri, Sagar Jamle and Kundan Meshram (2020), "Response Spectrum Analysis", LAP LAMBERT Academic Publishing, Mauritius.
- [40] Sapan Chawla, Sagar Jamle, Kundan Meshram, (2020), "A Review on Economical Design of Intz Water Tank as per IS-875-III, for Wind Speed in India", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 1, pp. 147-151. https://dx.doi.org/10.22161/ijaers.71.19
- [41] Romesh Malviya, Sagar Jamle, Kundan Meshram, (2020), "Examination on Increasing Stability of Multistoried Building: A Theoretical Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 1, pp. 162-164. https://dx.doi.org/10.22161/ijaers.71.22
- [42] Romesh Malviya, Sagar Jamle, (2020), "Increasing Stability of Multistoried Building using Different Grades of Concrete in Column Member Sets at Different Locations", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 208-213. https://doi.org/10.14741/ijcet/v.10.2.3
- [43] Sapan Chawla, Sagar Jamle, Kundan Meshram, (2020), "An Analytical Approach to find out the Efficient Design of Intz Water Tank as per Different Breeze Speed of India", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 1, pp. 48-52. https://doi.org/10.14741/ijcet/v.10.1.9
- [44] Prafoolla Thakre, Sagar Jamle, Kundan Meshram, (2020), "Opening Area Effect of Shear Wall in Multistorey Building under Seismic Loading", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 2, pp. 122-129. https://dx.doi.org/10.22161/ijaers.72.17
- [45] Mohit Kumar Prajapati, Sagar Jamle, (2020), "Strength irregularities in multistoried building using base isolation and damper in high Seismic zone: A theoretical Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 235-238. https://dx.doi.org/10.22161/ijaers.73.37
- [46] Gagan Yadav, Sagar Jamle, (2020), "Opening Effect of Core Type Shear Wall Used in Multistoried Structures: A Technical Approach in Structural Engineering", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 344-351. https://dx.doi.org/10.22161/ijaers.73.50
- [47] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "A Review on Stability Improvement with Wall Belt Supported Dual Structural System Using Different Grades of Concrete", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 293-296. https://dx.doi.org/10.22161/ijaers.73.43
- [48] Gagan Yadav, Sagar Jamle, (2020), "Use of Shear Wall with Opening in Multistoried Building: A Factual Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 243-246. https://doi.org/10.14741/ijcet/v.10.2.9
- [49] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "Stability Enhancement in Wall Belt Supported Dual Structural System using Different Grades of Concrete", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 237-242. https://doi.org/10.14741/ijcet/v.10.2.8



- [50] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by using Optimum Size of Beams with same Grade of Concrete: An Informative Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 259-262. https://doi.org/10.14741/ijcet/v.10.2.12
- [51] [50] Manoj Patidar, Sagar Jamle, (2020), "Optimization of Stability of Multistoried Structure by Changing Grades of Concrete in Shear Wall Member", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 2479-2497. https://doi.org/10.37896/JXAT12.04/979
- [52] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by Using Optimum Size of Beams in Top Floors with Different Grades in Multistoried Building at Different Levels", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 293-296. https://dx.doi.org/10.22161/ijaers.74.20
- [53] Sagar Jamle, Nirmal Delmiya, Rahul Singh, (2020), "Efficient Use of UPV Meter: A Non Destructive Test of Concrete by Fragmentation Analysis", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 3385-3394. https://doi.org/10.37896/JXAT12.04/1078
- [54] Manoj Patidar, Sagar Jamle, (2020), "Use of different Grades of Concrete in Shear Wall: A Comprehensive Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 355-359. https://dx.doi.org/10.22161/ijaers.74.44











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)