



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: VI Month of publication: June 2022

DOI: https://doi.org/10.22214/ijraset.2022.44478

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Human-Eye Controlled Virtual Mouse

Mr. Dhanaraju¹, Dr. Sreenivas Mekala², A. Harsha Vardhan Rao³, CH. Pavan Kumar⁴, R. Lokesh⁵ Associate Professors, Dept of IT, Sreenidhi Institute of Science and Technology(A), Hyderabad. B.Tech Students, Dept of IT, Sreenidhi Institute of Science and Technology(A), Hyderabad.

Abstract: There's always room for advancement in the realm of computers, thanks to new technology in our digital era. Handsfree computing is popular nowadays because it caters to the needs of quadriplegics (people suffering from paralysis of all four limbs). We want to demonstrate a Human-Computer Interaction (HCI) system that is essential for amputees and others who have trouble using their hands. The system is a mouse-like eye-based interface that converts eye movements like blinking, staring, and squinting into mouse cursor actions. The software requirements for this technique include Python, OpenCV, NumPy, and a few more facial recognition tools, as well as a basic camera. In the creation of face detectors, the HOG (Histogram of Oriented Gradients) is often utilised. and hence the window technique, which combines this feature with a linear classifier. It is completely hands-free and does notrequire any additional hardware or sensors.

I. INTRODUCTION

Moving the pointer along with the screen using a computer mouse or by moving one's finger has become fairly common in today's technology. Every movement of the mouse or finger is detected and mapped to the movement of the pointer by the system. Because their arms are not functioning, certain people, known as "amputees," will be unable to use present technology to use the mouse. If the amputee's eyeball and facial features, as well as the direction in which their eye is staring, can be recorded, the movement of the facial features may be transferred to the cursor, allowing the amputee to move the cursor at whim. An 'eye-tracking mouse' is a gadget that tracks the user's eye movements. The project relies on mapping facial traits to the cursor to recognize and capture them in video. When the camera isopened, the application must extract all of the video's frames. Since the video's frame rate is typically around 30 frames per second, every frame will be processed in about 1/30th of a second. The application then goes through a series of steps to identify and map the characteristics of the video to the point .After the frame has been retrieved, the face areas must be identified. As a result, the frames will go through a set of image-processing routines to appropriately analyse the frame, allowing the algorithm to distinguish things like eyes, mouths, and noses.The Overview Our Project performs the following functions or actions which are as follows.

- Opening the Mouth
- Right Eye Wink
- Left Eye Wink
- Squinting Eyes
- Head Movements (Pitch and Yaw)

A. Objective of the Project

The objective of our project is to make the work of 'amputees' (people who don't have their arms to be operational) easy. Amputees or quadriplegics can benefit from our project (people affected by paralysis of all four limbs) can use and operate the mouse using their facial features and actions of their eyes.

To deliver a user-friendly human-computer interaction project, this project will design a system that will just require acamera to employ human eyes and facial characteristics as a pointing device for the computer system. The following are the objectives:

- Eyes and face Detection
- Eye end points extraction
- Develop an algorithm to calculate the point gaze based on eye features extracted



- Develop a GUI that shows a result
- Develop a Calibration technique

II. DESIGN OF THE SYSTEM

A. System Design

The process of building a system's architecture, components, modules, interfaces, and data to meet specified criteria is known as system design. In a word, it is when systems theory is applied to product development. Object-oriented design and analysis processes are progressively gaining popularity as the most frequent methodology for designing computer systems.

B. Architectural Design



Figure 2.2. Architectural Design

III. METHODOLOGY

A. Implementation

- 1) Language or Technology Used: Python language is used to write the code. Python provides a wide variety of libraries for scientific and computational usage. Libraries such as hashlib, rsa
- 2) Algorithms Implemented: Deep learning models may currently be the most effective for face identification. Face detection, on the other hand, existed before deep learning. Previously, traditional feature descriptors and linear classifiers were a great way to recognize faces .HOG and Linear SVM, to be precise. The HOG (Histogram of Oriented Gradients) feature descriptor and a Linear SVM machine learning approach are used to identify faces. HOG is an easy-to-understand and useful feature description. It is frequently employed in the detection of objects, such as vehicles, dogs, and fruits, in addition to face detection. Because the local intensity is used to characterize the geometry of the item, HOG is reliable for object detection.



Step 1: HOG's primary concept is to divide a picture into small linked cells



Figure 3.1. Dividing an image into cells

Step 2: Computes the histogram for each cell.



Figure 3.2. Cell to Histogram

Step 3: Bring all of the histograms together to create a feature vector, which creates a single histogram from all of the tiny histograms that are unique to each face.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue VI June 2022- Available at www.ijraset.com



Figure 3.2. Histogram to feature vector

a) SVM Algorithm

Support Vector Machine, also known as Support Vector Classification, is a supervised and linear Machine Learning technique for dealing with classification issues. Support Vector Regression (SVR) is a subset of SupportVector Machines (SVM) that solves regression issues using the same ideas.

b) Implementing SVM in Python

With Scikit Learn's SVM package, the implementation is quite easy and basic.

- Importing Dataset

import pandas as pd

data = pd.read_csv("dataset.csv")

- Creating Training and Test Samples from the Dataset

from sklearn model_selection import train_test_split

training set, test_set = train_test_split(data, test_size = 0.2, random_state = 1)

- Classifying the Predictors and Determining the Target

X_train = training_set.iloc[:,0:2].values

Y_train = training_set.iloc[:,2].values

X_test = test_set.iloc[:,0:2].values

Y_test = test_set.iloc[:,2].values



1. Setting Up Support Fitting using the training data using VectorMachine

from sklearn.svm import SVC

classifier = SVC(kernel='rbf', random_state = 1)

classifier.fit(X_train.Y_train)

2. Predicting classes for a test set Y_pred = classifier.predict (X_test)

3. Attaching the predictions to the test set for comparing

test_set["Predictions"] = Y_pred

4. Calculating the accuracy of the predictions

from sklearn.metrics import confusion_matrix

cm = confusion_matrix(Y_test,Y_pred)

accuracy = float(cm.diagonal().sum())/len(Y_test)

print("\nAccuracy Of SVM For The Given Dataset : ", accuracy)

Output: Accuracy Of SVM For The Given Dataset : 0.875



IV. RESULTS AND ANALYSIS



To move the pointer in the desired direction, the user must point his nose towards the left andright of a rectangle. The pointer moves quicker the more he moves away from the rectangle.



To move the pointer in the desired direction, the user must point his nose on the top and down of a rectangle. The pointer moves quicker the more he moves away from the rectangle

R3 Frame	-	C × rReg	ular X G Google Photos	x a ipl-1	learth X +	- 0 ×
SEADING INPUT	Name and Address of the Owner, where the	nd+c	aa79b890cc64b4887287756a7	112370&aqs=edge.69i57.10	78j0j1&pglt=43&FO	5 th the 🔹 …
UP		Univer	sit 🕒 coursera 🗭 AWS Ac	ademy Clou 🗭 Course Mod	Mes: A	Other favorites
				\$ ⊗ ۹	English - Chintl	• 8 Q ≡
FF			MAPS SHOPPING		Get the	Wallpaper App >
	The last				Indian Premier 🖉 🕄 INDIAN	
					League	PREMIER
	Montonico		STATS	NEWS	Indian cricket tournament	
	Match 69	May 21	Match 70	May 22		
	👙 pc	159/7 (20.0)	Y SRH	157/8 (20.0)	The Indian Premier Let here 1	An official design of the second seco
	► <u>at</u> , MI	160/5 (19.1)	PBKS	160/5 (15.1)	TATA IPL for sponsors	ave you ever thought about
	MI won by 5 wickets	- 11:49	PBRS won by 5 wickata	12:40 mile	of seven Indian cities	hat a bowling alley might be left bet it's pretty fun to bowl an
					G ipit20.com Type a	nessage
	Qualifier 1	May 24	Eliminator	May 25	Countries India	2000
	RR RR	188/6 (20.0)	RCB	207/4 (20.0)	Administrator Board of Control f	or Cricket in India
	▶ 📥 GT	191/3 (19.3)	W LSG	193/6 (20.0)	Format Twenty20	
	OT won by 7 wickets	- 050	ROB won by 14 runsi	6770	First edition 2008	



The mouse can be scrolled upwards or downwards by the user. He must squint his eyes so that both of their aspect ratios are less than the necessary value. Instead of moving the pointer, the mouse performs a scrolling function if the user nose is outside the rectangle. He may scroll higherby moving his nose above the rectangle or downwards by moving his nose below the rectangle.

Frame – D X	Regular X G Google Photos X	q ipl-Search x + - i	a x	
READING INPUT!	rid=caa79b890cc64b4887287756a7112370&aqs=er	dge69i57.1078j0j1&pglt=43&FO 🛞 🗛 😘 📬 🦉	j	
SCROLL MODE IS ON!	Universit 🕝 coursera 🐌 AWS Academy Clou 🐌 Course Modules: A			
		solution		
RCB 157/8	ay 27 Final Yeste (20.0) • RR 130/9 (20	rday 0.0) Related people	>	
• 🔵 RR 161/3	(18.1) 🕨 📥 GT 133/3 (18	3.1)	1	
BR won by 7 wickets	GT won by 7 wickets	Virat Kohli Chris C		
See more matches				
News about IPL bing.com/news		2021 frand work was added to your Joropbox. be careful to ADTIL MAY 2021		
● 32°C	0	📄 📰 📑 🔳 🔿 👯 📥 🔤 🖉 🕬 🗩 🗤 🕬	11:41	

V. CONCLUSION AND FUTURE SCOPE

The works may be enhanced to boost the system's speed by using better-trained models. Furthermore, the computer may be made more dynamic by making the pointer position change proportionate to the degree of rotation of the user's head, allowing the user to choose how quickly the cursor position changes. Given that the range of values is a function of the aspect ratios, which are typically minuscule, future research might focus on enhancing the ratio's precision. As a result, it's possible that some adjustments to the formulae for the aspect ratios used will be required to increase the algorithm's detection accuracy. Certain image processing techniques may be used before the model recognises the face and its attributes in order to speed up the face recognition process.

Many persons who are unable to use a normal computer mouse or keyboard due to hand or armlimitations may be able to benefit from a multimodal system, which allows them to manage a computer without utilizing a standard mouse or keyboard in the future. Head motions are used to move the pointer across the screen, while speech is used to give control commands.

REFERENCES

- Alex Poole and Linden J. Ball, "Eye Tracking in Human-Computer Interaction and Usability Research: Current Status and Future Prospects," in Encyclopedia of Human Computer Interaction (30 December 2005) Key: citeulike:3431568, 2006, pp. 211-219.
- [2] D. H. Yoo, J. H. Kim, B. R. Lee, and M. J. Chung, "Non-contact Eye Gaze Tracking System by Mapping of Corneal Reflections," in Fifth IEEE International Conference on Automatic Face and Gesture Recognition (FGR02), 2002, pp. 94-99.
- [3] Rafael Barea, Luciano Boquete, Manuel Mazo, and Elena Lpez, "System for assisted mobility using eye movements based on electrooculography," IEEE TRANSACTIONS ONNEURAL SYSTEMS
- [4] H. Singh and J. Singh, "A Review on Electrooculography," International Journal of Advanced Engineering Technology, vol. III, no. IV, 2012.
- [5] P Ballard and George C. Stockman, "Computer operation via face orientation," in Pattern Recognition, 1992. Vol.I. Conference A: Computer Vision and Applications, Proceedings., 11th IAPR International Conference on, 1992, pp. 407-410.
- [6] T. Horprasert, Y. Yacoob, and L.S. Davis, "Computing 3-D head orientation from a monocular image sequence," in Second International Conference on Automatic Face and Gesture Recognition, 1996, pp. 242- 247.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)