



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 13 Issue: IV Month of publication: April 2025

DOI: https://doi.org/10.22214/ijraset.2025.68733

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Maritime Environment Safety: Advanced Oil Spill Detection through AIS and Remote Sensing

Prof. Senthilnathan S¹, Prof. Rajakumar R², Sanjai A³, Yuvasri S³, Suganya E⁴, Vasanth D⁵

^{1, 3, 4}Dept. of Computer Science and Engineering, JNN Institute of Engineering Chennai, India
 ⁵Dept. of Artificial Intelligence and Data Science Engineering, JNN Institute of Engineering Chennai, India
 ²Dept. of Robotics and Automation Engineering, JNN Institute of Engineering, Chennai, India

Abstract: Oil spills constitute one of the most devastating environmental disasters that threaten marine ecosystems, coastal communities, and wildlife. From identification to intervention, prompt action is necessary to reduce the impact of oil spills. Traditionally used techniques for detection of oil spills involve direct visual surveillance or simple sampling which continues to be extremely costly, slow, and unsustainable for operating on a larger scale. In this scenario, AIS data, together with technologies for satellite remote sensing, are gradually becoming promising tools for detection and monitoring of oil spills in real time over vast stretches of ocean areas. This paper looks into the feasibility of combining the two types of data, namely vessel movements tracked by AIS, and satellite datasets consisting of SAR and optical imagery for detecting and assessing oil spills in marine waters. The strengths and challenges of integrating them as a way of enhancing the efficiency of oil spill detection and timeliness in the response is highlighted.

Keywords: Marine Oil Spill Detection, Deep Learning, Swin Transformer, DeepLabv3+, U-Net, Satellite Imagery, Automatic Identification System (AIS), Environmental Monitoring, Remote Sensing, Semantic Segmentation.

I. INTRODUCTION

Oil spills are one of the most devastating types of environmental incidents, leading to long-term harm to marine ecosystems, wildlife, and coastal economies. These incidents are generally caused by maritime accidents, illegal dumping, or due to accidental leakages while performing offshore oil drilling. While the aftermath of oil spills has far-reaching ecological damage, including the loss of habitats, the affected coastal areas, and the toxins that marine species are subjected to, oil spills also have extended economic impacts on fishing activities, tourism, and the personal livelihoods of coastal-based communities. With

Increasing volumes of oil now transported across seas and oceans, along with the unpredictable nature of maritime incidents, there is an urgent requirement for new and efficient tools to detect oil spills in the marine environment and lay down a proper mitigation both in terms PM from pollution, as well as economical compensation for marine life losses. Responding quickly and effectively is critical for minimizing damage from spills. This can only be achieved via efficient surveillance and monitoring systems. Oil spill detection has most often been conducted through traditional means such as visual searches made by aircraft or ships, satellite imagery, and on-site sampling. Thus far, these means have been useful; however, they have a series of setbacks: such cases or instances can be very costly and time-consuming, apart from a limited scope for continuous overview of wide oceanic areas. For example, visual searches are resource-intensive and require trained personnel to them, in addition to being dependent on favourable weather conditions. Altogether, obtaining real-time rapid information for quick mitigation strategies has been an important issue. For the last few years, however, the advancement in Automatic Identification System (AIS) technology and satellite remote sensing have opened up a new avenue wherein identification of oil spills may be accomplished in an instantaneous and economic manner. Both technologies have some complementary benefits, which are leveraged together to augment the oil spill detection system for more success.

A. The Key Contributions of SAR in oil Spill Detection

All-weather and Night-time Monitoring: Unlike optical sensors, it ensures continuous surveillance in cloudy and dark conditions. Large area Coverage: It has the ability to scan huge ocean areas in one single pass, making it real efficient for detecting spills in faroff regions. Detection of Thin Oil Layers: It has found and ascertained even minute oil slicks, assisting in making an early spill detection and response. Distinguishing Oil from Water: Oil smoothens surface roughness, appearing as dark patches in SAR images, helping differentiate it from seawater. Integration with other Sensors: There are SAR data to couple with optical, thermal, and AIbased models for more efficient accuracy.



Limitations & Challenges: Low-wind areas or natural biogenic films are very likely mistaken for oil spills. Further validation is required through optical imagery, drones, or in-situ sampling. Overall, SAR is an efficient instrument for oil spill detection enhancement in marine environmental protection and disaster response.



II. LITERATURE REVIEW

The Automatic Identification System (AIS) is a tracking system adopted for vessels and vessel operations. It facilitates the automatic exchange of navigational data, in particular, the identification and position of the ship, speed, and course, among other vital information. Moreover, the AIS was, in concept, originally intended for collision avoidance and other maritime safety purposes, but has now found much broader applications in marine surveillance. "VTS" is called "Vessel Traffic Services," having made inroads into the collection of this data, and being in turn, monitored by maritime authorities, and eventually made publicly available through various global databases. These databases contain real-time information about vessel location, route, or speed, along with organization data that can be analyzed in the search for various types of anomalous activity that might signify a potential spill event. For example, any deviations from the course by the vessel, unexpected stops, or sudden reductions in speed, in AIS data may all signal possible involvement of such vessels in an accident or spill. However valuable AIS might be in offering insights into ship movements and activities, it possesses equally daunting limitations; foremost is the fact that vessels can deliberately switch off their AIS transponders to avoid detection. It is therefore deemed one with the perilous advantage of keeping the vessel involved in an oil spill hidden from the eyes of nearest authorities. Another concerning limitation of the AIS with respect to aiding in spill detection is that it does not provide direct information regarding environmental conditions or sea surface status; consequently, although it may indicate the presence of a vessel, it is incapable of actually detecting the spill.

A. Methods for using AIS for Oil Spills Tracking

The AIS (Automatic Identification System) directly helps track oil spills by providing useful vessel movement data, which can then be analyzed, in order to suggest suspect sources of pollution. When integrated with satellite imagery and environmental modeling, AIS plays a crucial role in spill detection, investigation, and response. The following methods outline how AIS is used for oil spill tracking:

1) Monitoring Ships and Collecting Data in Real Time

Based on shipboard transponder data, the Automatic Identification System (AIS) provides continuous and real-time broadcast data on vessel identity, position, speed, heading, and type of cargo. The vessel movement data is thus collected by coastal stations, satellites, and ship-based receivers. Such monitoring helps authorities observe movements of those vessels with oil sensitive interests such as shipping channels, offshore oil drilling zones, and marine protected areas.

2) Anomaly Detection for Identifying Potential Polluters

Using analysis of the AIS data, different kinds of unusual behaviors of vessels can be tracked to suggest illegal oil discharge. Automatic notifications may issue for anomalies such as an unplanned sudden speed reduction, irregular deviation of course, or vessels stopping in prohibited areas. Likewise, vessels that shut off or deliberately would not transmit their AIS signals (AIS spoofing-like behaviors) while on the high seas may be regarded as high risks, so monitoring is heightened.



3) Cross-Referencing AIS with Remote Sensing

Before pollution takes place, once oil pollution is confirmed through satellite observation, aerial survey, or reports from the field, then the recorded time and location of the spill are cross-checked against the AIS records by authorities to know which vessels were in the vicinity. Synthetic aperture radar (SAR)-derived images, thermal infrared imagery, and optical satellite imagery will confirm whether an AIS-traced vessel could be contributing to the pollution or not.

4) Historical Analysis of AIS Data for Source Attribution

Archival AIS data affords historical records of vessel movements and thus can provide evidence in determining if indeed a certain ship was accountable for a prior spill. By tracing the routes of ships to and from ports and identifying transferred cargo information, authorities could trace oil pollution back to the source. A clear advantage of this technique is when the spill in question is noted after a certain ship has already left the area.

5) Predicting the Movement of Spills by the Integration of AIS and Oceanographic Data

The oceanographic modeling integrated to predict the oil spills' trajectory or drift uses AIS data. According to this scheme, stabbing for the way of spills and what part of the coast they may strike could be estimated based on the provided wind, current, and wave data, along with ship traffic monitoring information. Such predictions facilitate fast reaction and containment options in upper cases. Data tracked by the Automatic Identification System is used as a basis for environmental investigations and in legal proceedings. When such vessels are suspected to be involved in oil pollution, authorities may inspect such records, examine former behaviors, and impose fines or penalties when there is evidence of illegal discharge. Therefore, by using evidence from AIS to enforce existing regulations, authorities are able to deter violations in the future and promote cleaner shipping practices. When aided by AIS data, an oil spill response can better coordinate by identifying vessels nearby that can assist with cleanup tasks. This enables response teams to quickly assess which ships are available, including oil recovery vessels or coast guard units, for deploying containment booms, skimmers, and dispersants to mitigate any environmental damage. In conclusion, AIS plays a critical role in oil spill tracking through the provision of real-time vessel monitoring, suspicious activity detection, identification of sources of spills, prediction of oil movement, and backtracking for legality enforcement. Conjoined with remote sensing, environmental modeling, and AI-built anomaly detection algorithms, AIS improves maritime safety and introduces a strong defense in protecting marine ecosystems against oil pollution.



B. Ship Tracking or Vessel Tracking/AIS

The Automatic Identification System is an important system applied in oil spill investigations, since it does not directly detect the oil itself. Instead, AIS details the history of vessel movements, which provides insight into safeguarding the identification of the spill source. If an oil slick is detected, investigators are able to use the information from the AIS system in reconstructing which ships moved through a particular area when this oil slick was present. The information broadcasted from the AIS system includes such data as the ship's identification, position, course, and speed, thus allowing the authorities to track which vessels were present and when they were there. Once this data is assessed, ships may be identified that could have been responsible, such as tankers or any other vessels carrying oil. Vessels that deviate from their given courses, come to a sudden stop, or display other unusual behavior are good candidates for suspicion.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue IV Apr 2025- Available at www.ijraset.com

Moreover, there is the necessity to combine the information from the AIS with some environmental information, such as ocean currents and wind patterns, in order to construct an improved model about how the oil spill may spread. This leads to a better prediction of the spill's trajectory, while also providing insight about where to put containment and cleanup efforts. AIS records serve as justification for any legal case against vessels responsible for oil spills, therefore, making it a key aspect of maritime enforcement. Simply put, AIS gives the background needed to explain vessel activity, which is necessary for the identification of possible sources and the tracking of oil spill impacts.

C. Ship Tracking (AIS) in Oil Spill Detection

- 1) The Automatic Identification System (AIS) is a system for locating ships designed to provide information about the position, speed, course, and identity of vessels in real time. Ships do the information transmission via VHF radio signals. The transponders always send this data to authorities, researchers, and organizations interested in monitoring vessel movements.
- 2) A Simple Explanation on the Role of AIS in Oil Spill Detection: This is the part is where it raises the question of "How does AIS help in the Oil Spill Detection?" It would look deep into this question by highlighting oil spills sources of the Marine environment as one of its major foci.
- 3) The Four-Step Process of Using AIS in Oil Spill Detection:
- Step 1: Vessel Movements Surveillance:

Gathering AIS data from the vessels in the questionable region of the sea; Close monitoring of ships particularly transporting oil or other hazardous matters;Data included ship identification, type of ship, route history, speed and current status (anchored, moving, etc.).

Step 2: Flagging anomalous behavior that would:

Draw attention with sudden speed variations, curbing their course, etc., thus being suspected of illegal discharge; Attention is given to ships that purportedly turn off their AIS transponders in open waters to evade detection and may be dumping illegally.

Step 3: In combination with remote sensing data:

Once a satellite image identifies the oil slick (SAR or optical or thermal sensors), the position is overlaid on the corresponding AIS data to check what ships could be in them. If an oil slick is identified, the AIS data will also allow the historic record of this flapping boat to be made.

Step 4: Confirming the oil spill and alerting authorities for real-time response:

Once an oil spill is confirmed and the ship identified, real-time alerts are given to authorities to make quick action; Environmental agencies and Coast Guard employ AIS data as legal torque in investigating and punishing polluters. Integrated with remote sensing and artificial intelligence-based analytics, AIS can provide better oil spill detection and monitoring. This suitable collaboration brings about quick reactions, improved enforcement, and the protection of marine ecosystems from impending damages. Future developments in AI-based anomaly detection coupled with satellite surveillance will only increase the potential of AI.



III. METHODOLOGY

The oil spill detection modelling process involves many stages: data collection, preprocessing, analysis, prediction and preparation for response planning. By combining remote sensing, AIS data and AI, the oil spill detection models offer precise identification, tracking, and movement prediction.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue IV Apr 2025- Available at www.ijraset.com

The process for modeling begins with data collection, involving several data sources, including satellites, aerial unmanned drone footage, and oceanographic information. Satellite images mostly providing from synthetic aperture radar and optical sensors enables to detect oil spills under any weather conditions. The AIS tracks all vessel movements to provide pollution sources evidence by keeping records of ship locations, speed, and course, among others. Also, oceanographic and meteorological data are acquired-wind speed, sea currents, and wave height, respectively-to understand how an oil spill would spread through its duration.

Then follows the data preprocessing, and, a little before that, data fusion. This involves remote sensing image processing to noise removal, contrast enhancement, and aligning of all datasets to a common coordinate system. Following that, for a better representation of vessel movement, AIS data should be cleaned up to eliminate duplicating or inconsistent records. Finally, integrating satellite imagery-AIS ship tracking and environmental parameters-in one with data fusion techniques renders an overall assessment of possible oil spills. This is then an AI and ML based oil spill detection model. The model extracts relevant features from the satellite images, Darcy slicks on SAR images, spectral signatures in optical images, and thermal anomalies in infrared images. Likewise, analysing the AIS info recognizes suspicious behaviors, such as sudden speed drops, undesired route changes, or loss of the AIS signal, which may indicate illegal discharges. Different technologies, including machine learning algorithms, supervised classification models, deep learning convolutional neural networks (CNNs), and unsupervised anomaly detection techniques, are used to differentiate true oil spills from false positives, such as wave shadow or algal bloom. Once the oil spill is pinpointed, predictive models simulate their movements according to hydrodynamic and atmospheric factors. Spill drift simulations scale how the oil slick will unfold over time according to the wind, currents, and water temperature. From there, environmental impact assessments will gauge what potential effects these spills have on marine ecosystems and the coasts. These simulations help the response teams effectively mobilize during containment and cleanup efforts. Regarding informing authorities, operators will receive real-time alerts enabling them to initiate prompt response actions. Decision support systems analyze the data to determine the best containment strategies to deploy, including booms, skimmers, or chemical dispersants when required. By tracking this, the AIS also helps catch which vessels are responsible, giving the polluters legal enforcement. Example diagrams include model continual refinement through ground-truth verification, a process in which observations from the field validate model predictions. Past oil spill case studies are another form of trainable data that continues to enhance model functions.

Also, advancement in satellite technology further fine-tunes hyper spectral sensor and AI-based pattern recognition capabilities into regional spill detection routines .In a nut shell, all in oil spill detection modeling works using multi-technology platforms of remote sensing, ship tracking, Artificial Intelligence, and oceanographic simulation to offer a rapid response operation in the detection, tracking, and responding to an oil spill efficiently and reliably. With such a comprehensive system in place, maritime environmental safety is greatly enhanced through a far quicker response mechanism against illegal discharges and improved long-term monitoring of marine ecosystems.

A. Swin Transformer for Oil Spill Detection

Swin Transformer is a state-of-the-art model in image processing, particularly in semantic segmentation. The Swin Transformer features hierarchical representation of image features and a shifted window mechanism, thus performing better than ordinary Vision Transformers (ViT).

- 1) Input Processing: Remote sensing images (SAR, optical, or infrared) are divided into small patches. Hierarchical feature extraction, not simply CNN-extracted features like the CU-Net .Operates on shifted windows, focusing on a specific region of an image while retaining the spatial relationships of the image .A self-attention mechanism is in position to capture long-range dependencies .Segmentation output: Produces pixel-wise oil spill segmentation maps.
- Advantages of the Oil-Spill Segmentation: Captures global and local context with equal efficiency .Handles multi-inland images much better than CNNs. Works well for multi-spectral satellite and SAR images. Cuts computation costs in comparison to standard vision transformers.





B. U-Net for Oil Spill Detection

The U-Net is a CNN architecture for image segmentation designed specifically for oil spill detection. It follows a symmetric encoder-decoder structure, making it suitable for oil spill detection. Encoder - By taking advantage of convolutional layers, it extracts important features from the input image. Bottleneck Layer - This layer captures very deep representations of oil spills. Decoder - It up samples the feature maps back to the original image size. Skip Connections - These are necessary in order to preserve the fine-grained details by means of combining multi-scale, low-level and high-level features. Final Output - It contains a binary or multichannel segmentation map that indicates trials from oil to non-oil.

1) Advantages for Oil Spill Detection: Works well with small datasets (requiring few training samples); spatial details are preserved due to skip connections; performs well for high-resolution SAR & optical images; fast and computationally more efficient than transformer-based models.



C. DeepLabV3+ for Oil Spill Detection:

DeepLabV3+ is a trendy and prosperous deep-learning CNN-based architecture that combines atrous (dilated) convolutions and spatial pyramid pooling for fine segmentation. Atrous convolution: Expanding the receptive field for gluing the oil features at multi-scales without increasing computational cost. Atrous spatial pyramid pooling: Using different sizes of receptive fields and capturing global and local oil spill features.

- 1) Encoder-decoder architecture: Encoder: Has a modified ResNet or Xception backbone for extracting deep features. ASPP: Processing oil spills at different scales. Decoder: Up sampling feature maps for accurate boundary detection. Final output: A high-resolution segmentation map with oil spills highlighted. Advantages in oil spill detection: Deals well with complex oil features and shapes. Boosts segmentation accuracy compared to plain CNNs. Effective for SAR images and multispectral satellite data. It is a trade-off between detail keeping and computational efficiency.
- 2) Conclusion: For fast and lightweight segmentation, U-Net; for high accuracy and intricate oil spill structures, DeepLabV3+; for large-scale satellite imagery and advanced modeling, Swin Transformer.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue IV Apr 2025- Available at www.ijraset.com

IV. RESULTS

Automated Oil Spill Detection Capability Demonstrated: The developed system effectively showcases the potential for automated oil spill detection through satellite imagery analysis. The integration of a Convolutional Neural Network (CNN) model, specifically the U-Net architecture, into the processing pipeline has demonstrated a robust capability for identifying and segmenting potential oil slicks within uploaded satellite images. The system outputs detection results with associated confidence scores, providing a quantifiable measure of the model's certainty in its identification of oil spill events. This capability highlights the system's promise for automating the labor-intensive task of manual image review in oil spill monitoring. Interactive and Informative Maritime Data Visualization: The web-based platform offers a highly interactive and visually rich environment for maritime data exploration. The integration of a Leaflet-based mapping interface enables users to effectively visualize vessel positions derived from Automatic Identification System (AIS) data, alongside spatial representations of detected ship anomalies and historical oil spill incidents. Users benefit from features such as location search functionality and base map layer switching, enhancing their ability to investigate specific maritime areas and analyze spatial patterns related to vessel traffic and environmental events. This visualization component provides a critical tool for situational awareness and maritime domain understanding. Functional Prototype for Core Monitoring Tasks Validated: The Marine Oil Spill Monitoring System prototype successfully validates the feasibility of an integrated platform for key marine environmental monitoring tasks. The system's functionality extends across several crucial areas, including: Vessel Activity Visualization: Displaying and interacting with maritime vessel data on an interactive map. Anomaly Detection Review: Filtering and examining detected ship anomalies based on type and severity, facilitating targeted investigation of unusual vessel behaviors. Oil Spill Detection Testing: Uploading and processing satellite imagery through the AI-powered detection model to obtain automated oil spill identification results. These combined functionalities demonstrate the system's potential as a comprehensive tool for enhancing marine environmental surveillance and response capabilities. The prototype effectively integrates data streams, advanced AI analysis, and a user-friendly interface to support informed decision-making in maritime safety and environmental protection.



REFERENCES

- Garcia, F., & Thomas, D. (2020). "Use of AIS and Remote Sensing Data for Oil Spill Detection in the Mediterranean Sea." Marine Pollution Bulletin, 150(1), 26-34.
- [2] Lu, W., & Zhao, S. (2019). "The Application of Satellite SAR for Monitoring Oil Spills in the Ocean." Remote Sensing, 11(12), 1432.
- [3] Manfreda, S., & Tarantino, A. (2021). "Integrating AIS Data and Satellite Imagery for Oil Spill Monitoring." International Journal of Environmental Monitoring, 8(2), 112-125.
- [4] Solberg, A.H.; Brekke, C.; Husoy, P.O. Oil spill detection in Radarsat and Envisat SAR images. IEEE Trans. Geosci. Remote Sens. 2007, 45, 746–755.
 [CrossRef].
- [5] Fingas, M.; Brown, C. Review of oil spill remote sensing. Mar. Pollut. Bull. 2014, 83, 9–23. [CrossRef] [PubMed].
- [6] Fingas, M.F.; Brown, C.E. Review of oil spill remote sensing. Spill Sci. Technol. Bull. 1997, 4, 199–208. [CrossRef].

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue IV Apr 2025- Available at www.ijraset.com

- [7] Espedal, H.; Johannessen, O. Cover: Detection of oil spills near offshore installations using synthetic aperture radar (SAR). Int. J. Remote Sens. 2000, 21, 2141–2144. [CrossRef].
- [8] Kapustin, I.A.; Shomina, O.V.; Ermoshkin, A.V.; Bogatov, N.A.; Kupaev, A.V.; Molkov, A.A.; Ermakov, S.A. On Capabilities of Tracking Marine Surface Currents Using Artificial Film Slicks. Remote Sens. 2019, 11, 840. [CrossRef].
- [9] Solberg, A.S.; Storvik, G.; Solberg, R.; Volden, E. Automatic detection of oil spills in ERS SAR images. IEEE Trans. Geosci. Remote Sens. 1999, 37, 1916–1924. [CrossRef].
- [10] Fiscella, B.; Giancaspro, A.; Nirchio, F.; Pavese, P.; Trivero, P. Oil spill detection using marine SAR images. Int. J. Remote Sens. 2000, 21, 3561–3566. [CrossRef].
- [11] Espedal, H. Satellite SAR oil spill detection using wind history information. Int. J. Remote Sens. 1999, 20, 49-65. [CrossRef].
- [12] Karantzalos, K.; Argialas, D. Automatic detection and tracking of oil spills in SAR imagery with level set segmentation. Int. J. Remote Sens. 2008, 29, 6281– 6296. [CrossRef]











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)