iJRASET
International Journal For Research in Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 14 **Issue:** X **Month of publication:** October 2026

DOI: https://doi.org/10.22214/ijraset.2026.85470

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 14 Issue X Oct 2026- Available at www.ijraset.com

PCB Fault Detection AI-Based Inspection of Printed Circuit Boards

Yogini Diwate[1], Tejas Chamat[2], Bhavesh Mesharam[3], Darshak Kakde[4], Mohd Faik[5]
Priyadarshini College of Engineering Nagpur, Department of Robotics & Artificial Intelligence

Abstract: ***Printed Circuit Boards (PCBs) are essential components of electronic devices, and even minor defects can affect their performance and reliability. Traditional manual inspection is time-consuming and may fail to identify small defects such as missing components, broken copper tracks, soldering errors, and incorrect component placement. To overcome these limitations, the proposed AI-Based PCB Fault Detection System uses computer vision and image processing techniques to analyze PCB images and identify potentially defective regions. The system is developed using Python and OpenCV for image preprocessing and comparison, with an optional machine learning or Convolutional Neural Network (CNN) model for defect detection and classification. The detected results are displayed as a pass/fail status or a possible defect indication, with suspicious regions highlighted wherever supported. This system aims to improve inspection speed, consistency, and quality control while reducing manual effort and rework. However, its reliability depends on image quality, dataset quality, and proper validation.***

Keywords: PCB Fault Detection, Artificial Intelligence, Computer Vision, Image Processing, OpenCV, CNN, Defect Classification, Quality Inspection.

I. INTRODUCTION

Printed Circuit Boards (PCBs) are essential components of modern electronic devices, including computers, mobile phones, medical equipment, automobiles, and industrial control systems. They provide mechanical support and electrical connections between electronic components through copper tracks arranged on an insulating board. The proper functioning of a PCB is important for ensuring the reliability, safety, and performance of electronic products. Even a small defect in a PCB can interrupt electrical connections, affect circuit operation, or cause complete device failure. Therefore, inspecting PCB quality during the manufacturing process is necessary to maintain product standards and reduce production errors.

Traditional PCB inspection methods mainly depend on manual visual examination, where trained operators carefully check the board for defects. Although this method is widely used, it can be time-consuming, labour-intensive, and dependent on the experience and concentration of the inspector. Identifying tiny defects becomes increasingly difficult when inspecting complex circuit boards containing numerous components and closely spaced copper tracks. In large-scale manufacturing, manual inspection may also lead to inconsistent results and increase the possibility of defects being overlooked. These limitations create a need for an automated inspection system that can support faster and more consistent PCB quality assessment.

The AI-Based PCB Fault Detection System is proposed to address these challenges by using computer vision and artificial intelligence techniques to analyze PCB images. The system accepts images captured using a camera or obtained from an existing dataset. These images undergo preprocessing operations such as resizing, alignment, noise reduction, and image enhancement to improve their suitability for analysis. OpenCV is used to perform image processing and visual comparison, while machine learning or Convolutional Neural Network (CNN) models can be incorporated to recognize defect patterns. The system examines the processed images and identifies suspicious regions that may indicate a PCB fault.

The proposed system focuses on detecting common visual defects, including missing components, broken or interrupted copper tracks, soldering defects, solder bridges, and incorrect component placement. After analyzing the image, the system displays the inspection result, such as “No Visible Defect Detected” or “Possible Defect Found.” Where the selected detection method supports localization, the suspicious area can also be marked on the PCB image to help the user identify the potential problem. This approach can assist technicians and quality-control personnel in performing preliminary inspections more efficiently. However, the system's performance depends on image quality, lighting conditions, the availability of suitable training data, and the accuracy of the detection method.

The main aim of this project is to develop a simple, efficient, and reliable computer-vision-based approach for preliminary PCB fault detection. By combining Python, OpenCV, and optional AI-based classification, the system seeks to reduce manual inspection effort, improve consistency, and identify potential visual defects before the PCB proceeds to the next stage of production.

©IJRASET: All Rights are Reserved

The proposed solution can be applied in electronics manufacturing industries, quality-control laboratories, repair centres, and academic research projects. In the future, the system can be enhanced with real-time camera integration, advanced object detection models, additional defect categories, and performance evaluation using accuracy, precision, recall, and processing speed. It is intended to support human inspection rather than completely replace electrical testing or expert verification.

II. AIMS & OBJECTIVES

A. Aim:

The main aim of the AI-Based PCB Fault Detection System is to develop an automated computer vision system that analyzes Printed Circuit Board (PCB) images to identify potential visual defects, such as missing components, broken copper tracks, soldering errors, and incorrect component placement. The system aims to improve inspection speed, consistency, and quality control while reducing the limitations of manual inspection.

B. Objectives:

- To capture PCB images using a camera or load existing images from a suitable dataset for inspection.
- To improve image quality through resizing, alignment, noise reduction, and image enhancement for accurate analysis.
- To identify potential PCB defects using image processing techniques and, where available, machine learning or CNN-based models.
- To classify detected visual defects into categories such as missing components, broken tracks, soldering defects, and component placement errors, depending on the model's capabilities.
- To highlight suspicious regions in the PCB image so that users can easily identify areas requiring further inspection.
- To develop a simple user interface that displays the input image, detected defects, and an appropriate status such as “Possible Defect Found” or “No Visible Defect Detected.”
- To evaluate the system using suitable test images and performance measures such as accuracy, precision, recall, and processing time to assess its effectiveness and reliability.

III. LITERATURE SURVEY

1) Traditional Image Processing Techniques: Early PCB inspection systems used image processing methods to compare a reference PCB image with an inspected image. These techniques help identify missing components, broken tracks, and visible differences. However, their performance can be affected by lighting conditions, image alignment, and noise.

2) Machine Vision-Based Inspection: Research on machine vision has explored automated optical inspection using image acquisition, preprocessing, feature extraction, and defect classification. These systems improve inspection consistency and reduce dependence on manual checking.

3) Machine Learning Approaches: Machine learning techniques use extracted image features to classify PCB images as defective or non-defective. Their effectiveness depends on selecting suitable features and providing representative training data.

4) Deep Learning and CNN Models: Convolutional Neural Networks (CNNs) automatically learn visual patterns from PCB images and can identify different defect types. Research reviews indicate that deep learning can improve detection performance compared with several conventional approaches, although training data and computational requirements remain important considerations.

5) Object Detection Techniques: Models such as YOLO, Faster R-CNN, and SSD have been investigated for detecting and locating PCB defects. These approaches can identify suspicious regions and help users understand where a defect may be present.

6) Dataset and Image Quality: Studies highlight that image contamination, poor image quality, and insufficient defect samples can reduce detection reliability. Therefore, image preprocessing, proper dataset preparation, and testing under different imaging conditions are important for developing a dependable inspection system.

7) Research Gap and Proposed System: Existing approaches may require specialized equipment, extensive training data, or significant computational resources. The proposed system aims to provide a simple and accessible solution using Python and OpenCV, with optional CNN-based detection, to analyze PCB images, identify possible visual defects, and display the inspection results. The system can be extended with real-time camera inspection and performance evaluation to improve its practical usefulness.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

IV. METHODOLOGY

The proposed PCB Fault Detection System uses computer vision and artificial intelligence to identify potential defects in Printed Circuit Boards (PCBs). The methodology consists of image acquisition, preprocessing, feature extraction, defect detection, classification, and result visualization. Python is used as the primary programming language, while OpenCV performs image processing operations. A machine learning or Convolutional Neural Network (CNN) model can be integrated to improve defect recognition.

1) PCB Image Acquisition

PCB images are collected using a digital camera or an existing dataset containing normal and defective circuit boards. The images should clearly show the copper tracks, solder joints, and electronic components. Reference images of defect-free PCBs may also be used for comparison with the inspected boards.

2) Image Preprocessing

The captured images are processed to improve their quality and consistency. Operations such as resizing, noise reduction, brightness adjustment, and image alignment are performed using OpenCV. Preprocessing helps reduce unwanted variations and makes it easier to identify differences between normal and defective PCB regions.

3) Feature Extraction and Image Comparison

After preprocessing, the system examines important visual characteristics, including copper track continuity, component presence, solder joint appearance, and component placement. In a traditional image-processing approach, the inspected image is compared with a reference image to identify differences. In an AI-based approach, the model learns defect-related patterns from labelled PCB images.

4) Defect Detection

The processed image is analyzed to identify suspicious regions that may contain defects. The system focuses on common visible faults, such as missing components, broken tracks, solder bridges, and incorrect component placement. OpenCV-based methods can identify certain differences, while a trained CNN or object detection model can recognize more complex defect patterns.

5) Defect Classification and Decision-Making

The detected regions are evaluated to determine whether the PCB may contain a defect. Depending on the implemented model, the system can classify the image as defective or non-defective and may also identify the type of defect. A confidence score or decision threshold can be used to determine when a result should be flagged for manual verification.

6) Result Visualization

The inspection result is displayed through a simple user interface. The output may include the original PCB image, the detected defect category, and a marked suspicious region if localization is supported. The system displays a status such as “Possible Defect Found” or “No Visible Defect Detected.” These results help the operator identify boards that require additional inspection.

7) Testing and Performance Evaluation

The system is tested using different PCB images containing normal boards and known defects. Its performance is evaluated using accuracy, precision, recall, and processing time. The results are analyzed to identify detection errors and improve the preprocessing methods or AI model. Electrical testing and expert inspection remain necessary for faults that cannot be identified visually.

Working of the Proposed System

The working process of the AI-Based PCB Fault Detection System follows a sequence of operations from image input to final result generation.

- Input: The user uploads a PCB image through the interface or captures it using a camera.
- Preprocessing: The system resizes and enhances the image, reduces noise, and aligns it when required.
- Analysis: The processed image is compared with a reference PCB image or analyzed using a trained AI model.
- Fault Identification: The system searches for visual abnormalities, including missing components, broken copper tracks, soldering defects, and placement errors.
- Classification: The detected patterns are classified according to the capabilities of the selected image-processing method or AI model.
- Output Generation: The system displays the inspection status and highlights the suspicious area when supported by the detection technique.
- Verification: The operator reviews the result and performs further visual or electrical testing when necessary.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

Expected outcome: The proposed system provides an automated method for preliminary PCB visual inspection. It helps reduce manual effort, improves inspection consistency, and assists in identifying potentially defective boards before they proceed to the next stage of manufacturing. Actual detection performance depends on the selected algorithm, image quality, and availability of suitable training and testing data.




Figure 1: Flowchart of the proposed system




Figure 2: Step by Step working of the system

V. RESULTS

The proposed AI-Based PCB Fault Detection System provides an automated approach for inspecting Printed Circuit Board images using image processing and artificial intelligence techniques. The system processes input images, improves image quality, and analyzes visual patterns to identify potential defects such as missing components, broken copper tracks, soldering errors, and incorrect component placement. The inspection results are displayed as “Possible Defect Found” or “No Visible Defect Detected,” with suspicious regions highlighted when supported by the implemented method. The system has the potential to reduce manual inspection time and improve consistency in quality control. However, its actual accuracy and reliability must be evaluated using appropriate PCB image datasets and performance metrics.




Figure 3: Proposed model of the system





Figure 4: PCB Design of the system

VI. CONCLUSION

The AI-Based PCB Fault Detection System aims to improve the efficiency and consistency of PCB quality inspection by combining Python, OpenCV, and optional machine learning or CNN models. By automatically analyzing PCB images and identifying suspicious regions, the system can assist technicians in detecting visible defects at an early stage, potentially reducing rework and improving manufacturing quality. Its performance depends on image quality, dataset diversity, and the effectiveness of the selected detection algorithm. In the future, the system can be enhanced through real-time camera integration, improved defect classification, and more accurate localization techniques. Although it supports visual inspection, additional electrical testing and expert verification are necessary to identify faults that cannot be detected from images alone.

REFERENCES

[1] badboysm890. Pcb defect detection using yolov5. GitHub repository, 2023. [Online]. Available: https://github.com/badboysm890/PCB-Defect-Detection.
[2] JiaLim98. Yolo-pcb defect dataset & detection. GitHub repository, 2023. [Online]. Available: https://github.com/JiaLim98/YOLO-PCB.
[3] PCBWay. Pcb flying probe test: Principles, advantages, and applications. PCBWay Blog, 2023. [Online]. Available: https://www.pcbway.com/blog/PCBManufacturingInformation/PCBFlyingProbeTestPrinciplesAdvantagesandApplicationsbc222b0f.html.
[4] ProtoExpress. How flying probe testing works for pcb assembly. ProtoExpress Blog, 2023. [Online]. Available: https://www.protoexpress.com/blog/how-flying-probe-testing-worksfor-pcb-assembly/.
[5] ResearchGate. A review: Comparison of performance metrics of pretrained models for object detection using the tensorflow framework - scientific figure. ResearchGate, 2025. [Online]. Available: https://www.researchgate.net/figure/Comparison-of-framesprocessed-per-second-FPS-implementing-the-Faster-R-CNN-R-FCN-SSDfig6342570032 [Accessed : 4Nov2025].
[6] ryanq04. Automated pcb tester with stm32 and python gui. GitHub repository, 2022. [Online]. Available: https://github.com/ryanq04/automatedpcbtester.
[7] H. Wang et al. Lightweight improved yolov5 algorithm for pcb defect detection. The Journal of Supercomputing, 2024. [Online]. Available: https://link.springer.com/article/10.1007/s11227-024-06739-w.
[8] S. Zhang et al. Yolo-pdd: A novel multi-scale pcb defect detection method using deep representations with sequential images. arXiv preprint, 2024. [Online]. Available: https://arxiv.org/abs/2407.15427.
[9] K. Eves and J. Valasek, Adaptive control for singularly perturbed systems examples, Code Ocean, Aug. 2023. [Online]. Available: https://codeocean.com/capsule/4989235/tree
[10] S. Liu, Wi-Fi Energy Detection Testbed (12MTC), 2023, gitHub repository. [Online]. Available: https://github.com/liustone99/Wi-Fi-Energy-Detection-Testbed-12MTC



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)