



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 13 Issue: III Month of publication: March 2025

DOI: <https://doi.org/10.22214/ijraset.2025.67478>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Robotic Arm using joystick Control for Pick-and-Place Operations

Shruti Vrushabh Kokile¹, Samiksha Sachin Magdum², Manasi Adinath Patil³, Sanika Nitin Patil⁴, Aasma Babu Mujawar⁵

Sharad Institute of Technology, Polytechnic Yadrav

Abstract: *The advancement of automation and robotics has led to the development of more intuitive control systems for robotic arms. This paper presents the design and implementation of a joystick-controlled robotic arm for efficient pick-and-place operations. Unlike traditional pre-programmed robotic systems, this approach allows real-time human intervention, making it suitable for industrial, warehouse, and educational applications.*

The system comprises a joystick interface, microcontroller (Arduino/Raspberry Pi), servo motors, and a gripper mechanism. The joystick provides user input, which is processed by the microcontroller to control the robotic arm's movements across multiple axes. The system is programmed using C++ and Python, ensuring smooth and precise motor control through PWM signals and PID algorithms.

Experimental results demonstrate high accuracy, low response time, and ease of use. The system effectively picks and places objects with minimal error, making it a viable alternative to complex automated systems. Future enhancements include AI-based path optimization, computer vision integration, and wireless control for remote operation.

This project bridges the gap between manual and automated control, offering a flexible, user-friendly robotic solution for various industries.

Keywords Explanation:

- 1) **Robotic Arm:** A programmable mechanical arm designed to mimic human hand movements for industrial and automation tasks. It consists of multiple joints and actuators to perform precise operations.
- 2) **Joystick Control:** A manual input device that allows users to control the movement of the robotic arm in real-time, providing an intuitive and flexible alternative to pre-programmed automation.
- 3) **Automation:** The process of using technology to perform tasks with minimal human intervention, increasing efficiency and accuracy in industries such as manufacturing and logistics.
- 4) **Pick and Place:** A common robotic operation where an object is picked from one location and placed at another, widely used in assembly lines, warehouses, and packaging industries.
- 5) **Embedded Systems:** A combination of hardware and software designed to perform dedicated functions, such as controlling robotic movements, using microcontrollers

I. INTRODUCTION

A. Background & Importance

Automation and robotics have transformed industries by enhancing efficiency, precision, and reliability. Robotic arms are widely used in manufacturing, warehousing, and material handling to perform repetitive tasks with high accuracy. Traditional robotic arms rely on pre-programmed movement sequences, which require specialized programming knowledge and lack flexibility.

A joystick-controlled robotic arm offers a real-time, user-friendly alternative, allowing direct manual control for tasks such as pick-and-place operations. This makes it suitable for environments where human intervention is necessary, such as custom assembly lines, research labs, and educational purposes. By integrating joystick-based control, users can operate the robotic arm intuitively, eliminating the need for complex coding.

B. Problem Statement

Most existing robotic arms depend on pre-programmed automation or AI-based vision systems, which are often costly and complex. Fully automated solutions are efficient but lack adaptability in dynamic environments where objects may not be in fixed positions. A joystick-controlled system provides greater flexibility, allowing operators to manually guide the robotic arm in real time. The challenge lies in ensuring smooth, precise, and responsive movement while maintaining ease of use, accuracy, and affordability.

C. Objective

This project aims to design and implement a joystick-controlled robotic arm for pick-and-place operations. The specific objectives include:

- 1) Developing a microcontroller-based control system to process joystick inputs and drive motors.
- 2) Implementing smooth and precise movement algorithms using PWM signals and PID control.
- 3) Ensuring accurate object gripping and placement using a servo-controlled end effector.
- 4) Testing system performance in terms of accuracy, speed, and load capacity.
- 5) Exploring future enhancements, such as AI-based semi-automation and wireless control.

D. Scope of the Study

This project focuses on hardware and software integration for an intuitive robotic arm control system. The key areas of study include:

- 1) Mechanical Design: Selection of lightweight and durable materials for the robotic arm structure.
- 2) Electronic Components: Integration of joystick, microcontroller (Arduino/Raspberry Pi), motor drivers, and servo/stepper motors.
- 3) Software Development: Programming joystick movement mapping, motor control, and safety mechanisms using C++/Python.
- 4) System Testing & Calibration: Evaluating performance based on accuracy, response time, and weight-handling capacity.
- 5) Applications: Suitable for industrial automation, warehouse logistics, educational training, and assistive robotics.

II. LITERATURE REVIEW

A. Existing Methods of Robotic Arm Control

1) Pre-Programmed Movements

Pre-programmed robotic arms follow predefined motion sequences set through coding or offline programming. These systems are commonly used in automated manufacturing and industrial production lines, where repetitive tasks like welding, assembly, and packaging are performed with high precision.

Advantages:

- High accuracy and repeatability.
- Efficient for mass production and repetitive tasks.

Disadvantages:

- Lacks flexibility—cannot adapt to dynamic environments.
- Requires skilled programming for modification.

2) AI-Based Automation

AI-powered robotic arms use machine learning and computer vision to recognize objects, adapt to different conditions, and optimize motion. These systems are used in smart factories, autonomous warehouses, and robotic-assisted surgery.

Advantages:

- Adaptive and capable of decision-making.
- Reduces human intervention in hazardous environments.

Disadvantages:

- High computational and hardware costs.
- Requires extensive training data for machine learning models.

3) Sensor-Based Control

This method uses various sensors (ultrasonic, infrared, vision, force sensors) to guide robotic movements. The robotic arm detects objects and obstacles, adjusting its path accordingly. Used in assembly lines, quality inspection, and medical robotics.

Advantages:

- Enhances accuracy by responding to environmental changes.
- Suitable for applications requiring precise object manipulation.

Disadvantages:

- Can be expensive, depending on the type of sensors used.
- Complex integration and calibration are required.

B. Comparison with Joystick-Based Control

Joystick-controlled robotic arms provide real-time manual control, making them ideal for applications requiring human decision-making and adaptability.

Joystick-based control bridges the gap between manual operation and full automation, making it suitable for applications where real-time human control is essential.

C. Research Gap

Limited real-time adaptability in existing methods: Pre-programmed systems lack flexibility, while AI-based and sensor-driven automation is expensive and complex.

Need for cost-effective, easy-to-use solutions: Small industries, research labs, and educational institutions require an affordable, real-time robotic control system.

Bridging manual control with automation: Joystick-controlled robotic arms can be further enhanced with semi-automation using AI and sensor feedback, creating a hybrid control system.

This research focuses on developing a low-cost, real-time joystick-controlled robotic arm while exploring future AI and sensor integration for semi-automated functionality.

III. METHODOLOGY

A. System Architecture

The system consists of:

- Joystick: Provides user input for arm movement.
- Microcontroller (Arduino/Raspberry Pi): Processes joystick signals and controls motors.
- Motor Drivers: Interface between microcontroller and motors.
- Robotic Arm: Performs the pick-and-place action.
- Power Supply: Provides energy to the system.

B. Hardware Components

• *Joystick*

Analog or digital joystick for multi-axis control.

Provides X, Y movement for the arm, Z for grip control.

• *Microcontroller*

Arduino, ESP32, Raspberry Pi, or STM32 for signal processing.

Converts joystick signals into motor commands.

• *Motors*

Servo Motors for precise movement control.

Stepper Motors if higher accuracy is needed.

• *End Effector*

Gripper or suction mechanism for picking objects.

• *Frame & Materials*

Aluminum or 3D-printed plastic for lightweight and durability.

C. Software & Control System

- Programming in C++, Python, or MATLAB to process joystick inputs.
- PWM signals and PID control algorithms for motor precision.
- Wireless Communication (if used): Bluetooth or RF module for remote operation.

IV. IMPLEMENTATION & EXECUTION

A. Assembly & Wiring

Connecting joystick to microcontroller.
Wiring motors through motor driver.
Power supply integration for stable operation.
Creating a mechanical frame for the robotic arm.

B. Software Development

Joystick Mapping: Translating user movements into robotic arm motion.
Motor Control Code: PWM signal generation for smooth movement.
Safety Mechanisms: Implementing software limits to prevent overextension.

C. Testing & Calibration

Accuracy Testing: Ensuring the robotic arm follows joystick input correctly.
Load Testing: Evaluating the maximum weight the arm can lift.
Speed & Response Time Analysis: Measuring delays between input and action.

V. RESULTS & DISCUSSION

A. Performance Evaluation

Accuracy: The arm successfully places objects with minimal error.
Speed: Real-time response with joystick input.
Load-bearing capacity: Can handle small industrial objects.
Comparison with Fully Automated Systems:
Joystick Control: Provides human flexibility.
Pre-programmed Automation: More efficient but lacks adaptability.

B. Challenges Faced & Solutions

Latency Issues: Optimized with better microcontroller processing.
Mechanical Limitations: Improved by selecting lightweight materials.

VI. CONCLUSION & FUTURE WORK

A. Conclusion

The joystick-controlled robotic arm successfully performed pick-and-place tasks with high precision. It provides a user-friendly alternative to complex automated systems.

B. Limitations

Requires constant manual operation.
Limited by the range of the joystick movement.

C. Future Work

AI-based automation: Learning from joystick inputs for semi-automation.
Computer Vision Integration: Allowing the robotic arm to recognize and pick objects autonomously.
Wireless & Cloud Control: Remote operation via IoT.

REFERENCES

- [1] Cite relevant research papers, books, and websites used.
- [2] Follow APA, IEEE, or required citation style.

APPENDICES

Circuit Diagrams for electronic connections.
3D Models or CAD Drawings of the robotic arm.
Source Code for joystick and motor control.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)