



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 13 Issue: X Month of publication: October 2025

DOI: https://doi.org/10.22214/ijraset.2025.74533

www.ijraset.com

Call: © 08813907089 E-mail ID: ijraset@gmail.com



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue X Oct 2025- Available at www.ijraset.com

Simulating the Future Flow: An AI-Powered Framework for Predicting River Health

Taruna Sharma¹, Priyansha Sachdev²

¹Associate Professor, HMR Institute of Technology and Management, Hamidpur

²Data Engineer, Orange Business Services, Gurugram

Abstract: Rivers are a part of ecosystems, are increasingly vulnerable to the cumulative impacts of human activity, including urban sprawl, industrial discharge, and agricultural intensification. Addressing the complexity of these evolving threats requires some intelligent, data-driven approaches that move beyond conventional monitoring. This study presents NeuroAquaMorph, a comprehensive AI-powered framework designed to model, simulate, and forecast the morphological and physico-chemical evolution of aquatic systems under anthropogenic stress. By integrating diverse datasets ranging from water quality metrics and climatic variables to land use patterns and population density,the framework employs a hybrid suite of machine learning modelsincluding Random Forest, Support Vector Regression, and engineered LSTM-GRU simulations. The system is further enhanced through explainability techniques such as SHAP and permutation importance, ensuring transparency and trust in predictions. Detailed spatial and temporal analyses illuminate critical changes in river parameters like sediment load, microbial contamination, nutrient influx, and channel geometry. Interactive visualizations and scenario-based simulations offer actionable insights for sustainable river basin management and policy-making. With its modular architecture, interpretability, and scalability, NeuroAquaMorph represents a significant step toward intelligent environmental governance. The research concludes by outlining pathways for real-time integration, deep learning enhancement, and cross-regional application, aiming to support long-term ecological resilience and informed decision-making.

Keywords: River Health Monitoring, Machine Learning, Anthropogenic Impact, Environmental Modeling, AI in Water Resource Management

I. INTRODUCTION

Rivers, the lifelines of every civilization, are silently enduring the consequences of human ambition. Once pristine and self-sustaining, many aquatic ecosystems today are choked by pollution, manipulated by infrastructure, and strained by the unchecked demands of development. Across the globe, these flowing ecosystems reflect a stark reality where rapid urbanization, industrialization, and agricultural expansion have distorted the natural rhythms of rivers, threatening both ecological balance and public health. This research emerges from the urgent need to understand, predict, and mitigate these complex impacts. At the heart of this study is NeuroAquaMorph, an intelligent and AI powered framework designed not merely to monitor but to simulate and forecast the morphological and physicochemical evolution of river systems under anthropogenic pressure. It brings together data science and environmental stewardship, combining machine learning algorithms, geospatial analysis, and temporal modeling to reveal how human activity reshapes river morphology, water chemistry, and overall ecological health.

By analyzing parameters such as sediment load, nutrient pollution, microbial contamination, and channel morphology, this paper constructs a data driven narrative of riverine degradation. Yet, it does not stop at diagnosis. It offers a path toward solution. Through scenario simulations, predictive modeling, and visual analytics, NeuroAquaMorph functions as a powerful decision support system for sustainable river management, informed policy planning, and ecological restoration. This work is more than a technical study. It is a call to reimagine our relationship with nature through the lens of intelligence, clarity, and responsibility. It reminds us that in every altered riverbank and declining pH level lies a story not only of environmental loss but of decisions made however the future is still within reach. In decoding these patterns, this research aims to transform knowledge into action and data into meaningful change.

II. LITERATURE REVIEW

Numerous studies have explored the use of machine learning and data-driven approaches to assess and predict riverine health. Guo et al. (2019) applied Random Forest and Support Vector Regression to predict water quality indicators like BOD and COD, demonstrating strong accuracy across diverse datasets [1].



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue X Oct 2025- Available at www.ijraset.com

Similarly, Noori et al. (2011) used ANN-based models for dissolved oxygen prediction, outperforming traditional regression methods. In the realm of time-series analysis, Zhang et al. (2020) highlighted the effectiveness of LSTM networks for capturing long-term dependencies in water quality trends [7]. However, due to the high data and computational demands of deep learning, researchers such as Yaseen et al. (2018) proposed hybrid models using engineered features to simulate sequential behavior in simpler algorithms.

Spatial analysis has also played a pivotal role in the study. Li and Zhang (2018) utilized GIS and remote sensing to map sediment transport and land use change, while Ahmed et al. (2021) integrated climate and land cover data into hydrological models to forecast pollution hotspots [6]. The need for model interpretability has been addressed by Lundberg and Lee (2017) through SHAP, enabling transparent decision-making in environmental AI. These foundational works collectively inform the development of integrated, interpretable, and scalable frameworks like the one proposed in this study.

III. METHODOLOGY

The framework is designed as a comprehensive, scalable, and intelligent system to simulate and predict the morphological and physico-chemical evolution of aquatic ecosystems under anthropogenic influence. Its architecture follows a structured data flow beginning with the collection of heterogeneous inputs, ranging from water quality indicators and climatic variables to land use patterns and population density.

After rigorous preprocessing and feature engineering, this refined dataset is funneled into a diverse suite of AI/ML algorithms including Random Forest, Linear Regression, SVR, and engineered LSTM/GRU simulations. These models are strategically chosen to capture both linear and non-linear dependencies as well as simulating temporal dynamics through sequential feature inputs. The system architecture is modular and layered, ensuring adaptability and reproducibility through clear separation of data ingestion, modeling, simulation, and explainability components. To deepen insights and transparency, a statistical and interpretability analysis is integrated using SHAP, permutation importance, and trend decomposition enabling causality tracing and actionable understanding.

Visualizations such as time-series plots, spatial heatmaps, and anomaly graphs further bring the data to life, complemented by autogenerated analytical reports. This synergistic workflow bridges advanced computational modeling with environmental science, providing a robust tool for real-time monitoring, scenario forecasting, and policy-level decision support in river health and water resource management.

A. FLOW

The NeuroAquaMorph framework adopts a structured and iterative workflow designed to model and simulate the morphological and physio-chemical evolution of aquatic systems under anthropogenic influence. The workflow initiated with data acquisition from diverse sources, including water quality metrics, climatic variables, population density, and land use patterns [4].

These heterogeneous datasets are integrated following rigorous preprocessing steps such as spatial and temporal alignment, missing value imputation, and feature engineering to enhance data quality and model readiness. Subsequently, the refined dataset is utilized to train multiple machine learning models, including both traditional regression algorithms and advanced time-series architectures. This multi-model approach enables comparative evaluation and robust scenario analysis, ensuring reliability across a range of environmental contexts.

The trained models are then employed to forecast future trends under defined scenarios—such as business-as-usual or highdevelopment trajectories while accounting for uncertainty through statistical quantification methods. The workflow culminates in the generation of interactive visualizations and comprehensive analytical reports that facilitate interpretation and communication of results to both technical and policy-oriented audiences.

Furthermore, the system is designed for periodic updates, allowing incorporation of new data and re-training of models to maintain predictive accuracy over time. This end-to-end pipeline ensures a reproducible, adaptable, and scalable solution for environmental modeling.




Figure 1: The complete flow of the NeuroAquaMorph

B. TECHNOLOGY AND MODULES USED

The framework is developed using a robust scientific computing stack built on Python 3.9, incorporating essential libraries such as NumPy and Pandas for numerical computation and data handling, and Scikit-learn for implementing machine learning algorithms including ensemble methods, support vector regression, and linear models. Visualization capabilities are supported through Matplotlib and Seaborn, while Streamlit is utilized for creating interactive and interpretable dashboards. Data storage and configuration management are facilitated through formats such as CSV, Parquet, JSON, and YAML, ensuring both flexibility and compatibility with diverse data sources.

The system adopts a modular, layered architecture organized around core functional components, data ingestion, modeling, simulation, and explainability allowing for seamless extensibility and clear separation of concerns. Each layer communicates through well-defined interfaces, ensuring interoperability and maintainability. The core orchestrator governs the overall workflow, integrating submodules for data preprocessing, model training and evaluation, simulation of future scenarios, explainable AI, and visual analytics. The data module harmonizes heterogeneous datasets including water quality parameters, climate indicators, land use patterns, and synthetic data generation. The model manager supports multiple ML models, while the simulation engine enables forecasting under varied socio-environmental scenarios. Explainability is achieved through SHAP and LIME, and results are presented through customizable visual dashboards.

```
import logging
import numpy as np
import pandas as pd
from typing import Dict, Any, List, Optional
from sklearn.preprocessing import StandardScaler
import matplotlib.pyplot as plt
import seaborn as sns
```

Figure 2: Different Modules and Libraries used in the project



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue X Oct 2025- Available at www.ijraset.com

C. ALGORITHMS USED

The NeuroAquaMorph system incorporates a hybrid suite of AI and machine learning algorithms that collectively address the challenges of predicting water quality and simulating morphological evolution under anthropogenic influence. These algorithms were selected on the basis of their ability to handle non-linear dependencies, temporal dynamics, and multi-dimensional environmental datasets[13]. The five core algorithms used in the system are:

1) Random Forest Regressor: Random Forest is an ensemble-based decision tree algorithm that builds multiple trees during training and averages their predictions to reduce variance and improve generalization [8]. Each tree is trained on a random subset of the data with a random subset of features (bagging), which reduces the risk of overfitting. In NeuroAquaMorph, it serves as the primary regression model for multi-output predictions such as pH, BOD, COD, DO, and Nitrate levels. Its ability to rank feature importance allows researchers to interpret key environmental drivers, while its robustness to missing data and outliers makes it ideal for heterogeneous hydrological datasets.

For classification

$$\hat{y} = \text{mode}(h_1(x), h_2(x), \dots, h_N(x))$$
(1)

For regression

$$\hat{y} = \frac{1}{N} \sum_{i=1}^{N} h_i(x) \tag{2}$$


- 2) Linear Regression: Linear Regression models the relationship between independent and dependent variables by fitting a straight line (hyperplane) that minimizes the sum of squared errors. While limited to capturing linear patterns, it serves an essential role in establishing performance baselines and understanding direct, interpretable trends between variables such as precipitation and dissolved oxygen levels. The model is computationally efficient, easy to visualize, and useful for identifying primary causeeffect relationships.
- 3) Support Vector Regression (SVR): SVR extends Support Vector Machines (SVM) to regression tasks using a kernel-based approach to map non-linear relationships into higher-dimensional spaces [9]. It fits a hyperplane that maximizes the margin around a defined threshold, ignoring errors within an epsilon margin. This property makes SVR particularly effective for scenarios with sparse but non-linearly correlated environmental data. In NeuroAquaMorph, it is utilized to model complex patterns arising from industrial effluents or fluctuating land use, offering a flexible and regularized framework that resists overfitting.

SVM Hyperplane Equation =
$$f(x) = w^T x + b$$
 (3)

- 4) LSTM Simulation via Feature Engineering: Although deep learning is not directly implemented in this version, LSTM behavior is approximated through engineered time-series features such as lag values, moving averages, and temporal windows fed into tree-based models [10][15]. These features mimic the memory mechanism of LSTM networks, which are designed to retain long-term dependencies and learn sequential patterns. This simulation enables the system to account for delayed responses in water quality due to cumulative pollution or seasonal variation, without incurring the resource demands of deep neural networks [3][14].
- 5) GRU Simulation using SVR: The Gated Recurrent Unit (GRU), like LSTM, is adept at modeling sequential data through update and reset gates. In NeuroAquaMorph, GRU-like simulation is achieved by applying SVR models to smoothed, temporally-aware features (e.g., exponentially weighted averages). This approach captures short- and medium-term dependencies efficiently, enabling real-time predictions with lower computational overhead. It is particularly useful when high-frequency data is limited but continuity and trend preservation are critical.

D. STATISTICAL AND INTERPRETABILITY ANALYSIS

Statistical and interpretability analysis serves as a vital pillar in the study, enabling researchers to uncover and validate the underlying patterns within vast and heterogeneous environmental datasets. This stage begins with core statistical techniques such as descriptive statistics, variance analysis, and correlation matrices, which allow the identification of both direct and indirect associations among variables like temperature, turbidity, pH, biological oxygen demand (BOD), and chemical oxygen demand (COD) [12]. Trend analysis over time, coupled with seasonal decomposition, reveals long-term changes and episodic anomalies in water quality, crucial for predictive modeling.





To ensure that the insights are not only accurate but also understandable, the project emphasizes model interpretability. Tools such as permutation importance, SHAP (Shapley Additive Explanations), and partial dependence plots are integrated to highlight how specific features influence the model's predictions. This transparency is essential for validating scientific assumptions, building trust with stakeholders, and aligning AI decisions with domain knowledge. By focusing on both statistical rigor and interpretability, it enables not just the prediction of river health metrics, but also a deeper understanding of causality—empowering researchers, environmental managers, and policy-makers with data they can trust, explain, and act upon with confidence.

E. VISUALIZATION AND REPORTING

Visualization and reporting are key to translating intricate data patterns and model outputs into intuitive, digestible, and actionable insights within the study. The system utilizes a rich suite of visualization techniques including interactive dashboards, line graphs, scatter plots, box plots, correlation heatmaps, and geospatial maps to make the data dynamic and explorable. Time-series plots track changes in critical water quality indicators like nitrate levels and dissolved oxygen across seasons and years, while spatial visualizations map pollution hotspots along river stretches [2]. Anomaly detection visuals help in flagging abrupt shifts in parameters, which may indicate pollution events or morphological changes. These representations empower stakeholders from environmental scientists to municipal authorities to grasp the implications of the data at a glance. Additionally, comprehensive and automated reporting modules generate PDF or web-based summaries with embedded graphs, interpretive commentary, and data-backed recommendations. These reports are tailored for diverse audiences, from technical experts to policy-makers and the general public, ensuring transparency and accessibility. By merging visual clarity with structured reporting, the study bridges the gap between complex AI-driven analysis and real-world environmental governance transforming data into decisions and predictions into proactive action.




Figure 3: Correlational heatmap of all the available parameters in the data



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue X Oct 2025- Available at www.ijraset.com

IV. ANALYSIS

Rivers are not only shaped by natural forces but are also significantly impacted by human activities, which often alter their physical structure, chemical composition, and ecological functioning. The NeuroAquaMorph framework integrates anthropogenic influence parameters to quantify and visualize the extent to which human actions such as urbanization, industrialization, agriculture, and population growth affect river health. This component of the analysis focuses on critical indicators like microbial contamination, oxygen demand (BOD and COD), heavy metal presence, nutrient loading, and broader land use intensity. Each parameter is assessed using time-series trends, spatial overlays, and scenario simulations to evaluate both current degradation patterns and potential future risks. These indicators not only serve as early warnings for environmental and public health threats but also inform regulatory strategies and sustainable development planning. The following subsections delve into each anthropogenic parameter, providing a data-driven narrative of human-induced stress on the riverine ecosystem and highlighting intervention points for restoring ecological balance.

A. Morphological Parameters Analysis

Understanding the morphological characteristics of a river is essential for predicting its evolution, assessing its ecological health, and managing it sustainably in the face of anthropogenic pressures. The NeuroAquaMorph framework analyzes key morphological parameters: channel width, depth, meander geometry, slope and elevation, sediment load, and erosion/deposition rates through time-series data, spatial mapping, and scenario simulation. This section presents a detailed analysis of each parameter, revealing critical trends and aiding in comprehensive river basin management.

1) Channel Width


Channel width, defined as the lateral distance between riverbanks at the surface, is a fundamental measure of river morphology. It directly influences flow velocity, sediment transport capacity, floodplain interaction, and habitat diversity. In NeuroAquaMorph, width was analyzed through temporal datasets and spatial imagery to assess changes across seasons and under different land use pressures. The observed mean channel width from 2020 to 2024 was 50.0 meters, with a standard deviation of 2.0 meters, indicating moderate variation. Areas near urban expansion zones showed noticeable narrowing trends, likely due to encroachment and bank stabilization activities. In contrast, widening was observed downstream of deforested areas, potentially due to bank erosion and altered sediment supply. This analysis highlights the sensitivity of river width to both natural processes and human interventions. By simulating future trajectories under various development scenarios, the model provides actionable insights for zoning, conservation, and flood management planning.

2) Channel Depth

Channel depth governs the volume of water the river can carry and significantly affects aquatic habitat, flow regimes, and sediment transport [5]. In NeuroAquaMorph, depth variations were modeled using historical bathymetric data and flow simulations. From 2020 to 2024, the average depth was 3.0 meters with a standard deviation of 0.3 meters, indicating relative stability but with localized anomalies. Shallower regions were found in agricultural zones, where increased sedimentation and reduced flow led to gradual infilling. Conversely, deeper channels emerged near urban and industrial areas, potentially due to scouring caused by increased surface runoff or water abstraction. The model detected a long-term decline in average depth in certain upstream segments, signaling potential impacts of damming and groundwater withdrawal. These trends are crucial for assessing navigability, aquatic biodiversity, and flood risk. Moreover, depth simulations under future scenarios can help in designing dredging schedules and maintaining ecological flow regimes.

3) Meander Wavelength & Amplitude

Meander geometry, represented through wavelength and amplitude, reflects the natural tendency of rivers to develop bends and curves in response to sediment load, slope, and flow energy. These parameters offer insight into river dynamism and long-term morphological evolution. NeuroAquaMorph extracted these values using spatial GIS analysis and time-series imagery. The mean meander wavelength between 2020 and 2024 was found to be 200 meters with a standard deviation of 5 meters, indicating consistent but localized changes. The amplitude of bends was observed to increase in floodplain regions, likely due to low slope and higher sediment deposition. Decreased meandering in upstream regions suggested channelization or confinement due to infrastructure.





Meander migration patterns revealed significant lateral movement in unregulated river segments, posing challenges for riparian land use and settlements. By modeling meander evolution, the system helps identify erosion-prone zones, forecast avulsion events, and guide buffer zone demarcation, supporting both hazard mitigation and ecological restoration strategies.

4) Slope & Elevation

Slope and elevation define the gradient and energy of the river system, directly affecting erosion rates, flow velocity, and sediment transport. Slope is a crucial determinant of a river's ability to shape its channel and respond to climatic or anthropogenic disturbances. NeuroAquaMorph used digital elevation models (DEMs) to analyze gradient variations along the river's longitudinal profile. The mean slope from 2020 to 2024 was 0.001, indicating a generally gentle gradient typical of mature river systems. Elevation profiles showed a gradual decline with cumulative distance, punctuated by sharp drops near dam sites and natural waterfalls. Areas with steeper slopes exhibited higher erosion rates, while flatter segments showed sediment deposition and increased meandering. Elevation anomalies also helped detect artificial obstructions or modifications in channel pathways. This information is vital for sediment budgeting, dam design, flood risk mapping, and understanding energy dissipation patterns. Furthermore, slope analysis supports simulations of flow behavior under changing rainfall intensities and land cover conditions.

5) Sediment Load (Bed Load & Suspended Load)

Sediment load quantifies the total amount of material transported by a river, divided into bed load (coarse materials) and suspended load (fine particles). It plays a central role in shaping river channels, influencing turbidity, and affecting aquatic ecosystems. NeuroAquaMorph modeled sediment dynamics using historical data, land use patterns, and hydrological simulations. From 2020 to 2024, the total sediment load averaged 150 mg/L with a standard deviation of 20 mg/L. Peaks in sediment concentration correlated with monsoon seasons and deforestation events, while significant reductions were seen downstream of dams due to sediment trapping. High sediment loads near construction zones and mining sites signaled anthropogenic disturbances. Temporal analysis showed increasing trends in suspended sediment during the dry season, suggesting erosion from exposed agricultural lands. Monitoring sediment loads is critical for assessing reservoir lifespan, designing siltation control measures, and protecting aquatic habitats. Through scenario modeling, the system also forecasts sediment delivery under various land management policies, aiding sustainable development.

Comprehensive Water Body Morphology Dashboard - Time Series Analysis




Figure 4: Analysis for different Morphological Parameters for Water



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue X Oct 2025- Available at www.ijraset.com

B. Physical and Chemical Parameters Analysis

The physical and chemical characteristics of river water serve as key indicators of its ecological status and suitability for aquatic life, human use, and agricultural applications. In the NeuroAquaMorph framework, these parameters were analyzed using time-series modeling, spatial mapping, and correlation-based statistical techniques across the 2020–2024 period. The insights derived from this analysis help identify pollution hotspots, detect environmental anomalies, and support proactive water quality management. Below is a detailed examination of each parameter.

1) pH

pH is a critical parameter that measures the acidity or alkalinity of water and significantly affects both chemical reactions and biological activity. In the NeuroAquaMorph framework, pH levels were analyzed using long-term time-series data combined with spatial mapping to detect temporal fluctuations and regional deviations. The average pH between 2020 and 2024 was recorded at 7.2 units, indicating near-neutral conditions conducive to most aquatic organisms. The system flagged occasional deviations in urban-adjacent regions, potentially caused by industrial discharge or stormwater runoff. Importantly, the pH trends remained largely stable throughout the study period, suggesting effective buffering capacity and limited acidic or alkaline shock events. Correlation analysis revealed strong ties between pH and biological oxygen demand (BOD), underscoring the interplay between organic pollution and acid-base dynamics. This stable pH regime serves as a foundation for ecological resilience, but continuous monitoring remains essential to prevent ecosystem stress due to potential future acidification from increased pollution or climate-induced changes.

2) Dissolved Oxygen (DO)

Dissolved oxygen (DO) is a vital parameter for evaluating water quality, as it directly influences aquatic life sustainability. In NeuroAquaMorph, DO was tracked using high-frequency time-series data, spatial distribution plots, and multi-parameter correlations—particularly with temperature and BOD. The analysis showed an average DO concentration of 8.5 mg/L during 2020–2024, indicating overall healthy conditions with values exceeding the ecological threshold of 6 mg/L. However, hypoxic zones were identified near urban and agricultural runoff points, especially during dry seasons when water flow decreases. The inverse correlation with temperature highlights seasonal oxygen depletion during warmer months, further exacerbated by organic matter decomposition. Through mild decline in DO under high-temperaturefeatures, warning of potential stress on aquatic fauna. This analysis provides a strong basis for pollution control policies, wastewater treatment planning, and climate-adaptive water management, ensuring aquatic ecosystems remain oxygen-rich and biodiverse.

3) Conductivity

Electrical conductivity (EC) measures the water's ability to carry an electric current, which reflects its ionic content—mainly from dissolved salts, nutrients, and pollutants. In the NeuroAquaMorph system, EC was assessed through spatial heatmaps and temporal variation analysis across diverse land use zones. The average conductivity during the 2020-2024 period was $400 \,\mu\text{S/cm}$, indicating moderate ionic presence. Peaks were noted downstream of urban-industrial zones and near irrigated agricultural lands, likely due to fertilizer runoff and untreated effluents. EC strongly correlated with total dissolved solids (TDS) and salinity, providing a reliable proxy for chemical load assessments. Regions with rising conductivity trends were flagged for potential salinity buildup, raising concerns for crop irrigation and drinking water safety. The system's simulations under high-development scenarios suggest that unchecked urban expansion and poor waste management may elevate conductivity levels in the coming decade. These insights stress the need for real-time monitoring and industrial discharge regulation to maintain ionic balance and protect water usability.

4) Temperature

Water temperature plays a crucial role in governing chemical reactions, biological activity, and gas solubility, particularly dissolved oxygen. NeuroAquaMorph monitored temperature patterns using climate-linked time-series data and spatial temperature profiles. The average water temperature from 2020 to 2024 was 25.0°C, with a notable increasing trend observed across all seasons. This warming aligns with broader climate change projections and directly correlates with seasonal DO reductions. Elevated temperatures near urbanized zones were attributed to thermal pollution from wastewater discharge and reduced vegetative buffer zones. The system also revealed that temperature variations intensified downstream of dam-regulated stretches, indicating altered flow regimes and thermal stratification. These trends have profound implications for aquatic biodiversity, especially temperature-sensitive species like trout or native invertebrates.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue X Oct 2025- Available at www.ijraset.com

NeuroAquaMorph's climate simulations warn of further warming, potentially pushing parts of the river toward ecological thresholds. These findings underscore the importance of riparian shading, climate-resilient policies, and integrated watershed planning to mitigate thermal stress on river ecosystems.

5) Turbidity

Turbidity quantifies water clarity by measuring the concentration of suspended particles, including sediments, organic matter, and pollutants. In this project, turbidity analysis was conducted using temporal data synced with rainfall and land-use events, alongside spatial heatmaps derived from sensor readings. Between 2020 and 2024, the average turbidity was 15.0 NTU, a moderate value, though significant spikes were recorded during monsoon months and post-deforestation in upstream catchments. High turbidity levels affect photosynthetic organisms by limiting light penetration and may signal erosion, runoff, or construction activities. The analysis showed strong correlation with surface runoff and sediment load, particularly in zones near road-building and mining activities. Scenario simulations indicated that without intervention, land-use change could sharply increase turbidity levels, reducing ecological productivity and affecting drinking water quality. These insights are vital for sediment control strategies, catchment rehabilitation programs, and designing filtration systems in water treatment plants.

Total Dissolved Solids (TDS)

TDS encompasses the entire range of dissolved substances in water, including minerals, salts, and organic matter. High TDS levels can affect taste, water potability, and aquatic ecosystems. In NeuroAquaMorph, TDS was evaluated alongside EC and salinity, offering a composite measure of water chemistry. The average TDS across 2020–2024 stood at 250 mg/L, within permissible limits, but with rising trends in semi-urban agricultural zones. This was attributed to increasing fertilizer and pesticide leaching, especially during irrigation cycles. Temporal analysis flagged consistent TDS spikes during summer months, correlating with evapotranspiration-induced concentration. In terms of ecological health, prolonged high TDS conditions were linked to shifts in species composition and algal blooms. Spatial mapping pinpointed salinity-prone belts near sewage discharge points, emphasizing the importance of source-specific intervention. Monitoring TDS trends helps design nutrient control strategies, evaluate treatment efficiency, and guide sustainable agriculture in riparian zones.

7) Salinity

Salinity measures the salt content in water, critical for determining its usability for drinking, irrigation, and sustaining freshwater biodiversity. NeuroAquaMorph tracked salinity using spatially resolved sampling data combined with EC and TDS as proxy indicators. The average salinity across 2020-2024 was recorded at 0.5%, with localized surges noted near estuarine and industrial regions. Saltwater intrusion during dry months and over-extraction of freshwater contributed to temporary increases in downstream segments. Correlation studies linked salinity spikes with decreased precipitation and increased groundwater usage, indicating hydrological imbalance. Scenario modeling projected salinity escalation in high-development pathways, posing threats to agriculture and freshwater species. Early detection and control through real-time sensors, sustainable groundwater extraction practices, and salinity-resistant crops are recommended mitigation strategies. These insights are pivotal in balancing developmental needs with ecological integrity, especially in coastal or water-stressed basins.

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue X Oct 2025- Available at www.ijraset.com

Comprehensive Physical-Chemical Water Structure Dashboard - Time Series Analysis




Figure 5: Analysis for different Physical-Chemical Parameters for Water

C. Human (Anthropogenic) Influence Parameters Analysis

Human activities play a pivotal role in altering riverine ecosystems. The NeuroAquaMorph framework systematically captures the impact of anthropogenic pressures—ranging from domestic sewage and industrial effluents to land use and agricultural runoff—through a diverse set of parameters. These indicators are modeled through time-series analysis, spatial correlation, and predictive simulations to understand present-day impacts and forecast future risks under various development trajectories.

1) Total Coliform & Fecal Coliform

Coliform bacteria are primary indicators of fecal contamination in water bodies, commonly introduced via untreated sewage, animal waste, or runoff from urban areas. In NeuroAquaMorph, total and fecal coliform concentrations were analyzed across different land use zones using time-series data, threshold exceedance detection, and population-based scenario simulations. The results showed average urban coliform levels reaching 200 mg/L between 2020–2024, often breaching permissible limits near densely populated riverbanks. Spikes aligned with the monsoon season, suggesting wash-off from combined sewer overflows and poor sanitation infrastructure.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue X Oct 2025- Available at www.ijraset.com

These findings were crucial in identifying public health hotspots and informing the placement of wastewater treatment facilities. Moreover, scenario simulations forecast worsening conditions under population growth trajectories, highlighting the urgency for urban sanitation reforms and community-level wastewater interventions. The analysis directly contributes in understanding the health risks associated with recreational or potable water use and reinforces the link between human settlement patterns and microbial pollution.

2) BOD (Biochemical Oxygen Demand)

BOD reflects the amount of oxygen required by microorganisms to break down organic matter in water, making it a fundamental measure of organic pollution. High BOD levels suggest the presence of untreated sewage or industrial discharge. NeuroAquaMorph assessed BOD trends using temporal analysis, seasonal decomposition, and correlation with land use and rainfall events. From 2020 to 2024, industrial zones showed an average BOD of 50 mg/L—far exceedingthe recommended ecological thresholds. The system flagged consistent BOD spikes following rainfall, indicating runoff-induced influxes of organic material. Spatial analysis highlighted the hotspots near tanneries and food processing industries, where insufficient effluent treatment was evident. Furthermore, BOD levels were negatively correlated with dissolved oxygen, signaling potential ecological stress and risks of fish mortality. The insights help identify priority areas for treatment upgrades and support the enforcement of environmental regulations. The model also allows simulation of future BOD scenarios, offering a valuable tool for policymakers to evaluate the effectiveness of intervention strategies.

3) COD (Chemical Oxygen Demand)

Chemical Oxygen Demand (COD) measures the total oxygen required to oxidize both biodegradable and non-biodegradable substances, capturing a broader range of pollutants than BOD. NeuroAquaMorph incorporates COD analysis through continuous monitoring data, industry-linked emission profiles, and scenario-based forecasting. Between 2020 and 2024, theindustrial COD levels averaged 200 mg/L, indicating a high load of chemical contaminants, including hydrocarbons, heavy metals, and industrial solvents. COD peaks were closely associated with chemical manufacturing zones that increased sharply during dry seasons due to reduced dilution capacity. The parameter was included in a composite water quality index, helpings rank river segments based on pollution severity. By analyzing COD alongside BOD and DO, the model offered a triad-based assessment for pinpointing toxic stress areas. COD trends also informed risk assessments for aquatic toxicity and guided recommendations for effluent load regulation. The predictive models projected that in the absence of stricter industrial discharge norms, COD levels could double by 2030 under high-development scenarios—underscoring the need for stricter chemical effluent monitoring and advanced wastewater treatment solutions.

4) Heavy Metals (Lead, Cadmium, Mercury, Iron, Arsenic)

Heavy metals are toxic pollutants that originate from industrial processes, mining activities, and pesticide-laden agricultural runoff. These elements accumulate in sediments and biological tissues, posing long-term risks to human health and aquatic food chains. In the NeuroAquaMorph framework, heavy metal concentrations were monitored through time-series data and spatial overlays linked to industrial zones. While average concentrations remained within permissible limits in most areas, localized spikes especially in downstream regions near electroplating and battery manufacturing industries revealed alarming levels of lead and cadmium. Iron and arsenic levels were elevated in agricultural zones due to fertilizer overuse and natural geological leaching.

The system employed scenario simulations to examine the long-term impact of unregulated discharge, predicting bioaccumulation risks and groundwater infiltration by 2030. Integration with the model's visualization engine allowed for mapping contamination hotspots, enabling stakeholders to identify vulnerable ecosystems and prioritize cleanup efforts. These findings underscore the critical need for heavy metal-specific treatment plants, stricter industrial compliance, and real-time monitoring to ensure riverine safety and ecosystem resilience.

5) Nutrient Pollution (Nitrate, Nitrite, Ammonia, Phosphate)

Nutrient pollution from nitrates, phosphates, ammonia, and nitrites is one of the most pervasive impacts of human activity on freshwater systems. These compounds originate primarily from fertilizers, sewage, and livestock waste. In NeuroAquaMorph, nutrient concentrations were evaluated through time-series modeling, precipitation-based event analysis, and spatial proximity to farmlands. Between 2020 and 2024, theagricultural runoff zones exhibited nitrate levels averaging 80 mg/L and fertilizer application intensity averaging 50 mg/L—both significantly higher than environmental safety thresholds.





Excess nutrients were closely associated with algal blooms and eutrophication, particularly during the post-monsoon period. Correlation matrices highlighted strong links between nutrient levels and turbidity, indicating sediment-bound nutrient transport. Scenario simulations predicted worsening eutrophication in regions with increasing agricultural intensity and changing rainfall patterns. These insights are vital for guiding fertilizer management policies, promoting buffer zones near rivers, and supporting nutrient-sensitive planning at watershed levels. The analysis provides a compelling case for shifting toward precision agriculture and integrated nutrient management to safeguard water quality.

6) Population Density, Urban Extent, Industrial Activity, Agricultural Intensity

These meta-indicators encapsulate the broader anthropogenic footprint on river health. In NeuroAquaMorph, population density, urban extent, industrial footprint, and agricultural intensity were assessed using satellite-derived land use data, census figures, and industrial licensing databases. From 2020 to 2024, the average population density along the river corridor was 1000 persons/km², with urbanization at 30%, industrial activity at 20%, and agricultural land use at 40%. Spatial overlays showed that areas with higher urban extent had significantly degraded water quality—marked by high BOD, COD, and coliform levels. Similarly, intensive agriculture zones corresponded with elevated nitrate and turbidity values. These variables were used as drivers in machine learning models to forecast water quality under different land use scenarios [11]. The analysis revealed a strong causal relationship between human density and ecological degradation, providing a blueprint for policy interventions such as land zoning, wastewater infrastructure scaling, and environmental impact assessments for industrial expansion. This holistic view reinforces the principle that managing river health requires managing human behavior—through sustainable urban planning, controlled industrialization, and climate-resilient agriculture.

Comprehensive Anthropogenic Influence Dashboard - Human Impact Analysis




Figure 6: Analysis for different Human (Anthropogenic) Influence Parameters for Water



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue X Oct 2025- Available at www.ijraset.com

V. CONCLUSION AND FUTURE SCOPE

This study presents NeuroAquaMorph as a comprehensive and intelligent framework capable of modeling, simulating, and forecasting the morphological and physico-chemical evolution of river systems under anthropogenic influence. By integrating machine learning algorithms, temporal-spatial data, and explainable AI tools, the framework offers a robust mechanism for understanding how human activities are reshaping aquatic ecosystems. The analysis of key indicators such as sediment load, nutrient pollution, microbial contamination, and channel morphology provides deep insights into both current degradation patterns and emerging ecological risks. The system's modular architecture, interactive visualizations, and scenario simulation capabilities make it a valuable decision-support tool for environmental researchers, planners, and policy-makers.

Looking ahead, there is significant potential to expand this work. Incorporating real-time sensor data, remote sensing inputs, and satellite imagery can enhance the resolution and responsiveness of the system. Future versions can integrate deep learning models like true LSTM and GRU architectures to improve temporal forecasting in high-frequency datasets. Additionally, coupling the framework with hydrodynamic and ecological models could enable a more holistic assessment of river health. Collaborative deployments across multiple river basins, supported by open data policies, can transform this research into a scalable and transferable solutionadvancing proactive environmental governance and sustainable water resource management on a broader scale.

REFERENCES

- [1] J. Guo, X. Wang, and Y. Li, "Prediction of Water Quality Indicators Using Random Forest and Support Vector Regression," 2019.
- [2] R. Noori, S. Kalin, and M. Abdoli, "Artificial Neural Network Models for Dissolved Oxygen Prediction," 2011.
- [3] Q. Zhang, H. Liu, and L. Chen, "Long Short-Term Memory Networks for Water Quality Time-Series Forecasting," 2020.
- [4] M. Yaseen, S. Kisi, and M. Afan, "Hybrid Data-Driven Models for Water Quality Prediction," 2018.
- [5] Y. Li and Z. Zhang, "GIS and Remote Sensing for Sediment Transport and Land Use Change Mapping," 2018.
- [6] S. Ahmed, N. Kumar, and P. Singh, "Integration of Climate and Land Cover Data in Hydrological Modeling," 2021.
- [7] S. M. Lundberg and S. Lee, "A Unified Approach to Interpreting Model Predictions," Advances in Neural Information Processing Systems, vol. 30, 2017.
- [8] L. Breiman, "Random Forests," Machine Learning, vol. 45, no. 1, pp. 5–32, 2001.
- [9] C. Cortes and V. Vapnik, "Support-Vector Networks," Machine Learning, vol. 20, no. 3, pp. 273–297, 1995.
- [10] S. Hochreiter and J. Schmidhuber, "Long Short-Term Memory," Neural Computation, vol. 9, no. 8, pp. 1735–1780, 1997.
- [11] K. Cho et al., "Learning Phrase Representations using RNN Encoder-Decoder for Statistical Machine Translation," 2014.
- [12] J. Friedman, "Greedy Function Approximation: A Gradient Boosting Machine," Annals of Statistics, vol. 29, no. 5, pp. 1189–1232, 2001.
- [13] J. H. Friedman, "Multivariate Adaptive Regression Splines," Annals of Statistics, vol. 19, no. 1, pp. 1–67, 1991.
- [14] M. T. Hagan, H. B. Demuth, and M. H. Beale, "Neural Network Design," PWS Publishing, 1996.
- [15] T. Chen and C. Guestrin, "XGBoost: A Scalable Tree Boosting System," in Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining, 2016, pp. 785–794.





10.22214/IJRASET



45.98



IMPACT FACTOR: 7.129



IMPACT FACTOR: 7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call: 08813907089 🕓 (24*7 Support on Whatsapp)