iJRASET
International Journal For Research in Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 14 **Issue:** XI **Month of publication:** November 2026

DOI: https://doi.org/10.22214/ijraset.2026.85654

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538
Volume 14 Issue XI Nov 2026- Available at www.ijraset.com

SmartKrishi-AI: A Survey of AI-Integrated Agriculture Decision Support and Farm Resource Management

Namrata Shinde[1], Tejashree Torave[2], Gayatri Bhise[3], Suhani Yadav[4], Prof. P. N. Kadam[5]
[1, 2, 3, 4]*Department of Computer Engineering, SVPM's College of Engineering Malegaon BK, Pune, India*
[5]*Project Guide, Department of Computer Engineering, SVPM's College of Engineering, Malegaon BK, Pune, India Academic*
Survey Paper | Academic Year 2026–2027

Abstract: ***Agricultural choices depend heavily on a complex mix of environmental variables, including soil properties, fluctuating weather patterns, crop compatibility, market dynamics, pest threats, and the availability of vital farming resources. Most contemporary digital services target only one of these factors, forcing growers to manually gather data from multiple disconnected websites and local contacts. This paper reviews recent developments related to SmartKrishi–AI, a conceptual, integrated platform designed for agricultural decision-making and asset coordination. Our analysis evaluates several vital domains, including crop recommendation frameworks, weather forecasting networks, commodity price models, plant disease diagnostics, public welfare discovery, equipment leasing, and labor scheduling. We analyze recent research from 2023 to 2026 indexed across major venues such as IEEE, Elsevier/ScienceDirect, and MDPI, exploring their mathematical approaches, dataset constraints, evaluation methods, and practical challenges. Based on these insights, we introduce a conceptual multi-layer architecture that connects data-driven analytical models with verified institutional channels and peer-to-peer resource exchange workflows. Because the proposed ecosystem serves as a structural blueprint rather than an experimentally field-tested software tool, no project-specific crop yield or predictive precision increases are claimed. Finally, we highlight persistent open challenges in this sector, such as data quality gaps, geographic adaptation limits, model interpretability, forecast volatility, system interoperability, regional language support, and the necessity for rigorous field trials.***
Index Terms: ***smart agriculture, crop recommendation, machine learning, weather forecasting, market price prediction, crop disease risk, farm equipment rental, labour hiring, decision support.***

I. INTRODUCTION

Strategic planning in agriculture demands making a continuous series of interconnected choices throughout the crop cycle. A grower must select a crop variety compatible with local soil chemistry and seasonal constraints, estimate weather-related risk factors, optimize planting and harvesting timelines, anticipate marketplace trends, track potential crop-health hazards, and obtain machinery or external labor at the exact required time. Historically, these critical management choices have been executed based on fragmented, uncalibrated, or highly localized information sources. For example, a soil-centric recommendation tool might completely ignore upcoming seasonal rainfall anomalies, while an independent market price forecasting model fails to integrate with seasonal harvesting timelines, leaving producers unable to optimize their sales windows. Similarly, localized plant pathology alerts lose their genuine utility if they are delivered late, presented ambiguously, or disconnected from certified agronomic solutions. Modern computing paradigms—including machine learning (ML), deep learning (DL), remote sensing arrays, advanced meteorological engines, and decentralized digital marketplaces—offer the necessary core components to build unified agricultural decision platforms [12]. Recent academic efforts have explored specialized crop recommendation engines driven by environmental and soil metrics, interpretable recommendation frameworks, and IoT-integrated precision farming networks [1]–[4], [13], [15]–[18]. Concurrently, prominent research in ScienceDirect focuses on deep commodity price forecasting, high-resolution weather downscaling, and computer-vision-based pest and pathogen identification [5]–[9]. Additionally, emerging literature on shared equipment economies illustrates viable frameworks through which smallholders can utilize advanced machinery without facing prohibitive upfront capital costs [14]. Although these isolated studies reflect significant technical progress within specific domains, building a practical, farmer-centric environment requires addressing systemic challenges such as data lineage, predictive uncertainty, regional adaptation, and the conversion of raw data into actionable field strategies.

©IJRASET: All Rights are Reserved

This paper makes three key contributions to the domain:

- A structured review of peer-reviewed research from 2023 to 2026 directly mapping to the core architectural functional modules of the SmartKrishi–AI framework.
- A qualitative evaluation outlining the mathematical approaches, dataset constraints, structural advantages, and operational drawbacks of contemporary predictive and resource-allocation models.
- A conceptual, multi-layered architecture and evaluation matrix designed to link predictive AI intelligence with real-time weather analytics, market feeds, public welfare discovery, and decentralized equipment/labor networks.

The structural flow of this paper is organized as follows: Section II reviews primary farmer requirements and operational boundaries; Section III surveys contemporary AI approaches; Section IV breaks down the proposed data and intelligence workflow; Section V offers a comparative analysis of existing literature; Section VI defines prevailing research gaps; Section VII illustrates the SmartKrishi–AI architectural framework; Section VIII outlines the evaluation matrix; Sections IX and X analyze open challenges and future vectors; and Section XI concludes the study.

II. BACKGROUND AND FARMER REQUIREMENTS

A. *Decision Needs Across the Crop Cycle*

A producer's operational priorities evolve dynamically through pre-sowing, cultivation, harvesting, and post-harvest phases. In the initial pre-sowing stage, parameters such as macronutrient concentrations, soil pH, moisture levels, microclimates, operational budgets, and regional seasonal trends dictate optimal crop selection [1], [13]. Once cultivation begins, localized weather alerts and real-time plant health diagnostics become paramount to mitigate risk [6], [9]. As harvest approaches, decisions are shaped by marketplace supply volumes, historical pricing trends, logistical constraints, and available storage infrastructure [5], [7]. Finally, agricultural machinery and labor represent highly time-sensitive operational assets; variables like proximity, rental parameters, cost-efficiency, and scheduling mechanics dictate whether a theoretical agronomic recommendation can be successfully executed on the ground [14].

B. *Requirements for an Integrated Platform*

To deliver genuine utility, an integrated platform must satisfy the following core requirements: (i) location-specific insights that avoid generic crop listings by generating recommendations tailored to precise geographic coordinates and micro-regions; (ii) explainability and confidence intervals providing transparent, interpretable outputs backed by clear uncertainty metrics rather than obscure black-box calculations
[2]; (iii) verifiable meteorological feeds delivering timely weather data containing clear source attributions and issue timestamps; (iv) probabilistic market forecasts presenting future commodity valuation trends as ranges and probabilities rather than definitive, guaranteed price commitments [5], [7];
(v) guided phytopathology diagnostic alerts framing computer-vision disease identifications as alerts requiring validation from local agronomic experts [8]; (vi) verified public scheme portals maintaining continuously updated and auditable eligibility criteria for state-sponsored agricultural programs;
(vii) dynamic resource directories featuring live, searchable listings for agricultural machinery and labor, detailed with current availability and direct connection channels [14]; (viii) localized accessibility implementing user interfaces in regional languages like Marathi, optimized for mobile deployment and low-bandwidth connectivity [12]; and (ix) robust governance ensuring secure, role-based access controls and explicit data privacy standards.

C. *System Boundary*

SmartKrishi–AI is strictly conceptualized as a decision-enrichment and asset-management architecture. It does not replace professional agronomists, certified meteorological agencies, official government welfare bodies, or the ultimate personal judgment of the producer.
Market datasets and weather metrics rely on external provider APIs, while equipment and labor listings depend entirely on participant updates. Consequently, this study maintains a strict distinction between predictive analytical models and operational transactions, acknowledging that a conceptual design blueprint does not serve as empirical evidence of real-world field efficacy.

III. RECENT AI APPROACHES IN SMART AGRICULTURE

A. *Crop Recommendation and Explainability*

Crop recommendation models typically map key soil indicators—such as nitrogen, phosphorus, potassium, pH, alongside ambient temperature, relative humidity, and historical rainfall metrics [1]–[4], [13]. Peer-reviewed studies from 2025 have thoroughly analyzed standard supervised classifiers for crop assignment, while parallel research introduced explainable AI models to translate deep-learning outputs into legible, trustworthy rationale [1], [2]. Further investigations integrated IoT edge-sensing arrays with machine learning architectures to provide resource-conscious decision platforms [3]. This baseline has been expanded to support joint crop-fertilizer optimization [10], [17], deep neural network integrations [11], and dedicated decision environments built on multi-class classification frameworks [15]. These collective developments support a hybrid structural approach for the SmartKrishi ecosystem: first, narrow down candidate crops using hard agronomic constraints; second, rank the remaining options via an optimized machine learning model; and third, isolate and display the most dominant environmental features driving that output. Notably, high training performance on static, curated datasets should not be misconstrued as uniform field accuracy across diverse regional soils or volatile seasons; for context, multiple studies have noted near-99% accuracy markers when evaluated strictly on homogenous public internet datasets [13].

B. *Weather Intelligence*

Reliable weather intelligence serves as the backbone for crop selection, irrigation modeling, chemical application scheduling, and emergency risk management. Recent research by Kow *et al.* introduces a hybrid framework combining convolutional autoencoders with long short-term memory (LSTM) transformers to downscale macro-weather datasets into high-resolution, farm-level temporal insights [6]. Within the SmartKrishi architecture, meteorological inputs function via two distinct pipelines: directly displaying verified official forecasts alongside their validity windows, and feeding live weather variables into soil-crop models for advanced decision modeling. Critically, these workflows must retain source metadata and confidence windows, ensuring machine learning adjustments never silently overwrite or hide official government weather advisories.

C. *Market Price Forecasting*

Agricultural market prices are highly non-linear, driven by a complex mix of crop arrivals, seasonal patterns, meteorological shifts, macro-demand, logistics, policy adjustments, and global economic factors. A 2025 evaluation published in ScienceDirect compared various hybrid forecasting techniques across volatile commodity markets, noting that accuracy fluctuated significantly based on market volatility and the length of the forecasting horizon [5]. Complementary research proposed attention-boosted deep learning architectures designed for simultaneous multi-commodity price tracking and market anomaly detection [7]. These findings emphasize the importance of comparing traditional time-series baselines with tree-based models and sequence networks. Consequently, the SmartKrishi framework is designed to show historical price points, expected pricing ranges, prediction horizons, and historical error margins rather than an absolute, single-value price guarantee.

D. *Crop Disease and Pest Risk*

Computer-vision architectures excel at identifying visible symptoms on plant tissue, whereas comprehensive disease risk forecasting models combine weather variables, crop growth stages, precise geographic data, and regional outbreak histories. Liu *et al.* surveyed contemporary AI-driven pest and disease identification frameworks, highlighting persistent real-world obstacles like training data scarcity, model execution efficiency, and edge deployment limitations [8]. A 2026 review in *Engineering* mapped the integration of advanced sensors, algorithmic modeling, and early-warning networks for automated crop disease tracking [9]. The SmartKrishi ecosystem explicitly separates instant image-based symptom classification from forward-looking disease risk models. Every diagnostic alert must highlight the suspected issue, confidence intervals, visual evidence, and a clear instruction to seek local expert confirmation, while strictly avoiding unverified, automated pesticide prescriptions.

E. *Equipment Rental and Labour Hiring*

Research into agricultural equipment sharing treats machinery access as a structured resource-allocation problem, focusing on smallholders who lack the capital to purchase heavy assets [14]. A digital platform can structure these transactions by indexing machinery specifications, owner verification, geolocation, available time slots, rental pricing, deposit criteria, and live booking updates. Labor directories can similarly organize skill categories, availability, location, expected project durations, and direct booking communication.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

Unlike analytical crop classification engines, these modules depend less on predictive machine learning accuracy and more on real-time data freshness, mutual trust, efficient scheduling, equitable access, and clear dispute resolution protocols. While preliminary studies on digital asset exchange are beginning to emerge [14], peer-reviewed data regarding standardized, cross-platform agricultural resource sharing remains sparse. As a result, the SmartKrishi architecture treats these components as proposed workflows rather than proven AI capabilities.

F. Government Schemes and Advisory Information

The identification of state-sponsored agricultural programs is primarily an information-verification and eligibility-matching task. Practical examples include discovering Custom Hiring Center subsidies for local machinery leasing [14]. A unified system must systematically index official government notices, eligibility criteria, required documentation, application cut-off dates, and official submission portals, while maintaining strict records of the source origin and the last verification timestamp. Although natural-language processing can help farmers query these databases, eligibility outputs must always be framed as preliminary, non-binding guidance until officially validated by the relevant government representative. Furthermore, authorized administrative managers must have clear tools to continuously monitor, modify, and archive outdated program records.

IV. DATA AND INTELLIGENCE PIPELINE

A. Data Sources and Preparation

The platform's data engine is designed to ingest farmer-provided inputs—including district/village location, land holdings, soil test metrics, target season, financial budget, irrigation options, and personal crop preferences—and combine them with real-time weather feeds, historical market arrival data, plant health images, and verified resource listings. Every data source requires strict provenance tracking, chronological timestamping, unit standardization, missing-value imputation, and validation checks [13]. To ensure robust model validation, training datasets must be partitioned using strict temporal and geographic separation, preventing data leakage and ensuring a realistic measure of real-world model generalization.

B. Model Selection

For the crop recommendation module, performance should be systematically compared across Decision Trees, Random Forests, Support Vector Machines (SVM), gradient boosting models, and simple probabilistic baselines [13], [15]. Weather analytics should prioritize direct integration with authoritative meteorological streams; any localized downscaling or error-correction models must undergo rigorous regional testing before deployment [6]. Price forecasting pipelines should benchmark simple seasonal-naïve and ARIMA frameworks against Random Forests, gradient boosting, LSTM networks, or attention-based sequence models [5], [7]. Plant pathology vision tools should leverage lightweight CNN or transformer configurations suitable for mobile deployment, while comprehensive disease risk models rely on historical weather features and crop growth timelines [8], [9]. Ultimately, the most computationally complex model is not universally the optimal choice; model calibration, inference latency, interpretability, data access, and long-term maintenance overhead must be balanced.

C. Human-Centred Output

Every algorithmic recommendation must explicitly display the underlying input variables, a clear explanation of the logic, operational limitations, and a direct channel to contact a human agricultural expert [2]. The user interface must maintain a clear visual separation between machine-generated predictions, official institutional notices, and peer-to-peer marketplace listings. In addition, a direct feedback mechanism must allow users to report incorrect crop recommendations, outdated asset listings, or false disease warnings. This user-generated feedback must pass strict quality validation checks before being incorporated into future model retraining cycles.

TABLE I
QUALITATIVE COMPARISON OF REPRESENTATIVE SYSTEMS (2023–2026)

Sr. No.	Paper Title	Author(s)	Year	Existing Problem Statement	Existing Problem Solution	Future Scope / Gap
1	Intelligent Crop Recommendation Framework [4]	Not listed	2026	Producers require a clear software system to translate soil inputs into choices.	Presents an ML-driven crop selection platform design.	Requires extensive field trial metrics and reproducibility tests.

2	Recent Developments in Crop Disease Detection [9]	J. Yan *et al.*	2026	Pathology tracking demands integrated sensors and deployment workflows.	Reviews state-of-the-art plant disease warning environments.	Needs cross-regional testing and real-time farmer advice logs.
3	Machine Learning Based Crop Recommendation [1]	Not listed	2025	Crop assignment gets complicated when soil-weather indices interact.	Deploys supervised classifiers to rank ideal crops.	Must be evaluated across genuine farms and active seasons.
4	Data-Driven Crop Selection with XAI [2]	Not listed	2025	Opaque algorithmic outputs reduce farmer trust and comprehension.	Combines supervised learning with local LIME explainability.	Requires localized clarity tests with native speaking growers.
5	Optimizing Crop Suggestion with IoT [3]	Not listed	2025	Agronomic management suffers from disconnected hardware devices.	Integrates field-level edge telemetry data with an ML backend.	Needs evaluation of physical device cost and link stability.
6	Hybrid Forecasting of Commodity Prices [5]	B. A. Celik *et al.*	2025	Market price paths are highly volatile and hard to track alone.	Merges time-series nets with stochastic simulations.	Must be validated on hyper-local wholesale market feeds.
7	Multi-Commodity Price Architecture [7]	Not listed	2025	Cross-market anomalies are difficult to evaluate concurrently.	Applies attention-driven neural sequence models.	Requires explicit confidence intervals for local traders.
8	AI-Driven Meteorological Downscaling [6]	P.-Y. Kow *et al.*	2025	Macro-weather grids lack the fine spacing needed for farms.	Uses convolutional autoencoders and transformer models.	Needs validation against standalone independent stations.
9	Solutions in Pest & Disease Recognition [8]	X. Liu *et al.*	2025	Vision models suffer from changing field illumination and noise.	Reviews lightweight convolutional configurations for mobile use.	Must assess behavior on entirely out-of-domain images.
10	ML Optimization for Crop Allocation [13]	V. Tomar *et al.*	2024	Subjective intuition dominates regional agricultural practices.	Benchmarks supervised algorithms, noting high Naïve Bayes scores.	Lacks dataset provenance information and deep features.
11	Empowering Farmers via Equipment Sharing [14]	G. Rawat *et al.*	2024	Upfront capital constraints prevent smallholder mechanization.	Surveys cooperative asset pooling and leasing programs.	Socio-economic impact indices remain completely unexplored.
12	Decision Support Systems for Crop Choice [15]	M. K. Senapaty *et al.*	2024	Producers lack interactive software environments for pre-sowing.	Builds an interactive multi-class classifier framework.	Needs external regional validation and usability studies.
13	Advanced Techniques in Crop Optimization [16]	H. Lahza *et al.*	2023	Predictive modeling drops in quality without multi-source data.	Tunes supervised layers on blended environmental records.	Demands explainability layers to unpack recommendations.
14	Data-Driven Crop & Fertilizer Regimes [17]	C. Musanase *et al.*	2023	Farmers require simultaneous advice on crops and nutrients.	Applies multivariate analysis and matching ML rules.	Must automate connectivity to physical soil testing labs.
15	Environmental Yield Prediction Models [18]	E. Elbasi *et al.*	2023	A large matrix of overlapping parameters limits manual planning.	Applies standard classification baselines to yield logs.	Needs robustness tracking across highly diverse soil zones.

D. Benchmark Evidence and Preprocessing Practice in Crop Recommendation

Tomar *et al.* [13] evaluated Decision Trees, Naïve Bayes, SVM, Random Forest, and KNN using a public dataset containing soil metrics, pH, temperature, humidity, and rainfall across 22 distinct crop varieties. Their engineering pipeline mirrors the standard sequence adopted by the SmartKrishi–AI framework: exploratory data analysis, missing/incorrect value remediation, outlier mitigation, categorical variable encoding, feature scaling, and a strict train/test split prior to model benchmarking. On the held-out validation set, they reported high accuracy figures: approximately 99.5% for Naïve Bayes, 99.3% for Random Forest, 98.9% for Decision Trees, 96.8% for SVM, and 95.7% for KNN. These benchmarks confirm that structured soil and climate features provide clear mathematical boundaries for crop classification.

However, because the underlying training data was sourced generically from public internet repositories, evaluated solely on accuracy, and lacked geographic or seasonal partitioning, these findings must be interpreted strictly as benchmark evaluations rather than proof of real-world field precision.

This limitation underscores why the SmartKrishi–AI evaluation matrix prioritizes macro-F1 scoring, per-crop recall tracking, probability calibration, and rigorous geographic cross-validation.

E. Community and Platform-Based Equipment Sharing Models

With respect to agricultural asset exchange, Rawat *et al.* [14] analyzed various structural models through which small-scale Indian farmers can utilize modern machinery without the burden of individual capital ownership. Their study examines community asset sharing, agricultural cooperative networks, commercial rental services, digital platforms connecting owners of underutilized equipment with nearby growers, state-backed programs like Custom Hiring Centers, and private-public joint ventures. The same work emphasizes that shared agricultural models succeed only when supported by transparent governance structures: equitable access rules, robust scheduling mechanisms, clear maintenance responsibilities, standardized dispute resolution tracks, and practical logistics for remote regions must be explicitly established. Because this literature remains conceptual rather than experimental, it guides structural workflow design but does not provide empirical platform performance metrics. This insight shapes the SmartKrishi framework's insistence on timestamped asset availability, provider identity verification, live booking tracking, and dedicated dispute mediation pathways [14].

V. COMPARATIVE ANALYSIS OF REPRESENTATIVE SYSTEMS

A. Qualitative Comparison

Table I summarizes representative 2023–2026 research located in IEEE Xplore, ScienceDirect, and MDPI, arranged chronologically from the most recent to the oldest entries. This comprehensive synthesis outlines specific research directions and corresponding systemic constraints.

VI. RESEARCH GAPS

A. Fragmented Functionality

Crop selection, weather modeling, disease monitoring, price forecasting, public welfare tracking, machinery rental, and labor hiring are typically analyzed as completely isolated tasks in literature [14]. A unified architecture must coordinate these separate streams, explicitly clarifying how a shift in one parameter impacts downstream operational choices, without falsely implying that a single mathematical model can solve all agricultural dilemmas.

B. Local Generalization and Data Quality

Predictive layers optimized on highly static, manicured repositories frequently fail to generalize when exposed to real-world soil diversity, volatile microclimates, changing crop variations, or unmapped local trading networks [13]. Furthermore, historical wholesale price indices are routinely compromised by missing records or sudden systemic interventions, requiring data lineage and freshness to be measured as structural quality indices.

C. Explainability and Uncertainty

Outputting a deterministic crop label or absolute pricing point conceals critical underlying variance. End-users require multi-tier alternate options, probabilistic confidence boundaries, and interpretable rationale behind suggestions [2]. Statistical calibration is essential since automated outputs directly shape the grower's financial outlays and asset handling.

D. Accessibility and Governance

Smallholders frequently face poor cell connectivity, varying digital literacy levels, distinct regional language barriers, and limited access to professional physical laboratories [12].

Concurrently, an integrated environment demands clear user consent tracks, role-based database permissions, strict protection of spatial records, and moderation of marketplace inputs. Existing literature has not yet demonstrated a verified, unified system resolving these multi-tier concerns simultaneously.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

VII. SMARTKRISHI–AI: A CONCEPTUAL FRAMEWORK

A. Architecture

SmartKrishi–AI is conceptualized as a modular, decoupled web and mobile ecosystem that supports distinct operational roles: Farmer, Equipment Provider, Labor Provider, Agronomic Expert, and System Administrator. To maintain a secure and focused scope, a separate commercial Trader role is explicitly excluded from this framework. The core client interface interacts with individual modules through a centralized backend API gateway. Analytical AI computations execute within a dedicated Python service environment, while profile management, transaction workflows, and data persistence are handled by a robust Java/Spring Boot application framework connected to a secure relational database.

B. Functional Layers

1) *User Interface Layer:* Manages multi-lingual farmer dashboards, responsive entry forms, automated alert configurations, and natural-language search fields.
2) *Application & API Layer:* Handles secure user authentication, role-based database access, request validation, and transactional sequence coordination.
3) *Intelligence Processing Layer:* Houses the core machine learning models responsible for crop ranking, weather risk evaluation, price forecasting, and plant health diagnostics.
4) *Verified Information Layer:* Index public welfare scheme eligibility, certified advisory content, data lineage markers, and manual expert verification gates.
5) *Resource Exchange Layer:* Directs peer-to-peer machinery and labor listings, live availability schedules, lease requests, and booking tracking workflows.
6) *Data Persistence Layer:* Organizes storage arrays for profiles, historical soil data, model logs, listing inputs, and system metadata via a secured relational engine.
7) *Monitoring & MLOps Layer:* Tracks model versioning, execution logs, data drift diagnostics, system exceptions, and direct user feedback pipelines.

C. Design Principles

The platform prioritizes complete modularity, full lineage transparency, interpretable outputs, data minimization, and graceful failure paths. If meteorological connections drop, the system explicitly communicates that data outage rather than generating unverified values.

When an analytical model produces an output beneath established confidence margins, alternative options must be displayed alongside directions to consult a human agronomist. Every peer-to-peer asset posting must preserve verification timestamps, and public program entries must display direct institutional links.

VIII. EVALUATION METHODOLOGY

A. Model-Level Evaluation

Crop recommendation engines must be verified using multi-class criteria, including overall accuracy, macro-precision, macro-recall, and macro-F1 metrics alongside comprehensive confusion matrices; evaluating systems solely via standard accuracy scales is statistically insufficient [13]. Commodity price pipelines demand tracking through Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and Mean Absolute Percentage Error (MAPE), assessed over strict chronological validation splits [5]. Weather downscaling networks must report localized error boundaries across distinct environmental variables and forecast horizons [6]. Finally, plant pathology computer-vision tools must document precision, recall, F1 markers, probability calibration curves, and error behavior on datasets collected entirely outside the original training locations [8].

B. System-Level and User-Level Evaluation

Platform engineering quality must be assessed through technical indicators: system response times, uptime metrics, API sync freshness, error rates, the percentage of stale marketplace listings, and the volume of public scheme data containing active institutional links. Resource sharing modules require tracking via booking completion success, cancellation trends, asset verification latencies, and user trust indexes [14]. Any real-world field pilot must feature participants from multiple distinct agricultural zones working under explicit informed consent protocols. Table II summarizes the proposed evaluation matrix.

C. Reproducibility

This study presents a structural framework and does not report experimental results from an active software deployment. Future empirical validation of the SmartKrishi–AI platform must explicitly document dataset versions, preprocessing operations, chronological validation boundaries, baseline performance metrics, and specific execution hardware configurations. No claims regarding guaranteed crop yields or absolute model accuracy are made for the conceptual design outlined in this review.

IX. CHALLENGES AND OPEN ISSUES

A. Technical and Operational Challenges

1) Severe regional data scarcity combined with completely unverified or missing historical soil logs and yield registries [13].
2) Extreme data volatility and predictive uncertainty during climate shocks, sudden market disruptions, or policy changes [5], [6].
3) Significant domain shift in vision applications caused by shifting field lighting, hardware variations, and localized crop strains [8].
4) Intricate data pipeline coordination across incompatible APIs, legacy government portals, and local business platforms.
5) High computational cost for long-term retraining, deployment latencies, and intermittent cellular connectivity at the farm edge.
6) Mitigating outdated peer-to-peer asset listings, scheduling conflicts, and marketplace transactional disputes [14].

B. Trust, Safety, and Inclusion

Because faulty agronomic advice can prompt catastrophic financial losses, all automated recommendations must remain interpretable and explicitly bounded. Plant health diagnostics must never be presented as definitive legal evaluations, and price projections should never function as financial guarantees. Interfaces require complete localization into regional languages like Marathi, utilizing simplified interaction paradigms while maintaining an accessible pathway to human extension professionals [12]. Finally, strict privacy boundaries must protect spatial farm geolocations, land ownership papers, diagnostic images, and direct booking logs.

X. FUTURE DIRECTIONS

A. Research Opportunities

Future studies should investigate uncertainty-aware crop suitability ranking models, explainable multimodal recommendation architectures that process text, imagery, and tabular logs simultaneously, hyper-local meteorological error correction, and advanced commodity price models that blend market arrival volumes with immediate weather trends [5], [7]. Additionally, exploring privacy-preserving federated learning paradigms could enable regional research institutes to collaboratively optimize shared analytical layers without requiring growers to surrender or centralize their private raw agricultural records [2], [6].

B. Platform Development

A phased software implementation cycle is recommended: first, build secure grower profiles, baseline crop recommendation engines, official weather interfaces, and public welfare search tools; next, integrate deep commodity pricing models and forward-looking weather-driven disease risk alerts; then, introduce full peer-to-peer machinery and labor exchange features backed by identity checks and live availability verification [14]. Advanced optimization passes, including offline-first local caching, voice-assisted interaction channels, and automated referral routing, should be deployed only after core platform stability is verified. Comprehensive field testing must precede any full-scale public release.

XI. CONCLUSION

This comprehensive survey evaluated recent peer-reviewed literature relevant to the design of SmartKrishi–AI, a unified agricultural decision-enrichment and resource-management architecture. Contemporary studies [1]–[4], [13], [15]–[18] outline valuable algorithmic progress across machine-learning-driven crop selection, model interpretability, and IoT precision agriculture networks. Concurrently, specialized investigations [5]–[9] provide robust foundations for multi-market price modeling, weather downscaling, and computer-vision plant health monitoring. The primary operational opportunity lies in connecting these separate analytical blocks with verified public program registries and practical, localized machinery and labor exchange networks [14]. However, the proposed architecture remains entirely conceptual and demands careful software engineering, extensive regional validation, localized usability studies, and rigorous multi-metric evaluation before any empirical claims regarding yield optimization or farmer economic security can be substantiated.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |

Ultimately, building a sustainable agricultural platform relies on model optimization, data lineage verification, clear uncertainty communication, multi-language accessibility, and reliable peer-to-peer resource workflows.

TABLE II
PROPOSED STRUCTURAL EVALUATION MATRIX


Module	Candidate Input	Evaluation Measures	Key Caution
Crop recommendation	Soil NPK/pH, target season, regional rainfall, temperature, irrigation, budget	Macro-F1, per-crop recall performance, probability calibration	Prevent temporal data leakage; validate strictly by distinct district and season.
Weather intelligence	Official data streams, local historical observations, spatial coordinates	MAE and RMSE tracked by specific variable and horizon	Always preserve data origin source, issue timestamps, and model uncertainty bounds.
Market price forecast	Historical price points, market arrival volumes, seasonal factors, anomalies	MAE, RMSE, MAPE metrics, prediction-interval coverage	Projections must never be framed as a guaranteed or legally binding transaction price.
Disease risk	Crop type, growth phase, weather feeds, user images, regional outbreak records	Precision, recall, F1 scores, out-of-domain image calibration	Require validation from certified experts; prohibit automated chemical prescribing.
Scheme discovery	Official portal guidelines, eligibility rules, application deadlines, active links	Database source freshness, broken-link rates, query success	Frame program matching as non-binding guidance until verified by an official.
Equipment / labour	Provider credentials, spatial position, asset details, live availability, lease terms	Request completion success, listing freshness, provider response latency	Demands continuous listing verification, scheduling checks, and dispute mediation routes.

REFERENCES

[1] "Machine Learning Based Smart Crop Recommendation System," in Proc. 2nd Int. Conf. Computational Intelligence and Computing Applications (ICCICA), 2025, doi: 10.1109/ICCICA67008.2025.11337597.
[2] "A Data-Driven Crop Recommendation System with Explainable AI for Precision Agriculture," in Proc. 3rd Int. Conf. Augmented Intelligence and Sustainable Systems (ICAISS), 2025, doi: 10.1109/ICAISS61471.2025.11041903.
[3] "Optimizing Crop Recommendation with IoT and Machine Learning: A Smart Agriculture Framework 4.0," in Proc. IEEE 2nd Int. Conf. Computing, Applications and Systems (COMPAS), 2025, doi: 10.1109/COMPAS67506.2025.11381806.
[4] "Intelligent Crop Recommendation Framework for Optimized Agricultural Productivity using Machine Learning Techniques," in Proc. Int. Conf. Electronics and Renewable Systems (ICEARS), 2026, doi: 10.1109/ICEARS67481.2026.11416759.
[5] B. A. Celik and S. Celik, "Hybrid forecasting of agricultural commodity prices: Integrating machine learning, time series, and stochastic simulation models," Borsa Istanbul Rev., vol. 25, no. 6, pp. 1440–1462, Nov. 2025, doi: 10.1016/j.bir.2025.10.004.
[6] P.-Y. Kow et al., "AI-driven weather downscaling for smart agriculture using autoencoders and transformers," Comput. Electron. Agric., vol. 232, Art. no. 110129, May 2025, doi: 10.1016/j.compag.2025.110129.
[7] "An integrated framework for multi-commodity agricultural price forecasting and anomaly detection using attention-boosted models," J. Agric. Food Res., vol. 22, Art. no. 102021, Aug. 2025, doi: 10.1016/j.jafr.2025.102021.
[8] X. Liu et al., "Solutions and challenges in AI-based pest and disease recognition," Comput. Electron. Agric., vol. 238, Art. no. 110775, Nov. 2025, doi: 10.1016/j.compag.2025.110775.
[9] J. Yan et al., "Recent developments and applications of crop disease detection, prediction, and early warning: A review," Engineering, vol. 62, pp. 316–340, Jul. 2026, doi: 10.1016/j.eng.2025.10.032.
[10] "AI-Driven Crop and Fertilizer Recommendation: A Multi-Step Predictive Modelling Approach," in Proc. IEEE 3rd Int. Symp. Sustainable Energy, Signal Processing and Cybersecurity (iSSSC), 2025, doi: 10.1109/iSSSC66652.2025.11388308.
[11] "Crop Recommendation System for Best Farming Practices Using Various Deep Learning Algorithms," in Proc. Int. Conf. Emerging Technologies in Engineering Applications (ICETEA), 2025, doi: 10.1109/ICETEA64585.2025.11100010.
[12] Food and Agriculture Organization of the United Nations, "Digital technologies in agriculture and rural areas: Status report," FAO, Rome, Italy, 2019.
[13] V. Tomar, G. Sharma, R. Rajkumar, A. Singh, S. S. Dhakare, and K. Kumar, "Development of a machine learning-based system for optimizing crop recommendations," in Proc. 1st Int. Conf. Advances in Computing, Communication and Networking (ICAC2N), 2024, pp. 1594–1599, doi: 10.1109/ICAC2N63387.2024.10895212.
[14] G. Rawat, S. Faisal, M. Asim, and N. Bansal, "Empowering Indian farmers through agri-equipment sharing: A sustainable approach for small-scale farmers," in Proc. 1st Int. Conf. Advances in Computing, Communication and Networking (ICAC2N), 2024, pp. 458–463, doi: 10.1109/ICAC2N63387.2024.10895182.

[15] M. K. Senapaty, A. Ray, and N. Padhy, "A decision support system for crop recommendation using machine learning classification algorithms," Agriculture, vol. 14, no. 8, p. 1256, Jul. 2024, doi: 10.3390/agriculture14081256.
[16] H. Lahza et al., "Optimization of crop recommendations using novel machine learning techniques," Sustainability, vol. 15, no. 11, p. 8836, May 2023, doi: 10.3390/su15118836.
[17] C. Musanase, A. Vodacek, D. Hanyurwimfura, A. Uwitonze, and I. Kabandana, "Data-driven analysis and machine learning-based crop and fertilizer recommendation system for revolutionizing farming practices," Agriculture, vol. 13, no. 11, p. 2141, Nov. 2023, doi: 10.3390/agriculture13112141.
[18] E. Elbasi et al., "Crop prediction model using machine learning algorithms," Appl. Sci., vol. 13, no. 16, p. 9288, Aug. 2023, doi: 10.3390/app13169288.

©IJRASET: All Rights are Reserved | SJ Impact Factor 7.538 | ISRA Journal Impact Factor 7.894 |



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)