



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 13 Issue: VI Month of publication: June 2025 DOI: https://doi.org/10.22214/ijraset.2025.72341

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Vertical Handover Decision Modelling in Heterogeneous Wireless Network

Jaswinder

Student, Department of Computer Science & Engg., Delhi Global Institute Of Technology, Barhana

Abstract: In essence, handover refers to a function within cellular networks and related communication systems, where it involves the transition of active data or services from one channel to another. The identical form soft handover procedure can take place in both cellular networks and satellite communication systems to guarantee uninterrupted transmission of data or services. Handover management has been the topic of research for the past decade which is now more prominent issues due to the growth of generation in wireless communication standards. The current generation of wireless communication belongs to emerging wireless platform which are referred has heterogeneous networks. This heterogeneity exists in all aspect so communication stating from the access technologies used, frequency of operation, applications supported, operating systems, multimode handheld devices etc. This heterogeneity puts forth challenges in providing seamless connectivity to the user due to the complementary characteristics of the access technologies and networks used in overlay scenario. One of the prominent issues isproviding good mobility management is basis for seam less communication. To provide an on-disruptive communication the management has to be taken care more. As this work deals with heterogeneous networks, the issue of vertical handover is of prime importance in order to achieve service continuity.

The handoff parameter is controlled by ANFIS Techniques. The entire distance is monitored by RSS parameter. On the basis of RSS parameters, Channel capacity, throughput & jitter parameter is calculated. The handoff via ANFIS performed better throughput & Jitter values. For 4G Base Station, 2100MHz, 2300MHz and 2500 MHz is calculated for previous technique is calculated at 1118 meter, 1169 meter and 1215 meters respectively.

Forthe proposed technique, in4G Base Station for 2100 MHz, Handover is calculated at 951 meter. Similarly, 4G Base Station for 2100 MHz, 2500 MHz, and Handover is calculated at 983 meter and 1016 meters. The proposed throughput obtained from the algorithm for frequency 2100, 2300 and 2500 Hertz frequency is 70%, 84%, 92% respectively as compared to existing throughput are 60%, 80% and 90% respectively. The proposed throughput obtained from the algorithm for frequency 2100, 2300 and 2500 Hertz frequency as compared to existing throughput are 60%, 80% and 90% respectively. The proposed throughput obtained from the algorithm for frequency2100, 2300 and 2500 Hertz frequency is 0.028, 0.08, 0.003 secrespectively as compared to existing throughput are 0.03, 0.01 and 0.005 respectively.

I. INTRODUCTION

Major challenges exist between LTE and 3G. LTE uses OFDMA as its radio interface. LTE enables to operate with the flexibility in the spectrum usage and data rate. As the LTE is the technology that supports 4G wireless data communication the supporting mobility speed is almost in multiples of hundreds of kilometers per hour. So the probability of handover occurrence will be high which requires a proper and effective handover algorithm that could provide seamless connectivity and improvise the system performance in terms of throughput by reducing handover delay andpacket loss. The handover procedure in LTE networks are the key function which are required to decrease the call connection interruption period when compared with the 2G networks which uses circuit switched type of handover. LTE technology provides two types of handover. One is homogeneous handover which hhappens between the cells of the same type of network and the other is heterogeneous handover which support handover between various types of networks.

When a handover performed within an E-UTRAN it is referred as inter eNodeB handover. The handover also depends whether the UE is entering or leaving the cell.If the UE is entering a new cell, it is referred as targets in tere Node B hand over. If the UE is leaving a cell and entering a new cell which is handled by another eNB, such handover is referred as source NB handover. If a hand over is between E- UTRAN to a different radio access technology, it is referred as inter RAT handover. When a handover is performed from one sector to another sector which is controlled by the sameeNB it is referred as intraeNB handover. Whenhandover occurs between eNodeB, it is done using S1 interface in which MME and SGW are involved.

Figure gives a complete integrated architecture of UMTS and LTE systems .All the communication is supported by the SGSN of the UMTS network to LTE and through the GGSN to the other packet data networks.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue VI June 2025- Available at www.ijraset.com

A. Handover Mechanism

In this section we discuss the background of proposed scheme and essential fundamentals involved for the Vertical Handover (VHO) in the heterogeneous wireless network.

Fundamentally, handover is linked to cellular networks and their related communication frameworks, and it refers to the method of shifting active data or services from one transmission channel to another [1][2]. Comparable types of handover procedures can occur in both cellular networks and satellite communication systems [3][4], aiming to maintain a continuous and smooth flow of data or services. In Figure 1.3, It is observed that various types of access points are linked to the core network. These access points may be either homogeneous or heterogeneous in nature.

B. Importance of Handover Mechanism

A third key advantage of the handover mechanism is its ability to withstand interference from disruptive channels, particularly in non-CDMA (Code Division Multiple Access) networks. Typically, there is a significant likelihood that a communication channel may experience substantial interference when it is simultaneously used by multiple mobile users across different cells but operating on the same frequency channel. In such condition, the call is transferred to a different channel that could be present on different cellular region or either within the same cellular region itself [8]. A fourth significant benefit of the handover mechanism lies in the efficient allocation of frequency resources to accommodate the dynamic movementofmobileusers, particularlyinnon-CDMAnetworks.Insuchnetworks, it

II. RESULT ANALYSIS

A. MATLAB

MATLAB is a interactive system who uses arrays which does not have any dimensioning and can be specified by users itself. This permits the user to solve many computational problems, especially those problems which are in form of matrix and have vector formulation form. In this we can write a program in an non interactive language like C or FORTAN which takes a little time to write the programs.

MATLAB 2016b has evaluated over a long periods time with the various inputs and being successfully implemented.

MATLAB 2016b also have a feature which is application specific and it is" toolbox" this tool box have various kind of tools which have their own specification according to the software .Tool box contains the comprehensive functions that extend the capability of MATLAB to solve the various problems. Some field where we use tool boxes are: -

- 1) Image processing
- 2) Bioinformatics
- 3) Fuzzy logic
- 4) Control systems
- 5) Signal processing
- 6) Control systems
- 7) Wavelets

Most of the MATLAB toolbox contains M- files as demonstrated above, which are the MATLAB 2016b statements that are used to implement the special image processing algorithms. By the help of image toolboxwe can easily read the, write and modify various functions of an image.

The MATLAB consists of five main parts:

- *a)* The MAT LAB language: MAT LAB is a interactive system who uses arrays which does not have any dimensioning and can be specified by users itself. This permits the user to solve many computationa lproblems, especially those
- *b)* problems which are inform of matrix and have vector formulation form. In this we can write a program in an non interactive language like C or FORTAN which takes a little time to write the programs.
- *c)* The MATLAB working environment: this contains the set oftools and facilities by which you work as a MATLAB user and thus it can said to be an interface or other function by the help of which you can work on a high level language. This function contains managing the specified variables according to your system structure and to input and output of the software system data.
- *d)* Handle Graphics: it is MATLAB graphics system. Means there we can control and modify the graphics of our MATLAB this contains a 2-D and 3-D visualization. We can use the low level command to modify our graphics like to maximize minimize or various other image processing functions.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 13 Issue VI June 2025- Available at www.ijraset.com

- *e)* The MATLAB mathematical function library: MATLAB function library contains a large range of a, addition, subtraction, cosine sine, log to the more computational problems like matrix, inverse matrix etc.
- *f*) The MATLAB Application Program Interface (API): application program interface is the part where the user can interface with the MATLAB by the user friendly language which may be C or FORTAN and these can be easily written program language which a user can use to write it software program. It also contains various facilities from MATLAB.

III. PROPOSED METHODOLOGY

A. Network Design & Calculations

Under the different propagation conditions, the coverage area of the cellular systemis evaluated with a no.of handover points. It resolves the different channel faced by the cellular network. In this section, two basestationsi.e3G&4Gbasestationsareplaced in a particular manner as shown in fig 4.1.

The proposed two base station BS1 & BS2 are operated at 900 MHz & 1800 MHz respectively. The co-ordinate calculations analysis is given in fig4.2. As shown in fig 4.1, Point A indicating BS1 & Point B indicating BS2 respectively. It is assumed that user is moved out from BS1 to BS2 & make a trajectory along this straight line & represented by AB line

IV. CONCLUSION & FUTURE SCOPE

A. Conclusion

Handover management has been the topic of research for the past decade which isnow more prominent issues due to the growth of generation in wireless communication standards. The present era of wireless communication is part of the next-generation wireless systems, commonly known as heterogeneous networks. This heterogeneity exists in all aspects of communication stating from the access technologies used, frequency of operation, applications supported, operating systems, multi mode hand held device sets. This heterogeneity puts forth challenges in providing seam less connectivity to the user due to the complementary characteristics of the access technologies and networks used in overlay scenario. One of the prominent issues is providing good mobility management is the basis for seamless communication. To provide a non-disruptive communication the management has to be taken care more. As this work deals with heterogeneous networks, the issue of vertical handover is of prime importance in order to achieve service continuity.

For 4G Base Station, 2100 MHz, 2300 MHz and 2500 MHz iscalculated for previous technique is calculated at 1118 meter, 1169 meter and 1215 meters respectively. For the proposed technique, in 4G Base Station for 2100 MHz, Handover is calculated at 951 meter. Similarly, 4G Base Station for 2100 MHz, 2500 MHz, and Handover is calculated at 983 meter and 1016 meters.

B. Future Scope

Mobility management plays a vital role in providing continuous communication in an environment of het nets. The challenges depend on the availability and capability of various types of handheld devices which possess innumerable issues to be addressed while working in a heterogeneous environment. The work can be further extended in the waybymaking use ofmultiple attributes bothinthe decision making and network selection process in order to execute the handover by using the soft computing techniques.

REFERENCES

- Patil, M.B., & Patil, R.(2023).Fuzzy based network controlled vertical handover mechanism for heterogeneous wireless network. Materials Today: Proceedings, 80, 2385-2389.
- [2] Babalola, O. P., & Balyan, V. (2022). Vertical handover prediction based on hidden markov model in heterogeneous VLC-WiFi system. Sensors, 22(7), 2473.
- [3] Goh, M. I., Yew, H. T., Wen, D., Kiring, A., & Kheau, C. (2022). Vertical Handover Decision Making Algorithms for 5G Heterogeneous Networks: A Review. International Journal of Emerging Technology and Advanced Engineering, 12, 185-199.
- [4] Wang, S., Deng, H., Xiong, R., Liu, G., Liu, Y., & Liu, H. (2021). A multi-objective model-based vertical handoff algorithm for heterogeneous wireless networks. EURASIP Journal on Wireless Communications and Networking, 2021(1), 1-18.
- [5] Liu, C., Liu, X., Ng, D. W. K., &Yuan, J. (2020). Deep residual learning for channelestimation initelligent reflecting surface-assisted multi-user communications.
- [6] Naresh, M., Reddy, D. V., & Reddy, K. R. (2020). Multi-objective emperor penguin handover optimisation for IEEE 802.21 in heterogeneous networks. IET
- Communications, 14(18), 3239–3246.[7] GoutamS, UnnikrishnanS(2019) "AlgorithmforhandoverdecisioninIEEE
- [8] 802.11 WLAN Environment based on Fuzzy Logic." Int WIE ConfElectr Computer Eng(WIECON-ECE), Publisher:IEEE, Conference Location: Bangalore,India,India
- [9] Lahby M, Essouiri A, Sekkaki A (2019) A novel modeling approach for vertical handover based on dynamic k-partite graph in heterogeneous networks. Digital Commun Netw 5(4):297–307
- [10] Goutam S, Unnikrishnan S (2019) ''QoS based vertical handover decision algorithm using fuzzy logic.'' In 2019 International Conference on Nascent Technologies in Engineering (ICNTE 2019), IEEE, Mumbai

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 13 Issue VI June 2025- Available at www.ijraset.com

- [11] Goutam S, Unnikrishnan S (2019) "A geolocation based algorithm for vehicular congestion avoidance using fuzzy logic." Int J Inform Technol Electrical Eng pp. 68–73
- [12] Abdulwahhab,M.M.,Rasid,M.F.,&Hashim,F.(2019,October31).Bio-inspired Journal of Wireless & Mobile Networks (IJWMN), 11(5).
- [13] Al Emam, F. A., Nasr, M. E., &Kishk, S. E. (2019). Context-aware parallel handoveroptimizationinheterogeneouswirelessnetworks. In Guy, Pujolle (Ed.), Annals of Telecommunications (pp. 1–5).
- [14] Bisio, I., &Sciarrone, A. (2019). Fast multiattribute network selection technique forverticalhandoverinheterogeneousemergencycommunicationsystems. In Song, Guo (Ed.), Wireless communications and mobile computing (pp.1–17).
- [15] Coqueiro, T., Jailton, J., Carvalho, T., & Francês, R. (2019). Afuzzylogicsystem for vertical handover and maximizing battery lifetime in heterogeneous wireless multimedia networks. In Wireless Communications and Mobile Computing (pp. 1–12).
- [16] Goyal, R., Goyal, T., Kaushal, S., &Kumar, H. (2019). Fuzzy AHP Based Technique for Handover Optimization in Heterogeneous Network. In Proceedings of 2ndinternationalconferenceoncommunication, computing and networking springer, Singapore. 293–301.
- [17] Gupta,M.S.,Srivastava, A.,&Kumar,K.(2019).Seamlessverticalhandoverfor efficientmobilitymanagementincooperativeheterogeneousnetworks.InProceedings ofthe2ndinternationalconferenceondataengineeringandcommunicationtechnology springer, Singapore. 145–153.
- [18] Hosny,K.M.,Khashaba,M.M.,Khedr,W.I.,&Amer,F.A.(2019).Newvertical handoverpredictionschemesforLTE-WLANheterogeneousnetworks.PloSOne, 14(4), p/e0215334.
- [19] Kirsal, Y., Mapp, G., & Sardis, F. (2019). Using advanced handover and localization techniques for maintaining quality-of-service of mobile users in heterogeneous cloud-based environment. Journal of Network and Systems Management, 27, 1–26.
- [20] Naresh, M., Reddy, D. V., & Reddy, K. R. (2019). Improved vertical handoff decision scheme in heterogeneous wireless network based on SCS. In International conference on computer networks and communication technologies, Springer, Singapore, 727–737.
- [21] Pradeep, M.,&Sampath,P.(2019,October). Anoptimized multi-attributevertical handoff approach for heterogeneous wireless networks. Concurrency and Computation: Practice and Experience, 31(20).











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)