



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: I Month of publication: January 2018 DOI: http://doi.org/10.22214/ijraset.2018.1264

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



Automated Match Box Base Folding

M. Periyasamy¹, M. Ramya², V. MahaVishnu³, M. Sabarimuthu⁴

¹UG Scholar, Department of EEE, Kongu Engineering College Perundurai, Erode-638 060

²UG Scholar, Department of EEE, Kongu Engineering College Perundurai, Erode-638 060

³UG Scholar, Department of EEE, Kongu Engineering College Perundurai, Erode-638 060

⁴Assistant Professor, Department of EEEB Kongu Engineering College, Perundurai, Erode-638 060

Abstract: The economic development of a country is measured on the basis of the industrialization. Even though the technology has been developed worldwide, still there is a problem, which includes the production of matchbox base folding is done manually. With the increased number of workers for matchbox production, but their production output is very low. This also increases the risk of various health problems to the workers. Since the process is continuously repeated, it filling matchsticks may create stress to workers. In order to overcome these issues, we have designed an automated match box base folding. This paper describes about how automated matchbox folding box has been designed. Through this project, the productivity of company increases with less time consumption. It reduces the large amount of labor cost and also decreases stress to workers. Keywords: DC motor, conveyor belt, stepper motor, microcontroller

I. INTRODUCTION

Match industries are utmost necessity in the everyday life of human beings. The origin of the match industry dates back to new stone-age. Match industry has mass production and provides employment opportunities to the society. It plays a vital role in building up the economic structure of the society. Sweden is the famous and oldest manufacturer of match industry. The major market areas are Delhi, Gujarat and Rajasthan. The small match factories could not meet the total requirements of the country. However, India began to import matches from Sweden and Japan. Packing is the final stage process in the manufacturing industry which is the important process, as it determines the production rate of a manufacturing industry. Hence the production rate of the company decreases and it also has some limitations such as migration of labors, hike for increase in wages, handling of those sticks directly in hand may serious health hazards to the labor. So we created the automated matchbox base folding machine at low cost. Senthil et all[1]designed the automatic match box filling machine with the production rate of the company increases. The production cost of the product has been decreased. There is no need of thinking about the hikes on increases in wages and the absence of labor doesn't affect the productivity of the company. Mahajan et all[2]proposed an easy T-shirt Folding machine is an automatic motor controlled t-shirt folding machine to fold T-shirts merely by pressing a button. Here they used four DC gear motors to control the motion of the folding part and rotates according to the program which uses microcontroller. The microcontroller controls the overall motion of the folding Senthil et all[3] proposed an "Automatic match box filling machine "which deals about automatic filling of match sticks in the match box which increases the production and decreases the cost. Hani Buri [4] proposed about domain folding of plate structures. This makes complex geometries developed by economic ways.

Mahajan et all[5] proposed T-shirt folding machine discussed about T-shirts automatically using DC gear motors. This provide easy and full automatic technique to fold t-shirts and reduce human works.

II. PROPOSED METHOD

The proposed method designed an automated folding match box base and apply glue on it together, at low cost for middle class people with the advantages of Reduce manual works Increase perfections Time and enrgy consumption The block diagram of proposed system is shown in the figure 2.1



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887 Volume 6 Issue I, January 2018- Available at www.ijraset.com



Figure 2.1 Proposed Block Diagram

The components required for the proposed system includes: DC motor, stepper motor, conveyor belt and microcontroller.

A. DC Motor

A DC motor is mechanically commutated electric motor powered from DC current shown in the figure 2.2. The stator is stationary in space by definition and therefore the current in the rotor is switched by the commutator to also be stationary in space. The relative angle between the stator and rotor magnetic flux is maintained near 90 degrees, which generates the maximum torque. DC motor has rotating armature winding .For permanent magnetion -rotating armature magnetic field and a static field winding are present.



Figure 2.2 DC Motor

The speed of a DC motor can be controlled by changing the voltage or current applied to the armature. Modern DC motors are often controlled by power electronics system called DC drives. We have used 12V DC motor with a speed range of 60rpm. The motor operation is based on principle called simple electromagnetism. A simple 2-pole DC electric motor(here red represents a magnet or winding with a "North Polarization" while green represents a magnet or winding with a "South "polarization).



Figure 2.3 DC Motor working

Every DC motor has six basic parts namely: axle, rotor, stator, commutator, field magnet and brushes. In most common DC motors the external magnetic field is produced by high -strength permanent magnets. The stator is the stationary part of the motor where as the rotor is rotating part. The rotor consists of core winding, which connects electrically to the commutator. DC motor working is shown in figure 4.2

B. Operation

The geometry of the brushes, commutator contacts and rotor windings are given to the power, the polarities get energized the above windings and stator magnet are misaligned, and the rotor will rotate until it is almost aligned with the stator fields magnet. As the rotor reaches alignment ,the brushes move to the next commutator contacts and energize the next winding. For two-pole motor, the rotation reverses the direction of current through the rotor windings and avoids "dead spots" in commutator.



C. Stepper Motor

A stepper motor is a brushless DC motor that divides a full rotation into number of equal steps. Brushed DC motors rotate continuously, when DC voltage is applied to their terminals. The stepper motor converts a train of input pulses into an increment in the shaft position shown in figure 2.4. Each pulse moves the shaft through a fixed angle.



Fig 2.4 Stepper Motor

D. Operation

Stepper motor consists of electromagnets arranged around a central gear-shaped piece of iron. The electromagnets are energized by an external drive circuit or a microcontroller. To make the motor shaft turn first, one electromagnet given power, which magnetically attracts the gear teeth? When the gear teeth are aligned to the first electromagnet, they are slightly offset from the next electromagnet. This means that when the next electromagnet is turned on and the first is turned off, the gear rotates slightly to align with the next one and the process get repeats. Each rotation is "step" with an integer number of steps making a full rotation. Bipolar motors have a single winding per phase. The current in a winding needs to be reversed in order to reverse a magnetic pole. The windings obtained are better utilized and more powerful than a unipolar motor of the same weight. This is due to the physical space occupied by the windings. Stepper motor is strongly dependent on the driver circuit. To overcome the inductance and the switch the windings quickly, one must increase the drive voltage. This leads to the necessity of limiting the current with the high voltage or may otherwise induce.

E. Actuators

An actuator is a component of a machine that is responsible for moving or controlling the mechanism or system. An actuator requires a control signal and a source of energy. The source may be electric current, fluid pressure, or pneumatic pressure. When the control signal is received, the actuator responds by converting the energy into the mechanical motion shown in figure 2.5. An electric actuator is powered by a motor that converts electrical energy to mechanical torque. Some actuators arte intrinsically linear, such as piezoelectric actuators. conversion between circular and linear motion is commonly made via., few simple types of mechanism namely screw, wheel and axle.



Figure 2.5 Actuators internal diagram

Performance metrics for actuators include speed, acceleration ,force, energy efficiency and considerations such as mass, volume, operating conditions, durability and so on.,

F. Conveyor Belt

A conveyor belt is object carrying medium of a belt conveyor system. It is one of the type of conveyor system. A conveyor system consists of two or more pulleys which get powered by moving the belt. The powered pulley is called the drive pulley while the unpowered pulley calls as idler pulley. The belt consists of one or more layers as top cover, carcass and a bottom cover. The covers are usually various rubber or plastic material. Conveyors used in industrial settings include tripping mechanisms such as trip cords along the length of the conveyor. This allows for workers to immediately shut down the conveyor belt when problem arises.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887 Volume 6 Issue I, January 2018- Available at www.ijraset.com

G. Microcontroller

The PIC 16f877 is one of The latest products from Microchip. I t contains all features which get dumped into a single chip which is used for specific application. The pin configuration is shown in figure 2.6



Figure 2.6 Pin configuration of 16F877

III. WORKING PRINCIPLE

The base of the match box is placed on the metal sheet. The four slides\corners of the sheet starts folding automatically when the person presses the centre portion of the base. The two crocodile folding pins are used to complete the process. The process involved in folding are shown in figure 3.1.



Figure 3.1 Overview of base folding

IV. DESIGN CALCULATION

A. DC Motor Power Calculation		
Consider a total mass operated by a DC	Motor is 650 grams	
Total mass= 250+400= 650gms (approx)(1)	
We know that acceleration due to gravit	y in terms of meter per seconds square	
Acceleration = 9.81 m/s2	(2)	
From newton's law of motion,		
Force=Mass*Acceleration (3)		
Substitute(1)&(2)in(3)		
Force=650*9.81=6.38N	(4) Torque = Force*distance	(5) Distance between
linear stand, d=0.025m (6)		
(or)		
0.1595 kg.cm		
Let us take speed of a dc motor		
Speed, $N = 100$ rpm	(8)Power= $(2^{*}\pi^{*}N^{*}T)/60$	(9)
Substitute (7)&(8) in (9)		
Power=(2*3.14*100*0.01625)/60 Power=0.17W/0.000227HP		(10)



B. Actuator Power Calculation

- Data from Specifications..,
- 1) Inpu Voltage :12 V
- 2) Max.Push Load: 150
- 3) Max.Pull Load : 1200
- 4) Speed N : 5.7mm/sec 5) At No Load : <0.5
- 5) At No Load :

6) At Max Load : 3A Pmax=V *I max(11) Substitute (11)&(12) in (13) Pmax =12*3 =36W/0.048HP (12)

V. ESTIMATION COST

Maintenance Cost: (Depends upon Maintenance) Power consumed by Actuators : 96 W Power Consumed by DC Motor: 8 W

Operating Cost: 250W*8hr=2000W/Day Wattage Used per Month: 2KW*30= 60 Units Approx. cost: 60*3=rs.180

VI. HARDWARE IMPLEMENTATION

The hardware implementation were shown in figure 6.1.Here the balancing legs provides the enough mechanical support to balance on its own. The DC motor is attached to the circular disc.The hardware works on Crank Shaft principle which converts rotatry motion into linear motion.



Figure 6.1 Hardware Implementation

VII. CONCLUSION AND FUTURE SCOPE

This paper proposed that the automatic matchbox base folding process and with hardware implementation. Thus the proposed method increased the production rate of the company and decreases the production cost. Absence of labour does not affect the productivity of the company. The advantages are reduction of noise, pollution ,trade union and time reduction for match box folding .The future scope of this paper are cost of power supply has been reduced by using the solar energy. The arrangement of the hardware setup can be easily reassemble to any other places.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887

Volume 6 Issue I, January 2018- Available at www.ijraset.com

REFERENCES

- Mukesh P. Mahajan ,Srishti Prasad TejalBinnar, Nashik Monika Tamb, "Automatic T shirt Folding" International Journal of Computer Applications., (0975 8887) Volume 162 – No 10, March 201
- [2] Shriraman, T & S, Senthil&Vellaichamy, Ragavanandham, An innovative design of automatic match box filling machine. International Journal of Applied Engineering Research. 10. 3882. June 201
- [3] Masahirotaketsugu, Kunioniuchi, yoshiharukushiya, "New box making machine" Mitsubishi heavy industries, ltd. Technical review vol. 42 no. 1 (Feb. 2005
- [4] Suraj Shah, Utkarsha Mahajan," Automatic cloth folding and colour based sorting mechanism" IJTRE, Volume 2, Issue 7, March-2015.
- [5] N.Gomesh, Y.M.Irwan," Photovoltaic powered T-shirt folding machine" Conference Paper in Energy Procedia , February 2013.
- [6] Deepak Shroff, Paresh Somani." Automatic T-shirt folding machine".
- [7] http://www.mrprint.com/equipment/matchbox folding-packaging-machines
- [8] https://en.wikipedia.org/wiki/matchbox_ manufacturing











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)