



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: II Month of publication: February 2018
DOI:

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



Experimental Analysis on Diffusion of Liquid in To Gas

Dheramendra Kumar Rathore¹, Saurabh Kumar²,

¹ M. Tech, Thermal engineering scholar, Mechanical engineering department, Raipur institute of technology, Raipur, India) ²Assistant Professor, Mechanical engineering department, Raipur institute of technology, Raipur, India)

Abstract: With increasing demand of energy require environmental concern. It is the driving force to search the ways for saving the fuel. In the present work diffusion coefficient of the different volatile liquids are calculate by a simple experiment and study about the effect of temperature variation on diffusivity are also report. Keywords: Petrol, Methanol, Diffusion, Diffusivity, thermostatic water bath.

I. INTRODUCTION

In diffusion, we are basically find out the non-availability of diffusivity of volatile liquid. We are refers on previous papers, so, those are discussed about the liquid diffusion applied to analysis, determination of the diffusion coefficient by the using of different gas chromatographic, and the study about the effect on oxygen diffusion coefficient of the presence in clean water of some compounds encountered in biological media. In all the papers to study about the, determination of diffusion coefficient in simple liquid and their volatile property, and this are determined by the various chromatography method so do not find out the diffusion coefficient of whose liquid, diffusivity of those liquid are not available, and diffusivity is very important factor for the mass transfer we are already discussed about that, so we are find out the diffusion coefficient of the different volatile liquid by an simple experiments and study about the effect of temperature variation and also study about the changes in concentration of volatile liquid then what are the effect of its diffusion coefficient. Diffusion is the movement of an individual component through the mixture due to some physical driving force. It occurs all mass transfer operation in at least one phase or often both phase. Diffusion can be two types, molecular diffusion and Eddy diffusion depending up on the phase conditions. The transfer through the stagnant layers known as molecular diffusion and this is a slow process. Diffusion is a mass transfer phenomenon that causes the distribution of chemical species to become more uniform in space as time passes. The mass transfer species is the evolution of its concentration in space and time, if the concentration of species is initially not uniform then overtime, diffusion causes mass transfer in favour of a more uniform concentration. In case of molecular diffusion, since the mass transfer occurs from a region of high concentration to one of lower concentration, the flux is proportional to the concentration gradient.

$$J_a$$
 A $\frac{\partial ca}{\partial z}$

Or

$$a = -DAB \frac{\partial Ca}{\partial Z}$$

Where J_{α} is the molar flux of component a. And Dab is the proportionality constant, called the molecular diffusivity or diffusion coefficient of molecule a in b. Diffusivity is defined as the ratio of flux to its concentration gradient and its unit is m^2/s . It provides the diffusive mobility of a constituent and is a function of the temperature, pressure, nature and concentration of the other constituents. sing the water bath for an Experiment then the temperature is to be checked frequently to make sure that the water bath is maintaining the proper temperature.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor : 6.887 Volume 6 Issue II, February 2018- Available at www.ijraset.com



Fig: front view of thermostatic water bath.

A water bath is laboratory equipment made from a container filled with heated water. It is used to incubate samples in water at a constant temperature over a long period of time. All water baths have a digital or an analogue interface to allow users to set a desired temperature.

II. LITERATURE REVIEW

T. Graham [1], Discussed about the liquid diffusion applied to analysis. The property of volatility, possessed in various degrees by so many substances, affords invaluable means of separation, as is seen in the ever-recurring processes of evaporation and distillation. J Chromatogr A [2], Discussed about that the determination of diffusion coefficients by gas chromatography. Jamnong wong, Marupatch, Loubiere, Karine, Dietrich, Nicolas, Gilles[3], Those are discussed about the study of : (i) studying the effect on oxygen diffusion coefficients of the presence in clean water of some compounds usually encountered in biological media and (ii) quantifying their consequences on liquid-side mass transfer coefficients. The oxygen diffusion coefficients D were firstly measured in various synthetic liquid phases containing either salt, sugar (glucose) or surfactant. Brahm D. Prasher, Yi Hua Ma [4], those are study about the Liquid diffusion in micro porous alumina pellets.

III. METHODOLOGY

In case of non - availability of diffusivity value, we are the same can be determined by the using of simple experiment devised by Stefan. For the purpose, the liquid should be fairly volatile.

The different volatile liquid is taken in a different –different small diameter test tube and is allowed to diffuse to atmosphere by holding it inside a thermostatic bath. And by this thermostatic bath to maintaining the temperature is constant at the whole experiments.

The level of the liquid at the start of the experiment and after an appreciable time interval are accurately noted. The water bath temperature is set at the desired level and to wait the bath attains the set temperature.

The test tube is filled with petrol to within 2 centimeter of the top of the test tube.

The initial diffusion height of the liquid in the test tube from the top is noted down.

Then the diffusivity (D_{ab}) is calculated corresponding to its bath temperature. The diffusional flux or the diffusivity for the process is,

$$D_{ab} = \frac{P_{hm}RT\rho_L}{2M_L \theta P_T (Pal - Pa2)} (Z_2^2 - Z_1^2)$$

Where,

 $\mathbf{P}_{\mathbf{L}} = \text{Density of liquid}$

 M_L = Molecular weight of the liquid

 $\boldsymbol{\theta}$ = Time of diffusion

 $Z_2 - Z_1$ = Fall in the liquid level in the test tube.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor : 6.887 Volume 6 Issue II, February 2018- Available at www.ijraset.com



Fig : Experimental setup for measurement of diffusivity.

IV. RESULT AND DISCUSSION

LIQUID	DIFFUSIVITY (m ² /S)		
	OBTAINED VALUE		ACTUAL VALUE
	40°C	50 ⁰ C	
Methanol	0.47 X 1 0⁻⁶	0.7 X 1 0⁻⁶	10 ⁻⁵ -10 ⁻⁸
Petrol	0.8 X 1 0⁻⁵	1.83 X 1 0⁻⁵	1 0⁻⁴- 1 0⁻⁸

It can be concluded from the above experiments that the value of diffusivity for different volatile liquid is obtained and is approximate to the original value so our experiment is validate. so diffusivity increases with increases in temperature.

REFERENCES

- [1] "Mass Transfer Operations, "Robert E. Trebyl, McGrawvHill Book Co., International Edition, 1981.
- [2] "Fundamental of Heat and Mass Transfer, "G.K. Roy, Khanna Publishers, Fifth Edition, 2008.
- [3] "principles of Heat and Mass Transfer" S.D. Dawande, Central Techno Publications.
- [4] Beiki H, Esfahany M, Etesami N (2013) Turbulent mass transfer of Al₂O₃ and TiO₂ electrolyte nano fluids in circular tube. Micro fluid Nano fluidics 15(4):501–508.
- [5] Marupatch Jamnongwong, Karine Loubiere, Nicolas Dietrich, Gilles Hébrard Experimental study of oxygen diffusion coefficients in clean water containing salt, glucose or surfactant: Consequences on the liquid-side mass transfer coefficients., Chemical Engg. Journal.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)