



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: V Month of publication: May 2018

DOI: http://doi.org/10.22214/ijraset.2018.5234

### www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



## A Review on Revolution of Flat Plate Collector for Solar Water Heater

Prasad P. Patil<sup>1</sup>, Dr.D.S.Deshmukh<sup>2</sup>, Dr. A. M. Vaidya<sup>3</sup>, Izhak Paul<sup>4</sup> <sup>1, 2, 3, 4</sup>Department of Mechanical Engineering, North Maharashtra University, Jalgaon

Abstract: Energy is the significant need of the world either for nutrition or for development of the society. The power bank of the earth is the sun, which has tremendous amount of energy in it and will never exhaust. The conversion of solar energy to thermal energy is the function of collector. Flat plate collector (FPC) are cost effective and more convenience in all collectors. The paper reveals the different design of the flat collectors used to enhance the efficiency of the collector. Effect of using phase change material, nanofluids, heat pipe, different geometry of the tubes and absorber discussed. This review deals with the suggestion for the research work in flat plate collector.

Keywords: FPC Design; Solar Collectors; different collectors for SWH; Design of SWH

#### I. INTRODUCTION

Energy is the most important and a key factor in day-to-day life. The keen interest is towards the solar energy which is a pure green energy and available in plenty. The energy of Sun used to heat the water, which is the great need of each human being for various purposes. During review it is found that the various solar water heating system were made by many researchers with relatively high efficiency and reasonable cost, but the system does not meet the requirement of other countries due to climatic conditions and many other reasons. Today environment is the major issue and the awareness regarding the environment is increasing this promote solar and renewable energy system in world and decreases the dependencies' on fossil fuels.

The solar water heating system consist of riser tubes, absorbers a dark surface plate, insulation and glazed glass. The system when exposed to the sun, the absorber absorbs the solar radiation and transfers a part of it to the fluid flowing over/under it [3-7]. The more is the collector area more will be the energy, but the law of thermodynamics state that no machine can gives 100% output therefore we even cannot get the 100% percent conversion. Now, the design goals were to have the collector that can convert the maximum solar energy to heat energy with a lesser amount of losses; and cost. The objective for the review of solar water heating system is to get the various designs available and invented by researchers at one place to get the idea of possible development in it with the future of design in Solar Water Heater (SWH). The review is limited to the flat plate collector and other similar to it.

There are two broad categories of SWH (passive and active), each of them operating in either direct or indirect mode. The active systems give 35%–80% efficiency higher than those of the passive systems [3].

#### **II. LITERATURE REVIEW**

Many researchers have done the various experiments to prove their design and to increase the use of solar energy by applying different techniques of design. The review comprises the details of researcher design and the techniques they uses

#### A. Integrated Collector Water Storage(ICWS)

This is a simple type of solar water heater, which consists of storage tank, absorber plate and the glass. This is the oldest solar water heater and used for farm field [2]. The development goes on then with various new design and development [2-8]. This improved design gives the better thermal efficiency and better energy collection in ICWS system. The preceding discussion gives the brief idea of the integrated system with photovoltaic system, phase change material, concentrator collector with integrated storage system. The researcher [8] made a simple design of the ICWS for domestic purpose with a cost of `2500 only with a temperature output of 60°C in Jaipur Rajasthan, India. The Effective basin area of solar water heater is 0.14 m<sup>2</sup>. The vertical height and length of the solar water heater are 200 mm, 700 mm and 1000 mm respectively, wooden(10 mm thickness) structure is used to prepare the outer body and the collector was covered by a clear glass and insulation. The Fig 1 and 2 shows the schematic view of the BSWH design. The Experimental result shows that these types of solar water heater are enough for the family of 4 persons. It gives the good thermal efficiency but thermal losses is more at night. [9] Gives the report on the thermal performance of ICWS with absorber surface. Fig. 3. Shows the schematic diagram of the system it has rectangular shape with capacity of 100 liters, the tank is made of GI sheet of



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com

gauge 20. The depth of corrugated surface is 0.0004 m and 0.001m. The design include the night insulation cover to restrict the night losses. The corrugated absorber surface gives the high temperature with no increase in cost.



Fig.1 Line Diagram of Experimental Solar water heater (Front View) [8]



Fig. 2 Line Diagram of Experimental Solar water heater (Side View) [8]



Fig.3. Cross section schematic of rectangular solar water heater with corrugated surface [9]

1) Integrated collector-Storage Solar water heater (ICSSWH) with PV panel: Solar water heater with better efficiency and less heat losses always gives the most allowable system. The Photovoltaic (PV) cells use to convert the approximately 20% of incident radiation to electric energy [10]. [11] uses a combination of photovoltaic – thermal (PVT) module with an integrated collector storage solar water heater to investigate the effect of PV cell on tank, water mass and the collector area on this new system. The proposed gives the higher energy output as compared to the standard system. Fig 4 gives the schematic diagram and fig 5 & 6 shows the result of the PVT system. The use of PV panel is not the new trend but the use of PV with thermal collector gives the pre heating of the water [11-17]. The PVT system is also known as the hybrid system and gives the better enhancement to the temperature of the fluid [13, 14, 17].



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig 4. The ICSSWH systems for present model validating: (a) triangular storage tank (adapted from Ecevit et al. works); and (b) rectangular storage tank [11].



Fig 5. The effect of the tank water mass on the collector total efficiency [11]



Fig 6. The effects of both the collector area and the tank water mass on the tank water temperature.[11]



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com

Developed integrated storage solar water heater system: Solar passive water heater are probable aspirant for boosting heat 2) transfer [11, 18]. Cost and performance matter the most that is why [18, 19] created the design of solar water heater with low cost and with better performance. [18] Develop the integrated storage solar water heater system with a new design having a tank with black colored sands as a absorber and it is immersed into the water. The fig 7. Shows the tank of size 1.45 x 0.56 x  $0.17 \text{ m}^3$  with an effective area of 0.67 m<sup>2</sup> is used, the thickness of galvanized sheet of tank is 0.0015m. The black oil colored sand is use with the average diameters of 10 mm, there were two glass with airy distance of 0.045m between them. The important feature of this design is its large capacity with low cost [17-18]. The experimental result shows efficiency higher than 70% and the system simulated by using thermal network analysis, which shows the temperature can be increase up to  $90^{\circ}$ C. The experiment carried out at different situation and find that the west-south situation is better for the highest temperature. Integrated storage solar water heater is the simplest design of solar water heater and with minimum cost [18-19]. Fig. 8 gives the idea about the efficiency with direction and time. The main drawback in the system is that at night, the temperature get reverse, to overcome this drawback many researcher has done numerous modifications in design, [19] did the simplest modification by extending the storage section, there were two section as shown in fig 9. Section A is the regular collector that, interact with radiation and section B (shown in fig. 10) is the insulated section which store the hot water. The total volume of the two section is 100 liter and area of the absorber is  $1m^2$  the design analyzed and optimize in such a way that the temperature remain maximum in both the section. Fig. 11 shows the relationship between efficiency and volume ratio (volume A/ Volume B) the maximum efficiency was at 2.33 i.e (70/30) ratio.



Fig. 7. The schematics of (a)the compact solar water heater and (b) the thermocouple locations[18].







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig. 1. Cross-sectional view of modified integrated collector-storage solar water heater.





Fig 10. Cross section view of rectangular integrated collector storage solar water heater [19]



Fig. 11. Efficiency of water heater corresponding to different water volume ratios together with rectangular shape (R) ICSSWH. [19]

3) New trends in integrated collector storage solar water heaters: The integrated collector storage solar water heater system is a flat plate collector with compact design. This new design studied by [20] is integrated collector storage solar water heater (ICSSWH) with parabolic trough that is compare with the regular flat plate thermo-syphon unit. The important factor to be consider in ICSSWH is its depth, if the depth is more performance is low, therefore the depth of solar thermal devices that



#### International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

combine with Compound Parabolic Concentrating (CPC) reflector [18, 21-23]. The parabola trough gives the momentous improve in the thermal performance. [20] Studied the decrease in depth of ICSSWH with CPC and even with less maintenance. The three designs have the symmetrical reflector with involutes curve, parabolic curve and CPC reflector with different acceptance angle; fig 12 shows the schematics diagram of the storage collector, all three design have the same thickness of insulation on backside of storage tank i.e. 18.17% [19]. Fig 13 to 17 shows the design of all 3 model and fig 17. Gives the experimental view of the entire three model, the design is suitable for flat as well as for inclined surfaces and ICS 2 shows the satisfactorily performance in respect to thermal and depth. The new trend in design is to use computational studies on the performance of ICSSWH [24-25]. The [26-27] uses the new material known as phase change material (PCM). PCM has the high thermal capacity and constant change temperature. The use of PCM in solar collector system gives the promising result with decrease in thermal loss and efficiency increases by 11% [28]. The utilization of PCM in water tank boosts thermal energy density and capacity, introduction of PCM shows the higher temperature in water storage [27-32]. Fig 18 and fig 19. Shows schematic diagram of the experiments and thermal energy storage unit [26]. The use of PCM in ICSSWH is a better option to improve the thermal performance of this solar water heater system, the only thing is to use the proper PCM material at appropriate radius [27].



Fig. 12. Dimension description of the ICS experimental models.[19]



Fig. 14. Cross section of the experimental model ICS 1.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig. 15. Cross section of the experimental model ICS 2.[20]



Fig. 16. Cross section of the experimental model ICS 3. [20]



Fig. 17. Experimental ICS models mounted at the test field.[20]



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig. 18. Schematic diagram of the test rig. (1.Water storage; 2,11. Temperature sensor; 3. Three-way valve; 4. Pump; 5. Flow meter; 6. Valve; 7. All-glass vacuated tubular solar collector; 8. Pyranometer; 9. Shaded pyranometer; 10. Safety valve).[26]



Fig. 19. Schematic diagram of thermal energy storage unit using Ba(OH)<sub>2</sub>.8H<sub>2</sub>O as PCM.[26]

#### B. Zig Zag Collector Design

the Maximum temperature with less loss is the aim of every researcher and [33] experimentally analyzed the flat plate collector with zigzag pattern and at different flow rates. [33 -35] arrange the riser tubes of FPC (flat plate Collector) in zig zag pattern to attain the maximum solar radiation and to gain maximum temperature. Fig 20 shows the zigzag pattern of collector, in series and mixed mode the mixed flow collector increases the contact surface area and change in tube material of higher conductivity and that of using Nano-material can give better temperature result. [34 -36] arrange the riser tube in Z configuration which give the maximum performance as compared with conventional FPC. The new developed design is the Zig Zag design of riser tubes in FPC [20, 21]. This type of collector is suitable for both domestic and industrial purpose. The fig.20. Shows that the riser tube is arrange in the tubular arrangement [20, 21]. The design parameters of the zig-zag flat plate collector is similar to regular flat plate collector the only change is there are three header tubes, it is less utilized as its performance is approximately equivalent to the conventional design.

#### C. Micro tubes Flat plate Collector

Flat plate collector is always the point of research due to its surface area more is area more can be the energy storage but to get the maximum energy losses are to minimize, [37] uses the FPC with low cost and high efficiency micro heat pipes array. The FPC will contain 300 micro heat pipe per  $1m^2$  of diameter 0.4- 1.0 mm. These pipes are gravity assisted with a two stage closed thermosyphon with a liquid reservoir, it can transmit the heat at high rates over considerable distances with a minute temperature difference in a very little time [37].Fig 21. Shows the section of micro flat plate heat pipe of size 1500 x 26 x 2 mm with micro grooves and channel connected by stiffening rib. The cost of the micro tubes is less as it is made of aluminum alloy. Fig 22. Shows the charging circuit which charge the tube by using methanol in it. The experiment set up consist of a flat plate collector with heat pipes and a



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

well-insulated water tank of 150L capacity equipped with an electric heater, a thermostat, a circulating pump, control valves, safety instruments and a measuring system. The system gives excellent isothermal characteristics. Heat pipes eliminate the welding and scale formation while it gives 88% efficiency with low cost. [38] suggest that the pipe inclination angle have a substantial effect on heat transfer inside the wickless heat pipe. Similarly [39] shows that the increase in number of wickless heat pipe gives a significant effect on the collector efficiency. [40] examine the heat pipe for three different geometry that are circular, elliptical and semicircular. The result shows that the elliptical geometry gives better performance than the other does. The wickless heat pipe can transmit heat at high frequencies over substantial distances with small temperature differences. It behave like thermal diode. Fig 23. Shows the schematic diagram of the evacuation and charging rig of wickless heat pipe and Fig 24. Cross sectional views of the prototype wickless heat pipe flat plate solar collector [40].



Fig. 20. Sectional view of zig zag Flat Plate Collector (FPC) [21].



Fig 21. Section of micro flat plate heat pipe [37]







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig.23. Schematic diagram of the evacuation and charging rig [40]

#### D. Variable Geometry of Riser Tube

The flat plate collector is the medium to supply the thermal energy at adequate temperature. [45-46] studied the performance of few profile shapes namely, trapezoidal (R=0.2)[45-46,48], rectangular and rectangular profile wit step change in thickness (RPSLT) (R=0.5). Fig 25. shows the detail of new absorber plates design, analysis and optimization of these shapes shows that the trapezoidal profile is a better choice but it is difficult to manufacturing. The other choice is the RSPLT profile as it gives higher performance with fewer difficulties in fabrication.

The solar energy is depend on the surface area the more the surface area the more is the energy collection therefore [46] increases the surface area by using the semicircular type tube in the collector. Here the absorber is not modified but the tube is modified with more surface area; fig. 26 Shows the schematic view of semi-circular tube, which gives the idea that semi-circular cross section gives increasing absorber area of tube due to which heat gain increases drastically [46,48]. Fig. 27 shows effect of semi-circular tube over heat. The semicircular tube absorbed more heat than regular circular tube.

To improve the thermal performance of collector many different ideas were invented one this is changing the geometry of tube this will add the absorbing area to the collector, which will lead to the gain in surface temperature [48]. The absorber area and surface is important parameter in designing the collector [47, 48]. Therefore [48] experimentally checked the performance of the four different geometry namely circular, triangular, elliptical and square tubes been illustrated in fig. 28. Triangular tubes shows more efficiency then other tubes. [49] Changes the material of absorber and analyzed the results of temperature at different radiation condition.



Fig 24. Cross sectional views of the prototype wickless heat pipe flat plate solar collector [40]



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig. 26. Flat plate collector with semi-circular cross sectional tube [47].



Fig.27 graph of inlet vs heat gain [47]





International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887 Volume 6 Issue V, May 2018- Available at www.ijraset.com



Fig. 28. Different cross-section of the tubes [48]

#### E. Twisted Tape Design

Some researcher find that the heat transfer between tube and water is insufficient and there is a need of an idea that will increase the heat transfer between tube and water. [51-65] analyzed the issue of poor heat transfer coefficient at water tube surface and the solution to improve is it to insert the twisted tape in the tube. The conventional fin in tube shows the very low Reynolds number under thermosyphon effect [51]. This lead to the era of increasing the heat transfer enhancement from tube to water [51-65]. Fig 29. Shows the schematic view of twisted tape collector, many researcher studied the different parameters of twisted tape as the swirl flow increase the heat transfer coefficient but to get the optimum value the different parameters was discussed. [62] Investigate experimentally the heat transfer, friction factor and thermal performance of thermo syphon solar heater collector with helical and left right twisted tape and the ratio of twist is 3. [64] used twisted tape with working fluid as air and the parameters used were clearance ratio and Reynolds number. [65] experimentally studied the twisted tape with transition flow and parameter studied were twist ratio, volume, concentration of nanoparticle and Reynolds number.



Fig. 29. Schematic view of twisted strip system [51].



Volume 6 Issue V, May 2018- Available at www.ijraset.com

#### F. Nano Fluid in Flat Plate collector

Solar collector can be define as a heat exchanger because it convert the solar radiation energy to thermal energy. The direct absorption solar collect (DASC) is a type of solar collector which uses fluid as absorbing medium instead of absorber plate[66-69]. Fig. 30. Shows the schematic diagram of DASC. Many development has been taken place in this type of collector the recent achievement in DASC is the use of nano fluid which is the simple way of increasing the efficiency of new and the existing flat plate collector. It provide a boost to heat transfer rate [71-73]. There are different parameters to be considered for the nanofluids such as the settlement of nano particles, cost, pressure drop, foaming effect as it affect the viscosity of the fluid [74-75]. [76] performed the experiment for investigating the performance of collector using  $Al_2O_3$  / water nano fluid (wit and without Triton X-100 surfactant) (surfactant is the additive used to stable the nano fluid) as heat transfer agent. Nano particle used were of size 15-nm diameters at weight concentration of 0.2% and 0.4 %. The experiment shows that the use of triton X-100 stable the nano fluid for long time and the efficiency of the collector also increases but the temperature limit were  $60^{\circ}C$ . The research continue with different nano fluid and with different parameters i.e. pH effect on performance. Nano fluids are advanced fluid that have the capability to increase the thermal concentration and improve the heat transfer rate the only drawback is the cost of nano fluids.



Fig. 30. Schematic drawing of a direct absorption solar collector (DASC).[70]

#### **III.CONCLUSION AND RECOMMENDATIONS FOR FUTURE WORK**

The review discussed various flat plate collector and their parameters. The review finds that the maximum works were incorporated on the development of the geometrical parameters of collector to get the better thermal efficiency and heat transfer rate. The research work selected in this paper shows the increase in interest for this topic, which give the birth to the new and innovative ideas for the industry to compete with the future. The review caught the attention on some research work where costs were the main parameters for study were the cost of the solar water system [78-82]. As cost were not the parameter for our review, there were some interesting new technologies, that gives promising results with innovative materials, concentration of radiation, different geometries, integrated solar thermal collector, heat pipe collector which can be the future collector, hybrid collector i.e. PV solar collector, heat transfer through nano particles and the use of twisted tape to get the swirls effect for increasing the heat transfer. These shows the future of solar collector in the coming year is bright. The highlight is shown in table I.

| Topic      |           |       | Enrichment and Future work   |
|------------|-----------|-------|--|
| Integrated | collector | water | • To study the ICWS system with solar tracker.                             |
| storage    |           |       | • To check the performance of the collector with different phase material. |
|            |           |       | • To study the performance with large capacity of storage.                 |
|            |           |       | • To study the system with two or more storage tank.                       |
|            |           |       | • To study the performance of collector with two glass.                    |
|            |           |       | • To study the Hybrid ICWS with different geometry of tank.                |
|            |           |       | • Study of system with Transys, mathematical model and different           |
|            |           |       | optimization technique to get the best possible ways for                   |
|            |           |       | development with different parameters.                                     |



#### International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

| Zig Zag Collector                | • The zig zag pattern can be studied with swirl flow tubes.          |
|----------------------------------|--|
|                                  | • To study the effect of tubes in coils.                             |
|                                  | • To reduce the size of collector with zig zag tube and other        |
|                                  | parameters of collector.   |
| Micro Tubes                      | • To study the heat pipe with the simulation techniques.             |
|                                  | • To generate the mathematical model                                 |
| Innovation in absorber plate and | • To study the performance of collector with absorber and with       |
| riser tube                       | concentrator or reflector.   |
|                                  | • To study the effect of increase and decrease in pitch of riser     |
|                                  | tubes.   |
|                                  | • To study the different absorber material for low cost              |
| Nano Fluids                      | • To study the unstablity of nanofluids                              |
|                                  | • To study the behavior of nanofluids with temperature greater than  |
|                                  | $60^{0}$ C.  |
|                                  | • To compare the different nano fluids and their effect.             |
|                                  | • To study the long term stability of the nanofluids.                |
|                                  | •  |
| Decrease in Heat Loss            | • To reduce the top loss.  |
|                                  | • To reduce the heat loss by convection and radiation.               |
|                                  | • To study the collector with double glazed glass.                   |
|                                  | • To study the air gap between collector to get the less losses.     |
|                                  | • To study the different inert gas effect instead of air between two |
|                                  | top glazed glass.  |
| Heat Transfer rate               | • To study the heat transfer rate with twisted tape at various angle |
|                                  | of twisting.   |
|                                  | • To study the performance   |
| Low cost and Maintenance         | • To study the FPC with cheap material like polymer, PVC etc.        |
|                                  | • To study the optimization of collector on cost basis.              |
|                                  | • To study the effect of scale formations occur in riser tubes.      |
|                                  | • To study how to reduce the scale formation in riser tubes.         |

The new technique of simulation gives the deep study of collector with the help of latest software like EES, TRANSYS, MATLAB, CFD etc, to understand the losses and even the efficiency of collector soon, and by this the development ratio of new collector design can be increase to get the optimum value.

#### REFERENCES

- [1] S.P.Sukhatme, J.K.Nayak "Solar energy Principles of Thermal Energy Storage" 3rd edition, Mcgraw Hill Education, India, 2008.
- [2] Ramkishore Singh, Ian J. Lazarus ,Manolis Souliotis, Recent developments in integrated collector storage (ICS) solar water heaters: A review, Renewable and Sustainable Energy Reviews, volume 54, pp.270–298,2016.
- [3] Souliotis M, Tripanagnostopoulos Y. Experimental study of CPC type ICS solar systems, Solar Energy, vol. 76, 389–408, 2004.
- [4] Bari S. Optimum orientation of domestic solar water heaters for the low latitude countries, Energy Conversion Management, 2001.
- [5] Goetzberger A, Rommel M. Prospects for integrated storage collector systems in Central Europe, Solar Energy, vol. 39, pp. 211–9, 1987.
- [6] Kalogirou S. Design, construction, performance evaluation and economic analysis of an integrated collector storage system. Renewable Energy, vol. 12, pp. 179–92,1997.
- [7] Faiman D, Hazan H, Laufer I. Reducing the heat loss at night from solar water heaters of the integrated collector-storage variety, Solar Energy, vol. 71, pp.87–93,2001.
- [8] Chouhan Govind Singh, Agarwal Ram Kumar; 'Experimental analysis of a batch type solar water heater with integrated collector water storage system'. International Journal of Emerging Technology and Advanced Engineering, Vol. 3, Issue 5, pp-269-274, May 2013.
- [9] Rakesh Kumar, Marc A. Rosen, Thermal performance of integrated collector storage solar water heater with corrugated absorber surface, Applied Thermal Engineering,vol. 30, pp. 1764-1768, 2010.
- [10] Dubey S, Tay AAO. Testing of two different types of photovoltaic-thermal (PVT) modules with heat flow pattern under tropical climatic conditions, Energy Sustainable Development, vol. 17, pp. 1–12, 2013.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

- [11] Behrooz M. Ziapour, Vahid Palideh, Ali Mohammadnia, Study of an improved integrated collector-storage solar water heater combined with the photovoltaic cells, Energy Conversion and Management, vol. 86, pp. 587–594, 2014.
- [12] Fudholi A, Sopian K, Yazdi MH, Ruslan MH, Ibrahim A, Kazem HA. Performance analysis of photovoltaic thermal (PVT) water collectors, Energy Conversion Management, vol. 78, pp. 641–51, 2014.
- [13] Rommel M, Zenhäusern D, Baggenstos A, Türk O, Brunold S. Application of unglazed PVT collectors for domestic hot water pre-heating in a development and testing system, Energy Procedia, vol.48, pp. 638–44, 2014.
- [14] Rossi C, Tagliafico LA, Scarpa F, Bianco V. Experimental and numerical results from hybrid retrofitted photovoltaic panels. Energy Conversion Management, vol. 76, pp. 634–44, 2013.
- [15] Agrawal S, Tiwari GN. Overall energy, exergy and carbon credit analysis by different type of hybrid photovoltaic thermal air collectors. Energy Conversion Management, vol. 65, pp. 628–636, 2013.
- [16] Aste N, Pero CD, Leon forte F. Optimization of solar thermal fraction in PVT systems, Energy Procedia, vol. 30, pp. 8–18, 2012
- [17] Tiwari A, Sodha MS, Chandra A, Joshi JC. Performance evaluation of photovoltaic thermal solar air collector for composite climate of India. Solar Energy Material and Solar Cells, vol. 90, pp. 175–89, 2006.
- [18] Y. Taheri, Behrooz M. Ziapour, K. Alimardani, Study of an efficient compact solar water heater, Energy Conversion and Management, vol. 70, pp. 187–193, 2013.
- [19] Rakesh Kumar, Marc A. Rosen, Integrated collector-storage solar water heater with extended storage unit, Applied Thermal Engineering, vol. 31, pp. 348 354, 2011.
- [20] Helal O, Chaouachi S, Gabsi S. Design and thermal performance of an ICS solar water heater based on three parabolic sections. Renewable Energy, vol. 85, pp. 2421-2432, 2011.
- [21] Souliotis M, Tripanagnostopoulos Y. Study of the distribution of the absorbed solar radiation on the performance of a CPC type ICS water heater. Renewable Energy, vol. 33, pp. 846-58, 2008.
- [22] Blanco ME, Gomez-Leal E, Gordon JM. Asymmetric CPC solar collectors with tubular receiver: geometric characteristics and optimal configurations. Solar Energy, vol. 37, issue 1, pp. 49-54, 1986.
- [23] Carvalho MJ, Collares-Pereira M, Gordon JM. Rabl A. Truncation of CPC solar collectors and its effect on energy collection. Solar Energy, vol. 35, issue 5, pp. 393-399, 1985.
- [24] Gertzos KP, Caouris YG. Experimental and computational study of the developed flow field in a flat plate integrated collector storage (ICS) solar device with recirculation. Experimental Thermal and Fluid Science, vol. 31, pp. 1133-1145, 2007.
- [25] Henderson D, Junaidi H, Muneer T, Grassie T, Currie J. Experimental and CFD investigation of an ICSSWH at various inclinations. Renewable & Sustainable Energy Reviews, vol. 11, pp. 1087-1116, 2007.
- [26] H. Sheng Xue, Experimental investigation of a domestic solar water heater with solar collector coupled phase-change energy storage, Renewable Energy, vol. 86, pp. 257-261, 2016.
- [27] Monia Chaabane, Hatem Mhiri, Philippe Bournot, Thermal performance of an integrated collector storage solar water heater (ICSSWH) with phase change materials (PCM), Energy Conversion and Management, vol 78, pp. 897–903, 2014.
- [28] Saw Chun Lin, Hussain H. Al-Kayiem, Mohd Shiraz Bin Aris, Experimental investigation on the performance enhancement of integrated PCM-flat solar collector, Journal of Applied Science, vol. 12, issue 23, pp. 2390-2396, 2012.
- [29] Yoram L. Shabtay, John R.H. Black, Compact hot water storage systems combining copper tube with high conductivity graphite and phase change materials, Energy procedia, vol. 48, pp. 423 - 430, 2014.
- [30] Alvaro Camops-Celador, Gonzalo Diarce, Jon Ter\_es Zubiaga, Tatyana V. Bandos, Ane M. García-Romero, L.M. L\_opez, Jos\_e M. Sala, Design of a finned plate latent heat thermal energy storage system for domestic application, Energy Procedia, vol. 48, pp. 300 – 308, 2014.
- [31] Dan Nchelatebe Nkwetta, Pierre-Edouard Vouillamoz, Fariborz Haghighat, Mohamed El-Mankibi, Alain Moreau, Ahmed Daoud, Impact of phase change materials types and positioning on hot water tank thermal performance: using measured water demand profile, Applied Thermal Engineering, vol. 67, pp. 460 – 468, 2014.
- [32] Esen M, Esen H. Experimental investigation of a two-phase closed thermo-syphon solar water heater. Solar Energy, vol. 79, pp. 459–68, 2005.
- [33] M. Sridharan, N. Prasanna, E. SivaPrakash, R. Varadha Rajan, Experimental Investigation on Series Solar Flat Plate Collectors with Variable Mass Flow Rates, International Journal of Innovative Research in Science, Engineering and Technology, Vol. 3, Special Issue 3, pp-1150-1154, March 2014.
- [34] P.Sivakumar, W.Christ Raj, M.Sridharan and N.Jayamalathi, "Performance Comparison of Differently Configured Solar Water Heaters" European Journal of Scientific Research, Vol. 91 issue 1,pp.23-31, November, 2012.
- [35] Rusel . D . Salem , Aqeel . Y . Hashim , Jassim . M . AL-Asadi, Comparison between Different Designs of Solar Collector in Basrah City, IOSR Journal of Applied Physics (IOSR-JAP), Vol. 7, Issue 2 Ver. II, pp 26-32, Mar.- Apr. 2015.
- [36] Mustafa Adil, Osama Ibrahim, Zainalabdeen Hussein, Kaleid Waleed, Experimental Investigation of SAHs Solar Dryers with Zigzag Aluminum Cans, International Journal of Energy and Power Engineering, vol. 4, issue 5, pp. 240-247, 2015.
- [37] Yao-Hua Zhao, Fei-Long Zou, Yan-Hua Diao, Zhen-Hua Quan, Experimental Investigation of a New Flat Plate Solar Heat Collector by Micro Heat Pipe Array, Proceedings of the 14th International Heat Transfer Conference IHTC 14 August 8-13, 2010, Washington, DC, USA.
- [38] Hussein, H.M.S., M.A. Mohamad, A.S.El-Asfouri, Theoretical analysis of laminar-film condensation heat transfer inside inclined wickless heat pipes flat-plate solar collector, Renewable Energy, vol. 23, issue 3-4, pp. 525-535, March 2001.
- [39] Hussein, H.M.S., Theoretical and experimental investigation of wickless heat pipes flat plate solar collector with cross flow heat exchanger, Energy Conversion and Management, vol. 48, pp. 1266-1272, 2007.
- [40] Hussein, H.M.S., Performance of wickless heat pipe flat plate solar collectors having different pipes cross sections geometries and filling ratios, Energy Conversion and Management, vol. 47, pp. 1539-1549, 2006.
- [41] Rittidech, S., Wannapakne, S., Experimental study of the performance of a solar collector by closed-end oscillating heat pipe(CEOHP), Applied Thermal Engineering, vol. 27, pp. 1978-1985, 2007.
- [42] Mathioulakis, E., Belessiotis, V., A new heat-pipe type solar domestic hot water system. Solar Energy, vol. 72, pp 13-20, 2002.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

- [43] Esen, M., Yuksel, T., Performance of thermosyphon flat plate solar collector with heat pipes, Firat University Journal of Science and Engineering, vol.12, pp. 201-207, 2000.
- [44] S. M. Thompson, H. B. Ma, R. A. Winholtz, C. Wilson, Experimental Investigation of Miniature Three-Dimensional Flat-Plate Oscillating Heat Pipe, Journal of Heat Transfer, Vol. 131, issue 4, pp. 1-9, Feb 2009.
- [45] K.G.T. Hollands, B.A. Stedman, Optimization of an absorber plate fin having a step change in local thickness, Solar Energy, vol. 49, pp. 493–495, 1992.
- [46] Balaram Kundu, Performance analysis and optimization of absorber plates of different geometry for a flat-plate solar collector: a comparative study, Applied Thermal Engineering, vol. 22, pp. 999–1012, 2002.
- [47] Alok Kumar, "Performance of Solar Flat plate by using Semi- Circular Cross Sectional Tube" International Journal of Engineering Research and General Science, Vol. 2, Issue 2, pp. 33-37, Feb-Mar 2014.
- [48] Dattatray D.Chincholkarl P. R. Kulkarni, Performance Improvement of Solar Flat Plate Collector using Formed Tubes, IJSRD International Journal for Scientific Research & Development, Vol. 4, Issue 02, pp. 32-33, 2016.
- [49] Rahul.D.Gorle, Vipin.B.Nanhe, Mayuri.M.Wandhare, Performance Analysis of Flat Plate Solar Water Collector using Trapezoidal shape and Semicircular Tubes, International Journal for Research in Applied Science & Engineering Technology (IJRASET), Vol. 4 Issue VIII, pp-278-284, August 2016.
- [50] Nandurkar, Y.Y. and Shelke R.S. "Performance and analysis of ISI flat plate collector with modified flat plate collector" International Journal of Engineering Science and Technology, Vol-4, page 944-946, 2012.
- [51] Chandresh Sharma, Rajendra Karwa, Experimental Study on an Enhanced Performance Solar Water Heater, International Journal of Computer Applications, NCATAS, pp-20-25, 2014.
- [52] Chandresh Sharma and Rajendra Karwa, "Flow visualization studies for low Reynolds number laminar flow in a smooth tube with twisted tape inserts, Proceeding of National Conf. on Innovative Development in Next Decade, Challenges, Issues & Solutions, Jodhpur National University, Jodhpur, Feb. 11-12, 2011.
- [53] Bharadwaj P., Khondge A.D. and Date A.W., Heat transfer and pressure drop in a spirally grooved tube with twisted tape insert, International Journal of Heat and Mass Transfer, vol. 52, issue 7-8, pp. 1938-1944, 2009.
- [54] L. Wang, and B. Sunden, "Performance comparison of some tube inserts", International Communication in Heat Transfer, vol. 29, pp. 45–56, 2002.
- [55] Kumar and B.N. Prasad, Investigation of twisted tape inserted solar water heaters-heat transfer, friction factor and thermal performance results, Renewable Energy, vol. 19, issue 3, pp. 379-398, 2000.
- [56] M.M. Abu-Khader, Further understanding of twisted tape effects as tube insert for heat transfer enhancement, International Journal of Heat and Mass Transfer, vol. 43, pp. 123-134, 2006.
- [57] A.G. Patil, Laminar flow heat transfer and pressure drop characteristics of power law fluids inside tubes with varying width twisted tape inserts, Journal of Heat Transfer, vol. 122, pp. 143-149, 2000.
- [58] S.W. Chang, T.L. Yang and J.S. Liou, Heat transfer and pressure drop in tube with broken twisted tape inserts, Experimental Thermal and Fluid Science, vol. 32(2), pp. 489-501, 2007.
- [59] S Jaisankar, T.K. Radha Krishnan and K.N. Sheeba, Studies on heat transfer and friction factor characteristics of thermosyphon solar water heating system with helical twisted tapes, Energy, vol. 34, issue 9, pp. 1054-1064, may 2009.
- [60] S Jaisankar, T.K. RadhaKrishnan and K.N. Sheeba, Experimental studies on heat transfer and friction factor characteristics of thermosyphon solar water heater system fitted with spacer at trailing edge of twisted tapes, Applied Thermal Engineering, vol. 29, issue 5-6, pp. 1224-1231, 2009. (doi:10.1016/j.applthermaleng.2008.06.009)
- [61] S. Jaisankar, T.K. RadhaKrishnan, K.N. Sheeba and S. Suresh, Experimental investigation of heat transfer and friction factor characteristics of thermosyphon solar water heater system fitted with spacer at trailing edge of left-right twisted tapes, Energy Conversion and Management, vol. 29(5-6), pp. 2638-2649, 2009.
- [62] S. Jaisankar, T.K. Radhakrishnan, K.N. Sheeba, Experimental studies on heat transfer and thermal performance characteristics of thermosyphon solar water heating system with helical and Left–Right twisted tapes, Energy Conversion and Management, vol. 52, pp. 2048–2055, 2011.
- [63] Varun a, M.O.Garg, HimanshuNautiyal, SourabhKhurana, M.K.Shukla, Heat transfer augmentation using twisted tape inserts: A review, Renewable and Sustainable Energy Reviews, vol. 63, pp.193–225, 2016.
- [64] Zhang X, Liu Z, Liu W. Numerical studies on heat transfer and flow characteristics for laminar flow in a tube with multiple regularly spaced twisted tapes. International Journal of Thermal Science, vol. 58, pp. 157–167, 2012.
- [65] Sharma K V, Syam Sundar L, Sarma P K. Estimation of heat transfer coefficient and friction factor in the transition flow with low volume concentration of Al2O3 nanofluid flowing in a circular tube and with twisted tape insert. International Communication in Heat and Mass Transfer, vol. 36, pp. 503–507, 2009.
- [66] Ladjevardi, S.M., Asnaghi, A., Izadkhast, P.S., Kashani, A.H., Applicability of graphite nano fluids in direct solar energy absorption. Solar Energy, vol. 94, pp. 327–334, 2013.
- [67] Lenert, A., Wang, E.N., Optimization of nano fluid volumetric receivers for solar thermal energy conversion. Solar Energy, vol. 86, issue 1, pp. 253–265, 2012.
- [68] Phelan, P., Otanicar, T., Taylor, R., Tyagi, H., Trends and opportunities in direct-absorption solar thermal collectors. Journal of Thermal Science Engineering Application. Vol. 5, issue 2, pp. 1-9, 2013.
- [69] Sani, E., Barison, S., Pagura, C., Mercatelli, L., Sansoni, P., Fontani, D., Francini, F., Carbon nano horns-based nano fluids as direct sunlight absorbers. Optics Express, vol. 18, issue 5, pp. 5179-5187, 2010.
- [70] Wail Sami Sarsam, S.N. Kazi, A. Badarudin, A review of studies on using nanofluids in flat-plate solar collectors, Solar Energy, vol. 122, pp. 1245–1265, 2015.
- [71] Abdin, Z., Alim, M.A., Saidur, R., Islam, M.R., Rashmi, W., Mekhilef, S., Wadi, A., Solar energy harvesting with the application of nanotechnology. Renewable and Sustainable Energy Reviews, Vol. 26, pp. 837–852, 2013.
- [72] Javadi, F.S., Saidur, R., Kamali sarvestani, M., Investigating performance improvement of solar collectors by using nanofluids. Renewable Sustainable Energy Review, vol. 28, pp. 232–245, 2013.
- [73] Mahian, O., Kianifar, A., Kalogirou, S.A., Pop, I., Wongwises, S., A review of the applications of nanofluids in solar energy. International Journal of Heat and Mass Transfer. Vol. 57, issue 2, pp. 582–594, 2013.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 6.887

Volume 6 Issue V, May 2018- Available at www.ijraset.com

- [74] Madni, I., Hwang, C.-Y., Park, S.-D., Choa, Y.-H., Kim, H.-T., Mixed surfactant system for stable suspension of multi walled carbon nanotubes. Colloids Surface, vol. 358 issue 1–3, pp. 101–107, 2010. <u>http://dx.doi.org/10.1016/j.colsurfa.2010.01.030</u>.
- [75] Ghadimi, A., Metselaar, I.H., The influence of surfactant and ultrasonic processing on improvement of stability, thermal conductivity and viscosity of titania nanofluid. Experimental Thermal Fluid Science. vol. 51, pp. 1–9, 2013.<u>http://dx.doi.org/10.1016/j.expthermflusci.2013.06.001</u>.
- [76] Yousefi, T., Veisy, F., Shojaeizadeh, E., Zinadini, S., An experimental investigation on the effect of MWCNT-H2O nanofluidon the efficiency of flat-plate solar collectors. Experimental Thermal Fluid Science, vol. 39, pp. 207–212, 2012. <u>http://dx.doi.org/10.1016/j.expthermflusci.2012.01.025</u>.
- [77] Yousefi, T., Veysi, F., Shojaeizadeh, E., Zinadini, S., An experimental investigation on the effect of Al2O3–H2O nanofluid on the efficiency of flat-plate solar collectors. Renewable Energy, vol. 39, issue 1,pp. 293–298, 2012. <u>http://dx.doi.org/10.1016/j.renene.2011.08.056</u>.
- [78] J. Hirunlabh, P. Chantawong, Dr P. Yodovard & Dr J. Khedari (2001) A simple low-cost solar water heater, International Journal of Ambient Energy, vol. 22, issue 4, pp. 171-180, 2001 DOI: 10.1080/01430750.2001.9674856.
- [79] D.A. Siqueira\*, L.G.M. Vieira, J.J.R. Damasceno, Analysis and performance of a low-cost solar heater, Renewable Energy, vol. 36, pp. 2538-2546, 2011.
- [80] R.S. Gill, Sukhmeet Singh, Parm Pal Singh, Low cost solar air heater, Energy Conversion and Management, vol. 57, pp. 131–142, 2012.
- [81] E.H. Mathews, P.B. Taylor, M. Kleingeld, L. O'Riordan, Chapter 205 A new Concept Low-Cost Solar Water Heater, World Renewable Energy Congress VI, Renewables: The Energy for the 21st Century World Renewable Energy Congress VI 1–7 July 2000 Brighton, UK, Pages 1015–1018.
- [82] R.L. Shrivastava, Vinod Kumar, S.P. Untawale, Modeling and simulation of solar water heater: A TRNSYS perspective, Renewable and Sustainable Energy Reviews, vol. 67, pp. 126–143, 2017.











45.98



IMPACT FACTOR: 7.129







# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24\*7 Support on Whatsapp)