



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 7 Issue: V Month of publication: May 2019

DOI: https://doi.org/10.22214/ijraset.2019.5687

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



Dynamic Hand Gesture Recognition

Prajakta Wankhede¹, Prof. Nakul Nagpal², Prof. Anil Bawaskar³, Guide, ¹PG Student, Department of Electronics and Telecomm Engg, VLSI, JIT, Nagpur ²Project Guide, Assistant Professor, Dept of E&TC Engg, VLSI, JIT, Nagpur ³Co-Guide, Assistant Professor, Dept of E&TC Engg, VLSI, JIT, Nagpur

Abstract: This paper intends to supply an summary on the subject of Human Computer Interaction (HCI), also sometimes referred as Man Machine Interaction or MMI. We will be discussing concerning basic definition and a short history concerning the origin of HCI. In the later sections, discussions will be made on existing technologies in HCI and their developments. In the end, we also intend to discuss about the future directions in HCI. Keywords: Dynamic Gesture Recognition, Static, Dynamic.

I. INTRODUCTION

Gesture is a few purposeful expression created by body elements to be communicated to others. It is a non-verbal communication which is the only way for physically challenged especially hearing-impaired people. Gesture recognition is that the method by that the expression or gesture created by the user area unit recognized by the receiver. Today, laptop and computer-based devices area unit influencing human's life in each step. Gesture, as a media in human-computer interaction (HCI) makes the globe a lot of easy and versatile. Moreover, applications of gesture recognition can be found in diversed areas like medicine, education, sports, dance, etc.

The approach of gesture recognition are often glove-based and vision-based. In glove-based approach of gesture recognition, the user needs to wear a tool and carry a load of cables connecting the device to a laptop. Though the vision-based approach destitute of these issues, it's several alternative challenges. For example, the complicated and untidy backgrounds, dynamic lighting conditions and a deformable human hand shape, wrong object extraction can cause a machine to misunderstand the gesture . The gestures are often generally classified into the subsequent teams that area unit shown in Table one .

Sr.No	Example	Gesture type
1	Hand and arm gestures	Recognition of hand poses, sign languages, and entertainment applications.
2	Head and face gestures	Nodding or shaking of head, direction of eye gaze, raising eyebrows, opening mouth to speak, winking, flaring the nostrils, looks of surprise, anger, sadness, etc.
3	Body gestures	Analyzing movements of a dancer for generating matching music and graphics, recognizing human gaits for medical rehabilitation and athletic training.

Presently, vision primarily based hand gesture recognition has become a extremely developing analysis field for the aim of human laptop interaction. Such recognition systems area unit deployed to function a replacement for the usually used human-machine interactive (HCI) devices like keyboard, mouse, joystick etc. in real world situations. Recently, gestures became a vital phase of such HCI devices.



Gesture could also be outlined as a physical movement of body elements like hands, arms, head, face etc. to express some data or



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue V, May 2019- Available at www.ijraset.com

feelings (Murthy & Jadon, 2009). Gestures play an important role in our day to day communication. The ability of a laptop or any process system to grasp the which means of

these gestures is referred to as gesture recognition. Among the various types of gestures, hand gestures are the foremost usually used, as they're natural, easy to use and more convenient for communication .Hand gestures area unit primarily of 2 types- static and dynamic (as shown in Figure 1). Static hand gestures do not involve any reasonably hand movement as compared to dynamic hand gestures, where either the entire hand moves (global motion) or solely the fingers move (local motion) (Ahmeda, Alexanderb, & Anagnostopoulos, 2008).There are a unit principally 2 approaches of hand gesture recognition: glove-based and vision-based. In glove based method, the user must wear a detector glove or a coloured glove, which serves as an interface to communicate with the computer. Although, this approach provides correct results, it affects the ease and naturalness with that the user interacts with the pc. Vision-based approach overcomes the drawback of glove primarily based approach because it is a natural suggests that of interaction. This method adopts computer vision and machine learning algorithms for recognizing the hand gestures. However, obtaining highly correct results may be a difficult task for vision primarily based approaches (Rautaray & Agarwal, 2012).

II. APPROACHES OF GESTURE RECOGNITION

The approaches of gesture recognition are often generally classified into 2 groups:

A. Glove-based Approaches

In this approach, the user needs to wear a glove which employs mechanical or optical sensors attached to it that transforms finger or flexions into electrical signals to determine the hand posture . A unitard is needed to wear for body gesture recognition. The user must carry a load of cables that connect the device to a laptop that hinders the benefit and naturalness of the user interaction in laptop controlled surroundings. Some of the analysis works during this approach are often found in .

B. Vision-based Approaches

Vision-based approaches area unit a lot of easy and don't need any additional devices for analyzing gestures. It is the most natural way of user interaction as human perceives information from their surroundings. The ways beneath this approach wear down some properties like texture and colour for analyzing gesture; whereas chase devices cannot. In this technique the input pictures or videos area unit captured by exploitation camera(s). Although these ways area unit straightforward however a great deal of challenges area unit concerned like the complicated background, lighting variation, noisy videos, besides system requirements such as recognition time, robustness, and computational efficiency.

III. VISION - BASED DYNAMIC GESTURE RECOGNITION

A dynamic gesture are often accepted by 3 distinct motion phases preparation, stroke and retraction. The stroke is the salient gestural movement. The preparation section orients the body elements for the stroke and also the retraction section returns it to rest or orients for consequent gestural stroke. The stroke is differentiable from the opposite 2 phases in rate and acceleration. Here totally different approaches of dynamic hand gesture recognition and full body gesture recognition area unit mentioned.

A. Hand and Arm Gesture Recognition

Vision based hand motion acknowledgment methodologies can be gathered into: 3D Model Based methodologies and Appearance Based methodologies.

1) 3D Model based Approaches : Demonstrate based methodologies utilize some hand parameters like, palm present, joint points from the info picture, and make 2D projection from 3D hand models . Display based methodologies , gauge the present hand state by coordinating a 3D hand model to the watched picture highlights. The trouble of this methodology is in highlight extraction since human hands are surface less and don't give solid edges inside . 3D Models can be grouped into volumetric and skeletal models. Volumetric models manage 3D visual appearance of human hand and generally utilized continuously applications. The fundamental issue with this demonstrating system is that it manages every one of the parameters of hand which are of enormous dimensionality. Skeletal models beat this issue of volumetric hand parameters models by constraining the arrangement of parameters in demonstrating hand shapes from 3D structures .

2) Appearance based Approaches : In these methodologies which are otherwise called View-Based Approaches, hand picture is remade utilizing highlights removed from visual appearance of the info picture. It shows the hand utilizing the power of 2D



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue V, May 2019- Available at www.ijraset.com

pictures and contrasts these displayed highlights and highlights separated from info camera(s) or video input. The challenges of 3D demonstrate based methodologies can be overwhelmed by utilizing appearance based methodologies .

Table 2 outlines the highlights extricated, following techniques, acknowledgment strategies and their confinements in their application territories.

A strategy for online motion acknowledgment frameworks is depicted in . It is a HMM-based technique that performed well for disconnected signal however not for constant motion acknowledgment. It can't section the signals consequently.

Hand motion acknowledgment has an incredible effect in the area of robot control. In they have exhibited a quick and basic calculation for hand signal acknowledgment for robot control application. The calculation is invariant to interpretation, turn and size of the hand. Be that as it may, they have considered a constrained arrangement of motions. In their acknowledgment system is a blend of static shape acknowledgment utilizing Contour Discriminant Analysis, Kalman channel based following and HMM-based transient portrayal conspire. The following rate is around 20 fps (outline every second) and the total framework works at 25 fps. This strategy can naturally fragment the begin and end of nonstop signal. Yet, it can't deal with the nonstop misshapening of hand shapes portrays a technique for directing a robot utilizing hand motion from a separation, in view of 2D skeleton portrayal of the hand and introduction histogram. Nearby introduction histogram is processed for static hand motion acknowledgment and dynamic mark is figured for each motion for dynamic motion acknowledgment. Ordinary layout coordinating strategy is utilized for grouping. This technique is reasonable for constrained arrangement of letters in order uniform foundation.

An expansive group of writing is done in the area of communication through signing acknowledgment where hand motion acknowledgment is powerful. [31] presents a dynamic hand motion acknowledgment technique that utilizes Dynamic Bayesian Network (DBN) display. This technique functions admirably for disengaged motions contrasted with ceaseless motions. perceives Taiwan communication through signing utilizing item HMM for acknowledgment. In this strategy there is no proper fixed edge to recognize non-sign fragments. In they propose a framework for perceiving 3D dynamic indications of Indian Sign Language (ISL). They have utilized Kinect camera for catching 3D dynamic motions of ISL words. In this technique, highlights are separated from the signs and changed over to the planned literary structure. This technique coordinates both nearby just as worldwide data of the dynamic sign. Utilizing the idea of Axis of Least Inertia (ALI), another direction based element extraction technique has been created. The outcome has demonstrated that execution of the framework has been improved as incorporating the nearby highlights with the worldwide. A work on communication through signing acknowledgment is exhibited in that utilization Dynamic Time Wrapping for motion acknowledgment. The framework has a confinement that it is fit for distinguishing the motions which doesn't include explicit finger developments. proposed a constant hand motion acknowledgment calculation which at the same time partition the persistent signals into disconnected motions and remember them. They have not thought about any limited suppositions for the movement of the hand between the disconnected motions. Deciding the outskirts for disconnected motions in consistent signal acknowledgment is a testing assignment. This work can without much of a stretch play out the undertaking. Division and acknowledgment of persistent motions are done all the while. Their test results demonstrated an acknowledgment rate of 91.3% for incoherent motions and 90.4% for nonstop signals. In this strategy, mistake sources can be seeing point of camera, lighting condition, distinctive apparel for clients, and so forth.

A great deal of work has been completed for dynamic hand signal acknowledgment basically for HCI applications. An imaginative strategy for dynamic signal acknowledgment is to change over the acknowledgment of dynamic motions to the combination of static edge pictures. This technique contains two stages: Firstly, they join outline combination with thickness dissemination highlights for harsh signal acknowledgment and furthermore second, the hausdorff separation or fingertip location is utilized for exact motion acknowledgment. The acknowledgment rate is above 90% from their trial. proposes a hearty framework for dynamic.

signal acknowledgment. In the initial step hand is identified in each picture outline acquired from USB camera, through skin division and hand highlight extraction. YCrCb shading space is utilized for hand area division and recognized by identifying the quantity of fingers. At that point, for hand following the calculation dependent on oval fitting and movement highlight is utilized. At long last, they have built up a calculation for direction acknowledgment. The dynamic motion acknowledgment technique proposed by can deal with signals of four sorts: realistic motion, figure motion, character motion and activity motion. This is a HMM-based technique to perceive complex courageous motion. Including the new highlights, hand size and hand shape, increasingly complex signals can be perceived. The proposed state-based spotting calculation can isolate the nonstop signals successfully. The all out acknowledgment rate is 96.67%. Another HMM-based programmed dynamic signal acknowledgment framework is proposed by. In this strategy, the client's hand is identified utilizing Adaboost calculation with (Histograms of Gradient) HOG highlights. After hand location the hand shading model is refreshed which will be utilized close by following. They have executed a form based hand tracker. Highlights are separated after the direction is acquired from the following calculation. These highlights are utilized to figure the likelihood of each signal sort with HMM. Vision-based powerful hand signal acknowledgment is as yet a testing errand and there is extension in different application spaces.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue V, May 2019- Available at www.ijraset.com

B. Full Body Gesture Recognition

Full body signal acknowledgment has a wide scope of uses in games, mechanical autonomy, tolerant checking, move and so on. Since human body is profoundly explained in nature, it is exceptionally hard to perceive full body motions from video. From the writing review it is discovered that chips away at full body signal acknowledgment are relatively not as much as hand motion acknowledgment. Table 3 outlines a few strategies for full body motion acknowledgment alongside their specific application. A view-invariant signal acknowledgment system utilizing voxel information acquired through visual structure recreation from various cameras is introduced in. View-invariant posture descriptors are extricated utilizing multilinear investigation. Signals are then treated as arrangements of posture descriptors and HMM are utilized for motion acknowledgment. The acknowledgment rate is useful for secluded signals. In a view-invariant video-based full body signal acknowledgment framework is proposed. Multilinear investigation is performed on the outline pictures of the static postures making up the motions by tensor disintegration and projection. The posture vectors are the contributions to the HMM for signal acknowledgment. This is the main framework that tends to full body human motion acknowledgment from video without the recuperation of body kinematics or 3D volumetric reproduction. Another viable and productive component extraction strategy is exhibited in for online human signal acknowledgment. They take care of the issue of how to consistently perceive signals from unsegmented streams and how to separate diverse styles of an equivalent motion from different sorts of motions. This strategy is pertinent in intuitive frameworks. Full body signal acknowledgment has application in the field of move. It is utilized for move signal acknowledgment, execution assessment of a move, In a methodology for move motion execution assessment of Bali conventional move is exhibited. This technique can be utilized as option of move signal acknowledgment. From the writing review it is discovered that full body dynamic signal acknowledgment has wide scope of utilizations and there is extension to work here.

IV. CONCLUSION

In this day, individuals are requesting the development of without touch innovation. The Natural User Interfaces are straightforward and simple to utilize, however extremely hard to execute.

In this paper, vision-based methodologies for dynamic motion acknowledgment systems have been inspected. This is a testing research territory and similarly a less work has been done then static signal acknowledgment till now. An agreeable outcome can be discovered just under controlled condition. Acknowledgment of dynamic motions contrasted with static signals needs more calculation. More pressure ought to be surrendered to construct a dynamic motion acknowledgment framework which gives tasteful execution. From the near examination of certain papers on powerful signal acknowledgment it is watched the extension towards this course could be motion division or motion spotting from video. Another course could be to create proficient calculation for extraction of applicable highlights and highlight determination that prompts great acknowledgment.

From the review it is seen that there is absence of appropriate dataset of dynamic signals which prevents to gauge the adequacy of the exploration contrasted with others techniques. So creating legitimate dataset could broaden examine around there.

REFERENCES

- [1]Mitra, S. and Acharya, T. 2007. Gesture recognition: A survey. Systems, Man, and Cybernetics, Part C: Applications and Reviews, IEEE Transactions on, 37(3), 311-324.
- [2] Englmeier, K-H., et al. "Virtual reality and multimedia human-computer interaction in medicine." Multimedia Signal Processing, 1998 IEEE Second Workshop on. IEEE, 1998.

[3] Thakkar, Varun, et al. "Learning Math Using Gesture." Education and e-Learning Innovations (ICEELI), 2012 International Conference on. IEEE, 2012.

[4] Takano, Kosuke, and Kin Fun Li. "Classifying sports gesture using event-based matching in a multimedia e-learning system." Advanced Information Networking and Applications Workshops (WAINA), 2012 26th International Conference on. IEEE, 2012.

[5] Nussipbekov, A. K., E. N. Amirgaliyev, and Minsoo Hahn. "Kazakh Traditional Dance Gesture Recognition." Journal of Physics: Conference Series. Vol. 495. No. 1. IOP Publishing, 2014.

[6] James, Jodi, et al. "Movement-based interactive dance performance." Proceedings of the 14th annual ACM international conference on Multimedia. ACM, 2006.

[7] Thomas, M. C., and Pradeepa, A. P. M. S. 2014. A COMPREHENSIVE REVIEW ON VISION BASED HAND GESTURE RECOGNITION TECHNOLOGY.

International Journal, 2(1).

- [8] Pavlovic, V., Sharma, R., and Huang, T. S. 1997. Visual interpretation of hand gestures for human-computer interaction: A review. Pattern Analysis and Machine Intelligence, IEEE Transactions on, 19(7), 677-695.
- [9] Li, X. 2003. Gesture recognition based on fuzzy C-Means clustering algorithm. Department Of Computer Science The University Of Tennessee Knoxville.

[10] Quek, F. 1994. Toward a vision-based hand gesture interface. InVirtual Reality Software and Technology Conference (pp. 17-29).

- [11] Moeslund, T. B., and Granum, E. 2001. A survey of computer vision-based human motion capture. Computer vision and image understanding, 81(3), 231-268.
- [12] Yu, S., et al. "Vision-based continuous sign language recognition using product HMM." Pattern Recognition (ACPR), 2011 First Asian Conference on. IEEE, 2011.
- [13] Yang, Z., et al. "Dynamic hand gesture recognition using hidden Markov models." Computer Science & Education (ICCSE), 2012 7th International Conference on. IEEE, 2012.
- [14] Rautaray, S. S., and Agrawal, A. 2012. Real time hand gesture recognition system for dynamic applications. Int J UbiComp, 3(1), 21-31.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)