



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 7 Issue: VI Month of publication: June 2019

DOI: http://doi.org/10.22214/ijraset.2019.6220

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



IOT based Biometric Finger Print Electronic Voting System for Rigging Free Governance

Pushpalata¹, Revati G²

¹PG Student, VLSI & ES, Sharnbasva University, Kalaburagi, Karnataka ²Asst. Professor, ECE, Sharnbasva University, Kalaburagi, Karnataka

Abstract: Biometric Fingerprint systems are used in the Voting machine for voter confirmation. fingerprint voting machine is designed where there is no need for the user to carry his ID which contains his essential details, so that the controller fetches the data from the fingerprint module and then compares it with already registered fingerprints of the voters. If this data matches then the person is allowed to cast is vote if not then the person is barred from polling his vote. By using push buttons voting will be done, the message regarding polling booth location and serial number information send to mobile numbers before a day of voting by using GSM module. MIT application is used for outside voters this is easier application to build electronic projects. Results are displayed in LCD as well as in thinkspeak IOT platform as a graph according to the applications thinkspeak is open source IOT platform Is used to save and store data. To connect this server esp2866 Wi-Fi module is used. Keywords: Fingerprint module, Gsm Module, MIT application, IOT platform.

I. INTRODUCTION

In democratic cultures, voting is a significant means to collect and react people thinking. project offers and implements a modest and protected technique of voting by using biometric. The fingerprint data is previously stored in the database. Hence this project delivers a best result to avoid the false voting [1].

Biometric Fingerprint systems are used in the Voting machine for voter confirmation. Voting machine is designed in such a way that user need not to take any ID card while going to cast vote, every details of person will be verified by his fingerprints so when person enters in to the polling booth just need to place finger on fingerprint-module and if present fingerprint matches with stored fingerprint then person allowed to cast his vote if it not matches then person is not allowed to cast his vote. Voting will be done by using switches, the message regarding polling booth location and serial number information send to mobile numbers before a day of voting by using GSM module. MIT application is used for outside voters this is easier application to build electronic projects. Results are displayed in LCD as well as in thingspeak IOT platform as a graph, according to the applications "thingspeak" is open source IOT platform to connect this server esp2866 Wi-Fi module is used [1].

II. FUNCTIONAL BLOCK DIAGRAM AND DECRIPTION

The Functional Block diagram of the entire system is as shown in the Figure 1. The project consists of arduino microcontroller. Once the system is rigged up, the primary step is, should enroll the fingerprint, to do so press registration key then press Id key and place a finger on the fingerprint module, now the fingerprint of first person will be stored. Now if another person finger is to be enrolled, we should just increase the Id number. If the person tries to register more than one it will display already registered and even buzzer will sound, once all fingerprints are stored the next step is voting. message regarding polling booth location and serial number will be send to respected mobile number before a day of voting using GSM module. While voting start the match button so that voting period is stared. The module will ask to place finger on fingerprint module, and if a person is authorized, it will display "welcome to polling booth user allowed for voting" he is allowed to vote, else no. on LCD display and now can vote by pressing a switch among different parties. After he makes a vote, he will get to know whether voting is successful or not and even the candidate to whom he voted on LCD display. If unauthorized person tries to vote then buzzer will sound and also displays as "Unauthorized Person contact polling officers for registration" on LCD or if voted person tries to vote once again, it will not be considered and displays "ALREADY VOTED" and also buzzer will sound. The person who is not there in native place can also vote through MIT app, this application only runs during voting period, even if person tries to vote more then once it shows already voted in app. User is having Unique ID as well as password to cast his vote. All the time when voting is successful, message will be sent to the respected person using GSM module. Once voting completes turn off the match button and result can be immediately displayed on the LCD display even results can be seen in thingspeak IOT platform as a graph for this nodeMCU is used.





ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue VI, June 2019- Available at www.ijraset.com



Fig 1: Functional block diagram

A. Arduino Microcontroller

The Arduino Mega 2560 is a microcontroller board subject to the ATmega2560. It has 54 electronic data/yield pins (of which 15 can be used as PWM yields), 16 basic wellsprings of information, 4 UARTs (gear successive ports), a 16 MHz valuable stone oscillator, a USB affiliation, a power jack, an ICSP header, and a reset catch. It contains everything expected to help the microcontroller; basically interface it to a PC with a USB connection or power it with an AC-to-DC connector or battery to start. The Mega 2560 board is great with most shields expected for the Uno and the past sheets Duemilanove or Diecimila.

B. Fingerprint module

It is accepted with solid confirmations that each unique mark is interesting. all person has his individual fingerprints with the changeless uniqueness. Along these lines, fingerprints have been utilized for recognizable proof and criminological examination for quite a while. matchless finger consciousness acknowledgment be a be obvious among the mainly solid recognizable proof procedures. Unique mark innovation is the most generally utilized for security purposes. The Technology is in effect oftentimes utilized in criminal examination reason.

C. Node MCU ESP8266

The ESP8266 is the name of a scaled down scale controller arranged by Espressif Systems. The ESP8266 itself is an autonomous WiFi sorting out plan offering as a framework from existing littler scale controller to WiFi and is in like manner fit for running free applications. This module goes with an inborn USB connector and a rich gathering of stick outs. With a littler scale USB connect, you can interface NodeMCU dev pack to your PC and burst it with no burden, much equivalent to Arduino. It is furthermore rapidly breadboard heartfelt.

D. GSM 800L Module

A GSM module or a GP-RS module is a chip or circuit that will be used to set up correspondence between a wireless or an enrolling machine and a G-SM or GP-RS system.GS-M speaks to Global System for Mobile Communication. SIM800L is a littler than common cell module which considers GPRS transmission, sending and getting SMS and making and tolerating voice calls. Simplicity and little impression and quad band repeat support make this module perfect response for any endeavor that require long range organize. In the wake of interfacing power module boots up, examines for cell organize and login normally.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue VI, June 2019- Available at www.ijraset.com

E. MIT Android Application

It uses a graphical interface on a very basic level equivalent to Scratch and the Star Logo TNG UI, which empowers customers to migrate visual things to make an application that can continue running on Android contraptions. In making App Inventor, Google drew upon critical before research in informative handling, similarly as work done inside Google on online improvement conditions.

F. Thing-Speak (server IOT Platform)

As shown by its fashioners, "Thing-Speak is an open-source Internet of Things application and API to store and recoup data from things using the HT-TP show over the Internet or by methods for a Local Area Network. Securing data in the cloud gives straightforward access to data. Using orderly instruments can examine and picture data. In fact, even we can find out new date and envision in plots, outlines and graphs.



Fig 2: Hardware implementation of Biometric finger print based electronic voting system for rigging free governance using IOT.

III.SOFTWARE IMPLEMENTATION

Arduino is an open-source stage used for structure equipment adventures. Arduino involves both a physical programmable circuit board. The Arduino stage has ended up being well known with people basically starting with contraptions, and in light of current conditions. Not in the slightest degree like most past programmable circuit sheets, the Arduino does not require an alternate piece of hardware to stack new code onto the board – you can basically use a USB interface. Proteus 8 is best replication programming for some structures with microcontroller. It is chiefly pervasive as a result of convenience of practically every microcontrollers inside it. In the wake of recreating your circuit in Proteus 8 Software you can legitimately make PCB structure with it so it could be an across the board bundle for understudies and specialists. Sketch the schematic is exceptionally simple utilizing Proteus. You can tap the "Pick gadgets" catch and choose the ideal segment. You can draw wires by tapping on the terminal of the segment or Vcc, Ground, and so forth.

🥯 main_code Arduino 1.6.7	10 - -21		\times
File Edit Sketch Tools Help			
			9
main_code			
			^
<pre>#include<eeprom.h></eeprom.h></pre>			
<pre>#include<liquidcrystal.h></liquidcrystal.h></pre>			
LiquidCrystal 1cd (13,12,11,10,9,8);			
<pre>#include <adafruit fingerprint.h=""></adafruit></pre>			
String str="";			
uint8_t id;			
Adafruit_Fingerprint finger = Adafruit_Fingerpri	Int (See	rial);	
#define match 22			
#define enroll 24			
#define del 26			
#define up 28			
#define down 30			
#define indVote 6			
#define swl 5			~
Done Saving.			
Arduino/Genuino Meda or Meda 2560 - ATmeda25	60 (Meda)	2560) 00 1	COMS
And the ochain of the ga of the ga 2000, A the gazo	oo qalega.	cooo) on	0.01010

Fig 3: Example program in Arduino IDE



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue VI, June 2019- Available at www.ijraset.com



Fig 4: Schematic simulation of biometric fingerprint voting machine using proteus 8 tool.

IV.RESULTS

The design is implemented with embedded C and programmed using Arduino tool. The output results are as shown below.



Fig 5: LCD display of voting results



Fig 6: voting results on mobile MIT app

Figure 6 shows voting through MIT application here voter is having individual ID and password by using these two voter can cast their vote for this Wi-Fi module is used, during the voting period only this application is available.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177

Volume 7 Issue VI, June 2019- Available at www.ijraset.com



Fig 7: voting results on thingspeak IOT server

Figure 7 shows results of election in Thingspeak According to its developers, "ThingSpeak is an open-source Internet of Things application and API to store and retrieve data from things using the HTTP protocol over the Internet or via a Local Area Network. Storing data in the cloud provides easy access to data. In the form of graph results of election can be declared. Results are declared soon after the voting period completes using nodeMCU WI-FI module.

V. COCNCLUSION AND FUTURE WORK

Finger print based voting machine using Embedded system is implemented. Design is done to meet all the requirements and specifications. Software tools like Arduino IDE to do program and dump the source code into the microcontroller, Proteus 8 Professional for the schematic design have been used to develop the simulation results before realizing the hardware.

The performance of the system is more efficient. Reading the Data and verifying the information with the already stored data and perform the specified task is the main job of the microcontroller. The mechanism is controlled by the microcontroller.

The performance has been verified both in software and hardware design. The design implemented in the present work provide portability, flexibility and the data transmission are also done with low power consumption. Once the result is on the server it could be relayed on the network to various offices of the election conducting authority. Thus, project makes the result available any corner of the world in a matter of seconds IOT module is used to check the result in website online.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177

Volume 7 Issue VI, June 2019- Available at www.ijraset.com

Future enhancement lists out some missing things in the current system. It also indicates adding more features to the existing system. Following are the future enhancements which could be implemented.

- *1)* Number of candidates are increased and also interfaced with the personal computer and result could be stored in the central server and its backup could be taken on the other backend servers.
- 2) Fingerprint scanners can also be fixed in online voting for those who are voting from the App.

VI.ACKNOWLEDGMENT

"I am thankful to all the faculties of ECE department, Sharnbasva University, Kalaburagi, for their encouragement and support throughout the work

I extend my sincere gratitude to my parents and friends who directly and indirectly supported in carrying out the work"

REFERENCES

- [1] Anandaraj S P.G , Anish R scholar- "Secured Electronic Voting Machine using Biometric" IEEE Sponsored 2nd International Conference on Innovations in Information, Embedded and Communication systems (ICIIECS)2015.
- [2] R. Murali Prasad, PhD Professor Dept. of ECE Vardhaman College of Engg., Hyderabad "AADHAR based Electronic Voting Machine using Arduino" International Journal of Computer Applications (0975 – 8887) Volume 145 – No.12, July 2016
- [3] 1P.G Scholar, M. Tech (ES), Department of ECE, SVEW, Tirupati, Andhra pradesh, India 2Associate Professor, Department of ECE, SVCE, Chennai, Tamil Nadu, India – "Solar Electronic Voting Machine Using Arduino" International Journal of Scientific Research in Science, Engineering and Technology (www.ijsrset.com)
- [4] P.Tamilarasu1, S.Aadhithyan2, K.Gowthaman3, V.Hariprakash4. 1Assistant Professor, Department of Electrical and Electronics Engineering, Kongu Engineering College – "FINGERPRINT BASED ELECTRONIC VOTING MACHINE" INTERNATIONAL JOURNAL OF CURRENT ENGINEERING AND SCIENTIFIC RESEARCH (IJCESR) ISSN (PRINT): 2393-8374, (ONLINE): 2394-0697, VOLUME-5, ISSUE-2, 2018
- [5] [5] V Syam Babu, A L Siridhara, R Karthik Department of Electronics and Communication Engineering, MLR Institute of Technology, Hyderabad, India and Koppula Srinivasa Rao Department of Information Technology, MLR Institute of Technology, Hyderabad, India "USER FRIENDLY AADHAR BASED ELECTRONIC VOTING MACHINE USING ARM7" International Journal of Civil Engineering and Technology (IJCIET) Volume 8, Issue 7, July 2017
- [6] 1NIKHIL NAIR, 2ADEL JATHANNA, 3HASHMEET SINGH OBHAN, 4SHIVAM SINGH 1,2,3,4Electronics And Telecommunication Department, Fr.C.R.I.T. Vashi, Navi Mumbai "BIOMETRIC BASED VOTING MACHINE" International Journal of Exploring Emerging Trends in Engineering (IJEETE) Vol. 03, Issue 05, SEPT-OCT, 2016
- M.Sudhakar, 2B.Divya Soundarya Sai, 1Professor in ECE, 2II Year M.Tech, Dept of ECE, CMR College of Engineering & Technology, Hyderabad, TS-India.
 "Biometric System Based Electronic Voting Machine Using Arm9 Microcontroller" IOSR Journal of Electronics and Communication Engineering (IOSR-JECE) e-ISSN: 2278-2834, p-ISSN: 2278-8735. Volume 10, Issue 1, Ver. II (Jan Feb. 2015),
- [8] Prawin Angel Michael Associate Professor, EEE, Karunya University, Tamil Nadu, India "ELECTRONIC VOTING MACHINE USING ZIGBEE" IJRET: International Journal of Research in Engineering and Technology Volume: 03 Special Issue: 07 | May-2014.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)