



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 7 Issue: XI Month of publication: November 2019 DOI: http://doi.org/10.22214/ijraset.2019.11111

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Modelling and Analysis of Connecting Rod

B. Naresh¹, G. Bhagyaraj², P. Vineeth Kumar³, S. Nagendar Reddy⁴, M. Srinath⁵ ^{1, 2}Department of Mechanical Engineering, Jawaharlal Nehru Technological University, Hyderabad, India

Abstract: Connecting rod is one among the foremost necessary half in automotive engine. Connecting rod is that the link between piston and crankshaft. Which it converts reciprocatory motion of piston into motion of crankshaft. In internal engines connecting rod is mainly made of steel and aluminium alloys (for light weight and absorb high impact loads) or titanium (for higher performance engines and for higher cost). As a connecting rod is rigid, it may transmit either a push or apull and then the rod could rotate the crank through each halves of a revolution, i.e. Piston pushing and piston pulling. Earlier mechanisms, such as chains, could only pull. In a few two-stroke engines, the connecting rod is only required to push. In which it undergoes structural deformations. Thus in this project we are modelling a connecting rod in catia V5R20 design software and doing static structural analysis in ansys work bench 17.0 software.

I. INTRODUCTION

Connecting rods are widely used variety of engine. The perform of rod is to transmit the thrust of the piston to the crankshaft, and as the result the reciprocating motion of the piston is translated into rotational motion of the crankshaft. It consist of a pin –end. A shank section, and crank end .Pin end and crank end pin holes are machined to permit accurate fitting of bearings. One finish of the rod is connected to the piston by the piston pin. The other end is assembled to crankshaft. Connecting rods area unit subjected to forces generated by mass and fuel combustion .Theses two forces results in axial load and bending stresses. A rod should be capable of transmission axial tension, axial compression, and bending stress caused by the thrust and full of the piston and by centrifugal force. Finite component (FEM) Modal may be a trendy manner for fatigue analysis and estimation of the element. The prestigious element factors area unit able to modification like material cross section conditions etc. In trendy automotive combustion engine, the connecting rods area unit most commonly made from steel for production engine. But is made from aluminium or atomic number 22 for prime performance of engines of forged iron for application like motor scooters. They are not bolt mounted at either finish, so that the angle between the connecting rod and piston will modification because the rod moves up and down and rotates round the crankshaft. The big finish connects to the bearings journal on the throw rod is underneath tremendous stress from the reciprocator load diagrammatical by the piston, actually stretching and being compressed with each rotation, and the load increases to the third power with increasing engine speed .Connecting rod as shown in figure.



Fig.1 Connecting rod

II. SOFTWARES USED CATIA

CATIA was started byFrench air craft manufacturer Avian Marcel Dassault system Initially CATIA name is AN abbreviation for laptop motor-assisted 3 Dimensional Interactive Application. The French assault systems is the parent company and IBM participates in the software's and marketing, and catia is used in broad industrial sectors. Catiais basically a modelling software which is adopted by many small and large industries to make a critical designs. Most of the people works on now is CATIA V5 or fifth version which is rewriting and revision of the fourth edition. For the fifth version there area unit versions from one to twenty. For example CATIA V5 R17 it means that catia fifth edition version seventeenth wherever as years system was adopted in sixth edition. For example CATIA V6 2011 means that catia sixth edition version of year 2011.



A. CADD (Computer AIDED Design and Drafting)

CAD (Computer power-assisted Design) is that the use of laptop software package style|to style} and document a product's design method. Engineering drawing entails the employment of graphical symbols like points, lines, curves, planes and shapes. Essentially, it offers elaborated description regarding any element during a graphical form.

B. CAE (Computer AIDED Engineering)

CAD (Computer power-assisted Design) is that the use of laptop software package style to style} and document a product's design method. Engineering drawing entails the employment of graphical symbols like points, lines, curves, planes and shapes. Essentially, it offers elaborated description regarding any element during a graphical form. Associate in Nursing acceptable mathematical formulation of the underlying physics. In the post-processing part, the results are presented to the engineer for review.

C. ANSYS

ANSYS Workbench, developed by ANSYS Inc., USA is a Computer Aided Finite Element Modeling (FEM) and Finite Element Analysis (FEA) tool. In the Graphical program (GUI) of ANSYS work bench, the user can generate 3-dimensional (30) and FEA models, perform analysis and generate results of analysis. ANSYS Workbench enables you to combine the stand-alone analysis system into a project and to manage the project workflow. The ANSYS work bench platform is that the frame work upon that the industry's broadest and suite of advanced engineering simulation technology is built. An innovative project schematic view ties together the whole simulation method, guiding the user through even complex multi physics analysis with drag-and-drop simplicity. With bi-directional CAD connectivity, powerful highly-automated meshing, a project-level update mechanism, pervasive parameter management and integrated improvement tools, the ANSYS work bench platform delivers unprecedented productivity, facultative Simulation Driven Product Development.

III. METHODOLOGY

To design the connecting rod for a diesel engine so as to determine the section thickness of connecting rod.

To geometrically model the rod as per the scale generated from the method of style procedure followed.

To analyse the transient total deformation and thermal stress which is acting on material of connecting rod. To analyse the transient total deformation and thermal stress using FEA approach on material selected for study.

To plot the results for transient total deformation and thermal stress actiong on the connecting rod. Sources

Y Filter Engineering Data 🗰 Engineering Dat	ta Sources												
Toobox 💌 🕂 🗙	Enginee	eering Data Sources											
Field Variables		A					E	3	с			D	
Physical Properties	1	Data Source					1	1	Location		D	lescription	
Linear Elastic	2	🔆 Favorites								Quick access list and default items			
Hyperelastic Experimental Data	3	Granta Design Sample Materials					1	8	R	More than 100 sample da	tasheets for s	standard engineering materials, including	
Hyperelastic		44						-		polymers, metals, cerami	cs and woods	Courtesy of Granta Design.	
Chaboche Test Data	4	General Materials					. 1	1	S.	General use material sam	ples for use in	n various analyses.	
Plasticity	5	Additive Manufacturing Materials					the state	1	2	Additive manufacturing m	aterial sample	es for use in additive manufacturing analyses.	
E Creep													
🗄 Life	Outine	of Favorites										÷ 4 x	
E Strength		A	В		C	D	E		E			F	
🗄 Gasket	1	Contents of Favorites	.	Add	6	Ø			Sour	rce		Description	
Viscoelastic Test Data	2	 Material 	15	- 17									
	3	📎 Air	5	P	_	ľ	Fluid_Materials.xml						
E Shape Memory Alloy		Chi. Structural Stead				100	@ Cross	P Conneral Materials und				Fatigue Data at zero mean stress comes from	
Geomechanical	1	- Suorma steel										-110.1	
🕑 Damage	5	📎 Water Liquid	8	3			Pluid_Materials.xml						
Cohesive Zone													
Fracture Criteria	Propert	ies of Outline Row 3: Structural Steel										* ‡ X	
Custom Material Modes		and the second se	4		8		c ^						
	1	Property								Valu	e	Unit	
	2	2 Density								7850		kg m^-3	
	3	Isotropic Secant Coefficient of Thermal Expanse											
	5	Isotropic Elasticity											
	11	E Strain-Life Parameters	_										
	19	Tensile Yield Strength		2.5E+08		Pa							
	20	2 Compressive Yield Strength								2.5E+08		Pa	
	21	2 Tensie Ultimate Strength								4.6E+08		Pa	
View All / Customize	22	Compressive Ultimate Strength								0		Pa	

Fig: 2 Material library window



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue XI, Nov 2019- Available at www.ijraset.com



Fig: 3 Design modular window

IV. RESULTS AND DISCUSSIONS



Fig:4 Total deformation

From the analysis of a connection rod, the result obtained is indicating maximum deformation takes place in a connecting rod of a structural steel material (Total deformation = 0.11826 m).

A. Total Deformation



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue XI, Nov 2019- Available at www.ijraset.com







From the above graph, we can see that according to the time the deformation in the connecting rod is gradually increased.

B. Equivalent Strain



Fig:6 Strain

From the analysis of a connection rod the result obtained is indicating minimum equivalent strain takes place in a connecting rod of a structural steel material (Equivalent strain = 2.9292e-13).





From the above graph, we can see that there is increasing in strain up to some interval of time (10 sec) and then it decreases suddenly and become zero. This indicates that, the connecting rod having minimum strain.

Fig:7 Strain graph



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue XI, Nov 2019- Available at www.ijraset.com

C. Equivalent Stress



Fig:8 Stress

From the analysis of a connection rod the result obtained is indicating minimum equivalent stress takes place in a connecting rod of a structural steel material (Equivalent stress = 0.12097).



Model (A4) > Transient (A5) > Solution (A6) > Equivalent Stress

From the above graph, we can see that there is increasing in stress up to some interval of time (10 sec) and then it decreases suddenly and become zero. This indicates that, the connecting rod having minimum stress.



D. Thermal Analysis

Steady State Thermal Analysis



Fig:10 Steady state thermal



Fig: 11 Study state thermal

E. Total Heat Flux



Fig: 12 Total heat flux

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.177 Volume 7 Issue XI, Nov 2019- Available at www.ijraset.com

V. CONCLUSIONS

This study will be focus on the finite element modeling and analysis. From this project we conclude that the results obtained under transient load and temperature are as follows

Total deformation=0.11826m

Equivalent strain=2.6363e-12 Equivalent stress=0.36291pa Steady state thermal=118°C

Heat flux=34322w/m2

REFERENCES

- [1] Nagaraju K L and Chandan R, "Buckling analysis of connecting rod", IRJET ISSN 23950056, Vol 3, Issue 8, 2016, pg 1358-1361.
- [2] Akbar H Khan and Dr. Dhananjay R Dolas, "Design modeling and static structural analysis of connecting rod", IJIR ISSN 2454-1362, Vol 3, Issue 1, 2017, pg 400-408.
- [3] Mohammed Mohsin Ali H, Mohamed Haneef, "Analysis of fatigue stresses on connecting rod subjected to concentrated loads at the big end,4th International conference on material processing and characterization,2214-7853, 2015, pg 2094-2103.
- [4] Akbar H Khan and Dr. Dhananjay R Dolas, "Static structural and experimental stress analysis of connecting rod using FEA and Photoelasticity", IJIRSET ISSN 2319-8753, Vol 6, Issue 1, 2017, pg 578-585.
- [5] Mohd Nawajish, Mohd Naimuddin, Mayank, "A comparative study and analysis of connecting rod", IJETMAS ISSN 2349-4476, Vol 3, Issue Special, 2015, pg 332-338.
- [6] Suraj Pal, Sunil Kumar, "Design evaluation and optimization of connecting rod using FEM", IJEMR ISSN 2250-0758, Vol 2, Issue 6, 2012, pg 21-25
- [7] Ram Bansal, "Dynamic simulation of a connecting rod made of Al|metal} alloy victimization finite element analysis approach", IOSR-JMCE ISSN 2278-1684, Vol 5, Issue 2, 2013, pg 01-05.
- [8] C. Juarez, F. Rumiche, A. Rozas, J.Cuisane, P. lean, "Failure analysis of a diesel generator connecting rod", Case studies in engineering analysis 7, 2016, pg 24-31.
- Kuldeep B, ArunL.R., Mohammed Faheem, "Analysis and optimization of connecting rod using ALFASiC composites", IJIRSET ISSN 2319-8753, Vol 2, Issue 6, 2013, pg 2480-2487.
- [10] K. Sudershn Kumar, DR. Tirupathi Reddy, Syed Altaf Hussain, "Modeling and analysis of two wheeler connecting rod", IJMER ISSN 2249-6645, Vol 2, Issue 5, 2012, pg 3367-3371.
- [11] Sharma Manoj, Shashikant, "Optimization of connecting rod with help of FEA", IJMET ISSN 0976-6359, Vol 6, Issue 7, 20115, pg 51-57.
- [12] Prof. Vivek C. Pathade, Dr.Dilip S. Ingole, "Stress analysis of I.C. Engine rod by FEM and Photoelasticity", IOSR-JMCE ISSN 2278-1684, Vol 6, Issue 1, 2013, pg 117-125.
- [13] Xiaolei Zhu, Jing Xu, Yang Liu, Bo Cen, Xiaofeng Lu, Zhuo Zeng, "Failure analysis of a failed connecting rod cap and connecting bolts of a reciprocating compressor", Engineering failure analysis, PII S1350-6307(16)30748-8, Reference EFA3027, 2017.
- [14] Shriram A. Phad and D.H. Burande, "Static and dynamic analysis of connecting rod of compressor", IJAnERD ISSN 2277-4785, Vol 3, Issue 3, 2013, pg 23-30.
- [15] Prof. Pushpendra Kumar Sharma, Borse Rajendra R., "Fatigue analysis and optimization of connecting rod using finite element analysis", IJARSE ISSN 2319-8354, Vol 1, Issue 1, 2012. [16]Professor s.karaiadiselvan cadd and analysis optimization managing director cadd Pvt.Ltd.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)