



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 8 Issue: VII Month of publication: July 2020

DOI: https://doi.org/10.22214/ijraset.2020.30454

www.ijraset.com

Call: © 08813907089 E-mail ID: ijraset@gmail.com



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429

Volume 8 Issue VII July 2020- Available at www.ijraset.com

Influence of Fire on Steel Reinforcement in R.C.C Structure

Navdeep¹, Er. Sandeep Singh²

¹PG Student, ²Assistant Professor, Civil Department, Matu Ram Institute of Engineering and Management, Rohtak, Haryana, India

Abstract: From last two decades, the construction industries had become not as effective including having traditional projects deliverance systems such as IPD, DB, DBB & CMR. Volume of wastes (human, funds, materials, as well as including time) in constructions activities are not suitably reduced due to the complication of infrastructure project. For wastes reducing proper optimize solutions and interdisciplinary teams are needed. The aim of Integrated-projects delivery (IPD) is to improve projects outcome with the help of collaborate approach by ahead concerned of all party, while Lean-constructions refer to the adjusting of the concept along with principle of the Lean-productions systems to construction for broaden values along with reduction into wastes material. So, Lean Integrated-Projects Delivery (LIPD) is the finest options as a combined collaboration alliances and malty parties agreements of IPD for accomplish combined projects aim and Wastes reducing strategy of lean for customers satisfactions, such work are act like experiments to develop wastes generation models of construction-waste for LIPD in infrastructure project of Gujarat. Sum of more than 75success factor are relate to wastes generation were identify in eight various part from the review of relate literature and interviews with field expert. The questionnairy are design based on factor identified and requirements of LIPD which are fill by 40 expert of an infrastructure-projects. AHP study is use for extracting 15 most censorious factor from sum of number of factor which were responsible of wastes generations. Factors study is use for the cross verification of result of AHP study. Interpretive-Structural-Modeling (ISM) is used for development of hierarchy based models in references of depend on and driving powers of 15 Most censorious factor. This would act as a design making support tools of projects teams of wastes reductions using LIPD. Key words: AHP, ISM, LIPD, Wastes Generations, Construction Activity, Wastes Reductions.

I. INTRODUCTION

We fight fires in every sort of building: people's homes, in high rise office buildings, factories, shops, schools, restaurants, hotels, electrical substations, sporting facilities, scout halls and museums. In all building fires, the priority is to save lives. Firefighters are trained to search a burning building, wearing breathing apparatus to protect themselves from the smoke, and rescue any occupants. In homes, this includes searching in and under beds, in cupboards or behind furniture or anywhere else where someone may have fallen or hidden. In high rise buildings and commercial premises like factories and shopping centers, firefighters work with the building fire wardens and use the fire safety systems to protect and evacuate the occupants as well as conducting search and rescue. The second priority is to save property. We aim to stop the fire spreading and then put it out as fast as possible, minimizing the damage to property. In 2001/02 we confined 65% of building fires to the object or room of origin. Once the fire is out, we assist the building owners and occupiers by salvaging furniture or other items from the damaged area, protecting them from further smoke or water damage, making sure that nothing is left smoldering and all safety hazards are identified and the premises are secure.

II. NEED OF STUDY

Concrete being the commonly and widely used material in construction, research on resistance to fire has come to light as fire is one of the serious potential risk to integrity of a structure. All over the world researchers have done research on this. With increase in temperature mechanical properties of all building materials start degrading. The behavior of reinforced concrete structure depends on its constituent materials, concrete and steel and their properties at high temperatures. Both materials showcase considerable change in physical properties, strength and stiffness after exposure to heat and some of the changes are permanent in nature.

So it becomes necessary for steel member in a structure to be safe, economical and easily applicable and not get damaged or collapsed in case of a fire incident. The yield strength of steel degrades as it is exposed to heat and is 1/3 of the strength at room temperature what it is at 600° C, to prevent this a fire resistant coating is applied which keeps steel member at lower temperature than the temperature in the structure during fire. This also depends on the distance of the steel member from centre of fire and ventilation also helps in keeping the temperature of the member at low point.

Due to increase in temperature of composite steel concrete element its yield stress, young's modulus and ultimate compressive strength are decreased which results in decrease in load bearing strength. Due to constant and prolonged exposure to fire load bearing resistance can decrease to the level that structure is collapsed.

1403



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VII July 2020- Available at www.ijraset.com

III. OBJECTIVES

To identify and rank the factor for Lean-Integrated Projects Delivery (LIPD) to reduce wastes generations. To develop ISM model for wastes generation in Lean Integrated Project Delivery (LIPD).

IV. SCOPE OF WORK

The scope of this work is restricted to infrastructure projects of Gujarat.

V. RESEARCH PLAN

No.	Activities	Time Line 2017-18									
		Aug.	Sep.	Oct.	Nov.	Dec.	Jan.	Feb.	Mar.	Apr.	May.
1	Projects Finalization										
2	Literature review										
3	Data-collection (Interview)										
4	Data-collection (Questionnaire)										
5	Data Study & Development of Models										
6	Conclusions										
7	Final-Report Preparations										
8	Reports Submissions										

REFERENCES

- [1] Journal of Sustainable Built Environment. The Gulf Organisation for Research and Development, 6(1), pp. 69 80.
- [2] Aia (2007) Integrated Project Delivery: A Guide, American Institute of Architects.
- [3] EI Asmar, M., Hanna, A.S and Loh, W. (2013) Quantifying Performance for the Integrated Project Delivery System as Compared to Established Delivery Journal of Construction Engineering and Management, 139(11), pp. 114.
- [4] Ahuja G (1996) Does it pay to be green? An empirical examination of the relationship between emissions reduction and firm performance. Bus Strategy Environ 5(1):30–37
- [5] Ahuja IPS, Khamba JS (2008) Strategies and success factors for overcoming challenges in TPM implementation in Indian manufacturing industry. J Qual Maint Eng 14(2):123–147
- [6] AlKhidir T, Zailani S (2009) Going green in supply chain towards environmental sustainability. Glob J Environ Res 3(3):246–256
- [7] Bhanot N, Rao PV, Deshmukh SG (2015) Enablers and barriers of sustainable manufacturing: results from a survey of researchers and industry professionals. Procedia CIRP 29:562–567
- [8] Bowen F, Cousins P, Lamming R, Faruk A (2001) The role of supply management capabilities in green supply. Prod Oper Manag 10(2):174-189
- [9] Carter CR, Dresner M (2001) Purchasing role in environmental management: cross-functional development of grounded theory. J Supply Chain Manag 37(3):12-26
- [10] Cheah ACH, Wong WP, Deng Q (2012) Challenges of lean manufacturing implementation: a hierarchical model. In: Proceedings of the 2012 international conference on industrial engineering and operations management, Istanbul, Turkey
- [11] Chen Y, Lai S, Wen C (2006) The influence of green innovation performance on corporate advantage in Taiwan. J Bus Ethics 67(4):331–339
- [12] Dües CM, Tan KH, Lim M (2013) Green as the new Lean: how to use lean practices as a catalyst to greening your supply chain. J Clean Prod 40:93–100
- [13] Edwards DK (1996) Practical guidelines for lean manufacturing equipment. Prod Inventory Manag J 37(2):51
- [14] Govindan K, Diabat A, Shankar KM (2014) Analyzing the drivers of green manufacturing with fuzzy approach. J Clean Prod. doi:10.1016/j.jclepro.2014.02.054
- [15] Grover S, Attri R, Dev N, Kumar D (2012) An ISM approach for modelling the enablers in the implementation of Total Productive Management (TPM). Int J Syst Assur Eng Manag 4(4):313–326



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VII July 2020- Available at www.ijraset.com

- [16] Heizer J, Render B (2006) Operations management, 8th edn. Pearson Prentice Hall, Upper Saddle River
- [17] Hemel VC, Kramer J (2002) Barriers and stimuli for eco-design in SMEs. J Clean Prod 10:439-453
- [18] Hillary R (ed) (2000) Small and medium sized enterprises and the environment: business imperatives. Greenleaf Publishing, Sheffield, pp 11-22
- [19] Jose PD (2008) Getting serious about green. Real CIO World 3(8):26-28
- [20] Kannan G, Pokharel S, Kumar SP (2009) A hybrid approaches using ISM and fuzzy TOPSIS for selection of reverse logistics provider. J Resour Conserv Recycl 54(1):28–36
- [21] King AA, Lenox MJ (2001) Does it really pay to be green? An empirical study of firm environmental and financial performance: an empirical study of firm environmental and financial performance. J Ind Ecol 5(1):105–116
- [22] Kumar N, Kumar S, Haleem A, Gahlot P (2013) Implementation lean manufacturing system: ISM approach. J Ind Eng Manag 6(4):996-1012
- [23] Kuriger GW, Chen FF (2010) Lean and green: a current state view. In IIE annual conference and proceedings, p 1. Institute of Industrial Engineers
- [24] Miller G, Pawloski J, Standridge CR (2010) A case study of lean, sustainable manufacturing. J Ind Eng Manag 3(1):11-32
- [25] Mittal V, Sangwan K (2011) Development of an interpretive structural model of obstacles to environmentally conscious technology adaptation in Indian industry. Int Conf Life Cycle Eng. doi:10.1007/978-3-642-19692-8_66

1405









45.98



IMPACT FACTOR: 7.129



IMPACT FACTOR: 7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call: 08813907089 🕓 (24*7 Support on Whatsapp)