



# **iJRASET**

International Journal For Research in  
Applied Science and Engineering Technology



---

# **INTERNATIONAL JOURNAL FOR RESEARCH**

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 8      Issue: VIII      Month of publication: August 2020**

**DOI: <https://doi.org/10.22214/ijraset.2020.30823>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call:  08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# Thermal Behavior of Ceramic Cup Filled with Coffee

Pitta Krishna Reddy<sup>1</sup>, Dr. V Sridhar Patnaik<sup>2</sup>, K. Ravindra<sup>3</sup>, U. S. Ramakanth<sup>4</sup>

<sup>1, 2, 3</sup>M. Tech Student, Department of Mechanical Engineering, #Visakha Technical Campus, Vizag, AP

<sup>4</sup>Associate Professor, Lendi Institute of Engineering and Technology, Vizianagaram, AP

**Abstract:** The goal is to predict transient thermal behavior of a ceramic cup filled of coffee. Ceramic cup with exterior temperature of 22° c is initially filled with coffee at high temperature of 45°C. 3D numerical model has been developed to understand the thermal behavior of ceramic cup, MASS71 element will be used to take into account the thermal capacitance of the coffee. The internal thermal resistance will be neglected. SURF152 element will be used for convection between coffee and cup. Transient analysis has ran for about 10 min and plotted fluid temperature evolution with time. Further approach has been modeled to get Optimized designed.

**Keywords:** ceramic, fluid temperature, transient, surf 152, mass 71

## I. INTRODUCTION

Ceramics are a solid non-metallic and inorganic substance, which can consist of metallic, non-metallic, or metallic atoms that are mainly kept in ionic or covalent bonds. Known for its brittle properties, the porcelain is solid, strong in pressure, and weak in shearing and stress. It also resists chemical corrosion and high temperatures. Ceramics are part of our daily life without realizing it; We are surrounded by it, from home and industrial building products, cutlery and the arts to medical devices and microchips. Traditionally, the raw materials used in ceramics were clay-like minerals, such as kaolinite. Recently, aluminum oxide, also known as alumina, has been widely adopted. Advanced ceramics contain materials such as silicon carbide and tungsten carbide, both of which are famous for their corrosion resistance, which makes them useful in crushing equipment and mining operations. Advanced ceramics can also be found in the medical, electrical and electronic industries. Since the raw materials are subject to depletion, the creation of artificial sand has been developed for use in ceramics. Artificial sand is an incomplete mud sand, mixed with bentonite or other clay-like materials to make it suitable for molding.

Research studies indicate that the first ceramic pieces appeared in Dolni Vestonice (Czech archaeological site) around 26,000 BC. Siberia followed in 12000 A.D. Jim, China in the year 11000 A. C. And Mesopotamia in 8000 A.D. And in Asia, the Middle East and Europe in the late Neolithic period between 7000 and 6000 BC [1-4]. Increasing the thermal efficiency of drying and releasing ceramic products plays an important role for industries that want to remain competitive in the market. (We, this work aims to assess the effect of the type and thickness of thermal insulation, applied to the outer side walls of a disconnected ceramic furnace, on heat transfer, temperature distribution in insulating materials, and the temperature of the maximum external surface and energy gain compared to the furnace without thermal insulation. All installations are based The proposed math to energy conservation, and mathematical measures are performed in Microsoft Excel Four types are tested here: thermal insulators: fiberglass, rockwool, calcium silicate and ceramic fibers The results indicate that the higher the thickness of the thermal insulation, the maximum external surface temperature decreases Energy gain increased compared to the furnace without thermal insulation, in addition to that the fiberglass is the insulation material, among the four types of ados analysis, which provides a greater increase in energy and a decrease in the maximum temperature of the outer surface [5]. In drying, a large amount of thermal energy is used to evaporate the water that was added to the part during the formation period and to provide the mechanical resistance necessary to reduce the possibility of failure during the cooking process. If the drying process is not done properly, it may cause material defects, lose productivity and increase energy consumption. According to the literature [6-15], the operating parameters that influence the drying process are temperature, relative humidity, air drying speed, time, shape, thickness, area / volume ratio, particle size, initial moisture content and properties. It is made of ceramic. After the drying stage, the molded part is exposed to high temperatures (ignition) to provide rigidity and mechanical resistance. (The burning of the ceramic materials in the furnaces must follow a predetermined firing curve. (The burning curve connects the temperature of the piece to the processing time, indicating the rate of heat transfer at which the piece must be heated. Or it cools and cools at the operating temperature at every moment of time. Figure 1 shows a typical release curve for ceramic products. For each material, there is a critical rate of heating and cooling so that if it is exceeded, it is certain that product quality losses occur.

Improving the burning curve for a particular material means knowing the critical heating and cooling rates at each temperature and type of product, and it can be defined The furnace as a structure in which the materials can be heated to high temperatures. Temperatures, that is, the equipment where the drying and burning steps of the casting part are made of ceramics, many of the equipment is made of refractory materials, which is a ceramic that is able to maintain its strength Its physical integrity is at a high level H. The temperatures (above 3000 ° C) are classified into two main groups: intermittent or continuous furnace (tunnel type) Five major stress ratios are considered (13%, 17%, 32.4%, 41%, 50% ) For experiment. The image is processed suck The sample is guided by "Adobe Photoshop CS2" and "Image J" is applied to estimate the average grain size. The annoying process was simulated with the finite element action code, ANSYS ver11.0. Al-Zinc / fly ash /SiC-supported compounds are manufactured by the vortex method using a casting path. The incorporation of fly ash the tensile properties, such as tensile and yield strength are improved. Reinforcement mechanisms to improve the properties of wear and corrosions are discussed [16-18].

## II. INTRODUCTON TO DESIGN OF COFEE CUP

Control of heat flow and temperature are important topics in chemistry and chemical engineering. Analysed the cooling curve of hot water in an insulated cup as an example of a first-order process. Although not explicitly stated, it was assumed that the hot water in the bowl loses heat to the surroundings according to a pure conduction model. In this project, we use hypothetical models and tests to show that conduction followed by convection is the correct form of hot fluid cooling in a mug. We'll start by showing that the pure conduction model predicts that the hot water in the insulated mug will cool much faster than was found experimentally. We assume that the water temperature in the bowl is T which is attached to the outer surface of the bowl is  $T_{\text{Room}}$ , room temperature. According to the law of conduction of heat in Fourier, the rate of heat flowing from the cup is equal

$$\frac{\Delta Q}{\Delta t} = mC \frac{\Delta T}{\Delta t} = -\kappa \frac{A}{d} (T - T_{\text{room}})$$

In this equation,  $\Delta Q$  is the amount of heat that flows from the cup over a short period of time,  $\Delta t$ . We use one minute intervals in our model. Thus  $\Delta t = 1.00 \text{ min} = 60.0 \text{ seconds}$ . In equation (2),  $a$  is the surface area of the cup,  $d$  is the wall thickness and the cup cover,  $m$  is the mass of the liquid in the cup,  $c$  is the specific heat capacity of that liquid and  $K$  is the thermal conductivity of the cup material. The thermal conductivity constant contains units of the second joule  $-1 \text{ m}^{-1} \text{ }^{\circ}\text{C}$ . The use of  $\kappa$  is allowed in place of  $K$  because equation (2) involves temperature differences instead of absolute temperatures.  $T$  is the temperature of the liquid in the cup, and  $T_{\text{Room}}$  is the room temperature. Again, it should be clear that the pure driving model assumes that the outer surface of the cup is at room temperature. For simplicity,  $A$  will be assumed to be the full surface area of the cup. Most of the cup comes into contact with the liquid in the cup, and heat escapes from the cup from the air area above the liquid level as well as below the liquid level. Remember that there is a lid on the cup of the same material, so there is no cooling due to evaporation. The base is not in contact with the air, but we will assume that the heat is lost here at the same rate as through the walls and ceiling. This is definitely not the case, but the space is small, so the error is small.

## III. TRANSIENT THERMAL ANALYSIS OF COFFEE CUP

This simulation project analyses the temperature distribution and heat flux of coffee mugs made of five types of ceramic materials and as two different simulation runs. A steady state heat transfer problem is simulated with convective heat transfer phenomena between coffee, coffee mug and surrounding air. The physical data of the appropriate fields have been referred from Internet and experimental data references. In this project we are chosen the low thermal conductivity ceramic materials. Surrounding temperature was maintained at  $22^{\circ}\text{C}$ , the transient condition was adopted that initial time is 1s and end time 600 s was maintained. And convection takes place on surface of the cup was given as  $25\text{W}/\text{m}^2\text{ }^{\circ}\text{C}$  as shown in Fig1.1

Table I  
Properties of the ceramic materials

Material	Thermal Conductivity $\text{W}/\text{mC}^{\circ}$	Density ( $\text{kg}/\text{cm}^3$ )
Ceramic	1.45	2000
Ceramic-1	1.4	2100
Fly ash	0.505	1000
Siliceous sand	1.36	2500
Clay (dry)	0.15	2300






Fig 1.1 shows Geometry the boundary conditions of the mug

ANSYS Parametric Design language program was developed in this project as given in the below. Fluid is used as hot coffee or tea for this volume, density and specific heat of the fluid is play a important role for this surface element on the fluid creation is needed for enhancement of the temp and heat flux.

```

1  ! Commands inserted into this file will be executed just prior to the ANSYS SOLVE command.
2  ! These commands may supersede command settings set by Workbench.
3
4  ! Active UNIT system when this object was created: Metric (m, kg, N, s, V, A)
5  ! NOTE: Any data that requires units (such as mass) is assumed to be in the consistent solver unit system.
6  ! See Solving Units in the help system for more information.
7
8
9
10
11
12
13  !*****SURF152*****
14  !find the maximum number of nodes and put it in the parameter maxnode
15  !create a node with coordinates (0,0,0) which will be the SURF152 extra node
16  !find the maximum number of element types and put it in the parameter maxtype
17  !define a SURF152 element with an element type maxtype+1
18  !change the keyoption 8 to 2 of the SURF152 element
19  !change the keyoption 5 to 1 of the SURF152 element
20  !activate the surf152 type
21
22  !select the nodes of the named selection Nodes_Fluid
23  !generate SURF152 elements on the selected nodes and specify that xnode is the extra node
24  !select all the nodes and elements
25
26  !select the SURF152 elements
27  !apply a convection with a film coefficient of 200 W.m-2.K-1
28  !select all the nodes and elements
29
30  !*****MASS71*****
31  !define a MASS71 element with an element type maxtype+2
32  !change the keyoption 3 to 1 of the MASS71 element
33
34  !parameter that defines the volume of the fluid
35  !parameter that defines the specific heat of the fluid
36  !parameter that defines the density of the fluid
37  !defining the thermal capacitance of the fluid as a real
38
39  !define a MASS71 element and connect it to the extra node of SURF152
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
```




Fig 1.3 Cooling Curves of different materials of coffee Cup and max heat flux of clay coffee cup

#### IV. TRANSIENT THERMAL ANALYSIS ON OPTIMIZED DESIGN

This simulation project analyses the temperature distribution and heat flux of coffee mugs with handle made of five types of ceramic materials and as two different simulation runs. And also an optimized model was developed to consider the ergonomics conditions of the human usage. A steady state heat transfer problem is simulated with convective heat transfer phenomena between coffee, coffee mug and surrounding air. The physical data of the appropriate fields have been referred from Internet and experimental data references. In this project we are chosen the low thermal conductivity ceramic materials. The geometry and meshed structure of the coffee mug is directly obtained from ANSYS space claim software as shown in Fig 1.4 In the x,y, and z direction lengths are taken as 0.1,0.1 and 0.12m respectively. The picture below shows the CAD geometry used for this analysis. Total number of nodes and elements on the entire body are 14758 and 7563 was meshed. Surrounding temperature was maintained at 22°C and convection takes place on surface of the cup was given as 25W/m<sup>2</sup>.°C as shown. The transient condition was adopted that initial time is 1s and end time 600 s was maintained.




Fig 1.3 geometry and meshed structure and boundary conditions

Fig 1.4 shows the max temp, heat flux and cooling curve of the ceramic and clay materials. The clay cup gives the better temp than others and the temp on the handle is 22°C ie room temp was given. For handling the clay cup with new design given the better results in the ergonomics point of view. The fly ash cup handling temp was 22.929 °C it was later better than clay cup in the ergonomics point of view.




Fig 1.4 shows the max temp, heat flux and cooling curve of the ceramic and clay materials

## V. RESULTS AND DISCUSSIONS

The 3D digital model of the ceramic cup at 220 ° C is designed filled with coffee at 450 ° C and the outer surface exposed to surrounding conditions and heat transfer due to heat load in a simulated transient for about 600 seconds. Case 2 was optimized with the handle, and the case of Case 1 was compared to each other. It was observed that the transient behavior of the ceramic cup after 10 minutes reached 400 ° C and 350 ° C min. From case 2, it has dropped to a minimum temperature of about 230 ° C. The evolution of fluid temperature is drawn taking into account mass 71 that provides a convenient means of modeling the effects of convection when the bulk temperature is unknown. Surf 152 provides additional flexibility in determining the temperature used to determine film coefficients based on temperature, surface temperature, fluid temperature, average temperature, and the absolute value of the differential temperature. Case-1 Plane Cup Results: Table II show the temp at the inner and outer surface of the plane cup and III show the directional heat flux of the cup with different materials. The results show that clay cup having good temperature distribution around the surface, after fly ash cup also gives the good temp results than other materials.

Table II

Thermal results of the different materials of the cup

Material	Temp(c <sup>0</sup> ) at inner surface	Temp(c <sup>0</sup> ) at outer surface
Ceramic	40.119	34.67
Ceramic-1	40.407	34.875
Fly ash	41.575	32.352
Siliceous sand	40.756	35.059
Clay	41.577	26.446

Table III

Directional Heat Flux of the different materials of the cup

Material	Directional Heat Flux(W/m <sup>2</sup> )
Ceramic	594.6
Ceramic-1	611.82
Fly ash	647.83
Siliceous sand	633.65
Clay	495.72

Case-2 Cup with handle (optimized) Results: Table IV shows the temp at the outer surface and temp at the handle of the optimized cup of the five different materials. The optimized clay cup gives the better temp results than others and the temp on the handle is 22°C ie room temp was given. For handling the clay cup with new design given the better results in the ergonomics point of view. The fly ash cup handling temp was 22.929 °C it was later better than clay cup in the ergonomics point of view

Table IV  
The comparison of temp

Type of Material	Temp(c°) at outer surface	Temp(c°) at handle
Ceramic	34.67	22.991
Ceramic-1	34.875	23.96
Fly ash	32.352	22.929
Siliceous sand	35.059	23.365
Clay	26.446	22




Fig 1.5 Temp at inner and outer surface of the of plane cup and temp at inner surface and at handle of the cup (new design) with different materials

Fig 1.5 the temp at the inner and outer surface of the cup with handle and show the directional heat flux of the cup with different materials. The results show that clay cup having good temperature distribution around the surface, after, fly ash cup also gives the good temp results than other materials.

## REFERENCES

- [1] P. B. Vandiver, "Venuses and wolverines: the origins of ceramic technology, ca. 26 000 B. P.," in *Ceramics and Civilization*, vol. 13, p. 5, Smithsonian, Washington, DC, USA, 1990.
- [2] P. Boch and J.-C. Niepce, *Ceramic Materials: Processes, Properties, and Applications*, ISTE Limited, Newport Beach, CA, USA, 2006.
- [3] J. Margueron, *Les Mésopotamiens*, Editions A&J Picard, Paris, France, 2003.
- [4] W. M. Kawaguti, "Study of the thermal behavior of "paulistinha" intermittent kilns used in the red ceramic industry," Master's thesis, Federal University of Santa Catarina Florianópolis, Brazil, 2004, in Portuguese.
- [5] Ricardo S. Gomez, Tu'lio R. N. Porto, Horte'ncia L. F. Magalhães, Clotildes A. L. Guedes, Elisiane S. Lima, Dannyelle M. A. Wanderley,4 and Antonio G. B. Lima, "Transient Thermal Analysis in an Intermittent Ceramic Kiln with Thermal Insulation: A Theoretical Approach", *Hindawi Advances in Materials Science and Engineering* Volume 2020, Article ID 6476723, 15 pages <https://doi.org/10.1155/2020/6476723>.
- [6] J. S. Reed, *Principles of Ceramics Processing*, Wiley, New York, NY, USA, 1995.
- [7] Y. Itaya and M. Hasatani, "R & D needs-drying of ceramics," *Drying Technology*, vol. 14, no. 6, pp. 1301–1313, 1996.
- [8] M. V. Ara'ujo, J. Delgado, and A. G. Barbosa de Lima, "On the use of CFD in thermal analysis of industrial hollow ceramic brick," *Diffusion Foundation*, vol. 10, pp. 70–82, 2016.
- [9] M. V. Ara'ujo, R. S. Santos, R. M. da Silva, and A. G. Barbosa de Lima, "Drying of industrial hollow ceramic brick: analysis of the moisture content and temperature parameters," *Defect and Diffusion Forum*, vol. 380, pp. 72–78, 2017.





- [10] M. K. T. Brito, D. B. T. Almeida, A. G. B. Lima, L. A. Rocha, E. S. Lima, and V. A. B. Oliveira, "Heat and mass transfer during drying of clay ceramic materials: a three-dimensional analytical study," *Diffusion Foundation*, vol. 10, pp. 93–106, 2016.
- [11] F. Augier, W. J. Coumans, A. Hugget, and E. F. Kaasschieter, "On the risk of cracking in clay drying," *Chemical Engineering Journal*, vol. 86, no. 1-2, pp. 133–138, 2002.
- [12] M. A. Cade, J. J. S. Nascimento, and A. G. B. Lima, "Drying of  $\gamma$  holed ceramic bricks: an approach by finite-volumes," *Matéria*, vol. 10, pp. 443–453, 2005, in Portuguese.
- [13] V. R. Batista, J. J. S. Nascimento, and A. G. B. Lima, "Drying and firing of solid and hollow ceramic bricks including dimensional variations and structural damage," *Revista Eletronica de Materiais e Processos*, vol. 3, pp. 46–61, 2008, in Portuguese.
- [14] V. R. Batista, J. J. S. Nascimento, and A. Lima, "Drying and volumetric retraction of solid and hollow ceramic bricks: a theoretical and experimental investigation," *Matéria (Rio de Janeiro)*, vol. 14, no. 4, pp. 1088–1100, 2009, in Portuguese.
- [15] J. B. Silva, G. S. Almeida, W. C. P. Barbosa de Lima, G. A. Neves, and A. G. B. de Lima, "Heat and mass diffusion
- [16] Uppada Rama Kanth, Putti Srinivasa Rao, Mallarapu Gopi Krishna, "Mechanical behaviour of fly ash/SiC particles reinforced Al-Zn alloy-based metal matrix composites fabricated by stir casting method", *Journal of Materials Research and Technology* Volume 8, Issue 1, January–March 2019, Pages 737-744.
- [17] U. S. Ramakanth & Putti. Srinivasa Rao, "Wear Behavior of Al 7075/Fa/Sic Hybrid Composites", *International Journal of Mechanical and Production Engineering Research and Development (IJMPERD)* ISSN(P): 2249-6890; ISSN(E): 2249-8001 Vol. 9, Issue 2, Apr 2019, 331-338.
- [18] U. Ramakanth & Putti. Srinivasa Rao, "Corrosion Studies on Ceramic Particulates Reinforced Hybrid Metal Matrix Composites", *International Journal of Mechanical Engineering and Technology (IJMET)* Volume 10, Issue 01, January 2019, pp. 661–666.





10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)