



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 8 Issue: VIII Month of publication: August 2020 DOI: https://doi.org/10.22214/ijraset.2020.30919

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



# **Retrofitting of Scooter using Electrical Power Pack**

Mr. Pankaj R. Beldar<sup>1</sup>

Mechanical Engineering Department, Savitribai Phule Pune University

Abstract: Mopeds that were factory-made in 2004 or before it reaching to be scrap in 2019 as RTO rule, therefore thanks to this reason we tend to modifying that in such some way that it'll run on road with zero emission. so as to sustain during this quick forward world we tend to should travel from place to position. It's important that point taking for motion ought to be less, additionally it ought to be economical and simply accessible. Taking all this into consideration, we must always shift aloof from typical fuels to renewable sources of energy. electrical mopeds plug-in electrical vehicles with 2 wheels which might be recharged from external supply of electricity provide, and also the electricity is hold on in a very reversible battery, that provides power to 1 or additional electrical motors to realize movement. The electricity is generated from associate degree external supply helps in acceleration of mopeds that causes no pollution .In This paper, we tend to victimisation recent mini-bike that having the Body and engine in it. BLDC Hub motor having the upper potency and wheel hub motor reduced size compared with brushed motor. It'll get power from Li particle and BMS. we tend to reaching to replaced engine with Wheel Hub Motor and controller and battery connected to wheel hub motor propel the vehicle. Keywords: Electrical Vehicle, Battery, Hub Motor, Scooter,

I. INTRODUCTION

To retrofit the Moped into Electrical vehicle, it requires some changes in the chassis design of old vehicle. The vehicle should be electric powered and driven with the help of a powerful dc motor. it requires new design of a special swing-arm this carries enough strength as well as is light in weight. Due to this design becomes an eco-friendly, zero emission and low-cost. To select the battery or power pack, study of the Various Battery used in Electric Vehicle should be done carefully because we nned to follow some standards while dealing with electrical vehicle.

# II. METHODOLOGY

Methodology includes Input Study- Deciding of geometry and material- Selction of motor- Selection of Controller and Bettery-Making CAD model of the vehicle- Structural analysis of the CAD model- Thermal analysis of the battery pack- Manufacturing phase- testing. Table no- 01 shows the wheel hub motor specifications selected .

Table no- 01 Wheel Hub Motor specification

		1
Sr. No.	Specification	Value
1.	Construction	Brushless Gearless Hub motor
2.	Rated Voltage (DCV)	48V
3.	Rated Power	1000W
4.	Weight	7.9 Kg
5.	Rated Efficiency	>80%
6.	Application	Electric Scooter
7.	Rim Size	10 Inch
8.	RPM At No Load	400 RPM -600RPM
9.	Tyre: F/R	3.00-10
10.	Torque	37 Nm
11.	Max Torque	72 Nm
12.	Max Carrying Capacity	200
	Sr. No.   1.   2.   3.   4.   5.   6.   7.   8.   9.   10.   11.   12.	Sr. No.Specification1.Construction2.Rated Voltage (DCV)3.Rated Power4.Weight5.Rated Efficiency6.Application7.Rim Size8.RPM At No Load9.Tyre: F/R10.Torque11.Max Torque12.Max Carrying Capacity

# A. Motor Selection



Volume 8 Issue VIII Aug 2020- Available at www.ijraset.com

- B. Cell Selection
- 1) Model:15S for 3.2V Rated LiFePO4
- 2) 15S 48V 50A bms is used for 15 series 48V battery pack
- 3) Common Version : common port for charge/discharge
- 4) constant discharge current: 50A
- 5) Charge Current: 40A
- 6) Extreme low power consumption. The consumption of the whole device is less than 50uA.

			1					
Parameter	Lead Acid	Nickel	Nickel	Nickel	Nickel	Lithium (	Zebra	Nickel
		Cadmium	Hydrogen	Metal	Zinc	Ion		Iron
				Hydride				
Specific Energy	35-50	30-60	50	60-80	70-100	80-180	90-120	50-60
(Whr/Kg)								
Specific Power	150-400	80-180	220	200-300	170-260	200-1000	130-	80-150
(W/Kg)							160	
Cell Voltage	2.1	1.2	1.4	1.2	1.6	3.05-4.2	2.58	1.2
Cycles (N)	250-1000	1000-50000	1300-6000	300-600	Upto200	3000	>500	2000
Life (Years)	5	10-15	15	2-5	-	5	-	30-50
Max. Depth of	20-80	60-80	-	-	100	100	-	80
Discharge (%)								
Self-Discharge	20-30	15	High	15-25	20	10	-	20-40
Rate / Month								
(%)								
Efficiency (%)	75-85	60-70	-	-	-	-	-	65
Operating	Poor	-40-80	-	Ambient	-	49	270-	-40-46
Temperature	Performance At			Temp.			350	
(°C)	Low Temp.							
Safety	Good	Less	-	Average	-	Average	Good	-
Recharge	8	1	15	1	2-3	2-3	8	8
Time(Hr.)								

### Table no: 02 Comparision of Batteries for the Selection

#### **III.DESIGN**

A. Powertrain Calculation Vehicle Calculations: Tyre size= 10" Coefficient of Rolling = 0.015Coefficient of drag = 0.5Air Density = 1.27 kg/m3 Frontal Area = 0.6m2For Maximum Speed Maximum Speed = 70 Kmph = 17.44 m/secWeight of the Vehicle with two people, (Gross weight)= 220kg Range= 80Km/charge @ speed of 70kmph Peak power= (Gwgt  $\times$  9.81 $\times$ V  $\times$  Cr) + (1/2  $\rho \times$ A $\times$ Cd $\times$ V3) = (220×9.81×19.44×0.015)+ (1/2 1.27×0.6×0.5×19.443) Peak power=2.028 KW (at top speed)





ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VIII Aug 2020- Available at www.ijraset.com

For Nominal Speed At speed of 50kmph (i.e., V = 13.88 m/sec) Peak power at 50kmph = 1.165 kW  $\cong 1.2 \text{ kW}$ Rolling Resistance (Rr) = 0.015× Gwgt×9.81 = 0.015×220×9.81 =32.373 N Air Drag (Ra) = $1/2 \times \rho \times A \times V2 \times Cd$  $= 1/2 \times 1.27 \times 0.6 \times 19.442 \times 0.05$ = 71.99Total Resistance = Rr+Ra= 72 + 32.373= 104.36Torque, T= 13.25 N.m  $N = (13.25*60*10^3)/(\pi *254)$ N= 996.6 RPM At Gradient Speed of the Vehicle= 25kmph Rr = 32.373 $Ra = 1/2 \times \rho \times A \times V2 \times Cd$  $= 1/2 \times 1.27 \times 0.6 \times 6.942 \times 0.5$ Ra = 9.186Gradient Force (Rg) =  $w*9.81*Sin \propto$ Gradient Angle ( $\propto$ ) =10° Rg= 374.76 N Total Resistance = = Rr+ Ra+Rg =374.76+9.186+32.373 = 416.32N Torque Required= 416.32\*0.127 = 52.87N.m B. Motor Selection

Normally, Brushless DC (BLDC) motor is used in all electric portable vehicles due to its speed torque characteristics and also it gives maximum starting torque.

Torque decreases with increasing speed so no external reduction gearbox is required. Also available in wide power ranges while not being expensive.

C. Battery

Range = 70 Km @ Speed 45Kmph Power/ Km = 1000/45 = 22.22 W.hr /Km For, 70 Km =22.22× 70 = 1555.55 W.hr Capacity of Battery Pack = 1555.55/48 = 32.40 A  $\cong$  40A Battery Pack capacity = 40A, 48V Battery pack Lithium ion 18650, Voltage = 3.7V, Current= 2.6A Series cell = 13 Parallel cell = 16 Total No. of cell = 208



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VIII Aug 2020- Available at www.ijraset.com



Figure 01: Battery Pack

D. Charger Selection
Specification of battery = 48V, 40Ah
Practically, 40% loss of current during battery charging
Then,
$Loss = 40 \times 40/100 = 16Ah$
Total current= 16+40= 56Ah
Charger 48V, 3Ah
Charging time = (total current )/(charging current )
= 56/3 = 18.66 Hr.
Charger 48V, 24Ah
Charging time = (total current )/(charging current $= 56/24 = 2.33$ Hr.
Charger 48V, 20Ah
Charging time = (total current )/(charging current )
= 56/20 = 2.8 Hr.
4.4 Heat Dissipation
The battery heat is generated in the internal resistance of each cell and all the connections.
Total no. of cell= 208
Nominal current capacity for each cell= 6000mah
Internal resistance of cell= $10m\Omega$
Power dissipated by each cell= $R \times I2$
= 10×10-3×62
P= 0.36
Total power dissipated by battery= $P \times$ Total no. of cell
$= 0.36 \times 208$
= 74.88
E. Swing Arm
Material Used
General Characteristics of 4130 Alloy Steel
1) AISI or SAE 4130 grade is a low alloy steel containing chromium and molybdenum as strengthening agents.
2) Its chemical composition is as follows:
Material iron carbon silicon chromium molybdenum manganese
4130 97% 0.81% 0.25% 0.80% 0.20% 0.80%





Figure 02: Activa Swing Arm



Figure 03: CAD model of Swing Arm

# F. Analysis of Swing Arm

Inspire software is used for the Analysis of Swing Arm. Displacement, Factor of Safety, yielding is calculated on Inspire software. Table noo- 03 represents the analysis results of swing arm.

Sr.	Result	Values
No.		
1.	Displacement	12.7 mm
2.	Stress	120.4 MPa
3.	Factor of Safety	1.08e+8
4.	Percentage of Yielding	334.12%

Table no 0	3- Analysis	Results
1 4010 110 0.	j i mai yong	results



Figure no-04 Displacement results



# International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VIII Aug 2020- Available at www.ijraset.com

G. Design Calculation for Helical Coil Spring of the Shock Absorber Material: Spring Steel (modulus of rigidity) G = 78600N/mm2 Mean diameter of a coil, D=27.375 mm Diameter of wire, d = 9.375 mmTotal no of coils, n1=17Height, h = 210mmOuter diameter of spring coil, D0 = D + d = 36.75 mmHence Square and ground end=number of active turn = (n1 - 1)=(17-2)No of active turns, n = 15Weight of bike = 118 kgLet weight of 1 person = 100 KgWeight of 2 persons =  $100 \times 2 = 200$ Kg Weight of bike + persons = 338 Kg Considering dynamic loads it will be double W = 338 Kg = 3315.78N We know that, compression of spring,  $\delta = (8WD^3 n)/(Gd^4)$ δ=(8×3315.78× [27.375] ^3×15)/(78600× [9.375] ^4) ∴ δ=23.44 mm C = spring index: D/d=36.75/9.375=3.92 Solid length, Ls =n1×d=17×9.375= 159.375 mm Free length of spring, Lf = solid length + maximum compression + clearance between adjustable coils $= 159.375 + 13.44 + (13.44 \times 0.15)$ = 174.831 mm Spring Rate=K 3315.78/13.44 =246.70 N-mm  $E=1/2 \times W \times \delta$ E = strain energy stored in spring (N-mm)E=22,282.04 N-mm Stresses in helical spring: maximum shear stress induced in the wire  $\tau = \text{Ks} \times 8\text{WD}/(\pi.d^3)$ k\_s=(4C-1)/(4C-4)+0.615/C KS = 1.41373τ=1032.39 N/ [mm]] ^2 For Series combination,  $1/k = 1/k_1 + 1/k_2$ k1 = k2 = 246.70k= 123.35 N-mm Pitch=p  $(l_f-l_s)/n_1+d$ = (174.831-159.39)/17+9.375 p = 10.28 mmCrippling load under which a spring may buckle KL = 0.1 (for hinged end spring)



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue VIII Aug 2020- Available at www.ijraset.com



Figure no- 05 Spring Analysis

# **IV.RESULTS**

After manufacturing the Vehicle, it gives Satisfactory driving experience to rider. Cost required for the retrofitting of old Activa into Electric vehicle is near about INR 22000. Average Charging cycle is for after 18 hours.

# V. CONCLUSION

It is concluded from the design and study of research papers, the motor power required for Retrofitting vehicle is much low due to less rated torque and heavy weight. The brushless DC motor is selected for this vehicle is suitable and easily available at cheaper cost. Also torque at standstill is sufficient to propel the vehicle with 150 kg weight. Selected battery type is cobalt based lithium ion battery pack. The li-on cell has maximum specific energy and Amp-hr capacity than any other type of batteries. The single cell of various capacities is easily available in market with affordable cost. The Swing arm is the most critical part and it is made up of steel with Circular cross section. It has good Strength and provide safe riding experience on bump road, so Retrofittment of this vehicle reduces cost also it reduce pollution.

# VI.ACKNOWLEDGMENT

I wish to acknowledge Mr. Raj Gaikwad, Mr.Lambodari Shrinith, Ms. Patil Bhagyashri and Ms. Ghatate Sneha for their valuable contribution for the results of this paper.

# REFERENCES

- [1] Wolfgang Gruber, Wolfgang Bäck and Wolfgang Amrhein, Design and Implementation of a Wheel Hub Motor for an Electric Scooter, 978-1-61284-247-9/11/\$26.00 ©2011 IEEE
- [2] [2] João Diogo da Cal Ramos, Front and Rear Swing Arm Design of an Electric Racing, Instituto Superior Técnico, Universidade de Lisboa, Portugal November 2016
- [3] [3] Wojciech Pawlak, Kacper Leszczyński, mechanical design and fem analysis of electric motorcycle's swing arm, on 25 June 2019.
- [4] Paper from Journals:
- [5] [4] Xiongbin Penga, Chong Maa, Akhil Garga, Nengsheng Baoa, Xiangping Liaob, Thermal performance investigation of an air-cooled lithium-ion battery pack considering the inconsistency of battery cells, 11 March 2019 1359-4311/ © 2019
- [6] [5]Tao Denga,b, Guodong Zhanga, Yan Rana, Ping Liu, Thermal performance of lithium ion battery pack by using cold plate, 05 July 2019 1359-4311/ © 2019
- [7] [6] Yinjiao Xing , Eden W. M. Ma 1, Kwok L. Tsui, and Michael Pecht, Battery Management Systems in Electric and Hybrid Vehicles, Energies 2011, 4, 1840-1857; doi:10.3390/en4111840
- [8] Paper from conference:
- [9] [7] Nur Hazima Faezaa Ismail, Simplified Heat Generation Model for Lithium ion battery used in Electric Vehicle, 5th International Conference on Mechatronics (ICOM'13) IOP Publishing IOP Conf. Series: Materials Science and Engineering 53 (2013) 012014.
- [10] [8]Guangming Liu, Analysis of the heat generation of lithium-ion battery during charging and discharging considering different influencing factors, Journal of Thermal Analysis and Calorimetry · May 2014
- [11] [9] Pavendhan R., Design and Analysis of Two Wheeler Shock Absorber Coil Spring, International Conference on Advances in Engineering and Management (ICAEM) Organized By Revo Technologies And Enterprises,2013











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24\*7 Support on Whatsapp)