



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 8 Issue: IX Month of publication: September 2020

DOI: <https://doi.org/10.22214/ijraset.2020.31489>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Optimization of Stability of Building based on Variation in Shear Wall & Concrete Grade Parameters: A Review

Zamran Khan¹, Sagar Jamle², Arvind Vishwakarma³

¹M. Tech. Scholar, Department of Civil Engineering, Oriental University, Indore (M. P.), India

^{2,3}Assistant Professor, Department of Civil Engineering, Oriental University, Indore (M. P.), India

Abstract: *As the height of building increases, stability and rigidity become more and more important factors in the structure. The project summarizes a report on the various parameters used to give stability to the building. Different researchers have used different types of changes, such as holes in shear walls, different varieties used, recycled materials in concrete, the height and thickness of the used shear walls changed, etc. Based on various studies and analyzes of the building, he came to the conclusion that the increase in stability is affected by the change in parameters. The most effective parameters are the concrete grade and the wall shear in it.*

Keywords: *Concrete grades, Optimization, Seismic analysis, Shear Wall.*

I. INTRODUCTION

Stability is an important problem in stable the structure such that it safe undee the collapse phenomenon in the building analysis. The importance of this material is that it is important in the construction of engineering, airport, nuclear engineering, marine engineering, and marine engineering and architecture. It plays an important role in some of the problems of space architecture, geotechnical structure, geophysics and science. The significance of the issue is evident from the history of the collapsed structure due to the neglect or misunderstanding of parts of the fixed structure. There are specific examples to show that this is important and appropriate for a design, ready-made. There are some example which are not with stand against the stability these examples are collapse of the Tacoma Narrows Bridge in 1940 due to aerodynamic instability and the collapse of the Quebec Bridge over St. Louis. Lawrence in 1907, but many other plagues taught important lessons; for example, the collapse of the construction of the Hartford Arena in 1978 and the design of the Post College Museum in the same year, the collapse of the steel bridge in Melbourne in a few years ago.

Concrete is basis part of any civil construction and it is the mixture of cement, sand, aggregate and water as a main parameter. It is used for the construction of multi-storey building, reservoir, on road, water tank, coastal structure, power lines. The method of selecting suitable concrete materials and determining their quantities as the requirement in concrete with the strength requirement, durability and workability when possible can be called concrete mixing designs. There are new materials used to increase the strength of the foundation based on the materials used as well as to improve the stability of the building. Some of them use recycled materials such as fly ash, silica fumes, etc. Concrete is the most undisputed and recycling equipment in development industries around the world.

Walls provide more strong and solid buildings on the side of their school, reducing the vibration of the building and reducing damage to its contents. Fences in high-intensity regions require special information. The walls and ceilings are modelled on a frame that looks good in movement against the reinforcement of building concrete. Most wall hangings have one or more open lines, which are typical examples of elevated posts, stairs, and gutters that usually pass through the entrances. The use of hedges as the mainstay of resistance to sloping surfaces and general load on apartment buildings is also common.

II. LITERATURE SURVEY

As per the theme, we listed out research paper and study has been carried out to get the optimised materials and techniques to enhance the stability of the building:-

The purpose of this study was to investigate the reduction of the shear wall section in multi-storey buildings to reduce costs. A total of 5 buildings are included in the Staad pro program abbreviated SA, SB, SC, SD, SE as they are located in Seismic Zone III. The results of the post-parametric study show that the reduction of the shear wall area should be adjusted to another limit of up to 20% in order to reduce costs. The above study shows that when there is an excessive use of the opening above the limit of 20%, the rigidity of the structure will be lower and the structural components will fail. Due to the members' load transfer criteria, a 20% deduction on the wall is sufficient. Building SD with 80% coverage is best of all. (Thakre P., Jamle S. & et. al.(2020))

The study is carried out on a 25-storey residential building. A standard plan with a base area of 825 m² used in this work. Different housings are created with shear belt on different floors. Response spectrum method with SRSS combinations used to determine various parameters, such as base shear, maximum nodal displacement in the longitudinal and transverse direction, drift values, and load cases that create a maximum derivation. In this regard, this paper presents the criteria for providing the shear belt at different heights using Staad pro software. Recommendations made to choose the optimal location of the position of the wall belt in the structure, along with the best of all. The optimal height for the location of the shear wall belt to increase the capacity to handle the lateral load from the upper parameters of the lens will be at 47.58m, ie shear band structure on the 12th floor. (Patel N., Jamle S. (2019))

In the current work, the shear core support system and belt support system are used on the main building where the G-10 resides in the seismic zone IV. The overall structure compares to both the belt buckle and the belt buckle support, using the best condition recommended by the Taranath method. Binding response methods are used to assess nodal changes, the period of story derivation and the extent of involvement and the significance of the adverse event. Seven chapters were used and compared with each other in this paper with the most useful of all the topics discussed in this article. The nodal curves on the X and Z sides have the lowest cost when using a shear core shear device and a system supported by a wall belt. For all cases in the X and Z series, the story flow at an altitude of 24.96 m from the base level appears to be the lowest. Because of; the belt is 24.96 m high holding the whole structure. The S4 case again shows the low values of all. The stress and stressors of the elements appear to be the lowest in the shear core support system and the wall belt support system. Also, the problem of external transfer to the center of the structure. The time period for case S4 is the shortest of all cases taken for details. After the standard test, Module No. 1, 2 and 3 show the importance of participating in large quantities at instructions X and Z. (Dangi A., Jamle S. (2019))

Patel N., Jamle S. Was worked on the system of outrigger. It was taken for analysis due to it is most optimum for high-rise buildings and skyscrapers. The main inner or outer core using support beams on different floors on the outer columns are connected to resist the demolition and rotating action of the core due to seismic and wind forces. The various articles related to the that area that has done a lot of work in this area in the past. Through the survey of the research work, we learned about the final result that will shape the research goals of our further research. The final best option from different cases is suggested using the above numerical data and Staad analysis. The focus is on the shear band, which is a modified part of the shear wall, its width and thickness are fixed, but the height at which it behaves as the optimal case may be the subject of serious research. The final conclusion is that the belts increase the strength of the building. (Patel N., Jamle S. (2019))

Using this idea, PEG-400 has used in this research work whereby cement is replaced in different percentages (0, 0.8, 1.6, 2.4 and 3.2) and calculates the strength and durability of concrete. For Mix-20 concrete, the maximum tensile strength achieved in PEG-400 is 1.6% and for Mix-25 concrete, the maximum strength achieved in PEG-400 is 2.4%. For added durability against acid attack, PEG-400 chemical when not used in conventional concrete, the loss of compressive strength is observed at 12.24 percent for M25 grade concrete and 11.35 percent for grade concrete. M20. Based on the previous result, the optimal tensile strength achieved with PEG-400 is 2.4 percent for Mix-25 and 1.6% for Mix-20. When PEG-400 was not used, the loss of compressive strength is observed at 12.24 percent for M25 grade concrete and 11.35 percent for M20 grade concrete, concluding that the addition of the chemical PEG-400 has better durability against acid attack. It is recommended to use chemical additives to achieve a good quality concrete. (Mandiwal P., Jamle S. (2019))

In the current study, the solution to the above problem is suggested by providing a shear wall in a specified ratio to the wall surface in the irregularity of the plane, which helps to withstand the lateral load generated by seismic forces. This paper provides a review of the research papers previously presented by various researchers, which shows the option of further research. A multi-storey building with different irregular shapes comprising "T" and "L" is taken for analysis with the opening in the shear wall system in all the stories one by one in different locations in the stories to better understand the effect of the opening ratio at wall the surface of the building and several seismic parameters in such a case of tall building. The analysis is done for seismic zone III to observe the values of the result parameters. The different seismic parameters are analyzed, such as nodal displacement, floor drift and modal participation factors, to examine the actual variation. Other decisive parameters, such as maximum bending moment, shear force and axial force, need to be analyzed for better optimization and conclusion for different cases. The condition of the Reintr action corner building is checked according to IS 1893 - 2016. (Thakre P., Jamle S, & et. al. (2019))

Designing the best telecommunications towers on the roof of multi-storey buildings under seismic load. focus on the useful needs of the website. In the cities there seems to be insufficient land and there is no substitute for the performance of the roofs of the buildings which satisfies the well-organized conditions according to their condition and height to include the radio spectrum in large part. In this work, the results are derived from the conditions of the multi-room building located in Seismic Zone-IV. The Staad Pro

software used in the structure facing nuclear power and the telecommunication tower is located in 5 different locations according to the square of the 'tower and the best position of the' tower on the roof. (Malviya S., Jamle S. (2019))

In this study, the effect of polyethylene glycol on the bond strength and bond strength of cement by changing the percentage of polyethylene glycol-400. Polyethylene glycol is replaced by cement in different percentages (0%, 0.8%, 1.5%, 2.4% and 3.2%, respectively). It contains a maximum strength of 2.4% polyethylene glycol by weight of M-20 cement and 1.6% polyethylene glycol by weight of M-25 cement. The high resistance achieved by PEG400 was 1.6% for Mik-25 and 2.4% for Mik-20. The strength of the cement obtained by PEG400 was comparable to mixtures of M25 and M20. (Mandiwal P., Jamle S. (2018))

The present paper examines the RCC configuration of the 3D G + 10 computer, under the influence of the earthquake. The location of the stabilizer used according to Taranath method. The belt response method used is used to observe the performance of seven unique, which includes standard, main shear, belt buckles and belt buckles and fasteners and seat belts. These were examined with models such as the base shear, axial spinal strength and shear force of the foot being examined. The shear base has a low response rate, as opposed to the general condition, which seems to be best under the seismic effect. Traditional home and basic shears. To cope with the present, buildings are recommended to be planned, as the Shear Core support system and the wall strap-supported system have the lowest cost of all cases. If the column image is the main source, the axial power generation shows the lowest cost when only the Shear Core system will be used. The scissors and wall support program will again be useful in power scissors for both Y and Z instructions in the elements. Torsion agents have been found to be an effective and effective case for constructing and shearing shears and wall stabilizers. The general setting of the parameter between both the Shear Core support system and the system supported by the wall belt. The belt buckle is more effective than the belt loop seen in this paper. (Dangi A., Jamle S. (2018))

The study which is based on the partial replacement for cement. The concrete industries with fly ash, glass waste, rice husk, etc. If little convenient and inexpensive waste material is found for concrete fabrication, there will be a significant gain in eliminating waste management and reducing construction costs. The work audits the viability of fly ash, glass dust as a partial substitute for cement respectively. The initial stage proceeds with the replacement of 25% of the cement content by variable proportions of fly ash (FA) and glass dust (GP). Subsequently, the resistance to bending and compression is analyzed, at 7, 14 & 28 days. The comparative study also taken. The adequate results were obtained with the combination of 75% cement and 25% fly ash in proportion, with respect to the properties tested. (Sironiya S., Jamle S., & et. al. (2017))

The work proves the inefficiency of demolished cement as a transformative part of the accumulated natural order. At the initial stage, the uniformity of optima cement and co gross altered nature of the composite (NCA) and recycling coated cement (RCA) in the added cement. For the experimental model, the combined aggregation was obtained from M25 cast concrete cube cubes at the laboratory. The variation of the combinations of the natural ability and the regenerative regression combined with the simulation models from this matrix was prepared for the same test. Under 90% NCA and 10% RCA replacement gives in comparison ratio led to reasonable results. (Sironiya S., Jamle S., & et. al. (2017))

Complementary materials are used to decrement in the cement amount in concrete. Silica fume is the most popular material used in concrete to improve its tensile and flexural strength. For this purpose, the silica fume is replaced by 0%, 5%, 7.5%, 12.5%, 15%, 20% and 25% by weight of cement. The ratio of water binder is taken 0.42 for concrete grade M-25. Several tests were performed in the research that showed the results of the same percentage at different 0% 5%, 7.5%, 12.5%, 15%, 20% and 25% under the time interval of 7,14 & 28 days. cured as a substitution of micro-silica for cement on Divided tensile strength, flexural strength .The results shown that silica fumes have great potential for use in concrete in place with substitute for cement. The maximum divided tensile strength was observed when the silica fumes 20% replacement. There is decrement will be observed in workability of concrete with increment in proportion of silica fumes increases. Under the silica fume substitution is approx. 15% the maximum flexural strength was observed. (Chouhan P., Jamle S., & et. al. (2017))

The researchers used recycled materials in concrete. Additional materials are used for the reduction in the cement portion in concrete. Silica is the most popular material used in concrete to improve its compressive strength. For this micro silica is replaced by 0%, 5%, 7.5%, 12.5%, 15%, 20% and 25% by weight of the cement. For concrete grade M-25, the coefficient of the water binder is taken as 0.42. In the course of the study, various tests were carried out that showed the results of the same percentage at different values of 0% 5%, 7.5%, 12.5%, 15%, 20% and 25% over time periods 7, 14 and 28 days. curing as a substitute for cement with micro silica in compressive strength. Results from existing research indicate that silica is good potential to use partial replacement. There is decrement will be shown in Concrete workability as the increment in of silica proportion. The optimum result was obtained in the case of silica with replaced 15%. On that result maximum compressive strength was observed. (Chouhan P. , Jamle S. & et, al. (2017))

Currently work has been carried out with the enthusiasm of research and analysis of various work studies related to the improvement of shear wall and their behavior in relation to heavy loads. While shear walls resist important parts of the lateral load on the basement and the frame supports the lateral load on the upper parts of the house, which is suitable for soft-floor high-rise buildings, houses of nature Similarly built in India, as in India, the ground floor is used for parking and garages or offices and the top floor is used for residential areas. In this project it is concluded that the shear wall of structure G + 10 generates less value of von-misses stress and deformation in the structure in location 1 compared to location 2. It is also concluded that in Shear wall of structure G + 20 is generated less stress value von-misses and less deformation in the structure at location 2 compared to location 1. It is also concluded that the shear wall of structure G + 26 generates less von-misses stress value and less deformation in the structure at location 1 compared to location 2. (Soni P., Tamrakar P. L (2016))

Sharma R., Amin J.A. Explore and evaluate and critically impact a 30-storey prototype building with different types of shear space in the wall and with and without a shear wall combination. Elements are tested using E-TABS software using response measurement methods (1893 (Part -1) -2002) and historical methods. The placement of gaps in shear walls without limiting the thickness of the shear wall is reduced by opening, reducing the hardness of the building in later times and increasing sliding on the sides. Movement and flow do not only depend on the size of the curve, but also the shape of the curve also plays a role when the viewing angle is large. The total number of shelves increases from 0.58% to 20.95%, and the float between floors increases by 1.04% to 23.63% due to the installation of different types of curtains on the walls. compared to houses without openings in the barbed wire walls. Second, the reduction of the vertical barrier due to the opening consists of an increase in the amount of adjacent contour elements, it seems that the relaxation is increased compared to the previous case. Thus, the total variable traffic and floating between floor levels decreased by 0.13% to 17.65% and from 0.34% to 21.45%, compared to the previous case. Providing space in ventilated walls demonstrates a high degree of local regulation and emphasizes the feeling around the space. Sharma R., Amin J.A. Investigate and evaluate and critically influence the building (Sharma R., Amin J.A. (2015))

The purpose of this paper is to investigate the complex responses of the three-story RC shear wall construction, and without opening. Development of mathematical models and details of reinforced cement shear barriers using different nonlinear methods (time history and pushover methods). These methods differ in the accuracy, simplicity, clarity and clarity of the historical background. Nonlinear static procedures have been developed in order to overcome the imperfections and limitations of linear lines, while maintaining a very easy to use. All procedures include performance-based ideas, taking into account the extent of damage. The analysis is performed using standard SAP2000 packages. Comparison of these models for different constraints such as slippery, slippery and scissor foundations was demonstrated by the construction of the RC wall with and without opening. The importance of seismic responses such as shear foundations, storey changes and moving around for both available methods increases the instruction for models 1, 2, 3, 4, and 5. The variation in height -post distribution increased with 84.97%, 85.91%, 87.09%, 90.05% over time with 71.14%, 78.32%, 81.21%, and 82.63% of pushover tests for sample 2, 3, 4, 5, compare the effectiveness of model 1. A percentage of openings increase and increase changes. The distribution of the free floating story on the high basis becomes the uniform while the high flow framework increases for all means. Determine flood rates for different damage levels of planned building classes in accordance with IS1893-2002. The flexible strap access mechanism requires visually capable capacity in IO operations (fast operation), so plastic sequences occur in a permanent structure. (Satpute S G, Kulkarni D B (2013))

Martong K., Agrawal T.P. use recycling additives for use in cement. The use of fly ash impactful under the replacement study of concrete. Due to the increasing durability of the composite cement and the environmental benefits. There are three common Portland cement (OPC) grade points used in the construction industry, namely 33, 43 and 53, as classified by the Bureau of Standards of India (BIS). This article reports a comparative study of the effect of cement properties on when a different OPC score changes and flies. With change in the replacement of 10%, 20%, 30% and 40% in fly ash the respective objective will be achieved. Strength, endurance and tolerance of cement were extensively studied. Test results show fly ash use often improves cement properties up to a percentage change in all OPC scores. (Marthong C, Agrawal T.P. (2012))

This document states that glass dust and brick dust can be used as other building materials to improve concrete. Altering the fine combination with fine powder coatings has proven to be most effective. The best substitute gets 20% energy of cement in 3 days, 7 days and 28 days more than the prepared cement without changing the sand. With up to 30% sand conversion, there is a significant reduction in strength achieved in 3, 7, and 28 days. The expected resistance was 26.6 MPa for M-20 class cement, but at 28 days, the resistance achieved was 25.10 MPa, so there was a deficit of 5.6%. The expected strength is 31.6 MPa for M-25 grade cement, but at 28 days, the achieved capacity is 28.5 MPa, so there is a deficiency of 9.81%. The target resistance is 38.25 MPa for the M-30 concrete class, while the 28-day resistance is up to 37.40 MPa, so there is a deficit of 2.22%. (Darshita T., Anoop P. (2012))

Shear strength, route failure and deformability of RC shear walls and shutters were significantly affected by the difference between the number and layout of spaces. The calculated shear strength of RC shear walls with equivalent perimeter opening is within the safety limit, but its predictive accuracy is not so adequate. On the other hand, the estimate proposed by Ono and Tokuhiko agrees with the shear strength in the experiment. The axial deformation and the stress distribution at the base of the cutting walls with opening were different from those without opening, where the columns, the walls of the wings, the central panels of the wall contribute to its basic moment. The RC shear wall with openings was simulated by FEM analysis to produce the spine curve and the progress of the failure and a good agreement between the experimental and analytical results was identified. (Sakurai M., Kuramoto H. & et. al. (2008))

III.CONCLUSIONS

After the deep study, conclusion made with respect to above research paper review and summery report are as follows:-

- A. The different researchers adopted different methodology for increment in strength and stability in the buildings.
- B. The methodology is based on the some key aspect such materials replacement, shear wall variations, concrete belt, change in thickness and height on different element of the structure& the use of software programme in it.
- C. The replacement of recycled materials such glass power, silica fumes, and fly play better and impactful result under the increment in stability of the building. The optimum replacements are under the range of 15 to 25%.
- D. Cement materials is best replacement for the optimum results in terms of strength and stability.
- E. Shear wall thickness also more predominate in the output of a structure with reference to get more precise results.
- F. The software analysis is based on the earthquake parameters only due to zone III maximum time used. The csi-etab and staad is more predominating in the papers.
- G. The shear wall variation such openings, thickness changes, grade of concrete used in the shear wall also affected for criteria of increment in strength and stability.
- H. The major concern taken high rise building for G+15 TO G+30.
- I. The overall conclusion made that a structure stability is based on the structural components and the increment in the strength and stability is achieved by variation in it.

IV.ACKNOWLEDGMENT

I Zamran Khan, would like to thank my guide *Mr. Sagar Jamle*, Assistant Professor, Department of Civil Engineering, Oriental University, Indore for his continuous support and guidance for the completion of this entire work. I am glad that he simultaneously works with 16 research scholars and do support individual scholars intensively.

REFERENCES

- [1] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building Analysis When Structure Length is greater than width under seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE), ISSN: 2347-4890 Vol.-05, Issue-3, pp. 32-53.
- [2] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building: A Review", International Journal of Advanced Engineering Research and Science, (ISSN : 2349-6495(P) | 2456-1908(O)),vol. 6, no. 4, pp. 310-314, <https://dx.doi.org/10.22161/ijaers.6.4.36>
- [3] Sachin Sironiya, Sagar Jamle, M. P. Verma, (2017), "Experimental Investigation On Fly Ash & Glass Powder As Partial Replacement Of Cement For M-25 Grade Concrete", IJSART - Volume 3 Issue 5, ISSN- 2395-1052, pp. 322-324.
- [4] Prabhulal Chouhan, Sagar Jamle, M.P. Verma, (2017), "Effect of Silica Fume on Strength Parameters of Concrete as a Partial Substitution of Cement", IJSART - Volume 3 Issue 5, ISSN- 2395-1052.
- [5] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building under Seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE), ISSN: 2347-4890 Vol.-05, Issue-3, pp. 14-31.
- [6] Taha A. Ansari, Sagar Jamle, (2019), "Performance Based Seismic Analysis of Regular R.C. Building", International Journal of Management, Technology And Engineering, ISSN: 2249-7455, Vol. 09, no. 07, pp. 342-351, DOI:16.10089.IJMTE.2019.V9I7.19.28639
- [7] Prakash Mandiwal, Sagar Jamle, (2018), "Use of Polyethylene Glycol as Self Curing Agent in Self Curing Concrete - An Experimental Approach", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 5, no. 11, pp. 916-918.
- [8] Surendra Chaurasiya, Sagar Jamle, (2018), "Determination of Efficient Twin Tower High Rise Building Subjected to Seismic Loading", International Journal of Current Engineering and Technology, INPRESSCO, E-ISSN 2277 – 4106, P-ISSN 2347 – 5161, Vol. 8, No. 5, pp. 1200 – 1203, DOI: <https://doi.org/10.14741/ijcet/v.8.5.1>
- [9] Archit Dangi, Sagar Jamle, (2018), "Determination of Seismic parameters of R.C.C. Building Using Shear Core Outrigger, Wall Belt and Truss Belt Systems", International Journal of Advanced Engineering Research and Science, (ISSN : 2349-6495(P) | 2456-1908(O)),vol. 5, no. 9, pp.305-309, <https://dx.doi.org/10.22161/ijaers.5.9.36>

- [10] Mohd. Arif Lahori, Sagar Jamle, (2018), "Investigation of Seismic Parameters of R.C. Building on Sloping Ground", International Journal of Advanced Engineering Research and Science, (ISSN: 2349-6495(P), 2456-1908(O)), vol. 5, no. 8, pp.285-290, <https://dx.doi.org/10.22161/ijaers.5.8.35>
- [11] Gaurav Pandey, Sagar Jamle, (2018), "Optimum Location of Floating Column in Multistorey Building with Seismic Loading", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 5, no. 10, pp. 971-976.
- [12] Suyash Malviya, Sagar Jamle, (2019), "Determination of Optimum Location of Rooftop Telecommunication Tower over Multistorey Building under Seismic Loading", International Journal of Advanced Engineering Research and Science, (ISSN : 2349-6495(P) | 2456-1908(O)),vol. 6, no. 2, 2019, pp. 65-73, <https://dx.doi.org/10.22161/ijaers.6.2.9>
- [13] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistorey Building", International Journal for Research in Engineering Application & Management (ISSN : 2454-9150),vol. 4, no. 10, pp. 596-603, doi: 10.18231/2454-9150.2018.1372
- [14] Taha A. Ansari, Sagar Jamle, (2019), "Performance Based Analysis of RC Buildings with Underground Storey Considering Soil Structure Interaction", International Journal of Advanced Engineering Research and Science (ISSN: 2349-6495(P) | 2456-1908(O)),vol. 6, no. 6, pp. 767-771, <https://dx.doi.org/10.22161/ijaers.6.6.89>
- [15] Sagar Jamle and Shirish Kumar Kanungo, (2020), "Determination of Stable Underground Storage Reservoir System- Recent Advancements in Structural Engineering Volume 1", LAP LAMBERT Academic Publishing, Mauritius, ISBN: 978-620-2-51435-4.
- [16] Sagar Jamle, Nirmal Delmiya, Rahul Singh, (2020), "Efficient Use of UPV Meter: A Non Destructive Test of Concrete by Fragmentation Analysis", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 3385-3394. <https://doi.org/10.37896/JXAT12.04/1078>
- [17] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by Using Optimum Size of Beams in Top Floors with Different Grades in Multistoried Building at Different Levels", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 170-178. <https://dx.doi.org/10.22161/ijaers.74.20>
- [18] Gagan Yadav, Sagar Jamle, (2020), "Use of Shear Wall with Opening in Multistoried Building: A Factual Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 243-246. <https://doi.org/10.14741/ijcet/v.10.2.9>
- [19] Surendra Chaurasiya, Sagar Jamle, (2019), "Twin Tower High Rise Building Subjected To Seismic Loading: A Review", International Journal of Advanced Engineering Research and Science, (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 4, pp. 324-328, <https://dx.doi.org/10.22161/ijaers.6.4.38>
- [20] Archit Dangi, Sagar Jamle, (2019), Stability Enhancement of Optimum Outriggers and Belt Truss Structural System", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 2, pp. 772-780.
- [21] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "Stability Enhancement in Wall Belt Supported Dual Structural System using Different Grades of Concrete", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 237-242. <https://doi.org/10.14741/ijcet/v.10.2.8>
- [22] Mohd. Arif Lahori, Sagar Jamle, (2019), "Response of Multistorey Building Located on 20° and 30° Sloping Ground under Seismic Loading", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 1, pp. 1063-1069.
- [23] Prafoolla Thakre, Sagar Jamle, Kundan Meshram, (2020), "Opening Area Effect of Shear Wall in Multistorey Building under Seismic Loading", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 2, pp. 122-129. <https://dx.doi.org/10.22161/ijaers.72.17>
- [24] Romesh Malviya, Sagar Jamle, (2020), "Increasing Stability of Multistoried Building using Different Grades of Concrete in Column Member Sets at Different Locations", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 208-213. <https://doi.org/10.14741/ijcet/v.10.2.3>
- [25] Mohammad Bilal Rasheed, Sagar Jamle, (2020), "Conceptual Approach on Effect of Various Concrete Grade in Outrigger and Wall Belt Supported System: A Perceptual Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 100-104. <https://dx.doi.org/10.22161/ijaers.75.14>
- [26] Sagar Jamle and Roshan Patel, (2020), "Analysis and Design of Box Culvert- A Manual Approach in Structural Engineering", LAP LAMBERT Academic Publishing, Mauritius, ISBN: 978-620-0-78760-6.
- [27] Mohit Kumar Prajapati, Sagar Jamle, (2020), "Strength irregularities in multistoried building using base isolation and damper in high Seismic zone: A theoretical Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 235-238. <https://dx.doi.org/10.22161/ijaers.73.37>
- [28] Gagan Yadav, Sagar Jamle, (2020), "Opening Effect of Core Type Shear Wall Used in Multistoried Structures: A Technical Approach in Structural Engineering", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 344-351. <https://dx.doi.org/10.22161/ijaers.73.50>
- [29] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "A Review on Stability Improvement with Wall Belt Supported Dual Structural System Using Different Grades of Concrete", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 293-296. <https://dx.doi.org/10.22161/ijaers.73.43>
- [30] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by using Optimum Size of Beams with same Grade of Concrete: An Informative Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 259-262. <https://doi.org/10.14741/ijcet/v.10.2.12>
- [31] Manoj Patidar, Sagar Jamle, (2020), "Optimization of Stability of Multistoried Structure by Changing Grades of Concrete in Shear Wall Member", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 2479-2497. <https://doi.org/10.37896/JXAT12.04/979>
- [32] Manoj Patidar, Sagar Jamle, (2020), "Use of different Grades of Concrete in Shear Wall: A Comprehensive Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 355-359. <https://dx.doi.org/10.22161/ijaers.74.44>
- [33] Sagar Jamle, Nirmal Delmiya, Rahul Singh, (2020), "Efficient Use of UPV Meter: A Non Destructive Test of Concrete by Fragmentation Analysis", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 3385-3394. <https://doi.org/10.37896/JXAT12.04/1078>



- [34] Shahdab Khan, Sagar Jamle, (2020), "Use of Shear Wall Member at Corners to Enhance the Stability Using Different Grades: An Immense Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 396-400. <https://dx.doi.org/10.22161/ijaers.75.47>
- [35] Ankush Nagar, Sagar Jamle, (2020), "Base Shear Reduction Techniques: A Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 466-471. <https://dx.doi.org/10.22161/ijaers.75.57>
- [36] Bhagwat Mahajan, Sagar Jamle, (2020), "Stability Increment Techniques by Altering Beam Members: A Review", International Journal for Research in Applied Science & Engineering Technology (IJRASET), ISSN: 2321-9653, vol. 8, no. 6, pp. 1403-1407. <http://doi.org/10.22214/ijraset.2020.6227>
- [37] Ankush Nagar, Sagar Jamle, (2020), "An Analytical Approach to Determine Base Shear Reduction Effects in Multistoried Building", International Journal for Research in Applied Science & Engineering Technology (IJRASET), ISSN: 2321-9653, vol. 8, no. 6, pp. 1395-1402. <http://doi.org/10.22214/ijraset.2020.6226>
- [38] Sakshi Goyal, Sagar Jamle, (2020), "Stability Increment Practices using Wall Outrigger Members: A Review", International Journal for Research in Applied Science & Engineering Technology (IJRASET), ISSN: 2321-9653, vol. 8, no. 6, pp. 1656-1661. <http://doi.org/10.22214/ijraset.2020.6270>
- [39] Soni P., Tamrakar P. L (2016) "Structural Analysis of Multi-story Building of Different shear Walls Location and Heights" International Journal of Engineering Trends and Technology (IJETT) ,Volume 32, Number 1,ISSN: 2231-5381 , pp 50-57.
- [40] Sharma R. , Amin J.A. (2015) "Effects of opening in shear walls of 30- storey building" Journal Of Materials And Engineering Structures, pp 44–55
- [41] Chouhan P., Jamle S., & et. al. (2017) "Effect of Silica Fume on Strength Parameters of Concrete As A Partial Substitution of Cement" IJSART - Volume 3 Issue 5, ISSN ONLINE: 2395-1052 Pp 968 -972,
- [42] Darshita T., Anoop P. (2012) International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Impact Factor (2012): 3.358 Volume 3 Issue 6, June 2014 Licensed Under Creative Commons Attribution CC BY Study of Strength and Workability of Different Grades of Concrete by Partial Replacement of Fine Aggregate by Crushed Brick and Recycled Glass Powder, Paper ID: 02014168, pp141-145.
- [43] Sakurai M., Kuramoto H. & et. al. (2008) Seismic Performance of Rc Shear Walls With Multi-openings The 14th World Conference on Earthquake Engineering October 12-17, Beijing, China , Beijing, China, Pp1-8
- [44] Satpute S G, Kulkarni D B (2013) "Comparative Study Of Reinforced Concrete Shear Wall Analysis In Multi-storeyed Building With Openings By Nonlinear Method" Int. J. Struct. & Civil Engg. Res. (IJSCER), ISSN 2319 – 6009, Vol. 2, No. 3.
- [45] Sakurai M., Kuramoto H. & et. al. (2008) Seismic Performance of Rc Shear Walls With Multi-openings The 14th World Conference on Earthquake Engineering October 12-17, Beijing, China , Beijing, China, Pp1-8
- [46] Satpute S G, Kulkarni D B (2013) "Comparative Study Of Reinforced Concrete Shear Wall Analysis In Multi-storeyed Building With Openings By Nonlinear Method" Int. J. Struct. & Civil Engg. Res. (IJSCER), ISSN 2319 – 6009, Vol. 2, No. 3.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)