



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 8 Issue: XII Month of publication: December 2020 DOI: https://doi.org/10.22214/ijraset.2020.32514

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Determination of Worst Location of Telecommunication Tower over Residential Apartment with Introduction of Outrigger and Wall Belt Supported System at Bikaner City under Seismic Loading

Chirag Singh¹, Mayur Singi²

¹*M.* Tech. Scholar, Department of Civil Engineering, B.M. College of Technology, Indore (M. P.), India ²Assistant Professor, Department of Civil Engineering, B.M. College of Technology, Indore (M. P.), India

Abstract: When the structure has been analysed under the effect of seismic activities, the main thing has been observed that we have only considered the efficient case, we have not considered the worst case. If there will be a provision of telecommunication tower over multistoried building in future and we have the worst location of tower position, we have to do some measures to erect the parametric values and to stable it. In this research, what we did was we actually take total 5 residential apartment building cases of G+19 of different telecommunication tower location. After analysis, we found out the worst case, we have used the outrigger system and erected as discussed in graphical representations in discussion part. In conclusion, parametric result comparison noted down. Overall it is observed that the Case TLA is very efficient among all the cases. Also, we have enhanced the property of worst case TLC which is found by our result and discussion by implementing the outrigger system. Keywords: Seismic activities, Multistoried Building, Response spectrum method, telecommunication tower

I. INTRODUCTION

When we are talking about human civilization, the major disaster was earthquake. This can harm lives, structures and property. There has been experimental work going on around the world to resolve this problem and provide a harmless environment so that one can easily live his life hassle free. Now a day's massive and huge structure designed with special techniques to withstand earthquake forces. This includes special buildings which have much higher cost of manufacture than its performance. But when we are thinking from safety point of view, there is not much greater than one's life.

In India, the most common practice to make a high rise structure is reinforced concrete frame. In this country, earthquake zones are divided under four zones viz. Zone II, Zone III, Zone IV and Zone V. The structure ought to be analysed first and then designed with extra stiffness and ductility requirements to reduce damages against this force. Hence use of steel bracing arrangement into the frame structure used to reduce the lateral effects on the structures. Bracings can easy to handle when construction, provides strength and stiffness to the frame structure. It can also be used as architectural performances. These are used in structure to resist movement of the components of any structure.

Another stiffness increasing element used in construction practices is shear wall, since it is generally provided in the periphery of the lift area. This arrangement is known as core type shear wall system. Shear wall not only provide the stiffness, but also increases the stability to the structure from overturning. Also lateral effects can also be reduced. As per Taranath's approach, shear wall can be used as a outrigger system to minimize the deflection parameter and also reduces the worst effects of lateral forces. This system can be implemented at 0.466 of the structural height. The shear wall outrigger in connection with shear core make the outrigger system.

II. PROCEDURE AND 3D MODELING OF THE STRUCTURE

Earthquake analysis is carried out on a G+19 Storey Residential Apartment by using software approach. The total 6 models are created on the software. Firstly, tower is placed at different placing over the top of the apartment. Then the efficient case and the worst case have been pointed out then the worst case parameters have been optimized using Outrigger system implication.

The analysis part consist of the effect on building under the different loads such as dead load, live load and lateral loads (earthquake and wind) etc. into it based on software mechanism. The seismic data is taken as per the IS 1893(PART1):2016. The response spectrum analysis method is adopted for analysis of building.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com

Models	Description
Case TLA	Building Without Outrigger System with Tower at Location 1
Case TLB	Building Without Outrigger System with Tower at Location 2
Case TLC	Building Without Outrigger System with Tower at Location 3
Case TLD	Building Without Outrigger System with Tower at Location 4
Case TLE	Building Without Outrigger System with Tower at Location 5
Case TLC-OT	Building With Outrigger System with Tower at Location 3

Table 1: Model Description

Table 2: Input details for Residential Apartment Building for all cases

Building configuration	G+19 (+ Shaped Structure)
Length of Apartment	25m
Width of Apartment	25m
Height of building	78m
Build up area of building	625 sq. m.
Concrete and Steel Grade	M 30 & FE 415
Earthquake parameters	Zone III with RF 4 & 5% damping ratio
Period in X & Z direction	1.404 sec. & 1.404 sec. for both direction
Dead load for floor finish	2.5 KN/sq. m.
Live load for floor and roof	3KN/ sq. m. & 1.2 KN/ sq. m.

III.RESEARCH OBJECTIVES

To find the most efficient and Worst location of Tower, following objectives have been decided for Residential Apartment Building:-

- A. To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- B. To determine Time period and Mass participation factor in both X and Z direction.
- C. To find Maximum Axial Forces, Shear Force and Bending Moment in Column.
- D. To compare Maximum Shear Forces, Bending Moments and Torsional Moments in beams parallel to X and Z direction.

To find the most efficient and Worst location of Tower, following objectives have been decided for Tower:-

- 1) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- 2) To determine Time period and Mass participation factor in both X and Z direction.
- *3)* To find Maximum Axial Forces, Shear Force and Bending Moment in Column.

To obtain the most efficient parametric case and worst case by comparing all and then to erect the worst one, following objectives have been decided for both Residential Apartment Building and Tower:-

- a) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- b) To determine Time period and Mass participation factor in both X and Z direction.
- *c)* To find Maximum Axial Forces, Shear Force and Bending Moment in Column.
- d) To compare Maximum Shear Forces, Bending Moments and Torsional Moments in beams parallel to X and Z direction
- e) To obtain the minimum values of Nodal Displacement and Base Shear in both X and Z direction
- *f)* To determine Time period and Mass participation factor in both X and Z direction.
- g) To find Maximum Axial Forces, Shear Force and Bending Moment in Column.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Fig. 1: Plan of Structure



Fig. 2: 3D model of Tower









Fig. 4: Case TLB: - Building Without Outrigger System with Tower at Location 2

Fig. 5: Case TLC: - Building Without Outrigger System with Tower at Location 3



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Location 4

Location 5

Fig. 8: Case TLC-OT: - Building with Outrigger System with Tower at Location 3

IV. RESULTS ANALYSIS

The result parameters obtained by the application of loads and their combinations on various cases as per Indian Standard 1893: 2016 code of practice.

Result of each parameter has discussed with its representation in graphical form below:-







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Fig. 10: Comparative representation of Time Period and Mass Participation Factor in X and Z direction obtained in all Cases for Residential Apartment Building



Fig. 11: Comparative representation of Maximum Axial Forces in Column obtained in all Cases for Residential Apartment Building







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Fig. 13: Comparative representation of Maximum Shear Forces and Bending Moments in Beams parallel to X and Z direction obtained in all Cases for Residential Apartment Building



Fig. 14: Comparative representation of Maximum Torsional Moment in beams parallel to X & Z direction obtained in all Cases for Residential Apartment Building







ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Fig. 16: Comparative representation of Maximum Shear Forces and Bending Moments in Members obtained in all Cases for Tower

As per comparison of the numerous cases against various parameters among each other, it has been pointed out that the optimum case evolved will be Case TLA in total 8 parameters and the worst case will be Case TLC with total 8 cases.

If there is no provision of placing of tower to the optimum case, again the provision at planning stage that the tower will be located at the worst case as per this research, it has to be erected first by providing the outrigger system into it to make it more stable than before. Comparative analysis of worst case with its erected case has shown below:-

- A. Discussion on Worst Case and Erected Case
- 1) For Residential Apartment Building







Fig. 18: Comparative representation of Time Period and Mass Participation Factor in X and Z direction obtained in Worst Case and Erected Case for Residential Apartment Building



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com







Fig. 20: Comparative representation of Maximum Shear Forces and Bending Moments in Columns obtained in Worst Case and Erected Case for Residential Apartment Building



Fig. 21: Comparative representation of Maximum Shear Forces and Bending Moments in Beams parallel to X and Z direction obtained in Worst Case and Erected Case for Residential Apartment Building



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 8 Issue XII Dec 2020- Available at www.ijraset.com



Fig. 22: Comparative representation of Maximum Torsional Moment in beams parallel to X & Z direction obtained in Worst Case and Erected Case for Residential Apartment Building





Fig. 23: Comparative representation of Maximum Displacement in X and Z direction obtained in Worst Case and Erected Case for Residential Apartment Building



Fig. 24: Comparative representation of Maximum Shear Forces and Bending Moments in Members obtained in Worst Case and Erected Case for Residential Apartment Building

As per comparison between the worst case and the erected case, it has been proved that if such kind of provision situation arises, provision of erection in the analysis phase should be performed before the construction to lessen the higher parametric values as discussed in this research.



Volume 8 Issue XII Dec 2020- Available at www.ijraset.com

V. CONCLUSIONS

The conclusion can be pointed out are as follows:-

- A. Nodal displacement for Residential Apartment Building seems to be least in Model Case TLB for X and Z direction and for story drift, again Model P4 shows least values among all tower placing.
- *B.* It is found that when determining the Base Shear for both X and Z direction, Base Shear values Decreases up to Case TLD and increases to TLC and TLE, average value should be taken into account and then compared.
- *C.* On comparing the mass participation factor in both X and Z direction, the maximum mass with respect of time has taken into consideration. The optimum case obtained was Case TLB and the worst was TLE in X direction, TLB and TLD in obtained optimum and TLA and TLC were the worst respectively.
- D. In Column Axial Forces, Case TLB suited best and Case TLD suited worst among all when compared amongst each other.
- *E.* It is found similar trend observed in Case TLA obtained as efficient case and Case TLC obtained as worst in both Column Shear Force and Bending Moment parameter.
- *F.* Again in Beam Shear Force, Beam Bending Moment and Torsion in Beam, the trend follows the same as Column Shear Force and Bending Moment.
- G. Minimum values have been observed in Case TLA for Tower Displacement parameter.
- *H.* The same case again obtained efficient for maximum axial force, for maximum shear force and maximum bending moment parameter and proves to be economical.

Overall it is observed that the Case TLA is very efficient among all the cases. Also, we have enhanced the property of worst case TLC which is found by our result and discussion by implementing the outrigger system.

Hence best suitable location of tower by considering different result parameters seems to be tower at center of the building roof i.e. Case TLA in Residential Apartment building. Also we have tried to minimize the worst effects in some parameters by implementing the Outrigger walls at 0.446 H as per Taranath's approach.

REFERENCES

- Arpit Chawda, Vijay Baradiya (October 2015) "Influence of structure characteristics on earthquake response under different position of rooftop Telecommunication Towers". International Journal Of Engineering Sciences & Research, Issn: 2277-9655.
- [2] C. Preeti and K. Jagan Mohan(2013)"Analysis of Transmission Towers with Different Configurations" Jordan Journal of Civil Engineering, vol. 7, No 4.
- [3] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "Stability Enhancement in Wall Belt Supported Dual Structural System using Different Grades of Concrete", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 237-242. https://doi.org/10.14741/ijcet/v.10.2.8
- [4] G. Ghodrati Amiri, M.A. Barkhordari, S. R. Massah (2004) "Seismic behavior of 4-legged self-supporting telecommunication towers" 13th World Conference on Earthquake Engineering Paper No 215.
- [5] G. Ghodrati Amiri, M.A. Barkhordari, S.R. Massah and M.R. Vafaei (2007) "Earthquake Amplification Factors for Self-supporting 4-legged Telecommunication Towers" ISSN 1818-4952.
- [6] Gagan Yadav, Sagar Jamle, (2020), "Use of Shear Wall with Opening in Multistoried Building: A Factual Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 243-246. <u>https://doi.org/10.14741/ijcet/v.10.2.9</u>
- [7] Ghyslaine Mcclure, Laura Georgi And Rola Assi (2004), "Seismic considerations for telecommunication towers mounted on building rooftops" 13th World Conference on Earthquake Engineering Vancouver, B.C., Canada, Paper No. 1988.
- [8] Gholamreza Soltanzadeh, Hossein Shad, Mohammadreza Vafaei, Azlan Adnan (2014) "Seismic performance of 4-legged Self-supporting Telecommunication Towers" Int. Journal of Applied Sciences and Engineering Research, Vol. 3, Issue 2, ISSN 2277 – 9442.
- [9] Hemal J shah Dr. Atul K Desai 2014 "Seismic analysis of tall tv tower cosidering different bracing systems" International Journal of Engineering, Business and Enterprise Application ISSN (Print): 2279-0020 ISSN (Online): 2279-0039s pp113-119.
- [10] Jitesh Rajasekharan, S Vijaya (2014) "Analysis of telecommunication tower subjected to seismic & wind loading" International Journal Of Advancement In Engineering Technology Management & Applied Science vol 1 issue 2 ISSN 2349-3224 pp 68-79.
- [11] Mohd. Arif Lahori, Sagar Jamle, (2018), "Investigation of Seismic Parameters of R.C. Building on Sloping Ground", International Journal of Advanced Engineering Research and Science, (ISSN: 2349-6495(P), 2456-1908(O)), vol. 5, no. 8, pp.285-290, <u>https://dx.doi.org/10.22161/ijaers.5.8.35</u>
- [12] Mohammad Bilal Rasheed, Sagar Jamle, (2020), "Conceptual Approach on Effect of Various Concrete Grade in Outrigger and Wall Belt Supported System: A Perceptional Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 100-104. <u>https://dx.doi.org/10.22161/ijaers.75.14</u>
- [13] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building: A Review", International Journal of Advanced Engineering Research and Science(ISSN : 2349-6495(P) | 2456-1908(O)),vol. 6, no. 4, pp. 310-314, AI Publications, <u>https://dx.doi.org/10.22161/ijaers.6.4.36</u>
- [14] Nitin Bhosale, Prabhat Kumar, Pandey.A.D (2012)"Influence of host structure characteristics on response of rooftop telecommunication towers" INTERNATIONAL JOURNAL OF CIVIL AND STRUCTURAL ENGINEERING Volume 2, No 3, ISSN 0976 – 4399 pp 737-748.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429

Volume 8 Issue XII Dec 2020- Available at www.ijraset.com

- [15] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by Using Optimum Size of Beams in Top Floors with Different Grades in Multistoried Building at Different Levels", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 170-178. https://dx.doi.org/10.22161/ijaers.74.20
- [16] Patil Vidya M.,Lande Abhijeet C."Structural Response of Lattice Steel Masts for Seismic Loading". Journal of Mechanical and Civil Engineering, ISSN: 2278-1684 PP: 36-42.
- [17] Richa Bhatt, A.D.Pandey, Vipul Prakash (2013) "Influence of modeling in the response of steel lattice mobile tower under wind loading" International Journal of Scientific Engineering and Technology Volume 2 Issue 3, ISSN : 2277-1581, PP : 137-144.
- [18] Sagar Jamle, Nirmal Delmiya, Rahul Singh, (2020), "Efficient Use of UPV Meter: A Non Destructive Test of Concrete by Fragmentation Analysis", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 3385-3394. <u>https://doi.org/10.37896/JXAT12.04/1078</u>
- [19] Shailesh S. Goral Prof. S. M. Barelikar (2007) "Review on Wind and Non-Linear Dynamic Analysis of Self-Supporting Telecommunication Tower" International Journal of Science Technology & Engineering volume 3 issue 10 ISSN (online): 2349-784X pp 183-185.
- [20] Siddesha. H (2010), "Wind Analysis of Microwave Antenna Towers" INTERNATIONAL JOURNAL OF APPLIED ENGINEERING RESEARCH, DINDIGUL. Volume 1, No 3, ISSN - 0976-4259
- [21] Sourabh Rajoriya, K.K. Pathak, Vivekanand Vyas (September 2016) "Analysis of Transmission Tower for Seismic Loading Considering Different Height and Bracing System" International Journal for Research in Applied Science & Engineering Technology, Volume 4 Issue IX, ISSN: 2321-9653.
- [22] Surendra Chaurasiya, Sagar Jamle, (2019), "Twin Tower High Rise Building Subjected To Seismic Loading: A Review". International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 4, pp. 324-328, AI Publications, <u>https://dx.doi.org/10.22161/ijaers.6.4.38</u>.
- [23] Suyash Malviya, Sagar Jamle, (2019), "Response of Multistorey Building with Rooftop Telecommunication Tower in Different Positions: An Approach to Efficient Case", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 4, pp. 3783-3790.
- [24] Tak, N., Pal, A. and Choudhary, M. (2020). Analysis of Building with Tower on Sloping Ground International Journal of Current Engineering and Technology, DOI: https://doi.org/10.14741/ijcet/v.10.2.10 E-ISSN 2277-4106, P-ISSN 2347-5161 pp. 247-254.
- [25] Tak, N., Pal, A. and Choudhary, M. (2020). A Review on Analysis of Tower on Building with Sloping Ground. International Journal of Advanced Engineering Research and Science, 7(2), pp.84-87.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)