



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: V Month of publication: May 2021

DOI: <https://doi.org/10.22214/ijraset.2021.33329>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Strategies for Production of Ethanol and Value Added Products from Agriculture Wastes

S. Sheik Asraf

#Department of Biotechnology, School of Bio and Chemical Engineering, Kalasalingam Academy of Research and Education, Krishnankoil.

Abstract: *Microbial ethanol has attained importance status because of the following reasons: i) the depletion of the naturally available energy resources like coal, lignite; ii) increase in urban development, global warming, pollution levels; iii) lack of availability of technologies to utilise tidal, wind and solar energy. Hence, non-renewable sources of energy are less favourable compared to microbial ethanol.*

Keywords: *Ethanol, agriculture waste, value added product, fermentation*

I. INTRODUCTION

Non-renewable sources of energy are less favourable compared to microbial ethanol [1]. In Virudhunagar district, wide varieties of crops are under cultivation [2]. The cultivation of these crops generates tons of agriculture wastes every year. Cellulosic biomass [3] from these agriculture wastes [4] can be converted into ethanol using microorganisms such as bacteria [5] and fungi [6]. In India, agriculture wastes are collected directly from farmers [7] for ethanol production. Cellulosic ethanol production from switchgrass plant is one of the major projects in United States of America. As lignin content interfere the ethanol production, extensive research was focused towards reduction of lignin content [8] Generally, wastes generated during cultivation of cereals and plant tubers are subjected to series of processes such as thermal pretreatment, liquefaction, saccharification, filtration, starch hydrolysis before proceeding to distillation of ethanol. In case of waste generated during sugarcane and sugar beet cultivation, raw juice and molasses are produced first and later ethanol is distilled [9]. Plant biomass and agro by-products are subjected to removal of lignin and acid hydrolysis before fermentation [10]. Various kinds of fermentation namely batch, semi-continuous, continuous are used for ethanol production using starch hydrolysate, raw juice, molasses and acid hydrolysate [11]. Distillation is the final and ultimate step in the ethanol production [12]. The following could be used as strategies for production of ethanol and value added products from agriculture wastes.

II. COLLECTION OF AGRICULTURAL WASTES

Agriculture wastes from various farmlands could be collected directly from farmers and could be transported.

III. STARCH HYDROLYSATE PRODUCTION

Cereals and plant tubers waste could be subjected to series of processes such as thermal pretreatment, liquefaction, saccharification, filtration and starch hydrolysate production [13]. Cereals and plant tubers should be washed, cut and milled using mixer/juicer. The resultant mash should be treated with microbial amylase and incubated at 85 °C for 20 min. After that, the mash should be cooled to room temperature (25 °C) and could be liquefied.

The mash should be autoclaved at 115 °C for 20 min. The mash should be cooled to room temperature (25 °C) and microbial xylanase and β -glucanase should be added. The mash should be subjected to 50 °C for 120 min and later should be cooled to room temperature (25 °C). Glucoamylase and *Saccharomyces cerevisiae* should be added to the mash [14]. Saccharification (30 °C), filtration, starch hydrolysate production should be done and later the hydrolysate should be proceeded for fermentation and distillation (strategies v) and vi).

IV. JUICE AND MOLASSES PRODUCTION

Raw juice should be obtained from sugarcane waste using the mixer/juicer. Sugarcane should be burnt (or) burnt sugarcane should be obtained from farmers. It should be subjected to cutting, crushing/mashing and crystallisation [15]. Both, raw juice and processed (crystallised) sugarcane i.e. molasses should be proceeded for fermentation and distillation (strategies v) and vi).

V. LIGNIN REMOVAL AND ACID HYDROLYSIS

Agro by-product wastes should be subjected to removal of lignin using resin, alkaline extraction using 2% green liquor and later acid hydrolysis (3% sulphuric acid) at 121 °C for 1 hour. This should be followed by filtration, washing, drying, detoxification and regeneration of resin [15]. The resultant acid hydrolysate could be proceeded for fermentation and distillation (strategies v) and vi).

VI. FERMENTATION

Starch hydrolysate, raw juice, molasses, acid hydrolysate obtained from [ii), iii) and iv) strategies] could be subjected to batch, semi-continuous, continuous fermentation as described by methods available [15].

VII. DISTILLATION

The fermented product obtained from strategy v) should be subjected to distillation using ethanol distillation unit [16] and ethanol could be estimated using method available [17].

VIII. CONCLUSION

Microbial ethanol has attained importance status because the exhaustion of the naturally accessible energy assets and increase in urban development, global warming, pollution levels, lack of accessibility of expertise to exploit tidal, wind and solar energy. Hence, non-renewable sources of energy are not as much of encouraging paralleled to microbial ethanol.

IX. ACKNOWLEDGMENT

The author thanks the management of KARE.

REFERENCES

- [1] Asraf, S. S. et al. (2013). Genomics Perspectives of Bioethanol Producing *Zymomonas mobilis*. In *Bioinformatics: Concepts, Methodologies, Tools, and Applications* (pp. 1354-1377). Hershey, PA: Medical Information Science Reference.
- [2] <http://www.virudhunagar.in/agriculture.php>. Accessed on 13 November, 2014.
- [3] Senthilkumar, V., & Gunasekaran, P. (2005). Bioethanol production from cellulosic substrates: engineered bacteria and process integration challenges. *JSIR*, 64(11), 845.
- [4] Gunasekaran, P., & Raj, K. C. (1999). Ethanol fermentation technology- *Zymomonas mobilis*. *Current Science*, 77(1), 56-68.
- [5] Asraf, S. S., & Gunasekaran, P. (2010). Current trends of β -galactosidase research and application. *Current research, technology and education topics in applied microbiology and microbial biotechnology*, 880-890.
- [6] Amutha, R., & Gunasekaran, P. (2001). Production of ethanol from liquefied cassava starch using co-immobilized cells of *Zymomonas mobilis* and *Saccharomyces diastaticus*. *JBB*, 92(6), 560-564.
- [7] Ramani, G. et al. (2012). Production, Purification, and Characterization of a β -Glucosidase of *Penicillium funiculosum* NCL1. *ABB*, 167(5), 959-972.
- [8] Mekala, N. K., Potumarthi, R., Baadhe, R. R., & Gupta, V. K. (2013). Current Bioenergy Researches: Strengths and Future Challenges. *Bioenergy Research: Advances and Applications*.
- [9] Cheng, P., Mueller, R. E., Jaeger, S., Bajpai, R., & Iannotti, E. L. (1991). Lactic acid production from enzyme-thinned corn starch using *Lactobacillus amylovorus*. *Journal of industrial microbiology*, 7(1), 27-34.
- [10] Ensinas, A. V., Nebra, S. A., Lozano, M. A., & Serra, L. M. (2007). Analysis of process steam demand reduction and electricity generation in sugar and ethanol production from sugarcane. *Energy Conversion and Management*, 48(11), 2978-2987.
- [11] Fatih Demirbas, M. (2009). Biorefineries for biofuel upgrading: a critical review. *Applied Energy*, 86, S151-S161.
- [12] Brethauer, S., & Wyman, C. E. (2010). Review: continuous hydrolysis and fermentation for cellulosic ethanol production. *Bioresource Technology*, 101(13), 4862-4874.
- [13] Wheals, A. E., Basso, L. C., Alves, D. M., & Amorim, H. V. (1999). Fuel ethanol after 25 years. *Trends in biotechnology*, 17(12), 482-487.
- [14] Huang, Y., Jin, Y., Fang, Y., Li, Y., & Zhao, H. (2013). Simultaneous utilization of non-starch polysaccharides and starch and viscosity reduction for bioethanol fermentation from fresh *Canna edulis* Ker. tubers. *Bioresource technology*, 128, 560-564.
- [15] Sun, Y., & Cheng, J. (2002). Hydrolysis of lignocellulosic materials for ethanol production: a review. *Bioresource technology*, 83(1), 1-11.
- [16] Senthilkumar, V., & Gunasekaran, P. (2005). Bioethanol production from cellulosic substrates: engineered bacteria and process integration challenges. *Journal of Scientific and Industrial Research*, 64(11), 845.
- [17] Somogyi, M. (1952). Notes on sugar determination. *Journal of biological chemistry*, 195(1), 19-23.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)