



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: III Month of publication: March 2021 DOI: https://doi.org/10.22214/ijraset.2021.33432

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Analysis the Enhancement of Heat Transfer Rate in Heat Pipe with Various Wick Materials for Effective Utilization of Waste Heat in Industries

Shanmugam M¹, Deva Prabhu M S², Giridharan Thiruvadi I³, Gopi V⁴, Kamalnath K⁵

¹Associate Professor, ^{2,3,4,5}Student Department of Mechanical Engineering, Nandha Engineering College, Erode-638052,

Tamilnadu, India.

Abstract: Miniature Metal Powdered Sintered Wick Heat Pipe (sintered heat pipe) is a passive device which as high thermal efficiency for heat flux in a electronic cooling. In this paper Circular heat pipe with various wick materials such as Poly-Phenylene Benzo-Bisoxazole and Ultra-high-molecular-weight polyehylene and also grooved in wick structure is taken. The necessary numerical computation are accomplished by FLUENT (the CFD solver program) and the result are given. The objective is to study the heat flux of grooved structure with different wick material.

Keywords: Capillary-driven two-phase systems, isothermal, grooved structure wick, evaporate, Condence.

I. INTRODUCTION

Historically, the utilization of metallic heat sinks has been sufficient to supply the specified thermal management for many electronic cooling applications. However, with the new breed of compact devices dissipating larger heat loads, the use of metallic heat sinks is sometimes limited due to the weight and physical size required. Accordingly, the use of heat pipes is becoming an answer of choice. Capillary-driven two-phase systems provides significant advantages over traditional singlephase systems. With the typically increased thermal capacity related to the phase transition of a working fluid, considerably smaller mass flow rates are required to move equivalent amounts than in single-phase liquid or gas systems for a given temperature range. Moreover, heat transfer coefficients of two-phase systems are much greater than in single-phase flows and end in enhanced heat transfer. Lower mass flow rates and enhanced thermal characteristics provide the advantages of smaller system size (and weight) while providing increased performance. The thermal capacity of a single-phase system depends on the natural process of the working fluid; thus, an outsized gradient or a High Mass flow is required to transfer a large amount of heat. However, a two-phase system can provide essentially isothermal operation no matter variations within the heat load. Additionally, single phase systems require the utilization of mechanical pumps and fans to circulate the working fluid, while capillary-driven two-phase systems haven't any external power requirements, which make such systems more reliable and free of vibration. The best known capillary-driven two-phase system is that the heat pipe, where a schematic of a standard heat pipe. However, the planning of the heat recovery systems with heat pipe units is that the key to providing a device system to figure as efficient needless to say. Without correct design of such systems, heat pipes aren't ready to transport enough heat and should function as a particularly poor thermal conductor within the systems. The performance of natural convection heat sinks is directly dependent on the effective area; simpler surface area leads to better performance. A heat pipe embedded into the bottom material of a typical aluminum extrusion can reduce the general temperature difference along the bottom material, tending to isothermalize the bottom material. In essence the localized heat source is spread equally along the length of the heat pipe, increasing the general efficiency of the heat sink. Although an embedded heat pipe heat sink is slightly more expensive due to the added cost of the heat pipe, it is an easy method of improving the performance of a marginal extrusion. The more elegant approach is to design a heat sink that utilizes full characteristics of a heat pipe. Typical extruded heat sinks have limited aspect ratios and thick fins, which results in lower surface area per length. The material thickness adds unnecessary weight, and most importantly obstructs the cooling air flow. To alleviate the extrusion limits, bonded fin heat sinks are developed which allow the utilization of a tall, thin fin, which optimizes cooling air flow. But bonded fin heat sinks can also be limited by the conduction losses within the base plate for concentrated heat sources. A heat pipe is utilized for conjunction with parallel plate fins provides more efficient area with minimum volume demands.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue III Mar 2021- Available at www.ijraset.com

This design application is beneficial when there's not enough physical volume, or airflow above the device to use an extrusion, and allows the designe rmuch latitude in component arrangement. The heat pipe can transport the heat to a "remote" parallel plate fin stack which have enough volume to dissipate the heat. Heat pipes can be designed into most electronic devices for various power levels, and should even allow the utilization of a natural convection conductor. Computational fluid dynamics may be a powerful tool for fluid dynamics and thermal design in industrial applications, also as in academic research activities. Based on the current capabilities of the main CFD packages suitable for industry (such as, FLUENT and CFX) and the nature of industrial applications, understanding the physics of the processes, introducing adequate simplifications and establishing an appropriate model are essential factors for obtaining reasonable results and proper thermal design.

A. Envelope

II. STRUCTURE AND OPERATION OF HEAT PIPES

The work of the Envelope is to isolate the working fluid from the outside environment. It is also to be there for leak proof, maintain the pressure differential across the walls, and enable transfer of thermal energy to take place from and into the working fluid.

B. Working Fluid

As the operation of the heat pipe is based on evaporation and condensation of the working fluid, its selection is an important factor in the manufacture and design of the heat pipe. The working fluid is selected based on the working temperature range of the heat pipe.

C. Wick

The wick structure in a heat pipe facilitates liquid and vapour return from the evaporator to the condenser or the condenser to the evaporator. The main purposes of wick are to distribute the liquid around the evaporator section of heat pipe, and to generate the capillary pressure.



Fig 2.1 Working Of Heat Pipe.

The Fig 2.1 is explained in the below lines, which explaines the working of Heat Pipe.

- *1)* The Thermal Energy is absorbed by Working Fluid and Evaporates to Vapour.
- 2) Vapour migrates along cavity to lower temperature end of the Heat Pipe.
- 3) The Thermal Energy is released with help of a external device like fan and Vapour Condenses back to fluid and is absorbed by the Wick.
- 4) Working Fluid flows back to the higher temperature end of the Heat Pipe.

III. SPECIFICATION OF WORK

Heat pipe material : Copper Wick material : Poly-Phenylene Benzo Bisoxazole (a), Ultra-High-Molecular-Weight Polyethylene (b). Type of Wick : Screen Groove Length of Heat pipe: 210 mm



A. Input Data
Water Velocity = 0.01m/s
Heat inlet Temperature = 300 k
Evaporator Section Temperature = 350 k
Condenser Section Temperature = 280 k

B. Flow Calculation



Fig 3.1 Flow Calculation.

$=1.229 x 0.001 x 0.002 / 1.87 x 10^{-5} = 19.7$

The flow is blow 2000 so the Laminar based formula to be used in this Flow analysis.

C. Properties

Material	Density(k g/m ³)	C _p (specific heat)(j/kg-k)	Thermal conductivity	
Poly-Phenylene Benzo-				
Bisoxazole	1540	502.48	0.9	
Ultra-High-Molecular-				
Weight Polyethylene	949	1900	0.42	

Table 3.1 Properties Of Wick Materials.

D. Specification of Working Fluid Distilled Water Saturation Temperature = 323.15k Density =0.08306 kj/m³

IV. RESULT AND DISCUSSION

A. Poly-Phenylene Benzo Bisoxazole



Fig 4.1 Velocity Flow Water.

The above Figure 4.1 shows how the velocity flow of water inside the heat pipe and variations in the chambers is clearly shown for Poly-Phenylene Benzo Bisoxazole material.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue III Mar 2021- Available at www.ijraset.com



Fig 4.2 Temperature Contour Wick Structure.

The above Figure 4.2 shows how the temperature contour on the wick structure which indicates how the elements have been made and temperature distribution is shown clearly.



Fig 4.3 Temperature Over Wick Structure.

The above Figure 4.3 shows the temperature over the wick structure and gives the information how it varies from chamber to chamber.





The above Figure 4.4 shows the heat flux for the given input and shows how it is efficiently transfers the heat as heat flux.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue III Mar 2021- Available at www.ijraset.com

B. Ultra - High - Molecular - Weight Polyethylene



Fig 4.5 Velocity Flow Water.

The above Figure 4.5 shows how the velocity flow of water inside the heat pipe and variations in the chambers were clearly shown for Ultra-High-Molecular -Weight-Polyethylene material.



Fig 4.6 Temperature Contour Wick Structure.

The above Figure 4.6 shows how the temperature contour on the wick structure which indicates how the elements have been made and temperature distribution is shown clearly.



Fig 4.7 Temperature Over Wick Structure.

The above Figure 4.7 shows the temperature over the wick structure and gives the information how it varies from chamber to chamber.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue III Mar 2021- Available at www.ijraset.com



Fig 4.8 Heat Flux.

The above Figure 4.8 shows the heat flux for the given input and shows how it is efficiently transfers the heat as heat flux.

Table 4.1				
Material	Heat Flux(W/m ²)	Wick structure Temperature(K)		
Poly-Phenylene Benzo-Bisoxazole	2.198×10^4	316.099		
Ultra-High-Molecular-Weight	$1.544 \mathrm{x} 10^4$	317.345		
Polyethylene				

V. CONCLUSION

The study of computional flow dynamics (CFD) is used to analyse the performance of Heat Pipe. The analysis was done for various wick material with grooved wick structure. The heat pipe model is created, simulated using ANSYS FLUENT. The variation of heat flux was observed for various wick materials.

The summary of the present work as follows

- A. The CFD result for poly-phenylene benzo-bisoxazole at 300k is 2.198×10^4 (W/m²) and groove wick structure temperature is 316.099k.
- *B.* The CFD result for ultra-high-molecular-weight polyethylene at 300k is 1.544×10^4 (W/m²) and groove wick structure temperature is 317.345k.

From the above summary it is clear that poly-phenylene benzo-bisoxazole has high heat flux in comparison with ultra-high-molecular-weight polyethylene.

REFERENCES

- A. Siricharoenpanich, S. Wiriyasart, A. Srichat, P. Naphon, "Thermal management system of CPU cooling with a novel short heat pipe cooling system". Science direct Case Studies in Thermal Engineering 15 (2019) 100545.
- [2] Bertrand Delpech, Brian Axcell, HussamJouhara,." Experimental investigation of a radiative heat pipe for waste heat recovery in a ceramics kiln". ScienceDirect Energy 170 (2019) 636e651.
- [3] BurcuCICEK, NecmettinSAHIN, MahmutALKAN." Analysis of Chip on Board Packaging of High Power Led's with Heat Pipe Using Cfd for Street ".Gazi UniversityJournal of Science.GU J Sci 31(4): 1229-1244 (2018).
- Ch.Naveenkumar, P.VijayKumar†and K. DilipKumar. "Simulation and CFD Analysis of Heat Pipe with Different Wick Geometry using CFX". International Journal of Thermal Technologies.01 Sept 2015, No.3 (Sept 2015).
- [5] Chen-Ching Ting and Chien-Chih Chen."Analyzing the Heat Transfer Property of Heat Pipe Influenced by Integrated Cooling Apparatus". Hindawi Publishing CorporationChinese Journal of Engineering Volume 2014, Article ID 409074.
- [6] Dong Xu, Huiming Liu, Linghui Gong, Xiangdong Xu, Laifeng Li. "A novel pre-cooling system for a cryogenic pulsating heat pipe". ScienceDirect 25th International Cryogenic Engineering Conference and the International Cryogenic Materials Conference in 2014, ICEC 25–ICMC 2014.
- [7] Fangyi Qua, Hai Liub, Cheng Jianga, ChunshengGuoa,b,*, Yong Liua, Chengfu Zhang." Nickel-ammonia loop heat pipe based on the molten salt pore forming startup and heat transfer failure characteristics experimental study".ScienceDirect10th International Symposium on Heating, Ventilation and Air Conditioning, ISHVAC2017, 19-22 October 2017, Jinan, China.
- [8] Fei XIN, Ting MA, Qiuwang WANG," Theoretical analysis of flat heat pipe with graded-porosity wick design". ScienceDirectEnergy Procedia 142 (2017) 3932–3938.



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue III Mar 2021- Available at www.ijraset.com

- [9] Gavril Sosoia, Robert ȘtefanVizitiua, Andrei Burlacua, Cătălin Daniel Gălățanu."A Heat Pipe Cooler for High Power LED's Cooling in Harsh Conditions". ScienceDirect Procedia Manufacturing 32 (2019) 513–519.
- [10] Gong Chena, Yong Tanga,, Zhenping Wan, GuishengZhong, HengTanga,, Jian Zeng." Heat transfer characteristic of an ultra-thin flat plate heat pipe with surface functional wicks for cooling electronics". Science direct International Communications in Heat and Mass Transfer 100 (2019) 12-19.
- [11] Govinda Mahajan, Scott M. Thompson, Heejin Cho." Experimental characterization of an n-pentane oscillating heat pipe for waste heat recovery in ventilation systems". Heliyon 4 (2018) e00922.
- [12] HussamJouhara, SulaimanAlmahmoud, Amisha Chauhan, Bertrand Delpech Giuseppe Bianchi, Savvas A. Tassou, Rocio Llera Francisco Lago Juan Jose Arribas, "Experimental and theoretical investigation of a flat heat pipe heat exchanger for waste heat recovery in the steel industry". Science Direct Energy 141 (2017) 1928e1939.
- [13] HussamJouhara, A. Chauhan, T. Nannou, S. Almahmoud, B. Delpech, L.C. Wrobel." Heat pipe based systems Advances and applications". Science Direct EnerYaboWang, Xiaoqing Chen, Hailong Lia,." Dynamic performance of loop heat pipes for cooling of electronics". Science Direct Energy Procedia 142 (2017) 4163–4168.
- [14] HussamJouhara, Nicolas Serey, NavidKhordehgah, Robert Bennett, SulaimanAlmahmouda Stephen P Lester." Investigation, Development and Experimental Analyses of a Heat Pipe Based Battery Thermal Management System". Elsevier IJTF 100004.J. Venkata Suresh, P. Bhramara, CH." Navaneeth.Effect of Filling Ratio on Thermal Characteristics and Performance of a Pulsating heat ".International Journal of Innovative Technology and Exploring Engineering (IJITEE)ISSN: 2278-3075, Volume-9 Issue-2, December 2019.
- [15] J. Venkata Suresh, P. Bhramara, CH. Navaneeth." of Filling Ratio on Thermal Characteristics and Performance of a Pulsating heat Pipe". International Journal of Innovative Technology and Exploring Engineering (IJITEE)ISSN: 2278-3075, Volume-9 Issue-2, December 2019.
- [16] Kai Zhua, XueqiangLia, YaboWanga, Xiaoqing Chena, HailongLia."Dynamic performance of loop heat pipes for cooling of electronics". Science Direct . Energy Procedia 142 (2017) 4163–4168.
- [17] .Kai Zhu, XueqiangLia,b, Hailong Lia, Zhen Yang, Yabo Wang. "Experimental investigation on the effect of heat sink temperature on operational characteristics of a new-type loop heat pipe".Science Direct 10th International Conference on Applied Energy (ICAE2018), 22-25 August 2018, Hong Kong, China.
- [18] Kai Zhu, Mingzhu Zheng, Bin Wang, Baomin Dai, Yabo Wang, JieWei, Xiaoqing Chen. "Experimental study of energy saving performances in chip cooling by using heat sink with embedded heat". The 8th International Conference on Applied Energy – ICAE2016. Energy Proceedia 105 (2017) 5160 – 5165.
- [19] .L. Asmaie M. Haghshenasfard A. Mehrabani-Zeinabad M. Nasr Esfahany." performance analysis of nanofluids in a thermosyphonheat pipe using CFD modeling.springer". ISSN 0947-7411Volume 49 Number 5.
- [20] Leonard L. Vasiliev. "Heat pipes in modern heat exchangers". Science Direct Applied Thermal Engineering 25 (2005) 1–19.
- [21] LI Yunzea, LI Mingmin, LEE KokMeng." A Dual-driven Intelligent Combination Control of Heat Pipe Space Cooling System". Elsevier Chinese Journal of Aeronautics 25(2012) 566-574.
- [22] Rakesh K. Bumataria , N.K. Chavda , Hitesh Panchal." Current research aspects in mono and hybrid nanofluid based heat pipe technologies". Elsevier Heliyon 5 (2019) e01627.
- [23] SantiphapNakkaew ,, ThunyawatChitipalungsri , HoSeonAhn , Dong-WookJerng , Lazarus Godson Asirvatham , Ahmet SelimDalkılıç , Omid Mahian , SomchaiWongwises." Application of the heat pipe to enhance the performance of the vapor compression refrigeration system". Elsevier Case Studies in Thermal Engineering 15 (2019) 100531.
- [24] SulaimanAlmahmoud, HussamJouhara." Experimental and theoretical investigation on a radiative flat heat pipe heat exchanger". Elsvier Energy 174 (2019) 972e984.
- [25] Zirong Lin, Shuangfeng Wang, Ryo. Shirakashi, L. Winston Zhang. "Simulation of a miniature oscillating heat pipe in bottom heating modeusing CFD with unsteady modeling. International Journal of Heat and Mass Transfer". 57 (2013) 642–656.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)