



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: IV Month of publication: April 2021

DOI: https://doi.org/10.22214/ijraset.2021.33684

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Comparative Analysis of Overhead Water Tank

Prasad D. Konde¹, Bharati Changhode²

¹P.G. Student, ²Assistant Professor, Department of Civil Engineering, G. H. Raisoni University, Amravati, Maharashtra, India

Abstract: Water tanks are important public utility and industrial structure. The design and construction methods used in reinforced concrete are influenced by the prevailing construction practices, the physical property of the material and the climatic conditions. Before taking up the design, the most suitable type of staging of tanks and correct estimation of loads including statically equilibrium of structure particularly in regards to overturning of overhanging members are made. The work presented in the research paper consists of the comparative analysis of the overhead water tank in terms of the shear force, bending moment and other parameters.

Keywords: Hydrodynamic Pressure, Elevated Water Tank, STAAD Pro V8i.

I. INTRODUCTION

Storage reservoirs and overhead tank are used to store water, liquid petroleum, petroleum products and similar liquids. These structures are made of masonry, steel, reinforced concrete and pre stressed concrete. Out of these, masonry and steel tanks are used for smaller capacities.

The cost of steel tanks is high and hence they are rarely used for water storages. Reinforced concrete tank is high and hence they are rarely used for water storages. Reinforced concrete tanks are very popular because, besides the construction and designs being simple, they are cheap, monolithic in nature and can be made leak proof. Generally no cracks are allowed to take place in any part of the structure of liquid retaining R.C.C tanks and they made water tight by using richer mix (not less than M20) of concrete. In addition sometimes water proofing materials are also used to make tanks water tight. Permeability of concrete is directly proportional to water cement ratio.

Proper compaction using vibrators should be done to achieve imperviousness. Cement content ranging from 330 Kg/m3 to 530 Kg/m3 is recommended in order to keep shrinkage low.

II. REVIEW OF LITERATURE

Manjare, S.A. et al [1] studied that for same capacity, same geometry, same height, with same staging system, in the same Zone, with same Importance Factor & response reduction factor; response by Equivalent Static Method to Dynamic method differ considerably. Simpi, B., et al [2] studied Static analysis water- structure interaction shows that both water and structure achieve a pick at the same time due to the assumption that water is stuck to the container and acts as a structure itself and both structure and water has same stiffness, while in Dynamic analysis we considered two mass model.

Solé, C., et al [3] studied that Column moment in bracing increases by increasing height of staging of water tank. Column moment is minimum for radial bracing. Shear force in bracing increases by increasing height of staging. Shear force in bracing is minimum for radial bracing.

III. MODELING

The modeling is carried out in the STAAD software, mentioned as follows.

The following models are prepared in the project

- 1) Model-I: Rectangular water tank-6m height by IS code
- 2) Model-II: Rectangular water tank-9m height by IS code
- 3) Model-III: Rectangular water tank-12m height by IS code
- 4) Model-IV: Rectangular water tank-6m height by ACI code
- 5) Model-V: Rectangular water tank-9m height by ACI code



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IV Apr 2021- Available at www.ijraset.com

Fig. No.1: Model-I: Rectangular water tank-6m height by IS code



Fig. No.2: Elevation of Model-I



Fig. No.3: Model-II: Rectangular water tank-9m height by IS code



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IV Apr 2021- Available at www.ijraset.com

Table No.1: Properties of Model-I & IV

Particulars	Dimension
Plan dimension of water tank	4.0 m X 6.0 m
Depth of water tank	2.0 m
Thickness of water tank	200 mm
Height of Column	6.0 m
Size of Beam	350 mm X 500 mm
Size of Column	400 mm X 600 mm

IV. RESULTS

The analysis is carried out in STAAD software and the results in terms of shear force, bending moment and other parameter is obtained as follows.



Fig. No. 6.1: Max Absolute stress of Model-I



Fig. No. 6.2: Max Bottom Principal stress of model-I



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IV Apr 2021- Available at www.ijraset.com

σ× STAAD.Pro V8i (SELECTseries 6) - Model-1-9m <u>File Edit View Tools Select Results Report Mode Window Help</u> 1919年日期以后×○≠○≠☆日請/ ●0,2014月月10 14日11日以来:21月 22日2月 0日 4日 4日 11日 2日 3日日日日 🗗 🗭 🗑 🛱 🛱 🛱 🗘 🕂 💠 💠 💠 🕹 😳 🚸 🔠 🛱 🤁 🕀 🍳 Q 🖉 🖗 🖉 🖉 🛠 👌 🦹 💈 GENERATED INDIAN CODE GEN 🗸 <u> / 玛莱氏 職 ↓ ② 田 | ぶ ぶ 米 G 田 / | № 竹 大 @ 塩 ≫ 9 個 句 / 5 |</u> 2 * <u>*</u> 6 14 Andeling Building Planner Piping Bridge Deck Postprocessing Foundation Design Steel Design RAM Connection Concrete Design Advanced Slab Design A* - - -[#] Model-1-9m - Whole Structu • X Node Shear, Membrane and Bending Max Absolute N/mm2 She N/mm2 <= 0.159 0.445 r SQX (local) SQY (local Beam Plate L/C Line 0.732 486 1 DL 2 GENERATE 3 GENERATE -0.023 -0.018 .02 Along -0.027 Plate 4 GENERATE 487 1 DL -0.020 -0.014 0.025 0.038 0.031 0.023 0.007 -0.002 1.59 1.88 2.16 -0.004 -0.003 **24** Animation 2.45 2.74 3.02 3.31 3.6 3.88 4 GENERATE Dage: 488 1 DL -0.007 < Reports Shear, Membrane and Bending 3.88 4.17 4.46 >= 4.74 子 口 以 岐 倉 SQX (local) Plate L/C Node Dynamics 486 1 DL 153 -0.010 -0.010 1000 -0.035 -0.035 -0.016 -0.016 t 2 GENERAT Ċh, de la como 1 254 -0.053 -374 -0.053 the state 3 GENERAT -0.013 函 ZX . . Load 2 1. Click on plates to select (Ctrl+click to toggle selection) Post Mode Load 2 : GENERATED INDIAN Input Units: kN-m

Fig. No. 6.3: Maximum Absolute stresses for model-II



Fig. No.4: Maximum Tau stresses for model-II





Fig. No.5: Maximum absolute stresses for model-III



Fig. No.6: Maximum principal stresses for model-III



Fig. No.7: Maximum absolute stresses for model-IV



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IV Apr 2021- Available at www.ijraset.com

STAAD.Pro V8i (SELECTseries 6) - Model-1-🗃 🗗 🗗 🛱 🛱 🛱 🗧 🕂 🕂 中 中 🧿 💿 🚸 📗 🛄 🔍 🕀 🍳 🍳 🔍 🖉 🖉 🗶 🗶 👔 🐒 🛃 🕴 👔 Z GENERATED ACI TABLE 1 1 - 💷 🏹 ÷ ± 15 84 Building Planner Piping Bridge Deck Postprocessing Foundation Design Steel Design RAM Connection Concrete Design Advanced Slab Design 2 4 5 4 3 × 6 8 8 8 8 × 5 @ M Node I Shear, Membrane and Bending Max Bottom (Principal M Stress) Stress) N/mm2 Shear SQX (local) SQY (local) r Beam L/C -1.17 Plate ł .845 0.021 0.015 0.004 0.006 0.005 0.005 -0.166 -0.126 -0.147 -0.206 -0.177 -0.133 -0.153 GENERAT .519 Animation 0.091 T Reports A A DIN Shear, M nbrane and Bending 2.09 2.41 2.74 3.06 3.39 >= 3.72 SQX (la in Dynamics 0.046 -0.325 -0.325 0.064 0.064 -0.455 -0.455 0.055 2 GENERA Ch. 3 GENERAT Ĭ_z× 120 (Ctrl+click

Fig. No.8: Maximum Bottom Principal stresses for model-IV



Fig. No.9: Maximum absolute stresses for model-V



Fig. No.10: Minimum Top principal stresses for model-V

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IV Apr 2021- Available at www.ijraset.com

V. CONCLUSION

The conclusions from the above study are as follows:

- A. The models are compared for different height and the code
- *B.* The nodal displacement and nodal reactions are higher for the higher height water tank
- *C*. The calculation of shear stress, membrane stress, principal stress, von mis stress and Tresca stresses are obtained for all the models.
- D. The stresses are found to be lower for the lower height of water tank
- E. The storey drift is found to be increasing as the height of the water tank increases.

REFERENCES

- Anil Baral and Manjare, S.A., Vhanalakar, S.A. and Muley, D.V., 2010. Analysis of water quality using physicochemical parameters Tamdalge tank in Kolhapur district, Maharashtra. International Journal of Advanced Biotechnology and Research, 1(2), pp.115-119.
- [2] Simpi, B., Hiremath, S.M., Murthy, K.N.S., Chandrashekarappa, K.N., Patel, A.N. and Puttiah, E.T., 2011. Analysis of water quality using physico-chemical parameters Hosahalli Tank in Shimoga District, Karnataka, India. Global Journal of Science Frontier Research, 11(3), pp.31-34.
- [3] Solé, C., Medrano, M., Castell, A., Nogués, M., Mehling, H. and Cabeza, L.F., 2008. Energetic and exergetic analysis of a domestic water tank with phase change material. International journal of energy research, 32(3), pp.204-214.
- [4] Nabavitabatabayi, M., Haghighat, F., Moreau, A. and Sra, P., 2014. Numerical analysis of a thermally enhanced domestic hot water tank. Applied energy, 129, pp.253-260.
- [5] Nayaka, B.S., Ramakrishna, S. and Delvi, M., 2009. Impact of heavy metals on water, fish (Cyprinus carpio) and sediments from a water tank at Tumkur, India. Oceanological and Hydrobiological Studies, 38(2), pp.17-28.
- [6] Singh, N.J. and Ishtiyaque, M., 2015. Design Analysis & Comparison Of Intze Type Water Tank For Different Wind Speed And Seismic Zones As Per Indian Codes. International Journal of Research in Engineering and Technology, 4(09).
- [7] Lokeshwari, H. and Chandrappa, G.T., 2007. Effects of heavy metal contamination from anthropogenic sources on Dasarahalli tank, India. Lakes & Reservoirs: Research & Management, 12(3), pp.121-128.
- [8] Ravikumar, P., Mehmood, M.A. and Somashekar, R.K., 2013. Water quality index to determine the surface water quality of Sankey tank and Mallathahalli lake, Bangalore urban district, Karnataka, India. Applied water science, 3(1), pp.247-261.
- [9] Chawla, S., Jamle, S. and Meshram, K., 2020. A Review on Economical Design of Intz Water Tank as per IS-875-III, for Wind Speed in India. International Journal of Advanced Engineering Research and Science, 7(1).
- [10] Godfrey, S., Labhasetwar, P. and Wate, S., 2009. Greywater reuse in residential schools in Madhya Pradesh, India—A case study of cost-benefit analysis. Resources, Conservation and Recycling, 53(5), pp.287-293.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)