



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: V Month of publication: May 2021

DOI: https://doi.org/10.22214/ijraset.2021.34781

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



A Review Paper on: Design of Reconfigurable Microstrip Antenna with Low Noise for Wi-Max Applications

Ms. Rohini Pochhi, Ms. Sonal Tikale

¹(HOD), ²Dept. of Electronics & Communication Engg

Abstract: A compact, single feed, multi frequency style of reconfigurable microstrip antenna with varied slots are given during this paper. An oblong patch loaded with horizontal slots having extended slot arms constitutes the basic structure of the antenna. The standardization of the multi resonant frequencies is completed by variable the effective electrical length of the slots by loading varactor diodes across the slots. A size reduction of eighty four for the lower operative frequency is obtained in comparison to standard rectangular microstrip patch. Planned antennas are helpful for multi-band wireless applications like GSM1800, IMT2000, WLAN etc operating over a good vary of bands. Measured and simulated results of come back loss, antenna gain and radiation patterns also are discussed.

Keywords: Single feed, multi frequency, WLAN, rectangular patch, return loss.

I. INTRODUCTION

With the advancement in wireless communications, there's a requirement to implement antennas that are "smart" to tune their operational characteristics (frequency, polarization, radiation pattern) consistent with the ever ever- changing communication needs. Moreover, victimization 2 antennas to hide every of the various wireless services that are scattered over a large frequency bands that will increase the system cost, the house requirements for the antennas, and their isolation. Reconfigurable antennas are potential candidates for future RF front-end answer to reduce the quantity of antennas needed in an exceedingly specific system.

Reconfigurable antennas are extensively studied over last two decades. this sort of antenna needs shift parts to alter the antenna electrical properties yet as its radiation characteristics. Electrically reconfigurable antennas use RF-MEMS, p- i-n diodes, varactors to perform the desired tunability within the antenna functionality. The activation/deactivation of those switching elements requires the incorporation of biasing lines in the diverging plane of the antenna. Therefore, the interference of these lines on the magnetic force properties of the antenna has to be minimized. This paper presents novel compact styles of single feed, reconfigurable twin frequency rectangular microstrip antennas capable of achieving high standardisation ranges while not victimization any matching networks. varied slots on an oblong patch are accustomed generate multi resonant frequencies. Varactor diodes are integrated across the slot arms that tune the resonant frequencies considerably. The important aspect of this design is that it provides a size reduction of 84% for the lower operating frequency, compared to conventional rectangular patch antenna. The radiation pattern, gain and polarization are essentially unaffected by the frequency tuning, which is essential characteristic for frequency reconfigurable microstrip antennas.

A. Brief Literature Survey

H. A. Majid, M. K. A. Rahim, M. F. Ismail, M. R. Sani "Frequency reconfigurable microstrip patch antenna", applied electronics (AGPCE) 2012 IEEE Asia-Paciffic Conference on Date-11-13 Dec-2012

In this paper a frequency reconfigural microstrip patch antenna is proposed three switches are used to produce six reconfigurable frequencies.

A. H. Ramadan, K.Y. Kabalan, A. EI- Haji, S. Khoury and M. Al-Husseini," A Reconfigurable U-koch microstrip antenna for wireless application", ECE department American University of Beirut

P. O. Box 11-0236, Bliss street, Beirut, 1107 2020, Lebanon.

In this paper the proposed antenna is simulated using the finite –element method for three different switching cases and the return loss is measured for each case.

II. PROBLEM FORMULATION

This paper presents novel compact styles of single feed, reconfigurable twin frequency rectangular microstrip antennas capable of achieving high standardization ranges while not victimization any matching networks. varied slots on an oblong patch are wont to generate multi resonant frequencies. Varactor diodes are integrated across the slot arms that tune the resonant frequencies considerably.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue V May 2021- Available at www.ijraset.com

The necessary facet of this style is that it provides a size reduction of eighty four for the lower operative frequency, compared to standard rectangular patch antenna. The radiation pattern, gain and polarization are basically unaffected by the frequency tuning, that is essential. 2 slot antenna characteristic for frequency reconfigurable microstrip antennas.

III. OBJECTIVES

The main objective of this paper is to have the conventional patch antenna is designed for 2.4 GHz the rectangular patch antenna is fabricated on glass epoxy substrate $\epsilon r =$

4.4 with thickness (h) of 1.6 mm, width of the patch is W=30mm and length L=40mm. Simulated and measured results of return loss are shown in Fig.1. These results are good agreement with each other. At first, in order to have three different resonance frequencies without considering the switches in the design, two horizontal slots have been placed on patch position of the antenna. Matching for each of the resonance frequencies is achieved by the theory of off-centered microstrip- feed slot antennas [3, 4]. By etching two slots on patch position of the antenna the simulated and measured return losses are in good agreement. Two slots on conventional antenna design is designed and fabricated and it is called as two slot antenna as shown in Fig.4.



Figure 1: A Typical Microstrip Patch Antenna

The breadth of all the slots is ready around to 1mm. the employment of two slots makes offers size reduction that is because of the excitation of each horizontal and vertical currents of the slots. it's additionally found that the radiation diagram of the 2-slot antenna has smart co-polar and cross polarized levels. Such slot doesn't have any effects on the far-field radiation characteristics. it's also studied that the various orientation slots is for having lower mutual coupling between the slots. The simulation and measured come losses are shown in Fig.2. the precise positions for diodes are found throughout the planning by numerous simulations iterations with completely different positions. it's mentionable that because the diodes are loaded remote from the co axial feed leads to broadsided radiation patterns. Hence, the varactor diode is placed 0.2 millimetre from the sting of every slot. The planned reconfigurable antenna is as shown in Fig.4.







Figure 2(b): Measured Curve for Patch Antenna

Fig.3 (a) with slots on top edge, middle and bottom edge of the patch. Simulated and measured return losses are shown in Fig.3 (b) and respectively. The proposed reconfigurable antennas are simulated using matlab software. The simulated patterns in the E planes are shown in Fig. From Fig. 3, it is clear that, the radiation pattern of such resonance does not change when the diodes turn off or on, which leads to the same pattern for the same resonance in different states.



Figure 3: Radiation pattern characteristics of the presented reconfigurable passive and active antennas in dB and at

a 3.5 GHz b 2.4 GHz International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue V May 2021- Available at www.ijraset.com

IV. PROPOSED SYSTEM

The bestowed reconfigurable microstrip monopole Associate in Nursingtenna structure with its style parameters is shown in Fig. 4. The designed antenna is written on an FR4 substrate with a thickness of 1.6 mm, permittivity of 4.4 and loss tangent of 0.018. The passive antenna structure consists of a truncated rectangular ground plane, a microstrip feed-line and a changed divergent patch that itself consists of two-folded arms and a microstrip stub which is placed between the two-folded arms. So as to divide the input among the collapsible arms and also the microstrip stub which is placed between them, the microstrip feed-line is modified at its intersection finish with the divergent patch. A surface-mount assembly instrumentation is connected to the opposite end of the feed-line for signal transmission, as are often determined in Fig. 4.

In the planned antenna structure so as to style a completely unique multiband antenna, rather than mistreatment typical rectangular or circular formed patches a mixture of two- folded arms with a microstrip stub between them is employed because the diverging stub. mistreatment this structure ends up in extra surface current methods which ends up to completely different resonance frequencies [4, 5]. The initial length of the rolled-up arms are chosen appreciate the WLAN band frequency (lg/4 at the centre waveband of 2.4 GHz) and therefore the length of the microstrip stub between the two-folded arms is correspondent to the WiMAX band frequency (lg/4 at the centre waveband of 3.5 GHz), wherever lg is that the radio- controlled wavelength [8], then a constant study has been conducted so as to attain an appropriate compromise between the antenna frequency responses at each higher and lower resonance frequencies The planned reconfigurable antennas are simulated mistreatment Zeeland IE3D software.



Figure 4: Geometry of the proposed passive reconfigurable antenna

BIBLIOGRAPHY

- [1] Y. Tawk, J. Costantine, and C. G. Christodoulou "A varactor-based reconfigurable filtenna" ieee antennas and wireless propagation letters, vol. 11, pp.716-719, 2012.
- [2] S. V. Shynu, G. Augustin, C. K. Aanandan, P. Mohanan, and K. Vasudevan "Design of compact reconfigurable dual frequency microstrip antennas usingvaractor diodes", Progress In Electromagnetics Research, PIER 60, pp.197–205, 2006.
- [3] R. Garg, P. Bhartia, I. Bahl, and A. Iittipiboon, Microstrip Antenna Design Handbook. Boston, MA: Artech House, 2001.
- [4] J. P. Kim and W. S. Park, "Network modeling of an inclined and off center microstrip-fed slot antenna," IEEE Trans. Antennas Propag., vol. 46, no. 8, pp. 1182–1188, Aug. 1998.
- Bahramzy, P., Jagielsky, O., Svendsen, S., Pedersen, G.: 'Compact agile antenna concept utilizing reconfigurable front end for wireless communications', IEEETrans. Antennas Wirel. Propag., 2014, 62, (9), pp. 4554–4563.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)