



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: VII Month of publication: July 2021

DOI: https://doi.org/10.22214/ijraset.2021.36453

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Design and Implementation of LEACH Protocol for Wireless Sensor Network to Reduce for Network Area Energy Improvement and Security Using MATLAB

Ms. Pranali Ikharkar¹, Dr. N. K. Choudhari², Dr. Ms. D. M. Kate³

¹PG Student, Department of EC Engineering, Priyadarshini Bhagwati College of Engineering, Nagpur, India ²Professor, Department of EC Engineering, Priyadarshini Bhagwati College of Engineering, Nagpur, India ³Assistant Professor, Department of EC Engineering, Priyadarshini Bhagwati College of Engineering, Nagpur, India

Abstract: In this Paper Wireless Sensor Networks (WSNs) have exploded in popularity in recent years as one of the fastestgrowing developing technologies for delivering data over the internet. WSN is rapidly expanding its branches in practically every field of science and technology today. The WSN is made up of several tiny nodes that handle sensing, data collecting, aggregation, compression, and transmission. Because the sensor nodes are so small, the little battery only has a limited amount of power. As a result, the key issue for WSN is to effectively employ this insufficient battery capacity to extend the sensor networks' lifetime while reducing energy usage. However, when it comes to numbers, However, a number of advanced clustered routing protocols have already been used in WSN to reduce the amount of energy consumed. The study's main goal is to improve the Low Energy Adaptive Clustering Hierarchy (LEACH) protocol by implementing a new clustering routing topology. The process for selecting cluster heads in our proposed model is identical to that used in the standard Leach protocol. We have, however, partitioned the network's whole area into many rectangle dispersed sections. The LEACH algorithm was used in each area.

Keywords: LEACH Protocol, WSN

I. INTRODUCTION

WSN has seen an upsurge in attention in recent years as a result of its employment in several sectors such as military, medicinal, and environmental applications [1, 2]. The WSN is made up of a large number of low-power microsensor nodes that are spread across a vast area and have at least one BS [3]. Every micro-sensor collects data about physical or environmental parameters such as pressure, temperature, humidity, and so on [4] and sends it back to the BS. The placements of the nodes in a WSN are not preset, allowing the network to organise itself autonomously [5, 6]. contains sensor nodes that are randomly scattered, a BS that receives all data obtained from the environment, and the user who obtained data through The power unit is one of the most significant units. Because the batteries can't be recharged or changed, sensor nodes in such an environment are energy-constrained [3]. As a result, building an energy-aware protocol has piqued attention as a means of extending network longevity [8]. As a result, in most applications where all sensor nodes are bound by energy, which is connected to the network's lifetime, energy consumption is the most critical element. The limited power of nodes necessitates the creation of an energy-saving communication protocol An organisation of organisations is called an internetwork, or just the web. It is the biggest organisation in presence on this planet. The web massively interfaces all WANs and it can have association with LANs and Home organisations. The Web makes use of the TCP/IP protocol stack and IP as its default protocol. In today's world, IPv4 is widely used to access the Internet. It is gradually migrating from IPv4 to IPv6 due to a scarcity of address spaces. (WSN) is a correspondence stage that can have an impact on a few Data Correspondence characteristics in the future. WSN has gotten a lot of attention recently because of its various applications in a variety of domains of human effort. WSNs are wireless sensor networks.

WSN's popularity continues to expand, with applications ranging from military to public, ground, and space. WSN has risen as a result of advancements in the creation of microelectromechanical systems (MEMS) and in distant commerce. WSNs have become a fascinating field of research in recent years; a WSN is made up of a couple of sensor centres (distant) that work together to form a sensor field and a sink.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com

The enormous number of centres used, their low power rating, and their impediment to short division correspondence are the major issues in the WSN. These centre points participate in information identifying, following, and transmission, making the distant locations accessible.. The enormous number of centres used, their low power rating, and their impediment to short division correspondence are the major issues in the WSN. These centre points participate in information identifying, following, and transmission, making the far away sensors useful for checking ordinary events and characteristic changes, surveying traffic advancements, and controlling security..

II. LEACH PROTOCOL

LEACH was created with the goal of lowering energy consumption. It has some advantages, such as the fact that each node can evenly divide the charge imposed at CHs to a degree because any sensor node that was selected as a CHs sensor can be used. A CH can't be reselected as a CH in some epochs yet [23]. Furthermore, the use of the TDMA prevents CHs from colliding. It does, however, have significant drawbacks, since it impairs single-hop when CHs are active. direct communication with the sink Furthermore, long-distance communication between the CH and the BS consumes more energy, making LEACH unsuitable for big networks.

The majority of remote sensor networks (WSNs) are made up of powerful sensor hubs (SNs) with minimal energy. WSNs are distributed arbitrarily in a given region in order to gather various types of ecological boundaries and to transfer data to the base station (BS) for monitoring and differentiating purposes. They've been widely used in backwoods fire detection, observation, military, human health identification, and other applications, and as a result, they've become a legitimate concern for analysts recently. Because WSNs are frequently transported in hazardous situations, recharging or replacing the SNs' batteries is particularly difficult. Wireless sensor networks have become increasingly popular in recent years. Sensor node life time is the most important metric in Wireless Sensor Networks. In the design of sensor network applications and protocols, minimising energy dissipation and optimising network longevity are critical considerations. Distributed cluster construction, local processing to decrease global communication, and randomised cluster-head rotation are all part of LEACH. A wireless sensor network is made up of hundreds or thousands of tiny, energy-constrained sensors that are densely distributed across a vast geographic area. LEACH (Low-Energy Adaptive Clustering Hierarchy) has been shown to be an energy-efficient clustering algorithm. We describe a cluster head selection strategy for LEACH in this research. We provide the LEACH concepts as well as the primary flowchart and algorithms for implementing LEACH. We enhance the cluster head selection approach by designating selected nodes with higher residual energy as cluster heads in the following round. We're looking for an energy-efficient network upgrade that increases network lifespan while still providing complete area coverage and sensor connections to cluster heads

III. METHODOLOGY

The fact that radio connections are reliant on transmission control, concealing, and impedance, which sabotage data transport execution, is a basic test in far-flung frameworks. This challenge is worsened in far-flung sensor networks (WSNs), when true necessity and resource constraints prevent the adoption of advanced approaches used in other remote systems. The most important, practical arrangement, which relies on a method of active bundle length management to accelerate execution in these changing settings. There is a tradeoff between the desire to reduce header overhead by making packs large and the want to reduce package bungle rates (PER) inside the packages

Wireless sensor networks have become increasingly popular in recent years. Sensor node life time is the most important metric in Wireless Sensor Networks. In the design of sensor network applications and protocols, minimising energy dissipation and optimising network longevity are critical considerations. Distributed cluster construction, local processing to decrease global communication, and randomised cluster-head rotation are all part of LEACH. A wireless sensor network is made up of hundreds or thousands of tiny, energy-constrained sensors that are densely distributed across a vast geographic area. LEACH (Low-Energy Adaptive Clustering Hierarchy) has been shown to be an energy-efficient clustering algorithm.

They have been generally applied in backwoods fire discovery, observation, military, human wellbeing identification, and so on, and accordingly have pulled in light of a legitimate concern for analysts lately .On the grounds that WSNs are typically conveyed in unsafe conditions, reviving or supplanting the batteries of the SNs is exceptionally troublesome.

Besides, the manual activity of the organization is profoundly troublesome, which brings a few difficulties with respect to the utilization of WSNs .To cure these downsides, the effective utilization of the battery energy of SNs ought to be considered as an essential objective when analysts plan conventions and equipment structures Consequently, a few steering conventions have been proposed to deliver the sensor network more energy proficient



IV. CLUSTERING SYSTEM



Fig III Block diagram for Clustering system

In the Fig III The data unit and the energy unit has a new multi-hop routing algorithm clustering head Formation into groups to minimize the total energy consumption and improve scalability of the WSN. Moreover, the protocol increases the balance of energy dissipation, scalability and reliability of WSN.

V. PHASES OF LEACH PROTOCOL

In proposed work, presents the current works identifying with our plan. Different sorts of get-together based planning shows have been proposed for far off sensor affiliations. These can be masterminded into two sorts of focus focuses called Static and Versatile Hubs. Channel is extraordinary grouping show for distant sensor affiliations. In Drain, the focuses are worked with themselves into neighborhood packs. Each middle point has an equivalent beginning energy in view of homogeneous affiliations. The development is distributed changes. In the set-up stage, the CH is investigated the coordinated packs if an abstract number some spot in the extent of 0 and 1 picked by CH isn't whatever amount of edge respect. In the anticipated state stage each non. The CH aggregates the information and sends it to the BS. In any case, the social event progression is started in each round isn't energy fit what's more it doesn't look after movability. The Filter Portable show is keeps up sensor community directs adaptability in WSN by adding selection verification toward the current Drain show. The Filter Versatile outperformsLEACH concerning bundle misfortune in mobility climate. In any case, it needs selection revelation. Social event head political race in Drain Versatile has been improved by Filter Portable Upgraded (Filter ME) as proposed whereby the sensor community with least movability factor is picked as pack head.CBR-Versatile help the sensor habitats convenientce by adaptively reassigning the timeslots as per sensor focuses flexibility and traffic. Two proprietors are made for each time that is exceptional proprietor and elective proprietor, with a definitive target that CBR-Versatile can work adaptively to sensor focus focuses conveyability and traffic. It is all things considered structures the bundle transport degree in evaluation with the Drain Versatile show. It needn't mess with any extra timeslot for discovering the adaptability of sensor focus. So it give quicker datadelivery to BS.Cluster-based Energy-able Plan (CES) for Mobile Remote Sensor Organizations (MWSNs) which depends onweighing kdensity, holding up energy and adaptability parameters for group head political decision. The CES plot does a periodical clusterhead political decision measure after each round. Moreover, CES empowers the making of changed 2-hopclusters whose size ranges between two edges calledupper and lower edgesChannel show gets the strategy that picks group heads arbitrarily, which avoids the social occasion head to be foreboding kicking the compartment because of the breaking point certification of energy and plan the marvel of checking a visually impaired region. Other than data blend appropriately diminishes the extent of data discussion. Thusly, regarding the by and large controlling shows and static organizing show, Drain show can develop the presence of inaccessible sensor network commonly 15%. Close to the ideal conditions attested by utilizing group managing protocols, a. Channel show does genuine variables mix at some point of records transmission, which diminishes the troubling data and extents the energy.



Fig IV. Phases of LEACH Protocol

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com

VI. OUTPUT



Fig V.1 Shows the No of Alive Niodes over time with respect to the dead Node.

The presented figure demonstrates the lifetime the network for our proposed protocol in comparison with the basic LEACH It also shows that the number of nodes that have been died e device is counted as a dead node and is unable to function further in terms of information transmission. To elaborate it more, this is counted as in which round the first sensing device will lose its energy (i.e., die).



Fig V.2 Shows the total number of Packets send to the sink Node during the interval of time t

The above fig shows the the total number of Packets send to the sink Node during the interval of time t The number of data packets received by the base station is also a parameter for evaluating the high energy utilization rate. The more balanced the energy distribution in the network, the more packets the base station receives. The significant increase in packet counts received by the base station is due to reduce the probability of cluster head clusters and effective reduction of energy consumption of negotiated communication within the cluster.



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com



Fig V.3 Indicates The Total Remaining Energy Of The System In Joules(J) with respect to the total energy of the network with respect to time

The above fig indicates the Node energy consumption is divided into mainly four parts: data transmission, data reception, data fusion, and negotiation communication within the cluster. The more uniform energy consumption the longer lifetime nodes alive ecause node energy consumption is more balanced, there is a large area of node death, which will not affect its energy consumption, and energy consumption per unit node



Fig V.4 Indicates the overall graph with respect to Leach ,Leach Mod and Eip Leach in terms of the number of rounds in the nodes

According to the MATLAB simulation data, the protocol can significantly prolong the lifetime of WSNs compared with the LEACH protocol and increase the energy efficiency per unit node in per round. Energy consumption of the proposed approach is only. The above overall graph with respect to Leach, Leach Mod and Eip Leach in terms of the number of rounds in the nodes

VII. CONCLUSION

Change of Channel show is proposed in this paper by describing unused count for CH choice. The anticipated outcome should include the extended lifespan of far off sensor sort out after the modification and execution of figuring in MATLAB programming. The study between the existing EiP-based and ICH-based versions of this revised Channel will be completed very soon. This proposed flaming parcel length streamlining strategy will provide accuracy in connection evaluation, increasing bundle transport extent, structure throughput, and effective essentialness use. LEACH is the simplest and most efficient of the various hierarchical routing techniques. LEACH's simple and adaptable character qualifies it for usage as a foundation for a variety of different procedures, and that's also what drew us to research it. MATLAB has been used to implement and evaluate LEACH. We may infer that LEACH is more efficient in terms of lifetime, throughput, and energy dissipation than typical routing protocols [4]. The energy use of each sensor node is equally distributed and lowered when cluster chiefs are elected among the number of sensor nodes.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429

Volume 9 Issue VII July 2021- Available at www.ijraset.com

REFERENCES

- W. Heinzelman, A. Chandrakasan and H. Balakrishnan."Energy-efficient communication protocols for wireless microsensor networks", Proceedings of the 33rd Hawaii International Conference onSystems Sciences, pp.1-10, Hawaii, 2000.
- Wendi,B.Heinzelman, Anantha P.Chandrakasan and Hari Balakrishnan"An Application specific protocol architecture for wireless Micro-sensornetworks,"IEEE Transactions on wireless communications vol.1 NO.4 2002.
- [3] Do-Seong Kim and Yeong-ee Chung, "Self Organization RoutingProtocol Supporting Mobile Nodes for Wireless Sensor Network Proceedings of the First International Multi Symposiums on Computerand Computational Sciences (IMSCCS'06), 2006.
- [4] G. S. Kumar, M. V. Vinu Paul, G.Athithan and K. P. Jacod, "Routing Protocol enhancement for handling node mobility in wireless sensor network", TENCON 2008 – 2008 IEEE Region 10 Conf, 2008, pp. 1-6.
- [5] Lehsaini M., Guyennet H. and Feham, M. "Wireless Sensor and ActorNetworks II," 2008, in IFIP International Federation for InformationProcessing, Volume 264; (Boston: Springer),
- [6] S. A. B. Awwad, C.K. Ng, N. K. Noordin and M. F. A. Raisd, "Cluster Based routing protocol for mobile node in wireless sensor network," in collaborative technologies and system, 2009. CTS '09. International Symposium on, 2009, pp. 233-241.
- [7] Razieh Sheikhpour, Sam Jabbehdari and Ahmad Khadem-Zadeh"Comparison of Energy Efficient Clustering Protocols inHeterogeneous Wireless Sensor Network,zs," International Journal of AdvancedScience and Technology Vol. 36, November, 2011.
- [8] V.Katiyar et al.. "Improvement in LEACH protocol for large-scale wireless sensor networks", International Conference on Emerging Trends in Electrical and Computer Technology (ICETECT), pp.1070-1075, Tamil Nadu, 2011.
- [9] Lutful Karim and Nidal Nasser "Energy efficient and Fault TolerantRoutingprotocol for mobile Sensor Network," IEEEICC2011 processdings.
- [10] Rabia Noor Enam, Mumtazul Imam and Rehan Inam Qureshi "Energy Consumption in Random Cluster Head selection Phase of WSN," 2012 IACSIT Hong Kong Conferences IPCSIT vol. 30 (2012) © (2012)IACSIT Press, Singapore.
- [11] Z. Aliouat an M. Aliouat. "Improving wireless sensor networks robustness through multi-level fault tolerant routing protocol", In the proceeding of the fourth International Conference on Modelling Approaches and Algorithms for Advanced Computer Applications (CIIA'2013), pp.115-124, Saida, Algeria, 2013.
- [12] El korbi et al. "Coverage-Connectivity based faulttolerance procedure in wireless sensor networks". In the Proceeding of the9th International Conference on Wireless Communications and Mobile ComputingConference (IWCMC'2013), pp.1540-1545, Sardinia, Italy, 2013.
- [13] M. Lehsaini and H. Guyyenet. "Improvement of LEACH for fault-tolerance in sensor networks. In the proceeding of the fourth International Conference on Modeling Approaches and Algorithms for Advanced Computer Applications (CIIA'2013), pp.175-183, Saida, Algeria, 2013.
- [14] Hla Yin Min, and Win Zaw "Energy Efficient, Fault Tolerant RoutingLEACH (EF-LEACH) Protocol for Wireless Sensor Networks" International Conference on Advances in Engineering and Technology (ICAET'2014) March 29-30, 2014 Singapore.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)