



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: VII Month of publication: July 2021 DOI: https://doi.org/10.22214/ijraset.2021.37222

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com

Dielectric Relaxation and Thermodynamic Study of Caffeine-Chloroform Solution using TDR

A. R. Lathi

Associate Professor, A.E.S. College, Hingoli, Maharashtra, India

Abstract: The Complex permittivity of caffeine – Chloroform solution for different temperature and various concentrations have been measured in the range of 10MHZ to 30 GHz using Time Domain Reflectometry. From complex permittivity spectra, Static dielectric constant (ε_0) and relaxation time (τ) were determined using nonlinear least square fit method. Using Erying rate equation, for different molar concentration of caffeine Enthalpy of Activation ΔH and Entropy of Activation ΔS were determined.

Keywords: Caffeine, Static dielectric constant, relaxation time, thermodynamic parameter.

I. INTRODUCTION

Caffeine is natural stimulant, most commonly found in tea, coffee. It works as stimulating brain and nervous system [1]. In 1827 a scientist named Oudry discovered caffeine in tea [2]. Caffeine is colourless compound in silky needles. Caffeine is nitrogenous compound. It is used for nerve and heart stimulant as a medicine [3]. Caffeine is extracted using chloroform from tea. Extraction process depends upon plants and solvent selected [4]. The pure caffeine is extremely toxic and must be handled with mask and groves.

The present paper reports the static dielectric constant (ε_o), relaxation time (τ), Enthalpy and Entropy of activation for different molar concentration in the frequency range 10 MHz to 30GHz using Time Domain Reflectometry.

A. Material

II. EXPERIMENTAL DETAILS

Caffeine was purchased from OTTO chemie India. Using chloroform as a Solvent, different concentrations in molar fraction were prepared.

B. Experimental Setup and Procedure

The Tektronics model No. DSA8200 sampling oscilloscope with 30 GHz bandwidth with TDR module 80E08 with Step generator unit was used. The experimental setup is as shown in Fig. 1



Fig. 2 Experimental setup of TDR

The complex permittivity spectra were studied using TDR method [5-7]. The complex permittivity of solution was observed in frequency range 10 MHz to 30 GHz at different temperature.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com

III. RESULT AND DISCUSSION

The time dependent data were processed to obtain complex reflection coefficient Spectra $\rho^*(\omega)$ over the frequency range 10 MHz to 30 GHz using fourier transformation [8,9] as

$$\rho * (\omega) = -\frac{\sigma p(\omega)}{j\omega dq(\omega)} - -(1)$$

The complex permittivity spectra $\varepsilon^*(\omega)$ were obtained from $\rho^*(\omega)$ by applying a bilinear Calibration method [10]. The Caffeine – Chloroform solution at all molar concentration could fit Debye type dispersion [11]. Experimental values of $\varepsilon^*(\omega)$ were fitted to Debye equation.

$$\varepsilon * (\omega) = \varepsilon_{\infty} + \frac{\varepsilon_0 - \varepsilon_{00}}{(1 + jw\tau)}$$
 -- (2)

A. Static Dielectric Constant (ε_o) and Relaxation Time (τ)

Using non linear least square fit method [12] with Debye equation 2, Static dielectric constant (ε_o) and relaxation time (τ) are obtained. These dielectric parameters for different temperatures and different concentration of caffeine are listed in table 1.

Table 1 (A) Dielectric relaxation parameters for solution of Caffeine – Chloroform at different concentration at temperature 25°C

25°C			
Concentration of Caffeine			
in Molar (M)	ε ₀	τ(ps)	∞ 3
0	4.82(1)	6.87(4)	2.00(1)
0.1	4.97(1)	7.15(5)	2.00(1)
0.2	4.96(1)	7.9(5)	2.00(1)
0.3	4.92(1)	8.65(8)	2.00(1)
0.4	5.03(1)	8.94(9)	2.00(1)
0.5	5.07(2)	9.34(11)	2.00(1)

Table 1 (B) Dielectric relaxation parameters for solution of Caffeine – Chloroform at different concentration at temperature 20° C

20°C			
Concentration of Brucine in			
Molar (M)	ε ₀	τ(ps)	∞ 3
0	4.98(6)	7.33(11)	2.22(7)
0.1	5.08(1)	7.56(5)	2.00(1)
0.2	5.08(8)	8.43(4)	2.00(1)
0.3	5.08(1)	8.23(6)	2.00(1)
0.4	5.21(1)	8.42(9)	2.00(1)
0.5	5.20(2)	9.91(12)	2.00(1)

Table 1 (C) Dielectric relaxation parameters for solution of Caffeine – Chloroform at different concentration at temperature 15°C

15°C			
Concentration of Brucine in			
Molar (M)	ε ₀	τ(ps)	∞ 3
0	5.53(2)	5.83(6)	2.02(3)
0.1	5.52(1)	6.37(2)	2.00(1)
0.2	5.53(8)	6.95(3)	2.00(1)
0.3	5.55(1)	7.78(4)	2.00(1)
0.4	5.68(2)	8.39(15)	2.00(1)
0.5	5.42(2)	8.38(12)	1.88(1)



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com

Variation of static dielectric constant (ε_o) with molar concentration of caffeine – chloroform at various temperature is as shown in fig.2



Fig. 2 Variation of static dielectric constant with molar concentration of Caffeine - Chloroform at various temperatures Variation of relaxation time with temperature at different concentration is shown in fig.3



Fig. 3 Variation of relaxation time with molar concentration of Caffeine - Chloroform at various temperatures



B. Determination of Thermodynamic Parameters

Using Erying equation, the energy of activation of relaxation process can be determined from relaxation time (τ), the Enthalpy of activation (Δ H) and Entropy of activation (Δ S) are calculated from Erying rate equation[13,14].

$$\tau = \frac{\hbar}{hT} \exp \frac{\Lambda H - T \Lambda s}{RT}$$
-- (3)

The Arrehenius plot of log (τT) versus 1000/T is as shown in fig.4



Fig. 4 The Arrehenius plot of log(τT) versus 1000/T for Caffeine – Chloroform solution

The values of Enthalpy of activation (ΔH) and Entropy of activation (ΔS) are obtained from Erying equation. These values are reported in table 2

Concentration of Caffeine (M)	Enthalpy of Activation	Entropy of Activation		
	$\Delta H (KJ mole^{-1})$	$\Delta S (J \text{ mole}^{-1} J^{-1})$		
0M	-14.26(11)	0.150(4)		
0.1 M	-10.76(9)	0.161(3)		
0.2 M	-11.68(10)	0.157(3)		
0.3 M	-9.86(1)	0.163(3)		
0.4 M	-6.94(2)	0.173(8)		
0.5 M	-10.26(9)	0.161(3)		

Table 2 - Enthalpy and Entropy of activation for Caffeine - Chloroform solution

IV. CONCLUSION

Static dielectric constant (ε_o increases with increase concentration of Caffeine, It also increases with decreases in temperature. Relaxation time (τ) increases with increase in concentration of Caffeine. Enthalpy of activation (Δ H) is negative i.e. heat energy is released. Such reactions are called Exothermic reaction [15]. International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VII July 2021- Available at www.ijraset.com

V. ACKNOWLEDGEMENT

Author A.R. Lathi thanks to J.E.S. College, Jalna and School of Physical Sciences, Swami Ramanand Teerth Marathwada University, Nanded.

REFERENCES

- [1] Nehlig A, Daval JL, Debry, G "Brain Research Reviews", Vol 17, issue 2, May-August 1992, pp 139-170.
- [2] Bennett A. Weinberg , Bonnie K. Bealer, ' The world of Caffeine' Rotledge Pub. , Newyork & London.
- [3] O. P. Agrawal, 'Organic Chemistry Natural Products Vol. I' Krishna Prakashan Meeru
- [4] E1 Din, A. M. M. N. and S. H. Abu-Raiia, J. Food Sci., 23, 241-245 (1995).
- [5] R.H. Fattepur, M.T. Hosamani, D.K. Deshpande, J. chem. Phys. 101(11), 9956, 1994.
- [6] A.C. Kumbharkhane, S.M. Puranik, S.C. Mehrotra, J.chem. soc. Faraday Trans. 87(10), 1569, 1991.
- [7] R.B. Talware, P.G. Hudge, Y.S. Joshi and A.C. Kumbharkhane. J-Physical and chem. Of Liquids, 2011, 1-11, I first.
- [8] H. A. Samulon, "Spectrum Analysis of transient response curves" Proc. IRE. 39, 175 (1951).
- [9] C. E. Shannon, "Communication in the Presence of Noise", Proc. IRE. 37, 10 (1949).
- [10] R.H. Cole, J.G. Berberian, S. Mashimo, G. Chryssikos, A. Burns and E. Tombari, J. Appl. Phys. 66(2), 793, (1989).
- [11] P.Debye, Polar molecules (The chemical catalogue company, New york) (1929).
- [12] P.R. Bevington, Data Reduction and Error Analysis for the Physical Sciences (McGraw-Hill New York, 1969)
- [13] H.Erying, J. chem. Phys, 4, 283 (1926).
- [14] J.B. Hasted "Aqueous dielectric" champan and Hall, London (1973).
- [15] B.S. Bahl, G.D. Tuli, Arun Bahl, "Essentials and Physical chemistry" S. Chand and Company Ltd., NewDelhi.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)