



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: VIII Month of publication: August 2021 DOI: https://doi.org/10.22214/ijraset.2021.37690

www.ijraset.com

Call: 🛇 08813907089 🕴 E-mail ID: ijraset@gmail.com



Large Deformation Analysis of Rubber by Software Fusion 360

Sathvik Reddy Dudipala¹, Divya Pasunuti²

^{1, 2}Department of Mechanical Engineering, Kakatiya Institute of Technology & Science, Warangal

Abstract: This paper articulates you the large deformation procedure of a rubber sheet. Nowadays, material selection of a component is very important as per the trend and compact ability, materials like rubber nitrile, rubber silicone is considered for the structural analysis of rubber. By the application of Fusion 360 software with the boundary conditions, the parameters like stress, strain and deformation is known for the specific material.

Keywords: Fusion 360, rubber, silicone, nitrile, stress, strain, deformation.

I. INTRODUCTION

Rubber is an elastic material which is extracted from the various plant resources. It has a large industrial usage, which is used for multiple purposes. Specially, in the medical sector it is used rapidly in form of gloves, masks and patient body fixtures. And also in the automobile sector it is used in the form of tires, belts in the engine and electrical plugs.

II. PROCEDURE

1) For designing the rubber of cylindrical shape, the following dimensions are taken generally.(as shown in Fig.1)





2) The solid part of rubber which is designed in fusion 360 is shown in the Fig. 2







- 3) Generally, rubber material that is used in medical sector is nitrile due to its high tensile strength and excellent wear and abrasion resistance, where when you look at external applications specially silicone rules the world which can operate at higher temperature of 230 °c.
- 4) Now, after designing the model of rubber, the simulation (static structural analysis) is done by applying a load of 10⁷ on one end of the designed part as shown in Fig.2.
- 5) The following figures are the simulation pictures of various materials that have been considered.



Fig. 3 Properties of rubber silicone



Fig. 4 Stress in rubber silicone

International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VIII Aug 2021- Available at www.ijraset.com





Min: 0 mm



aterial F	Rubber, Nitrile			
ensity		1.2E-06 kg / mm^3		
oung's Modulu	JS	0.002 GPa		
oisson's Ratio		0.49		
ield Strength		15 MPa		
timate Tensile	Strength	15 MPa		
hermal Condu	ctivity	2.43E-04 W / (mm C)		-
nermal Expans	ion Coefficient	1.6E-04 / C		
ecific Heat		1966 J / (kg C)		













Fig. 9 Strain in rubber nitrile





International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue VIII Aug 2021- Available at www.ijraset.com

III.RESULTS

A load of 10^7 MPa is applied (which is completely meshed). The following are the results obtained from the simulation performed in the software Fusion 360 :

Material	Stress (MPa)	Strain (mm/mm)	Deformation (mm) $* 10^7$
Rubber Silicone	462402	179100	4.715
Rubber Nitrile	462402	268650	7.073



Fig. 11 Comparison of stress, strain, deformation of different materials

IV.CONCLUSIONS

The project mainly focused on simulation as it helps the engineers to figure out the material which can be used to their constraints. The obtained results also determines why nitrile and silicone rubbers are used specially in definite streams. Generally, materials undergo elastic and plastic deformation as the results show stress, strain and deformation it helps the manufactures to what extent a particular material of rubber is used in our day to day life (cosmetics, package bands, shoes, wet suits, specially made belts).

REFERENCES

- [1] "Fatigue, Stress, and Strain of Rubber Components: A Guide for Design Engineers Hardcover" Illustrated, June 1, 2008 by Judson T. Bauman
- [2] "Polymer processing", Hanser publications
- [3] "Application on endochromic plasticity on simulation of technical rubber components", Herbert Baaser, Christian Heining.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)