



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: IX Month of publication: September 2021 DOI: https://doi.org/10.22214/ijraset.2021.37954

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



Proposal for Conceptualising Zero Waste City: Katraj

Tushar A. Gaikwad¹, Madhuri Nikam²

¹PG Student in Town & country planning, *Department* of Civil Engineering, SOET, Sandip University, Nashik, Maharastra, India ²Assistant Professor in Town & country planning, *Department* of Civil Engineering, SOET, Sandip University, Nashik, Maharastra, India

Abstract: The practices of "zero waste city concept" which has been implemented successfully in very few town /cities in the world, in that merely developed countries comes where there is availability of funds. It is in the developing countries that research have been made towards sustainability due to the less or unavailability of funds. "Zero waste city," where the entire municipal solid waste is treated with organic scientific method, is a perfectly sustainable & durable solution to the rapidly increasing ecological, eco friendly and socio-domestic problem facing today's era.

"Zero landfills approch" is another feature/side of zero waste city practices. Landfills requires high costs both private and external costs that get hidden in taxes on already tax-paying citizens. It then becomes very relevant to find out sustainable solutions to municipal solid waste management (MSWM). In this Zero waste city concept the "zero" or minimal waste to landfills creates a efficient solution to MSWM. We can not place / keep waste for future generations not even to incure unnecessary costs of maintaining unsustainable processes.

Keywords: zero waste city concept, MSWM, Zero landfills approch, SWM, sustainability

I. INTRODUCTION

Globaly today, we have adopted the linear economic model of manufacturing the goods and genrating the resultant waste from consumption of these goods by "use &throw" approach. The nature's free services of pure water, clean air and unpolluted land, has been increasingly get cantaminated/ distrubed due their over use

The zero waste concept enhance less/minimum/zero polution to land, water as well as air bt adapting effective methodolgy for MSW Processing Because when Municipal solid waste (MSW) released into nature untreated pollutes water heavily, air and land, and causes health issues and major climate change risks due to spread of pathoges air pollution due to release of toxic gases, soil and water contamination due to leachate percolation etc

Due to MSW dumping at openly on dumping site causes global warming as its major source of emmision of carban dioxide(CO) 2, & this unprocessed MSW releases methane & methaneous gases(GHG- green house gases) which are 16% contributor of global warming ,so that its is essential to avoid completely /minimise the such pollutions to decrease the impact /risk factor on environmental& living being's health.

This can be done in two ways: one, by recycling and processing the entire waste so that there is no release of waste into the ecosystem and, two, by analysing vital resources from the waste and using it for further production, this is the circular economy model a "cradle to cradle" approach. "Zero waste" is a concept that enhances minimum or less or zero pollution to land, water and air due to effective MSWM. Urban India is facing an increasing challenge to provide for the huge& exceeding infrastructural needs of the growing urban population. According to the 2011 census, the population of India was 1.21 billion, of this 31% lives in urban cities. It is further projected that by 2050 half of India's population will stay in urban cities.

Solid Waste Management is one of the most essential &unavoidable services for maintaining the quality of life of the people in the urban areas and for ensuring better standard facilities of health, sanitation and the weather. With this rapid increasing population, the management of Municipal Solid Waste (MSW) in the country has emerged as a severe problem not only because of the environmental and aesthetic & health concerns but also due to the overall quantities generated every day

With rising urbanization and change in lifestyle, food habits and social environment, the amount of municipal solid waste has been increasing widely and its composition is also varing step by step. With huge migration of rural areas masses to urban region, particularly in metro cities & cosmopolitian towns, MSW is being produced at an ever large increasing rate. The growing population directly impacted the municipal solid waste generated in the surrounding areas. Again industrialization affects on urbanization and increases population stage to there by increasing the overall waste generated



II. STUDY AREA

It is important place from all sides in Pune district & city. Katraj is situated on 18°27"13' north latitude and 73°51'42" east longitude in Pune District (Figure.1). The total area of Katraj is 20 km² urban area, and Population is 3124458 as per Census 2011.Katraj, Ward 40 in Pune city in the western state of Maharashtra, India, is unique of the 41 such wards under Municipal Corporation, pune(PMC). Katraj is a newly elaborated part of the town and the ward is a mix of slum households, semi-slum chowl-households, apartment complexes and commercial areas. It has 34,578 households/families in total, 675 slum households units, 31,917 non-slum households units and 1,986 commercial units. The statistics of residence in this region Katraj is 131,000. Ward 40 was., Ward 40 has maintained this status for the 2-3 years, until date to process all waste also Ward 40 has no landfills. Its success led to the replication of the model in 50 per cent of the wards, presently, memorandums of understanding (MOU) are being prepared to replicate the model in all the remaining 21 wards of the district. In the remaining wards which have been copied, few per cent (0-3%) of inerts are moved to landfill sites, hence they have not made it to the zero waste criteria. Ward 40 katraj can be termed as "zero waste town" in a country that is ridden with an insurmountable waste problem. Though it is a mix of slum region and semislum areas and waste segregation and disposal has been so hard to made in the other slum areas of the district, here they have gained almost total segregation of wet and dry waste. Total Area - 20 km2, Height from mean sea level -450m(1480ft), an Average temperature of katraj Pune - 31 0C and an Average Rainfall at katraj Pune - 600 mm



Figure.1 India-Maharastra- Pune-Katraj



Figure.2 Katraj, Pune(18°27"13' north latitude & 73°51'42" east longitude)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

158

12

23

10

89

65

III.METHODOLOGY

- A. Collection of Data
- 1) Pune generates around 1600 tons of solid waste per day.amongs that 60tonn is from katraj region
- 2) 160 trucks collect waste door--to--door, collecting an average of 198 tons per day.
- 3) 847containers and 116 compactor buckets dispersed around Pune.
- 4) Ward wise average-- 350 to 750 gms per capita per day
- 5) Construction and demolition waste generation -80--90 TPD
- 6) Garden waste generation 50--60 TPD
- 7) Biomedical waste 3 TPD

INTEGRATED SOLID WASTE MANAGEMENT





B. Analysing the data & Classification of Data

S N	Source of generation	Quantity(🎋 of total 🛸	Description	Percentage
		ini j		Organic Matter	45 to 50
				Recyclables from	35 to 40
1	Household	950	69.1	Commercial	
	Street sweeping & drainage cleaning	140	10.2	Inert Material	10 to 15
	Hotels &restaurants	150	10.9	Other Parameters • Density	 437 Kg/m³ 937 Kgal/Kg
	Markets / commercial area	50	3.6	• GCV • C/N	• 22.85
	C and D Waste	75	5.5		
	Fruit, vegetable, Vish meat market waste	7.5	0.5	5%	:% = a
	Biomedical waste	1.8	0.1	22%	5% Metal Glass
					Eeather / Rubber
				759	Inert Materials
				2370 33%	=

C. Implementation Of Data To Find Capasity, & Appropriate Technology

Technology Options for Treatment of Wet MSW

The technology options available for operation of the Municipal Solid Waste (MSW) are based on either bio conversion or thermal based conversion. The bio-conversion process is pertinent to the organic fraction of wastes (wet waste), to form compost or to collect biogas such as methane (biomethanation) and residual sludge (manure). The thermal conversion technologies are incineration with or without heat recovery, pyrolysis process and gasification method, plasma pyrolysis and pelletization process or manufacturing of Refuse Derived Fuel (RDF) are pertinent for treating dry waste or mixed waste. Composting Composting is a process of properly systematic decomposition of the organic waste, typically in aerobic conditions, resulting in the production of steady humus like product, compost. Considering the basic composition of waste and the climate conditions, composting is highly related in India. Composting of the segregated wet fraction of waste is followed. Mixed waste composing, with effective & durable and appropriate pre-treatment of feedstock may be considered an interim solution; in such cases severe following of the compost quality is needful.





International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429

Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

D. Biomethanation/ Anaerobic Digestion

Biomethanation involves controlled biological degradation cycle of organic wastes by microbial activity in the absence of oxygen. The process involves the anaerobic (without air) decomposition process of wet organic wastes to produce a methane rich biogas fuel and a small amount of residual sludge that can be used for making compost. It takes place in digester tanks or reactors, which enable control of temperature and pH levels for optimizing process control. Methane-rich gas produced is suitable as fuel for energy generation. The residual sludge is also produced, which is suitable for enriching compost materials. Input preparation or source separation is required to ensure that waste is free of non-organic contamination. Anaerobic digestion is best following practices to the treatment of wet organic feed stocks such as high moisture agricultural biomass, food waste, and animal wastes involving manure and domestic sewage. A made feedstock stream with less than 15 percent Total Solid (TS) is considered wet and feed stocks with TS greater than 15-20 percent are considered dry. Feedstock is typically diluted with process water to gain the achieveble solids content during the preparation stages.

D (BOR)	0	
t mille	Description	Value
	Biogas Generation	300+5% m3/day
	Calorific Value	48005000 Kcal/ cum
THE REAL PROPERTY AND A DESCRIPTION OF A	Engine Efficiency	25%
भारतकोलनी यायो मेस,पहरूर (सम्बार ७ वेर यथ पतिहिन्।)	Electricity Generation	1.5 kWh/cum of Biogas
	Equivalent Electricity Generation	450kWh/day
	Auxiliary Power requirement	@50 kWh/day
	Net Surplus Electricity for sale	400 kWh/day

Biomethanation



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

E. Selection of Appropriate tool & Technology for Processing

Criteria	Windrow Composting	Vermi Composting	Biomethanation
Applicable with Population Size	Above 1 Lakh	Between 5,000 to 1 Lakh	Small scale – between 5,000 to 25,000 Can be extended to Large
			scale as in case of Sholapur
Facility Location ¹ , ²	Plant should be located at least one km away from habitation, if it is open windrow composting. The distance could be 500m in case of covered plants.	Within the residential area (with appropriate environmental safe guards)	Plant should be located at least 500 m away from residential areas, for plant sizes upto 500 TPD.
Buffer Zone (no Development Zone)	500 m for facilities dealing with with more than 75 or less than 1 200 m for facilities dealing with For Decentralized plants handling adequate environmental control	th 100 TPD or more of MSW; 4 100 TPD; 300 m for facilities dea n less than 50 TPD MSW. ing less than 1 TPD MSW no bu s are required.	400 m for facilities for dealing ling with 50-75 TPD of MSW; ffer zone is required; however
Natural Environment	Composting in coastal/ high rainfall areas should have a shed to prevent waste from becoming excessively wet and thereby to control leachate generation	Composting in coastal/ high rainfall areas should have a shed to prevent waste from becoming excessively wet and thereby to control leachate generation	
Land Requirement	High	High	Low to Moderate
	(For 500TPD of MSW: 6 ha of land is required)	(Suitable for quantities less than 25 TPD)	For small units: 500 sq. m for 5MT unit
			For large scale: 300 TPD of MSW: 2 ha of land is required)
Waste Quantity which can be managed by a single facility	25 TPD and above	1 TPD to 25 TPD	1-5 TPD at small scale to
Requirement for Segregation prior to technology	High	Very high	Very high
Rejects	About 30% including inert if only composting is done	About 30% including inert	About 30% from mixed waste
Potential for Direct Energy Recovery	No	No	Yes
Technology Maturity	Windrow composting technique is well established	Community scale projects are successful	Feasibility for segregated biodegradable waste is proven. Not suitable for mixed waste



Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

F. Waste Treatment Technology Options Based on Population Size

Population Range/ Waste	Technolog	gy Option	Minimum Requirement	Value Added Product
Generated (TPD)	Wet Waste	Dry Waste		
Population: Less than 50,000 Quantity: Less than 10 TPD	 Windrow Composting Vermi Composting Biomethanation (Nisarguna) 	Material Recovery & Recycling	Segregate wet organic waste at source for Biomethanation/ Vermi Composting Dry waste for recycling and material recovery Inert to Regional Landfill	Compost (Manure)/ Biogas Recyclables: Paper/ Plastics/ Metals
Population: 50,000 to 1 Lakh Quantity: 10 TPD to 30 TPD	 Windrow Composting Vermi Composting Biomethanation (Nisarguna) 	 Material Recovery & Recycling 	Segregate wet organic waste at source for Biomethanation/ Vermi Composting Dry waste for recycling and material recovery Inert to Regional Landfill	Compost (Manure)/ Biogas Recyclables: Paper/ Plastics/ Metals
Population: 1 Lakh to 10 Lakh Quantity: 30 TPD to 500 TPD	 Windrow Composting Biomethanation 	 Material Recovery & Recycling RDF 	Segregate wet organic waste at source for Biomethanation Dry waste to be recycled or converted in to RDF as feedstock for centralized facility Inert to Regional Landfill	Compost (Manure)/ Biogas/ RDF Recyclables: Paper/ Plastics/ Metals
Population: 10 Lakh to 20 Lakh Quantity: 500 TPD to 1000 TPD	 Windrow Composting Biomethanation Waste to Energy 	 Material Recovery & Recycling RDF Waste to Energy 	Segregate wet organic waste at source for Biomethanation Dry waste to be recycled or converted in to RDF as feedstock for power plants	Compost (Manure)/ Biogas/ RDF/ Electricity Recyclables: Paper/ Plastics/



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

Population Range/ Waste	Technology Option		Minimum Requirement	Value Added Product
Generated (TPD)	Wet Waste	Dry Waste		
			Inert to Landfill	Metals
Population: 20 Lakh and above Quantity: More than 1000 TPD	 Windrow Composting Biomethanation Waste to Energy 	 Material Recovery & Recycling RDF Waste to Energy 	Segregate wet organic waste at source for Biomethanation Dry waste to be recycled or converted in to RDF as feedstock for power plants Inert to Landfill	Compost (Manure)/ Biogas/ RDF/ Electricity Recyclables: Paper/ Plastics/ Metals

G. Computation Of Requirment, Transportation, Cost, Misc Expences Etc

Table 1. Generation and Disposal Matrix of Waste in Ward 40 (March 2018)

TPD

3

19

30

52

End Uses

5

3

2

₹ 2,613

1,728

885 292,050

To biomethanation plant

To farmers for farm use

recycle and processing

tonnes

tonnes

tonnes

To private operator for segregation, re-use,

Generation Disposal

Generation and Disposal Matrix

Waste Type Wet waste

Dry waste

Total

per day

Mixed waste

Biomethanation Plant capacity

Input from Ward 40

Input from other wards

Revenue economics (Biomethanation) Particulars

Value of electricity (3-ton feed)

Less: Operating costs per day

Annual excess revenue

Net excess revenue/Saving per day

TPD

22

24

6

52

Table 3. Economics of the Biomethanation Plant

Table 2. Transport Cost Savings Accruing to the Pune Municipal Corporation (April 2018)

Transport Cost	Savings Ac	crued to PM	C
	M ton	Saving/MT*	Total/Day
Transport cost saving due to (WW) directly	o <mark>farmers</mark>	collecting wet	t waste
WW to farmers (savings)	19	700	13,300
Transport cost savings due to	o transfer o	of WW for bid	methanation
WW to biogas	3	700	2,100
Transport cost savings due operator	to transfer	of waste to	private
Transport charges to dumpsite	30	700***	21,000
Less: Tipping fees	30	350***	10,500
Net savings			10,500
Total savings/day			25,900
Annual savings			8,547,000

Source: The authors.

Notes: *: Metric Tonne.

**: http://pmc.gov.in/en/swm



Table 4. Revenues, OPEX and Net Cash Revenue of Segregation and RDF Plant Operator (March-April 2018)

Economics of Private Operators Segrega Re-using/Recycling	iting, Reselling,
	₹/Year
Revenue (30 TPD DW & MW feed)	12,771,000
Annual OPEX	7,976,000
Net retained cash revenue (post-tax)	5,356,500
(Operator). Notes: DW: Dry Waste. MW: Mixed Waste. Table 5. Costs and Revenues of the Plastic R (April 2018)	ecycling Plant
Economics of Plastic Recycling Pl	ant ^e
1	1TD
Input/feed	1.200
Sellable output	0.840
Scrap sale	0.360
	THE R. L.

 č/day

 Revenue
 22,800

 Total OPEX
 19,260

 Net revenue/day
 3,540

 Annual net revenue
 1,168,200

Source: The authors. Proceeding of the authors of the source of the sour

Table 6. Total Benefits to the Public-Private Partnership (PPP) of Ward 40 (April 2018)

Combined Benefits of PPP	2
Transport cost saving to PMC	8,547,000
Benefits to operators	6,816,750
Biomethanation	292,050
Segregation/resale/re-use	5,356,500/21
Recycling of plastics	1.168,200
Total financial benefits/year	15,363,750

Sources: The authors.

Table 8. Checklist of Critical Factors Necessary for a Successful Zero Waste Project

Sr. No	Governance and Planning	Ward 40 (*)
1	Substantial change in consumer's behaviour and consumption pattern	Ý
2.	PAYT, sufficient regulations and rules for MSWM	*
3.	Modifications in the logistics system, development of public-private partnership (PPP) and financial incentives system	~
4.	Promotion of green innovation— research and development of technologies around green production and waste management.	~
	Operational	
5.	Product redesigning to eliminate wastage and elimination of toxicity in the composition of products	~
6.	Prioritize use of renewable raw materials	*
7.	Investing in products made with sustainable designing	-
8.	Investing in labour training	~

Note: PAYT: Pay as you Throw.

Table 7. Employment/Income Due to the MSWM of Ward 40 (March 2018)

	Organization	No of People Employed	Annual Income Generated (₹)
1.	SWaCH (waste pickers	(10,000)	7,320.000
2.	Segregation/RDF plant	40	3,900,000
3.	Plastic plant	12	576,000
4	Janwani	3 (12,000)	432,000
2	Biomethanation plant	7	1,380,000
	Total employment and income created solely due to zero waste project Ward 40	123	13,608,000
6.	PMC (existing)	182 (168 labourers)	39,510,000
	Total employment and income generated	305	53,118,000 (US\$843,143 @ US\$1 = 63)

Source: The authors



Model for Metro Cities Converting Food Waste into Bio-CNG (Green Public Transportation) & Organic Manure 800 tons of Bio-waste per day in Pune Benefit Organic Manure 150 Tons per day Independence from expensive & imported fossil fuel India NobleExchange Environment Solutions 2 Organic Waste CNG Auto OEM Boost in CNG vehicle sales even in non CNG Grid locations Proc essing Cente 45 Tons s of Bio-CNG/day (Purified & Compressed Biogas) Clean & healthy cities, as no more open dumping of organic waste Society Urban & Rural Poor Gainful employment in organic 'waste to fuel' processing plants CNG Vehicle Auto OEM PMPML GHG Friendly Transport 1.6 lakh km per day CNG Buses GHG friendly transportation preserves climate for sustaining life 3.5 km/kg Bio-CNG Pune Mahanagar Earth Parivahan Mahamandal Ltd.

Trash to Treasure



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

DOORSTEP COLLECTION MODEL

WP delivers nonrecyclables to PMC; sent to Hanjer Plant

for processing

Below left, workers shred wet waste, the first step in the organic fuel pellet pro Right, wet waste is delivered to the new biogas plant in Katraj.

Households, societies, and commercial properties segregate waste into organic (wet) and inorganic (dry) waste

> Waste pickers collect regregated waste from households, societies,

businesses

WET WASTE

WP delivers wet waste for

composting, biogas, pelletization

Wet waste reused as fertilizer, electricity

or fuel

IV.RESULT



DRY WASTE

÷

WP sells

to scrap

buyers

Further segregation by WP into

recyclables and non-recyclables

IMPLEMENTATION METHODS

INTEGRATED SOLID WASTE MANAGEMENT SYSTEM

Weeks 1-2

 Study existing waste management system by ward. Collect maps and data on number of properties and containers, waste composition, etc.

- Define strategy based on study results and establish system requirements.
- Provision of materials including bins, pushcarts, cycle rickshaws, etc.

Weeks 3-4

- Presentation to ward officials; implementation plans.
- Launch project jointly with all partners.
- Distribute materials to waste pickers.
- Establish seperate system for wet and dry waste.

Weeks 5-6

- Creation of ward-level map; determine feeder points.
- · Implementation of door-to-door collection and feeder systems.
- · First round of training for PMC workers and waste pickers; education campaigns.
- Integrate waste pickers into doorstep collection.

Weeks 7-10

 Pocket-wise implementation. Remove community containers systematically, streamline new doorstep collection and feeder systems.

- Continued resident education campaigns; distribute separate bins to homes.
- Involve area residents in local cleanliness campaign, "Swatchnta Mitra".

Weeks 11-12

 Develop integrated disposal system. Sale of all dry waste and ward-level processing of all wet waste through biogas plants, composting and other technologies.



Steps in Establishing the Zero Waste System



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue IX Sep 2021- Available at www.ijraset.com

V. CONCLUSION

If we are looking at a durable & smart but effective, clean environment for our progeny to grow in, we definitely cannot behind waste and a "cradle to grave" linear economic model where resources are depleting at a rate that will not leave much for them and the generations to come. We also cannot leave a hierachy of landfills, nay dumpsites with mountains of waste polluting land, air and soil, the effects of which will be borne mostly by them in radical, dangerous and unfortunate ways for it takes time for this pollution to travel through the "earth, worm, healthy life cycle" and then leaves no bird song for the springs to come. If we are to bring this, then the only solution that can gain out in all types of ethics is a "zero waste" and round type model economy that reduces the stress on precious sources, follows the round economy's "cradle to cradle" map and leaves "zero landfills achievement " for the future scope

REFERENCES

- [1] Waste Management Initiatives And Activities In India For Society's Welfare K Venkata Rami Reddy, Dr. A. Sree Ram INTERNATIONAL JOURNAL OF SCIENTIFIC & TECHNOLOGY RESEARCH VOLUME 8, ISSUE 12, DECEMBER 2019 ISSN 2277-8616
- [2] Atiq Uz Zaman and Professor Steffen Lehmann 'Zero Waste' SA Research Centre for Sustainable Design and Behaviour (sd+b), School of Art, Architecture and Design, University of South Australia (UniSA), GPO Box: 2471, SA 5001, Australia. July 2011
- [3] Ackerman, F 2005, 'Materials flows for a sustainable city', International Review for Environmental Strategies, vol. 5, no. 2, pp. 499-510. APH 2008, Domestic jurisdictional comparison of waste levies, Parliament of Australia
- [4] Joshi, R, Ahmed, S. Environmental chemistry, "pollution & waste management: Review". Cogent Environ Sc http://home.iitk.ac.in/-anubha/H13.PDF
- [5] Zero Waste Circular Model of MSWM :Priti Mastakar Vijay Mastakar Kakali Mukhopadhyay Surabhi Jaju , Pune, Maharashtra, India .pp. 18(1) 36–56, 2019 Metamorphosis - A Journal of Management Research
- [6] Website: Pune munciple corporation, swachh bharat mission, swach NGO, Pune Cencus, etc.
- [7] Case study of Kamkatsu; Japan by SMALL TOWN, BIG STEPS The Story of Kamikatsu, Japan Copyright 2019 Global Alliance for Incinerator Alternatives , Auther :Patricia Parras
- [8] Townend W K. Editorial. Zero waste: an aspiration or an oxymoron? Waste management & research. 2010. Retrieved 16 May 2019 from https://www.ncbi.nlm.nih.gov/pubmed/20065044
- [9] Connett P, Sheehan В. A citizen's agenda for zero waste. 2001. Retrieved 16 May 2019 from https://www. researchgate.net/publication/247506767_Tourism_and_Waste_Management_A_Review_of_Implementation_of_Zero_Waste_at_Kovalam
- [10] Pariatamby A, Tanaka M, Sjogren P. Municipal solid waste management in Asia and the Pacific Islands: Challenges and strategic solutions (p. 377).. Retrieved 16 May 2019 from http://link.springer. com/10.1007/978-981-4451-73-4 .Springer; 2015











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)