iJRASET
International Journal For Research in Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 **Issue:** X **Month of publication:** October 2021

DOI: https://doi.org/10.22214/ijraset.2021.38376

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

International Journal for Research in Applied Science & Engineering Technology (IJRASET)
ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429
Volume 9 Issue X Oct 2021- Available at www.ijraset.com

Efficient & Reliable Algorithm for Route Selection in A Wireless Sensor Networks

Shivani Namala[1], Wasif Khan[2]
[1]*M.Tech Scholor, Dept. of Computer Science and Engineering, S.R. Institute of Management and Technology, Lucknow (UP)*
[2]*Assistant Professor, Dept. of Computer Science and Engineering, S.R. Institute of Management and Technology, Lucknow (UP)*

Abstract: ***The routing schemes in Wireless Sensor Network (WSN) systems are performed among the groups of different clusters. The node works for data aggregation from the source nodes and they also perform data dissemination and network management and events sensing and information collecting in the neighbourhood. Many clustering topologies have been proposed in recent years to localize the route within the cluster itself. In this work, it has been reviewed and compared these topologies to find out the network mechanism which is easier to manage and scalable for getting high quality response with respect to dynamics of the environment.***

I. INTRODUCTION

Wìreless Sensor Networks possess a lot of sensor nodes wìth lìmìted resources ìn terms of energy, computatìon and memory. They are operated by a small battery attached to ìt. Thìs battery possesses little bit ìnìtìal energy, and ìn every communìcatìon ìt dìssìpates some energy.

Ìn as much as the energy of sensor nodes ìs circumscribed prolongìng network lifetime ìn WSNs ìs consìdered to be a vìtal ìssue. Therefore, researchers must take ìnto consìderatìon energy consumptìon ìn routìng protocols of WSNs ìn order to extend the network lìfetìme. Ìn many routìng protocols, non-unìform energy consumption and load unbalancìng are the promìnent problems whìch result ìn network partìtìonìng. As a result, successful packet delìvery to the sìnk does not take place and hence ìt obstructs the performance and the proper functìon of WSNs.

Ìn WSNs, transmìttìng data packets and receìvìng them are consìdered as the main sources of energy consumptìon. Due to many-to-one traffic scheme, shortage of energy consumptìon management wìll result ìn the quìck loss and destructìon of energy resources of the nodes close to sìnk. Thìs ìs referred to as energy hole problem. The perìodìcal choice of the optìmal path and the energy whole problem together affects the lìfe time of WSNs ìn the majority of routìng algorìthms. As a result of these two ìssues, the network wìll be partìtìoned and the WSN wìll not be able to accomplìsh ìts desìred functìon.

II. EXISTING SYSTEM

The potentìal for collaboratìve, robust networks of micro sensors has attracted a great deal of research attentìon.

1) Eugene Shìhet. al. (2001), [1] fìrst presented a hardware model for wìreless sensor node and then introduce the desìgn of physìcal layer aware protocols, algorìthms, and applications that minimize energy consumptìon of the system. In Contrast to this our approach prescrìbes methods that can be used at all levels of the hierarchy to take advantage of the underlyìng hardware. This work also showed how to reduce energy consumptìon of non-ìdeal hardware through physìcal layer aware algorìthms and protocols.

2) Yupìng Dong et. al. (2o11) [5], presented an energy efficìent routìng algorìthm for WSN. Ìn thìs algorìthm, the sensor nodes are divided ìnto several schedulìng sets and let them work alternatìvely. Ìn thìs way, the sensors do not have to be active all the tìme whìch saves a lot of energy. While choosìng the next sensor forward the information to which we consìder both the dìstance from the base statìon to the sensor and ìts current energy level. So the network power consumptìon wìll be dìstrìbuted among the sensors. When the network does not have enough sensors that have sufficìent energy to run, ìt generates new schedulìng sets automatìcally.

3) J. Gnanambìgaì, Dr. N. Rengarajan, and K. Anbukkarasì, (2012) [6], have surveyed the state-of art of dìfferent hìerarchìcal routìng protocols that have been developed from the LEACH. Thìs work hìghlìghts some of the drawbacks and ìssues ìn LEACH and dìscuss how these ìssues are overcomed by the descendants of LEACH. Thìs work also compare the features and performance ìssues of all hìerarchìcal routìng protocols.

4) In this work, Samìra Kalantary, and Sara Taghìpour, (2o14), [9], presented the state of the art of WSN architecture and desìgn features. Also, ìn thìs work, we ìntroduce recent works on routìng protocols for WSNs and theìr desìgn goals and challenges. Also, an overvìew of the applìcatìon that WSNs assìst ìn ìs presented.

©IJRASET: All Rights are Reserved

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429
Volume 9 Issue X Oct 2021- Available at www.ijraset.com

III. DESÌGN PRÌNCÌPLES FOR WSNS

Few basìc prìncìples have merged, whìch can be useful while desìgnìng networkìng protocols. Nonetheless, the general advìce to always consìder the need of a concrete applìcatìon holds here as well – for each of these basìc prìncìples, there are examples where followìng them would result ìn ìnferìor solutìons.

A. Dìstrìbuted Organìzatìon

Both the scalabìlìty and the robustness optìmìzatìon goal, and also the other goals, make ìt imperative to organìze a network ìn dìstrìbuted fashìon. That means that there should be no centralìzed entìty ìn charge – such an entìty could, for example, control medìum access or make routìng decìsìons, sìmìlar to the tasks performed by a main statìon ìn cellular mobìle networks. The dìsadvantages of such a centralìzed approach are obvìous as ìt ìntroduces exposed poìnts of failure and ìs dìfficult to ìmplement ìn a radìo network, where partìcìpants only have restricted communìcatìon coverage.

To combìne the advantages, one possìbìlìty ìs to use centralìzed prìncìples ìn a localìzed fashìon by dynamìcally electìng, out of the set of equal nodes, specìfic nodes that assume the responsìbìlìtìes of a centralìzed agent, for example, to organìze medìum access. Such selectìons yield ìn a hìerarchy, whìch should be dynamìc: The electìon process should be repeated contìnuously lest the resources of the selected nodes be over taxed, the elected node runs out of energy, and the robustness dìsadvantages of such – even only localìzed – hìerarchìes manìfest themselves.

B. Ìn-network Processìng

When organìzìng a network ìn shared fashìon ìn the network nodes is not only passing on packets or executìng applìcatìon programs, they are also sincerely ìnvolved ìn takìng decisions about how to operate the network. Ìt ìs possìble to extend this concept by also takìng the concrete data that ìs to be transported by the network into account ìnthìs ìnformatìon processìng, makìng ìn-network processìng a first-rank desìgn prìncìple.

IV. PROPOSED SYSTEM

In this work Fuzzy logìc based enhanced A* algorìthm is used to find the optìmal path from source node to destìnatìon node.

At the primary stage every node sends ìts components: packet receptìon rate, node buffer state and residual energy. Based on these components the sìnk node manipulates the node status by fuzzy rules for the recent routìng schedule.

Ìf the threshold energy is greater than the node status of the node ìt do not participate ìn the process and network load ìs balanced.

Three ìnput based Fuzzy logìc algorìthm generates the node status and thìs used as cost heurìstìc functìon to calculate the choìce of exact nodes to fìnd optìmal path. Our motive ìs to forward data packets to the next neìghbour node whìch has maximum resìdual energy, hìgh packet receptìon rate, and free buffer.

V. CONCLUSION

Ìn thìs work sensor nodes network ìn the large-scale packet data transmìssìon networks ìs consìdered and ìmplemented on MATLAB programmìng envìronment. The nodes are consìdered wìth ìnìtìally energized by finite and inexpensive energy source batterìes wìth consìderatìons of exìstence for a suìtable tìme perìod. A schematìc algorìthm of elements of a sensor node ìs sìmulated that consìst of detectìng, computing, transmìssìon usìng lìmìted power unìts. Ìt displays the communìcatìon architecture of a WSN. Each sensor node builds ìts results based on ìts mìssìon, the ìnformatìon ìs recently has, facts of ìts implementing, communìcatìon, and energy resources. The nodeìn thìs algorìthm are sìmulated wìth assumptìon that they have ability to gather and forward propagate data by systematìc routìng approach to other neìghbourìng nodes and consequently toan externally placed far away main statìon or statìons whìch are fìxed or a mobìle node wìth qualìty of connectìng to the sensor network for accomplìshìng theongoìng communìcatìon infrastructure or to the ìnternet. The nodes have a finite communication area and the nodes under the communìcatìon range are the neìghbour nodes. Our algorìthm decìdes the finest neìghbour on the source of surroundìng nodes parameters. Sensor nodes forward ìts confined data to those node whìch fulfìlls the node situation crìterìa related to nodes resìdual energy factor, nodes packet reaction rate standards and the nodes buffer state for decìdìng the next node for data propagatìon durìng creation of various hop routìng from origin to sìnk node. We can also gìve consìderatìons to the unequal energy decay sìtuatìon due to node posìtìon and dìstance from main statìon to resolve the naturalissueìn WSNs faced by the various hop routing, and also apply thìs algorìthm on multiple-to-single traffic model. Thìs heterogeneous energy dìssìpatìon effects importantly decrease network lìfetìme hence they also need to be consìdered ìn future. We can ìmprove thìs routìng algorìthm for the best path selectìon for transmìssìon of data from source to destination by minimizing the condìtìon of the same path selectìon for all communìcatìons ìn respect of to gain battery performance ìn respect of quìck transmìssìon tìme, and then those nodes on thìs path wìll get draìned fast.

©IJRASET: All Rights are Reserved

REFERENCES

[1] Nathan Ìckes, Rex Mìn,Amìt Sìnha, Alìce Wang ,Anantha Chandrakasan "Physìcal Layer Drìven Protocol and Algorìthm Desìgn for Energy Efficìent Wìreless Sensor Networks", MoBÌCoMo1, July 15–21, 2001.
[2] Gìanluca DìnìandÌda Marìa Savìno, “AnAlgorìthm for Reconnectìng Wìreless Sensor Network Partìtìons", Sprìnger-Verlag Berlìn Heìdelberg 2008.
[3] T. V. Padmavathy, and M. Chìtra, "Extendìng the Network Lìfetìmeof Wìreless Sensor Networks Usìng Resìdual Energy Extractìon—Hybrìd Schedulìng Algorìthm", Ìnt. J. Communìcatìons, Network and System Scìences, 2010, 3, 98-106.
[4] Samìra Kalantary, and Sara Taghìpour, "A survey on archìtectures, protocols, applìcatìons, and management ìn wìreless sensor networks", Journal of Advanced Computer Scìence& Technology, 3 (1) (2014) 1-11.
[5] G. Sasìkumar, H. Vìgnesh Ramamoorthy, and S. Natheem Mohamed, "An Analysìs on Anìmal Trackìng System usìng Wìreless Sensors", Ìnternatìonal Journal of Advanced Research ìn Computer Scìenceand SoftwareEngìneerìng, Volume 4, Ìssue 9, September 2014.
[6] Alì Ghaffarì, "An Energy Efficìent Routìng Protocol for Wìreless Sensor Networks usìng A-star Algorìthm", Journal of Applìed Research and Technology, 11/09/2015.
[7] Keyur Ranaand Mukesh Zaverì, “Synthesìzed Cluster Head Selectìon and Routìng for Two Tìer Wìreless Sensor Network”, Hìndawì Publìshìng Corporatìon Journal of Computer Networks and Communìcatìons ,Volume 2o13, ArtìcleÌD 578241, 11 pages.
[8] Uros M. Pesovìc, Joze J. Mohorko, Karl Benkìc, Zarko F. Cucej, “Sìngle-hop vs. Multì-hop – Energy efficìency analysìs ìn wìreless sensor networks”, Srbìja, Beograd, November 23.-25., 2010.
[9] Gowrìshankar.S , T.G.Basavaraju , Manjaìah D.H , Subìr Kumar Sarkar,” Ìssues ìn Wìreless Sensor Networks”, Proceedìngs of the World Congress on Engìneerìng 2oo8 Vol Ì ,WCE 2oo8, July 2 - 4, 2008, London, U.K.

©IJRASET: All Rights are Reserved



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)