



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: X Month of publication: October 2021

DOI: https://doi.org/10.22214/ijraset.2021.38440

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue X Oct 2021- Available at www.ijraset.com

Brain Tumor Identification and Locating

Sanjeev Sriram¹, Ashwapuram Akshith Madhav², Akhil Vajja³, Dr. Sunil Bhutada⁴ ^{1, 2, 3}B.Tech 4th year, ⁴Professor, IT Department, Sreenidhi Institute of Scienceand Technology

Abstract: Various poorer-grade glioblastoma subtypes related with outline attribute have been identified in a late research. poorer-grade glioblastoma can have symptoms ranging from slight seizures to extensive seizures, affecting the capability to talk or even lift your arms and legs. This poorer-grade glioblastoma is handled with a combination of surgery and examination by monitoring the tumor with brain MRI scans. The study of this project enabled us to build a completely self-working system for segmentation of tumor utilizing computer vision techniques, and deploying models that would allow high- quality LGG detection in the brain MRI would potentially be self-working to identify the genomic subtype of the tumor by quick and low-cost imaging. The methodology, procedures, pros and their boundaries and their future ultimatums are discussed in this project.

I. INTRODUCTION

One of the eleventy diseases of the nervous system that have substantial distress to human health are brain tumors. Gliblastoma is one of the most sorely and somberly occurring intracranial tumors. The estimated life anticipation for the victim who advanced into HGG is about twenty-four months. For the most part this can be split between HGG and LGG. Numerous methodologies have been used to determine brain tumors including MRI's, Computed Tomography (CT), Tomography with Positron Emission. Out of all the imaging techniques, MRI imaging technique turned out to be significant for treating the brain tumor explicitly. A newfangled evaluations in the cancer, un- covered a novel investigation called radio- genemoics. These modest procedures in the surgical field helps in determining the tumors more explicitly. The improvements of the artificial intelligence systems join hands in resolving these tumor identifications. There are miscellaneous positive applications of expert systems and peculiarly in surgical domain. These expert systems every so often even manifested to be better than the actual radiologists. Preprogrammed segmentation methodologies using deep learning have provided outstanding results in the modern times. CNN is the pre-eminent and verified to be the prime among the deep learning models that favors in extract-ing the features which are commending in real time classification, given the original data. The medical brain tumor segmentation drew it's heed towards deep learning, considering the substantiate results and procurements it forged. Not long ago, the advances in the multi-scale feature extraction ways that exemplified the segmentation job. Even if there are numerous suggested ways of for extracting the features and assembling the feature map for segmentation, we in this paper evince a contemporary network using the residual blocks with the pre-existing Unet framework proposed by Olaf Ronneberger and team.



Fig. 1. Proposed Model Architecture

The proposed methodology includes following tasks, in essence, dataset splitting, dataset transfor- mation, hyperparameter tuning, modelling. Further details of each task are discussed below.



A. Dataset Splitting

In general, there are numerous ways of split-ing the data depending on the given data. The data-set is spitted by hold-out procedure, in essence 85% of train-ing data and 15% of test-ing or validation data, in the light of fact that the data-set used in this learning is not biased and has just about same consignment of classes.

B. Dataset Transformation

Given that, the brain tumor images and their commensurable masks are available in less number, 3929 samples each, we have used the Keras Image Data - Generator in order to grow the data-set proposition. This procedure is likely to be called as Data Augmentation.

C. Modelling

In general, the UNet structure proposed by Olaf Ronneberger is substantiated to be the best for segmentation tasks. The residual blocks in the UNet architecture provides the CNN model to get significant out-turns. In this work, we put forward a hybrid architecture blend-ing the residual blocks and the Unet architecture and we call it as ResUnet.

D. ResUnet



Fig. 2. ResUnet Architecture

ResUnet architecture (fig.2) incorporates UNet architecture with residual blocks to vanquish the dissipating gradient descent complications present in the deep architectures. UNet is established on Fully Convolutional Networks and recasted in a way that it out-runs well on segmentation tasks. ResUnet consists of three parts

- 1) Encoder or Contracting path
- 2) Bottleneck
- 3) Decoder or Expansion path
- *a) Contraction or Encoding path:* The contraction path embodies of numerous contraction blocks, each block takes an input that process through residual blocks accompanied by various 2x2 MaxPooling layers. Feature maps after each block doubles, which helps the model learn tortuous features effectively.
- *b) Bottleneck:* The bottleneck block, assists as a connection betwixt contraction path and the ex- pansion path. The block lay hold of the input and then process through a residual-block accompanied by 2x2 Upsampling convolution layers.
- *c) Expansion or Decoding path:* Consequential superiority of this structure lies in expansion or decoder path. Each block takes in the up-sampled input from the preceding layer and progressions with the commensurable output features from the residual blocks in the contraction path. This is then anew passed via the residual block accompanied by 2x2 Up-sampling convolution layers.

This succors to clinch that features learning while contracting are used while rebuilding the image. Ultimately, in the endmost layer of the expansion path, the yield from the residual block is moved across 1x1 conv layer to fabricate the desired yield with the identical as the input.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.429 Volume 9 Issue X Oct 2021- Available at www.ijraset.com

III. EXPERIMENTAL SETUP

A. Brain Tumor MRI Data

The suggested methodology is trained and assessed on the LGG Segmentation Data-set.



Fig. 3. MRI of Brain with tumor (left) and it's mask (right)



Fig. 4. MRI of Brain without tumor (left) and it's mask (right)

B. Evaluation Metrics

In this work we have used Tversky loss function [16] in array to fabricate evaluation more culpability free. This loss function has parameters that can be enhanced to provide exceptional solutions by penalising the loss- function.

This loss-function accomodates constants ' α ' and ' β ' to act as penalising factors in case of false positives and false negatives. In our work we have provided

 $\alpha = 0.7$

(1)

IV. RESULTS AND DISCUSSIONS

As introduced in the evaluation metrics section, we have provided the tversky loss function for evaluation. Below is the graph plotted betwixt Tversky loss and epochs.



Fig. 5. Segmentation model focal tversky loss

Below is the graph plotted betwixt the tversky score and the epochs.





After keen examination of fig.5 and fig.6, we can distincly understand that the model is perfect in accomplishing remarkable tradeoff betwixt over-fitting and under-fitting. Even though, we can still ameliorate the model, provided more digital images and computation. Following the modelling part is completed, we assessed the model on the real time data and the prophecy of the data is layed out below.



Fig. 7. Input Brain MRI (left), Output Brain MRI segmented image (right)



Fig. 8. Input Brain MRI (left), Output Brain MRI segmented image (right)

V. CONCLUSION

In this paper, we suggested a novel Res-Unet architecture to extricate numerous features methodically on brain tumor segmentation data. The model architecture can be improvised by appending more frame-works with several residual blocks at both the contraction and the expansion paths. On the account, our upcoming study is to see-through multiple elaborate features and also pinpoint the grade of tumor based on segmented tumor structure.

REFERENCES

- [1] G.Susmitha Valli "An approach to detect Bone Tumor Using Segmentation Technique" IJPR; ISSN No:0975-2366; 2018
- [2] Y. Lecun, L. Bottou, Y. Bengio and P. Haffner, "Gradient-based learning applied to document recognition," in Proceedings of the IEEE, vol. 86, no. 11, pp. 2278-2324, Nov. 1998, doi: 10.1109/5.726791
- [3] Mazurowski MA. Radiogenomics: what it is and why it is important. J Am Coll Radiol. 2015 Aug;12(8):862-6. doi: 10.1016/j.jacr.2015.04.019. PMID: 26250979.
- [4] Goodfellow, I.. "Deep learning of representations and its application to computer vision." (2015).
- [5] Yann LeCun and Yoshua Bengio. 1998. Convolutional networks for images, speech, and time series. The handbook of brain theory and neural networks. MIT Press, Cambridge, MA, USA, 255–258.
- [6] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation.
- [7] Havaei, Mohammad et al. "Brain tumor segmentation with Deep Neural Networks." Medical Image Analysis 35 (2017): 18–31.
- [8] Akkus, Z., Galimzianova, A., Hoogi, A. et al. Deep Learning for Brain MRI Segmentation: State of the Art and Future Directions. J Digit Imaging 30, 449–459 (2017).
- [9] Litjens G, Kooi T, Bejnordi BE, et al. A survey on deep learn- ing in medical image analysis. Med Image Anal. 2017;42:60-88. doi:10.1016/j.media.2017.07.005.
- [10] Mazurowski, Maciej A et al. "Deep learning in radiology: An overview of the concepts and a survey of the state of the art with focus on MRI." Journal of magnetic resonance imaging : JMRI vol. 49,4 (2019): 939-954. doi:10.1002/jmri.26534
- [11] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet classification with deep convolutional neural networks," in Proc. Adv. Neural Inf. Process. Syst., 2012, pp. 1097–1105.
- [12] Jiachi Zhang, Xiaolei Shen, Tianqi Zhuo. Brain tumor segmentation based on refined fully convolutional neural networks with a hierarchical dice loss. arXiv preprint arXiv:1712.09093, 2017.
- [13] S. Pereira, A. Pinto, V. Alves, and C. A. Silva, "Brain tumor segmenta- tion using convolutional neural networks in MRI images," IEEE Trans. Med. Imag., vol. 35, no. 5, pp. 1240–1251, May 2016.
- [14] tversky loss function for image segmentation using 3D fully con- volutional deep networks, Seyed Sadegh Mohseni Salehi and Deniz Erdogmus and Ali Gholipor, 2017











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24*7 Support on Whatsapp)