iJRASET
International Journal For Research in Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 4 **Issue:** XI **Month of publication:** November 2016

DOI:

www.ijraset.com

Call: 08813907089 | E-mail ID: ijraset@gmail.com

Volume 4 Issue XI, November 2016
ISSN: 2321-9653
International Journal for Research in Applied Science & Engineering Technology (IJRASET)

Optimization of MRR on ECM Using Taguchi Method

Viveka Nand[1], Meeraj Ahmad[2], Dwivesh Kumar Dubey[3], Dibya Tripathi[4], Sourabh Rai[5]
[1,2,3,4,5]*Department of Mechanical Engineering,*
[1,2,3]*Rajkiya Engineering Colleger,Azamgarh U.P, INDIA.*
[4,5]*Madan Mohan Malviya University of Technology, Azamgarh U.P, INDIA.*

Abstract: ***Non-conventional machining has grown out as the need to machine different engineering materials, composites and ceramics having good mechanical properties and thermal properties as well as better electrical conductivity. The work has been carried out on mild steel specimen having good thermal and electrical conductive properties. The work on output parameters like as Material Removal Rate (MRR) and Surface Roughness (SR) of stainless steel as a work piece material. Respect on the selection of input parameters of ECM such as Voltage, Electrolyte Concentration and feed rate are suitable for improving the productivity and other output parameters. This work formulates the relationship between input and output variables for improving the ECM operation. The Regression analysis is used for making the relationship between independent and dependent variables. Our main objective is to determine the optimal value of the process parameter commonly used in the ECM process which is Voltage, Electrolyte Concentration and Feed Rate so as to improve the output parameter such as Material Removal Rate and Surface Roughness by Minitab Taguchi optimization technique method.***
Keywords: ECM, MRR, SR, Regression analysis, Taguchi optimization technique.

I. INTRODUCTION

Electro-chemical Machining (ECM) is one of the most potential unconventional machining processes. This process generally belongs to a category called as electro-chemical category. ECM process may be considered as the antonym or opposite of electro-chemical process or electro-chemical displacement process. Thus a guided anodic dissolution at very molecular level of the work piece that is electrically conductive in nature by any tool respective of flow of high current at closely low potential difference with the flow of an electrolyte which is generally conductive neutral brine or NaCl salt solution is referred as Electro-chemical process.

II. EXPERIMENTAL WORK

For this experimental analysis, the total work is done out by Electrochemical Machining set up at SunMax Auto Engineering Private Ltd. , Manesar, Gurgaon, which is having Supply of - 425 v +/- 11%, 3 φ AC, 51 Hz.

III. PROCEDURE OF THE EXPERIMENT

Before starting the experiment the initial weight of the work piece is taken to calculate the MRR. Precaution has been taken so that end tip of the electrode should not come in contact with the surface of the work piece. The time of machining of the work-piece at fixed feed and voltage V is noted down during the through process.

A. Observation tables: Experiment No.1: - Taguchi design (mild steel)

S.no.	Voltage (V)	Feed F (mm/min)	Concentration (C)	MRR (mm3/min)	SR (μm)
1	8	0.2	12	0.0129000	5.20
2	8	0.4	14	0.0345700	6.91
3	8	0.6	16	0.0856000	9.20
4	10	0.2	14	0.0166500	7.20
5	10	0.4	16	0.0540600	7.00
6	10	0.6	12	0.0852000	9.60
7	12	0.2	16	0.0132243	6.60
8	12	0.4	12	0.0232400	10.25
9	12	0.6	14	0.0515180	11.23

©IJRASET: All Rights are Reserved

B. Calculation of Material Removal Rate (MRR)-

MRR is calculated by the following formula:-

$$MRR = \frac{(W_0 - W_1)\times 10^3}{\rho_w \times \text{time}}\ mm^3/\text{min} \qquad (4.7)$$

MRR = Material removal rate
W_0= initial weight
W_1 = final weight
ρ_w = density of the workpiece

C. Calculation of Surface roughness (SR)-

Surface roughness is measured by Handysurf E35B tracing driver profilometer.

IV. RESULTS & DISCUSSIONS

A. Effects on the value of MRR by S/N ratio

Electrolyte concentration, feed rate and voltage are the dominant factor on the value of MRR. Effects of different input machining parameters on MRR (and means of MRR) are shown in fig.1. When increasing the feed rate, The MRR value is increasing slightly. After that the factor which affects the MRR value the most is feed rate. But MRR increases with increases in concentration then increases furthermore with a faster rate with further increase in electrolyte concentration.



Figure - 1

In fig. 1 the most effective parameter and their level is feed (F=0.6mm/min)and that is why the maximum S/N ratio value is for feed, which indicates that a larger value of MRR is produced at such level of machining performance. Furthermore, one other parameters and their level is feed (F=0.6mm/min) has shown the optimum mean value. Now, the third parameter level is one of the concentration of electrolyte and the level 1 of the voltage (V=10volts) is also indicating the optimum condition of S/N ratio and mean value. Therefore the optimal values for the larger MRR is Voltage (V=10 volts), Feed (F=0.6mm/min) and electrolyte

©IJRASET: All Rights are Reserved

concentration (C=16g/l) as shown in figures.

REFERENCES

[1] S. K. Mukherjee, S. Kumar, and P. K. Srivastava "Effect of electrolyte on the current- carrying process in electrochemical machining" Proc. I Mech. Engg. Vol. 221 Part C: J. Mechanical Engineering Science
[2] K. P. Rajurkar, B. Wei, C. L. Schnacker "Monitoring and Control of Electrochemical Machining (ECM)" Journal of Engineering for Industry May 1993,Vol. 115/217.67
[3] B. Bhattacharyya, M. Malapati, J. Munda, A. Sarkar "Influence of tool vibration on machining performance in electrochemical micro-machining of copper" International Journal of Machine Tool and Manufacture 47 (2007) 335–342.
[4] Liu JW, Yue TM, Guo ZN. "Wire electrochemical discharge machining of Al2O3 particle reinforced aluminum alloy 6061". Mater Manufacturing Process 2009; 24(4):446-53.
[5] Jo ao Cirilo da Silva Neto, Evaldo Malaquias da Silva , Marcio Bacci da Silva "Intervening variables in electrochemical machining" Journal of Materials Processing Technology 179 (2006) 92–96.
[6] Sekar T, Marappan R. "Experimental investigations into the influencing parameters of electrochemical machining of AISI 202". Journal of Advanced Manufacturing Systems 2008; 7(2):337-43.
[7] Neto JCdS, Silva EMd, Silva MBd. "Intervening variables in electrochemical machining". J Mater Process Technology 2006; 179(1-3):92-6.
[8] Bhattacharyya B, Munda J. "Experimental investigation on the influence of electrochemical machining parameters on machining rate and accuracy in micromachining domain". Int J. Mach. Tools Manufacturing 2003; 43(13):1301-10.
[9] S.K. Mukherjee, S. Kumar, P.K. Srivastava, Arbind Kumar "Effect of valance on material removal rate in electrochemical machining of aluminum". Journal of materials processing Technology 202 (2008) 398–401.
[10] V.K. Jain, S. Adhikary "On the mechanism of material removal in electrochemical spark machining of quartz under different polarity conditions" Journal of materials processing Technology 200(2008) 460–470 .
[11] K.L. Bhondwe, Vinod Yadava, G. Kathiresan "Finite element prediction of material removal rate due to electro-chemical spark machining" International Journal of Machine Tools & Manufacture 46 (2006) 1699–1706.
[12] S.K. Mukherjee, S. Kumar, P.K. Srivastava, Arbind Kumar "Effect of valence on material removal rate in electrochemical machining of aluminum" Journal of materials processing technology 202(2008) 398–401.
[13] V.K. Jain, P.M. Dixit, P.M. Pandey "On the analysis of the electrochemical spark machining process" International Journal of Machine Tools & Manufacture 39 (1999) 165–186.

©IJRASET: All Rights are Reserved



10.22214/IJRASET

45.98

IMPACT FACTOR: 7.129

IMPACT FACTOR: 7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)