



# **iJRASET**

International Journal For Research in  
Applied Science and Engineering Technology



---

# **INTERNATIONAL JOURNAL FOR RESEARCH**

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 5      Issue: II      Month of publication: February 2017**

**DOI: <http://doi.org/10.22214/ijraset.2017.2001>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call: ☎ 08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# **Braking System of Electric Go-Kart**

Masood M<sup>1</sup>, Md Feroz Ahmed<sup>2</sup>, Mohd Sohail<sup>3</sup>, Syed Sajjad<sup>4</sup>, Shadab Ahmed<sup>5</sup>, Syed Faraaz<sup>6</sup>

<sup>1</sup>Professor and Director R&D, Mechanical Department, Lords Institute of Engineering and Technology, Hyderabad

<sup>2</sup>Assistant Professor of Mechanical Department, Lords Institute of Engineering and Technology, Hyderabad

<sup>3,4,5,6</sup>Students of Mechanical Department, Lords Institute of Engineering and Technology, Hyderabad

**Abstract :** A Go kart is a small four wheeled vehicle. Go kart by definition has no suspension and no differential. They are usually raced on scaled down tracks, but are sometimes driven as entertainment or as a hobby by non professionals. Carting is commonly perceived as the stepping stone to the higher and more expensive ranks of motor sports. Kart racing is generally accepted as the most economic form of motor sport available. As a free-time activity, it can be performed by almost anybody and permitting licensed racing for anyone from the age of 8 onwards. Kart racing is usually used as a low-cost and relatively safe way to introduce drivers to motor racing. Many people associate it with young drivels, but adults are also very active in karting. Karting is considered as the first step in any serious racer's career. It can prepare the driver for highs-speed wheel-to-wheel racing by helping develop guide reflexes, Precision car control and decision-making skills. In addition, it brings an awareness of the various parameters that can be altered to try to improve the competitiveness of the kart that also exist in other forms of motor racing.

**Keywords:** Go Kart, Disc, Caliper, Master Cylinder, Brake Line, Brake Pedal.

## **I. INTRODUCTION**

Go-kart is a simple four-wheeled, small engine, single sealed racing car used mainly in United States. They were initially created in the 1950s. Post-war period by airmen as a way to pass spare time. Art Ingles is generally accepted to be the father of karting. He built the first kart in Southern California in 1956. From then, it is being popular all over America and also Europe.

A Go-kart, by definition, has no suspension and no differential. They are usually raced on scaled down tracks, but are sometimes driven as entertainment or as a hobby by non-professionals. 'Carting is commonly perceived as the stepping stone to the higher and more expensive ranks of motor sports. Kart racing is generally accepted as the most economic form of motor sport available. As a free-time activity, it can be performed by almost anybody and permitting licensed racing for anyone from the age of 8 onwards. Kart racing is usually used as a low-cost and relatively safe way to introduce drivers to motor racing. Many people associate it with young drivels, but adults are also very active in karting. Karting is considered as the first step in any serious racer's career. It can prepare the driver for highs speed wheel-to-wheel racing by helping develop guide reflexes, Precision car control and decision-making skills. In addition, it brings an awareness of the various parameters that can be altered to try to improve the competitiveness of the kart that also exist in other forms of motor racing.

## **II. BRAKES**

### **A. Introduction**

A brake is a device by means of which artificial frictional resistance is applied to a moving machine member, in order to retard or stop the motion of machine. Brakes are generally applied to rotating axles or wheels but may also take other forms such as surface of a moving fluid (flaps developed into water or air). Some vehicles used combination of braking mechanism, such as drag racing car's with both wheel brakes and a parachute, or airplanes with both wheel brakes and drag flaps rise into the air during landing. Most brakes commonly use friction between two surfaces press together to convert the kinetic energy of the moving object into heat, through other methods of energy conversion may be employed.

### **B. Goals**

To design a braking system that is simple and ensures safety of the driver.

To design a braking system which takes least time to bring the vehicle to stop

## **III. SELECTION OF BRAKES**

We are using disc brake of Bajaj pulsar 150cc for both front wheels and rear wheel considering the respective advantages,

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

availability, and their limitations. The following reasons support the selection of disc brakes for the front and rear wheels.

Disk brake contributes for reduction in overall weight of the vehicle.

More braking torque needs to be generated by the rear brake even after weight transfer, because the single brake has to manage the braking torque requirement of the entire rear driveshaft.

Brake Caliper: achieving a better braking efficiency and to improve the for vehicle braking effect we have opted to use double calipers for rear wheels




Fig.1 Brake Layout

### IV. CALCULATIONS

#### A. Required Calculations

Where height of centre of gravity=1.01746m

$h=0.08824\text{m}$

Let us assume the static weight distribution ratio be 40:60

Static weight on front axle =  $(0.4 \times \text{vehicle weight}) = (0.4 \times 1275)$   
=510N

Static weight on rear axle =  $(0.6 \times \text{vehicle weight}) = (0.6 \times 1275)$   
= 765N

Let us take stopping distance as 2m.

From Newton's laws of motion

$$V^2 - u^2 = 2as$$

Where  $v$  is velocity after braking =  $0\text{m/s}^2$   $u$  is velocity before braking =  $21.11\text{m/s}^2$

(i.e., the maximum velocity of the vehicle)

$$\text{Deceleration} = ((v^2 - u^2) / 2s) = ((0)^2 - (21.11)^2) / (2 \times 2) = -111.408\text{m/s}^2$$

As we know  $u = at$

Where  $t$  is the stopping time

$$t = ((v - u) / a) = (0 - 21.11) / (-111.408) = 0.1893\text{s}$$

Stopping time is 0.1893 seconds.

$$\begin{aligned} \text{Dynamic weight transfer} &= h \times wt \times \text{Deceleration} / (1.01746 \times 9.81) \\ &= (0.0884 \times 1275 \times 111.408) / (1.0174 \times 9.81) \\ &= 1255.75 \text{ N-m} \end{aligned}$$

$$\begin{aligned} \text{Dynamic weight on front axle} &= (\text{static front weight} + \text{dynamic weight transfer}) \\ &= 510 + 1255.75 \\ &= 1765.75\text{N} \end{aligned}$$

$$\begin{aligned} \text{Dynamic weight on one front wheel} &= (\text{Dynamic weight on front axle} / 2) = 1765.75 / 2 \\ &= 882.87\text{N} \end{aligned}$$

$$\text{Dynamic weight on rear axle} = \text{static rear weight} + \text{dynamic weight transfer}$$

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

$$= (765 + 1255.75) \\ = 2020.75\text{N}$$

Frictional force at each front wheel =  $(0.4 \times \text{Dynamic weight on one front wheel})$   
 $= 0.4 \times 882.87$   
 $= 353.148\text{N}$

Frictional force at each rear wheel =  $(0.6 \times \text{Dynamic weight on rear axle})$   
 $= 0.6 \times 2020.75$   
 $= 1212.45\text{N}$

Required braking torque at front wheel =  $(\text{Frictional force at wheel} \times \text{Front wheel rolling radius})$   
 $= (353.148 \times 279.4 \times 10^{-3})$   
 $= 98.669\text{N-m}$

TABLE.I  
REQUIRED VALUES

Parameter	Value
Maximum velocity(Kmph)	76
Pedal effort(N)	178
Adhesion factor of road	0.4
Coefficient of friction between brake pads and rotor	0.4
Stopping distance(m)	2
Stopping time(Sec)	0.1893

Required braking torque at rear wheel =  $(\text{Frictional force at wheel} \times \text{Rear wheel rolling radius})$   
 $= (1212.45 \times 355.6 \times 10^{-3})$   
 $= 431.147\text{N-m}$

Effective rolling radius of front wheel = 228.6mm

Braking force acting on single front tire =  $(\text{Torque} / \text{effective rolling radius})$   
 $= 191.90\text{ N}$

For Rear wheel (Disc Brake)

Area of piston in the calipers =  $3086\text{mm}^2$

Pressure acting in the master cylinder = Pressure in the calipers.

Force acting on calipers =  $\text{Pressure} \times \text{area}$   
 $= 202920 \times 3086$   
 $= 626.211\text{N/m}^2$

Clamping force generated on disc = 1594.255N

Coefficient of friction between pad and rotor = 0.4

Friction force between disc and pad =  $\text{clamping force} \times \text{coefficient of friction}$

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

$$=1594.2550.4$$

$$=637.702\text{N}$$

Effective radius of rear disc = 114.3 mm

Torque developed = 143.25 N-m

Effective rolling radius of rear wheel = 304.8mm

Braking force acting on single rear tire = (Torque/ effective rolling radius)  
=469.9N

### V. OBTAINED CALCULATIONS

The calculations are same for both front and rear wheel brakes, up to the brake line after master cylinder.

Estimated speed of the vehicle= 76Kmph

Estimated pedal effort of the driver= 178N

Mechanical advantage or pedal ratio= 4:1

Force acting on master cylinder = (Estimated pedal effort of the driver $\times$ 4) =178 $\times$ 4  
=712N

Diameter of master cylinder =0.75" =19.05mm

Area of master cylinder=285 mm<sup>2</sup>

Pressure acting on master cylinder = (force  $\times$  area)  
= 712 $\times$ 285  
= 202920N/mm<sup>2</sup>

For Front wheels (Disc brakes)

Area of piston in the calipers=3086mm

TABLE.2  
OBTAINED CALCULATIONS

Parameter	VALUE
Static front load(N)	510
Static rear load (N)	765
Dynamic front load(N)	1765.75
Dynamic rear load (N)	2020.75
Braking torque at each front wheel(N-m)	98.669
Braking torque at rear wheels (N-m)	431.14

The master cylinder piston diameter that was calculated is the maximum possible diameter that can be used for safe braking. The team decided to use a master cylinder with 10mm piston diameter as it can provide better braking force and is also commonly found on bikes.

### VI. CONCLUSION

The conclusion of this paper is that to select an appropriate braking system for electric go kart and also help to enhance the stability of vehicle. The idea behind this braking system is that to get minimum stopping distance .As the design component of the paper, various, mathematical formula was derived from the fundamental to calculate the various parameters needed under assumption of some basic values of the vehicle

### VII. ACKNOWLEDGEMENT

The authors working on the design of braking system for an electric go-kart vehicle would like to thank all those who have sincerely and whole heartedly lend their support and contributed to the project. We express our gratitude and thankfulness to the professors for their valuable guidance and their co-operation in the project.

We are also very much thankful to Head of the Department, Mechanical Engineering and project guide for their inspiring guidance with helpful suggestions for the project. We are greatly obliged to the entire staff of the Department of Mechanical Engineering,

# International Journal for Research in Applied Science & Engineering Technology (IJRASET)

Lords Institute of Engineering and Technology, Hyderabad.

## REFERENCES

- [1] Parvez Hussain S. D, C. N. Veeramani, B. Amala Priya Shalini, R. Karthika, "An Innovative Energy Efficient Automobile Design, "International Journal of Innovative Science and Modern Engineering (IJISME).ISSN: 2319- 6386, Volume-2 Issue-10, September 2014.
- [2] Arumugam, S., Ramareddy, S., "Simulation comparison of class D/Class E inverter fed induction heating", Journal of Electrical Engineering, ISSN : 1335-3632, 12(2) (2012) pp. 71-76 .
- [3] P.M.Khans, V.G.Halbe, K.Rajkumar, K.N.Manjunath, Borulkar, K.C.Vora, Mahendra Mohan Rajgopal, "Development and Evaluation of Exact Brake Systems for Light commercial Vehicles", SAE Technical Paper 2005-26-063, 2005.
- [4] Savio Pereira, OmkarVaishampayan, Akshay Joshi., " A Review on Design of Hydraulic Disc Brakes and Calculations", PVG's COET, Pune 411009, Volume 3, Issue 2, February 2014 International Journal of Research in Science and Technology .\
- [5] Joseph Katz, "Race Car Aerodynamics- Designing for Speed".
- [6] U.S. Department of Energy, Transportation Energy Data Book Edition 2004, July 2006 (visite 15/2/2009).
- [7] Ayush Gandhi and Harsh Kansal, "Troubleshooting and Its Solutions in Designing of a Smart Go Kart", IJRMET Vol. 4, Issue: 2, spl- 2 May October 2014 ISSN: 2249-5762 (Online).





10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)